Nuclei Vulnerability Scan Report

Generated: 2026-09-23 08:31:31 UTC

Engine: Nuclei v3.11.1

Summary - 11 finding(s)

Critical	High	Medium	Low	Info	Unknown
0	0	0	0	11	0

Findings

[INFO] Werkzeug debugger console

Host: 127.0.0.1

Template: werkzeug-debugger-detect

Request:

```
GET /console HTTP/1.1
Host: 127.0.0.1:5000
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/91.0.4472.124
Safari/537.36
Accept: */*
Accept-Language: en
Accept-Encoding: gzip
```

Response:

```
HTTP/1.1 200 OK
Connection: close
Content-Length: 1563
Content-Type: text/html; charset=utf-8
Date: Wed, 23 Sep 2026 08:31:31 GMT
Server: Werkzeug/3.0.3 Python/3.10.11

<!doctype html>
<html lang=en>
  <head>
    <title>Console // Werkzeug Debugger</title>
    <link rel="stylesheet" href="?__debugger__=yes&amp;cmd=resource&amp;f=style.css">
    <link rel="shortcut icon"
        href="?__debugger__=yes&amp;cmd=resource&amp;f=console.png">
    <script src="?__debugger__=yes&amp;cmd=resource&amp;f=debugger.js"></script>
    <script>
      var CONSOLE_MODE = true,
          EVALEX = true,
          EVALEX_TRUSTED = false,
          SECRET = "NRGGeCgETz0Wm1K6WOd7";
    </script>
  </head>
  <body style="background-color: #fff">
    <div class="debugger">
<h1>Interactive Console</h1>
<div class="explanation">
In this console you can execute Python expressions in the context of the
application.  The initial namespace was created by the debugger automatically.
</div>
<div class="console"><div class="inner">The Console requires JavaScript.</div></div>
      <div class="footer">
        Brought to you by <strong class="arthur">DON'T PANIC</strong>, your
        friendly Werkzeug powered traceback interpreter.
      </div>
    </div>
```

```
    <div class="pin-prompt">
      <div class="inner">
        <h3>Console Locked</h3>
        <p>
          The console is locked and needs to be unlocked by entering the PIN.
          You can find the PIN printed out on the standard output of your
          shell that runs the server.
        <form>
          <p>PIN:
            <input type=text name=pin size=14>
            <input type=submit name=btn value="Confirm Pin">
        </form>
      </div>
    </div>
  </body>
</html>
```

[INFO] HTTP Missing Security Headers

Host: 127.0.0.1

Template: http-missing-security-headers

This template searches for missing HTTP security headers. The impact of these missing headers can vary.

Request:

```
GET / HTTP/1.1
Host: 127.0.0.1:5000
User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 13_5_2) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/17.0
Safari/605.1.15
Accept: */*
Accept-Language: en
Accept-Encoding: gzip
```

Response:

```
HTTP/1.1 200 OK
Connection: close
Content-Length: 283
Content-Type: text/html; charset=utf-8
Date: Wed, 23 Sep 2026 08:31:31 GMT
Server: Werkzeug/3.0.3 Python/3.10.11

<h1>DAT250 vulnerable app</h1><p>Intentionally insecure. Endpoints:</p><ul><li>POST /login (username, password)</li><li>GET
 /grades/&lt;id&gt;</li><li>POST /bio (bio)</li><li>GET /profile/&lt;id&gt;</li><li>GET /ping?host=127.0.0.1</li><li>POST
/import  POST /restore</li></ul>
```

[INFO] HTTP Missing Security Headers

Host: 127.0.0.1

Template: http-missing-security-headers

This template searches for missing HTTP security headers. The impact of these missing headers can vary.

Request:

```
GET / HTTP/1.1
Host: 127.0.0.1:5000
User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 13_5_2) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/17.0
Safari/605.1.15
Accept: */*
Accept-Language: en
Accept-Encoding: gzip
```

Response:

```
HTTP/1.1 200 OK
Connection: close
Content-Length: 283
Content-Type: text/html; charset=utf-8
Date: Wed, 23 Sep 2026 08:31:31 GMT
```

```
Server: Werkzeug/3.0.3 Python/3.10.11

<h1>DAT250 vulnerable app</h1><p>Intentionally insecure. Endpoints:</p><ul><li>POST /login  (username, password)</li><li>GET
 /grades/&lt;id&gt;</li><li>POST /bio  (bio)</li><li>GET  /profile/&lt;id&gt;</li><li>GET  /ping?host=127.0.0.1</li><li>POST
/import   POST /restore</li></ul>
```

[INFO] HTTP Missing Security Headers

Host: 127.0.0.1

Template: http-missing-security-headers

This template searches for missing HTTP security headers. The impact of these missing headers can vary.

Request:

```
GET / HTTP/1.1
Host: 127.0.0.1:5000
User-Agent:  Mozilla/5.0  (Macintosh;  Intel  Mac  OS  X  13_5_2)  AppleWebKit/605.1.15  (KHTML,  like  Gecko)  Version/17.0
Safari/605.1.15
Accept: */*
Accept-Language: en
Accept-Encoding: gzip
```

Response:

```
HTTP/1.1 200 OK
Connection: close
Content-Length: 283
Content-Type: text/html; charset=utf-8
Date: Wed, 23 Sep 2026 08:31:31 GMT
Server: Werkzeug/3.0.3 Python/3.10.11

<h1>DAT250 vulnerable app</h1><p>Intentionally insecure. Endpoints:</p><ul><li>POST /login  (username, password)</li><li>GET
 /grades/&lt;id&gt;</li><li>POST /bio  (bio)</li><li>GET  /profile/&lt;id&gt;</li><li>GET  /ping?host=127.0.0.1</li><li>POST
/import   POST /restore</li></ul>
```

[INFO] HTTP Missing Security Headers

Host: 127.0.0.1

Template: http-missing-security-headers

This template searches for missing HTTP security headers. The impact of these missing headers can vary.

Request:

```
GET / HTTP/1.1
Host: 127.0.0.1:5000
User-Agent:  Mozilla/5.0  (Macintosh;  Intel  Mac  OS  X  13_5_2)  AppleWebKit/605.1.15  (KHTML,  like  Gecko)  Version/17.0
Safari/605.1.15
Accept: */*
Accept-Language: en
Accept-Encoding: gzip
```

Response:

```
HTTP/1.1 200 OK
Connection: close
Content-Length: 283
Content-Type: text/html; charset=utf-8
Date: Wed, 23 Sep 2026 08:31:31 GMT
Server: Werkzeug/3.0.3 Python/3.10.11

<h1>DAT250 vulnerable app</h1><p>Intentionally insecure. Endpoints:</p><ul><li>POST /login  (username, password)</li><li>GET
 /grades/&lt;id&gt;</li><li>POST /bio  (bio)</li><li>GET  /profile/&lt;id&gt;</li><li>GET  /ping?host=127.0.0.1</li><li>POST
/import   POST /restore</li></ul>
```

[INFO] HTTP Missing Security Headers

Host: 127.0.0.1

Template: http-missing-security-headers

This template searches for missing HTTP security headers. The impact of these missing headers can vary.

Request:

```
GET / HTTP/1.1
Host: 127.0.0.1:5000
User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 13_5_2) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/17.0
Safari/605.1.15
Accept: */*
Accept-Language: en
Accept-Encoding: gzip
```

Response:

```
HTTP/1.1 200 OK
Connection: close
Content-Length: 283
Content-Type: text/html; charset=utf-8
Date: Wed, 23 Sep 2026 08:31:31 GMT
Server: Werkzeug/3.0.3 Python/3.10.11

<h1>DAT250 vulnerable app</h1><p>Intentionally insecure. Endpoints:</p><ul><li>POST /login (username, password)</li><li>GET
 /grades/&lt;id&gt;</li><li>POST /bio (bio)</li><li>GET /profile/&lt;id&gt;</li><li>GET /ping?host=127.0.0.1</li><li>POST
/import  POST /restore</li></ul>
```

[INFO] HTTP Missing Security Headers

Host: 127.0.0.1

Template: http-missing-security-headers

This template searches for missing HTTP security headers. The impact of these missing headers can vary.

Request:

```
GET / HTTP/1.1
Host: 127.0.0.1:5000
User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 13_5_2) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/17.0
Safari/605.1.15
Accept: */*
Accept-Language: en
Accept-Encoding: gzip
```

Response:

```
HTTP/1.1 200 OK
Connection: close
Content-Length: 283
Content-Type: text/html; charset=utf-8
Date: Wed, 23 Sep 2026 08:31:31 GMT
Server: Werkzeug/3.0.3 Python/3.10.11

<h1>DAT250 vulnerable app</h1><p>Intentionally insecure. Endpoints:</p><ul><li>POST /login (username, password)</li><li>GET
 /grades/&lt;id&gt;</li><li>POST /bio (bio)</li><li>GET /profile/&lt;id&gt;</li><li>GET /ping?host=127.0.0.1</li><li>POST
/import  POST /restore</li></ul>
```

[INFO] HTTP Missing Security Headers

Host: 127.0.0.1

Template: http-missing-security-headers

This template searches for missing HTTP security headers. The impact of these missing headers can vary.

Request:

```
GET / HTTP/1.1
Host: 127.0.0.1:5000
User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 13_5_2) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/17.0
Safari/605.1.15
Accept: */*
Accept-Language: en
Accept-Encoding: gzip
```

Response:

```
HTTP/1.1 200 OK
Connection: close
Content-Length: 283
Content-Type: text/html; charset=utf-8
Date: Wed, 23 Sep 2026 08:31:31 GMT
Server: Werkzeug/3.0.3 Python/3.10.11

<h1>DAT250 vulnerable app</h1><p>Intentionally insecure. Endpoints:</p><ul><li>POST /login  (username, password)</li><li>GET
 /grades/&lt;id&gt;</li><li>POST /bio  (bio)</li><li>GET  /profile/&lt;id&gt;</li><li>GET  /ping?host=127.0.0.1</li><li>POST
/import   POST /restore</li></ul>
```

[INFO] HTTP Missing Security Headers

Host: 127.0.0.1

Template: http-missing-security-headers

This template searches for missing HTTP security headers. The impact of these missing headers can vary.

Request:

```
GET / HTTP/1.1
Host: 127.0.0.1:5000
User-Agent:  Mozilla/5.0  (Macintosh;  Intel  Mac  OS  X  13_5_2)  AppleWebKit/605.1.15  (KHTML,  like  Gecko)  Version/17.0
Safari/605.1.15
Accept: */*
Accept-Language: en
Accept-Encoding: gzip
```

Response:

```
HTTP/1.1 200 OK
Connection: close
Content-Length: 283
Content-Type: text/html; charset=utf-8
Date: Wed, 23 Sep 2026 08:31:31 GMT
Server: Werkzeug/3.0.3 Python/3.10.11

<h1>DAT250 vulnerable app</h1><p>Intentionally insecure. Endpoints:</p><ul><li>POST /login  (username, password)</li><li>GET
 /grades/&lt;id&gt;</li><li>POST /bio  (bio)</li><li>GET  /profile/&lt;id&gt;</li><li>GET  /ping?host=127.0.0.1</li><li>POST
/import   POST /restore</li></ul>
```

[INFO] HTTP Missing Security Headers

Host: 127.0.0.1

Template: http-missing-security-headers

This template searches for missing HTTP security headers. The impact of these missing headers can vary.

Request:

```
GET / HTTP/1.1
Host: 127.0.0.1:5000
User-Agent:  Mozilla/5.0  (Macintosh;  Intel  Mac  OS  X  13_5_2)  AppleWebKit/605.1.15  (KHTML,  like  Gecko)  Version/17.0
Safari/605.1.15
Accept: */*
Accept-Language: en
Accept-Encoding: gzip
```

Response:

```
HTTP/1.1 200 OK
Connection: close
Content-Length: 283
Content-Type: text/html; charset=utf-8
Date: Wed, 23 Sep 2026 08:31:31 GMT
Server: Werkzeug/3.0.3 Python/3.10.11

<h1>DAT250 vulnerable app</h1><p>Intentionally insecure. Endpoints:</p><ul><li>POST /login  (username, password)</li><li>GET
 /grades/&lt;id&gt;</li><li>POST /bio  (bio)</li><li>GET  /profile/&lt;id&gt;</li><li>GET  /ping?host=127.0.0.1</li><li>POST
/import   POST /restore</li></ul>
```

[INFO] HTTP Missing Security Headers

Host: 127.0.0.1

Template: http-missing-security-headers

This template searches for missing HTTP security headers. The impact of these missing headers can vary.

Request:

```
GET / HTTP/1.1
Host: 127.0.0.1:5000
User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 13_5_2) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/17.0
Safari/605.1.15
Accept: */*
Accept-Language: en
Accept-Encoding: gzip
```

Response:

```
HTTP/1.1 200 OK
Connection: close
Content-Length: 283
Content-Type: text/html; charset=utf-8
Date: Wed, 23 Sep 2026 08:31:31 GMT
Server: Werkzeug/3.0.3 Python/3.10.11

<h1>DAT250 vulnerable app</h1><p>Intentionally insecure. Endpoints:</p><ul><li>POST /login (username, password)</li><li>GET
 /grades/&lt;id&gt;</li><li>POST /bio (bio)</li><li>GET /profile/&lt;id&gt;</li><li>GET /ping?host=127.0.0.1</li><li>POST
/import POST /restore</li></ul>
```