

Visualizing fish movements with animated videos in R: The ggplot2 and ganimate packages

Workshop Handout - GLATOS, March 27, 2018

Todd Hayden, Christopher Holbrook, Tom Binder, Mike Lowe

Updated: 2019-02-24

Introduction

The `glatos` package includes several functions that facilitate the creation of animated videos of animal movements from acoustic telemetry data. The primary functions for building animated videos are the `interpolate_path` and `make_frames` functions. `interpolate_path` calculates interpolated positions of animals between detections and `make_frames` creates a series of snapshots of interpolated and detected fish locations over time from the output of `interpolate_path`. In addition to creating and outputting frames, `make_frames` can also stitch frames together to create an animated video of movements using the open source FFmpeg software. Although `make_frames` was developed to allow customization of the output content and layout of frames, some may find the level of customization to be insufficient for their needs. In this vignette, we present a short example of an alternative approach for creating animations using the `ggplot2` and `ganimate` R packages.¹ `ggplot2` is a popular and powerful package for plotting figures based on The Grammar of Graphics approach to visualizing data and developed for R by Hadley Wickham.² `ggplot2` differs from other plotting functions in R by its layered, interactive approach to building graphical output. Variables in data sets are mapped to aesthetic categories used to describe and build the plot. This approach differs from other packages in R that require the structure and layout of the plot to generally be specified simultaneously. The `ganimate` package is an extension to `ggplot2` that provides support for animations³. In the following code, we use the `make_transition` function on an example dataset included in `glatos` to create a custom transition layer necessary for interpolating fish movements. We then use the `interpolate_path` function in `glatos` to interpolate fish positions in space and time⁴. Finally, we end the vignette with a demonstration of code to create an animation of fish movements using `ggplot2` and `ganimate`.

In the first chunk we load necessary packages, obtain example data from `glatos`, clean up the data, and create a figure of lakes Huron and Erie (Figure 1). The `data.table` R package is used for data manipulations in this vignette.⁵

```
library(glatos)
library(sp)
library(sf)
library(raster)
library(ganimate)
library(ggplot2)
library(data.table)
```

¹For more information about obtaining `ganimate` and `ggplot2`, see <https://ganimate.com/> and <https://ggplot2.tidyverse.org/>

²Leland Wilkinson, <https://www.amazon.com/Grammar-Graphics-Statistics-Computing/dp/0387245448>

³see <https://ganimate.com/articles/ganimate.html>

⁴See `glatos` package help for more information about functional arguments and outputs of `make_frames` and `interpolate_path`. Additional details about creating animated videos of fish movements using the `glatos` package is found in the workshop manual “A guide to R for analyzing Acoustic Telemetry Data V2.0”. A pdf of manual can be downloaded here <https://gitlab.oceantrack.org/GreatLakes/glatos/wikis/Past%20r%20workshops%20and%20manuals>

⁵Data.table information: <https://github.com/Rdatatable/data.table/wiki>

```

# get polygon of the Great Lakes
data(greatLakesPoly)

# convert to sf spatial object
lakes <- st_as_sf(greatLakesPoly)

# crop polygon to extract Lake Huron and Lake Erie
lakes <- st_crop(lakes, xmin = -84.8, xmax = -79.6, ymin = 41.3, ymax = 46.6)
plot(st_geometry(lakes), col = "grey")

```

```

# get example walleye detection data
det_file <- system.file("extdata", "walleye_detections.csv", package = "glatos")
det <- read_glatus_detections(det_file)

# bring in receiver file and convert to sf spatial object
rec_file <- system.file("extdata", "sample_receivers.csv", package = "glatos")
recs <- read_glatus_receivers(rec_file)
setDT(recs)
recs <- recs[deploy_long < -80, ]
recs_sf <- st_as_sf(recs, coords = c("deploy_long", "deploy_lat"), crs = 4326)

```

In the next bit of code, we create a transition layer from `lakes`. The transition layer is needed to calculate non-linear interpolated movement paths that avoid impossible overland movements of fish. We set the `all_touched` argument = TRUE to allow any pixel that touches the polygon outline of the Great Lakes to be coded as water in the resulting transition layer. If `all_touched` = FALSE, then more than half of the pixel must be in the polygon in order to be coded as water.

```

# temporarily convert sf spatial to sp make_transition only accepts sp
# SpatialPolygonsDataFrame
lakes <- as(lakes, "Spatial")

# make transition layer.
tran <- make_transition(lakes, res = c(0.01, 0.01), all_touched = TRUE)

# convert back to sf
lakes <- st_as_sf(lakes)

# create quick plot of fish and receivers to make sure they are 'on the map'
# (Figure 2)
unique_fish <- unique(det, by = c("deploy_lat", "deploy_long"))
plot(tran$rast)
plot(st_geometry(lakes), add = TRUE)
plot(st_geometry(recs_sf), pch = 20, col = "orange", add = TRUE)
points(unique_fish$deploy_long, unique_fish$deploy_lat, pch = 20, col = "red")

```

Next we interpolate detection data and do some cleanup.

```

# interpolate detections.
pos2 <- interpolate_path(det, trans = tran$transition, lnl_thresh = 0.99)

```



Figure 1: Lakes Huron and Erie extracted from Great Lakes polygon included in the `glatos` package




Figure 2: Plot of transition layer, receivers (orange circles), fish detection location (red circles) in lakes Huron and Erie.

```

# convert pos2 to data.table
setDT(pos2)

# extract unique bin_timestamp
int <- unique(pos2, by = "bin_timestamp")

```

In the next code chunk, we use a `data.table` join to add the `bin_timestamp` output in the interpolated positions (`pos2`) to the receiver object. We use receiver deployment and recovery timestamps to match with `bin_timestamp`. This is so we can display receiver deployment and recovery in the animation. We essentially need to know what receivers were deployed during each `bin_timestamp` interval.

```

# Add bin_timestamp to receivers, based on deploy/recover timestamps.
# Removes unnecessary columns in output to simplify
recs <- recs[int, .(deploy_lat = x.deploy_lat, deploy_long = x.deploy_long,
  station = x.station, deploy_date_time = x.deploy_date_time, recover_date_time = x.recover_date_time,
  bin_timestamp = i.bin_timestamp), on = .(deploy_date_time <= bin_timestamp,
  recover_date_time >= bin_timestamp), allow.cartesian = TRUE]

```

We are ready to create the animation. The first step is to create a static image of all receivers, detections, and interpolated detections with `ggplot2`. We changed the color of fish detections to red circles, interpolated positions to blue circles and made detections larger than interpolated detections.

```

ggplot(data = lakes) + geom_sf(color = "black", fill = "lightgrey") + geom_point(data = recs,
  aes(x = deploy_long, y = deploy_lat), size = 2, color = "orange", inherit.aes = FALSE) +
  geom_point(data = pos2, aes(x = longitude, y = latitude, group = animal_id,
    color = record_type, size = record_type), inherit.aes = FALSE) + xlab("Longitude") +
  ylab("Latitude") + scale_color_manual(values = c("red", "blue")) + scale_size_manual(values = c(2,
  1))

```

Now we will animate the plot with `ganimate`

```

ggplot(data = lakes) +
  geom_sf(color = "black", fill = "lightgrey") +
  geom_point(data = recs, aes(x = deploy_long, y = deploy_lat),
    size = 2, color = "orange", inherit.aes = FALSE) +
  geom_point(data=pos2, aes(x=longitude, y=latitude,
    group=animal_id, color=record_type,
    size=record_type), inherit.aes=FALSE) +
  xlab("Longitude") +
  ylab("Latitude") +
  scale_color_manual(values=c("red", "blue"))+
  scale_size_manual(values=c(2,1)) +
  transition_time(bin_timestamp) +
  ggtitle('{frame_time}')

```

Notice the addition of a `transition_time` and `ggtitle` component in the code above. The resulting animation may be customized by specifying arguments to the `animate` function. Please see `?animate` for more information. Also, specifying `anim_save` may be used to write animations to disk.

This vignette provides a basic, high-level summary of creating an animated video with `ggplot2` and `ganimate`. These packages provides much more functionality than included in this vignette. Please refer to documentation for `ganimate` and `ggplot2` for additional examples and customization that may be useful for visualizing fish movements.




Figure 3: Static figure of fish detections (red), interpolated positions (blue), and receivers (orange) plotted using ggplot2

2013-05-09 09:05:27




Figure 4: Animated figure of fish movements in lakes Huron and Erie. Only last image of animation is included in this vignette