

# niminst User's manual 0.14.3

Andreas Rumpf

June 29, 2016

## Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
<b>2</b>	<b>Configuration file</b>	<b>2</b>
2.1	Project section . . . . .	2
2.2	files key . . . . .	2
2.3	Config section . . . . .	2
2.4	Documentation section . . . . .	3
2.5	Other section . . . . .	3
2.6	Lib section . . . . .	3
2.7	Windows section . . . . .	3
2.8	UnixBin section . . . . .	3
2.9	Unix section . . . . .	3
2.10	InnoSetup section . . . . .	4
2.11	C_Compiler section . . . . .	4
<b>3</b>	<b>Real world example</b>	<b>4</b>

# 1 Introduction

niminst is a tool to generate an installer for a Nim program. Currently it can create an installer for Windows via Inno Setup as well as installation/deinstallation scripts for UNIX. Later versions will support Linux' package management systems.

niminst works by reading a configuration file that contains all the information that it needs to generate an installer for the different operating systems.

## 2 Configuration file

niminst uses the Nim parsecfg module to parse the configuration file. Here's an example of how the syntax looks like:

```
# This is a comment.
; this too.

[Common]
cc=gcc      # '=' and ':' are the same
--verbose

[Windows]
isConsoleApplication=False ; another comment

[Posix]
isConsoleApplication=True

key1: "in this string backslash escapes are interpreted\n"
key2: r"in this string not"
key3: """triple quotes strings
are also supported. They may span
multiple lines."""

--"long option with spaces": r"c:\myfiles\test.txt"
```

The value of a key-value pair can reference user-defined variables via the `$variable` notation: They can be defined in the command line with the `-var:name=value` switch. This is useful to not hard-coding the program's version number into the configuration file, for instance.

It follows a description of each possible section and how it affects the generated installers.

### 2.1 Project section

The project section gathers general information about your project. It must contain the following key-value pairs:

### 2.2 files key

Many sections support the `files` key. Listed filenames can be separated by semicolon or the `files` key can be repeated. Wildcards in filenames are supported. If it is a directory name, all files in the directory are used:

```
[Config]
Files: "configDir"
Files: "otherconfig/*.conf;otherconfig/*.cfg"
```

### 2.3 Config section

The `config` section currently only supports the `files` key. Listed files will be installed into the OS's configuration directory.

Key	description
Name	the project's name; this needs to be a single word
DisplayName	the project's long name; this can contain spaces. If not specified, this is the same as Name.
Version	the project's version
OS	the OSes to generate C code for; for example: "windows;linux;macosx"
CPU	the CPUs to generate C code for; for example: "i386;amd64;powerpc"
Authors	the project's authors
Description	the project's description
App	the application's type: "Console" or "GUI". If "Console", niminst generates a special batch file for Windows to open up the command line shell.
License	the filename of the application's license

Key	description
BinPath	paths to add to the Windows %PATH% environment variable. Example: BinPath: r"bin;dist\mingw\bin"
InnoSetup	boolean flag whether an Inno Setup installer should be generated for Windows. Example: InnoSetup: "Yes"

## 2.4 Documentation section

The documentation section supports the `files` key. Listed files will be installed into the OS's native documentation directory (which might be `$appdir/doc`).

There is a `start` key which determines whether the Windows installer generates a link to e.g. the `index.html` of your documentation.

## 2.5 Other section

The other section currently only supports the `files` key. Listed files will be installed into the application installation directory (`$appdir`).

## 2.6 Lib section

The `lib` section currently only supports the `files` key. Listed files will be installed into the OS's native library directory (which might be `$appdir/lib`).

## 2.7 Windows section

The windows section supports the `files` key for Windows specific files. Listed files will be installed into the application installation directory (`$appdir`).

Other possible options are:

## 2.8 UnixBin section

The UnixBin section currently only supports the `files` key. Listed files will be installed into the OS's native bin directory (e.g. `/usr/local/bin`). The exact location depends on the installation path the user specifies when running the `install.sh` script.

## 2.9 Unix section

Possible options are:

Key	description
InstallScript	boolean flag whether an installation shell script should be generated. Example: InstallScript: "Yes"
UninstallScript	boolean flag whether a deinstallation shell script should be generated. Example: UninstallScript: "Yes"

Key	description
path	Path to Inno Setup. Example: path = r"c:\inno setup 5\iscc.exe"
flags	Flags to pass to Inno Setup. Example: flags = "/Q"

## 2.10 InnoSetup section

Possible options are:

## 2.11 C\_Compiler section

Possible options are:

## 3 Real world example

The installers for the Nim compiler itself are generated by nminst. Have a look at its configuration file:

```
; This config file holds configuration information about the Nim compiler
; and project.

[Project]
Name: "Nim"
Version: "$version"
Platforms: ""
  windows: i386;amd64
  linux: i386;amd64;powerpc64;arm;sparc;mips;mipsel;powerpc;powerpc64el;arm64
  macosx: i386;amd64;powerpc64
  solaris: i386;amd64;sparc
  freebsd: i386;amd64
  netbsd: i386;amd64
  openbsd: i386;amd64
  haiku: i386;amd64
""

Authors: "Andreas Rumpf"
Description: ""This is the Nim Compiler. Nim is a new statically typed,
imperative programming language, that supports procedural, functional, object
oriented and generic programming styles while remaining simple and efficient.
A special feature that Nim inherited from Lisp is that Nim's abstract
syntax tree (AST) is part of the specification - this allows a powerful macro
system which can be used to create domain specific languages.

Nim is a compiled, garbage-collected systems programming language
which has an excellent productivity/performance ratio. Nim's design
focuses on the 3E: efficiency, expressiveness, elegance (in the order of
priority).""
```

Key	description
path	Path to the C compiler.
flags	Flags to pass to the C Compiler. Example: flags = "-w"

```

App: Console
License: "copying.txt"

[Config]
Files: "config/nim.cfg"
Files: "config/nimdoc.cfg"
Files: "config/nimdoc.tex.cfg"

[Documentation]
; Files: "doc/*.html"
; Files: "doc/*.cfg"
; Files: "doc/*.pdf"
; Files: "doc/*.ini"
Files: "doc/overview.html"
Start: "doc/overview.html"

[Other]
Files: "readme.txt;install.txt;contributors.txt;copying.txt"
Files: "makefile"
Files: "koch.nim"
Files: "install_nimble.nims"

Files: "icons/nim.ico"
Files: "icons/nim.rc"
Files: "icons/nim.res"
Files: "icons/nim_icon.o"
Files: "icons/koch.ico"
Files: "icons/koch.rc"
Files: "icons/koch.res"
Files: "icons/koch_icon.o"

Files: "compiler"
Files: "doc"
Files: "tools"
Files: "web/website.ini"
Files: "web/ticker.html"
Files: "web/*.nim"
Files: "web/*.rst"
Files: "web/*.csv"
Files: "web/news/*.rst"
Files: "bin/nimblepkg/*.nim"
Files: "bin/nimblepkg/*.cfg"

[Lib]
Files: "lib"

[Other]
Files: "examples"
#Files: "dist/nimble"

Files: "tests"

[Windows]
Files: "bin/nim.exe"
Files: "bin/c2nim.exe"
Files: "bin/nimgrep.exe"
Files: "bin/nimsuggest.exe"
Files: "bin/nimble.exe"
Files: "bin/*.dll"

Files: "dist/*.dll"
Files: "koch.exe"
; Files: "dist/mingw"
Files: "start.bat"
BinPath: r"bin;dist\mingw\bin;dist"

;          Section | dir | zipFile | size hint (in KB) | url | exe start menu entry
Download: r"Documentation|doc|docs.zip|13824|http://nim-lang.org/download/docs-${version}.zip|overview.html"
Download: r"C Compiler (MingW)|dist|mingw.zip|82944|http://nim-lang.org/download/${mingw}.zip"

```

```
Download: r"Support DLL's\bin\nim_dlls.zip|479|http://nim-lang.org/download/dlls.zip"
Download: r"Aporia IDE\dist\aporia.zip|97997|http://nim-lang.org/download/aporia-0.4.0.zip|aporia-0.4.0\bin\apori
; for now only NSIS supports optional downloads
```

```
[UnixBin]
Files: "bin/nim"
```

```
[Unix]
InstallScript: "yes"
UninstallScript: "yes"
```

```
[InnoSetup]
path = r"c:\Program Files (x86)\Inno Setup 5\iscc.exe"
flags = "/Q"
```

```
[NSIS]
path = r"c:\Program Files (x86)\NSIS\makensis.exe"
flags = "/V0"
```

```
[C_Compiler]
path = r""
flags = "-w"
```

```
[deb]
buildDepends: "gcc (>= 4:4.3.2)"
pkgDepends: "gcc (>= 4:4.3.2)"
shortDesc: "The Nim Compiler"
licenses: "bin/nim,MIT;lib/*,MIT;"
```

```
[nimble]
pkgName: "compiler"
pkgFiles: "compiler/*;doc/basicopt.txt;doc/advopt.txt"
```