

公告

昵称: bigshark
园龄: 1年2个月
粉丝: 0
关注: 0
[+加关注](#)

搜索

找找看

谷歌搜索

常用链接

[我的随笔](#)
[我的评论](#)
[我的参与](#)
[最新评论](#)
[我的标签](#)

我的标签

[maven\(5\)](#)
[环境搭建\(5\)](#)
[linux\(3\)](#)
[suse\(2\)](#)
[vmware\(2\)](#)
[虚拟机\(1\)](#)
[nexus\(1\)](#)
[OSGI\(1\)](#)
[Java\(1\)](#)
[JVM\(1\)](#)
[更多](#)

随笔分类

[Java学习笔记\(1\)](#)
[Linux\(2\)](#)
[Maven\(5\)](#)
[OSGI\(1\)](#)

随笔档案

2016年1月 (9)

阅读排行榜

1. [Maven基础配置一上传jar包到私服](#)(2863)
2. [Maven基础配置一本地Maven配置](#)(500)
3. [Maven基础使用](#)(163)
4. [Java虚拟机内存管理原理基础入门](#)(118)
5. [Maven仓库搭建--nexus私服](#)(85)

推荐排行榜

1. [Maven基础配置一上传jar包到私服](#)(1)

Maven基础配置一上传jar包到私服

一、配置

在需要上传的工程中的pom.xml文件中加入下面的配置

```
<distributionManagement>

<repository>

<id>release</id>

<name>Release Repository</name>

<url>http://ip/nexus/content/repositories/releases</url>

</repository>

<snapshotRepository>

<id>snapshot</id>

<name>Snapshot Repository</name>

<url>http://ip/nexus/content/repositories/snapshots</url>

</snapshotRepository>

</distributionManagement>
```

我们可以在settings.xml中配置全局的url地址，pom.xml中进行动态获取。

settings.xml的default-profile中加入下面全局配置

```
<properties>

<ReleaseRepository>http://ip/nexus/content/repositories/releases</ReleaseRepository>

<SnapshotRepository>http://ip/nexus/content/repositories/snapshots</SnapshotRepository>

</properties>
```

pom.xml中改为

```
<distributionManagement>

<repository>

<id>release</id>

<name>Release Repository</name>

<url>${ReleaseRepository}</url>

</repository>

<snapshotRepository>

<id>snapshot</id>

<name>Snapshot Repository</name>
```

```
<url>${SnapshotRepository}</url>
```

```
</snapshotRepository>
```

```
</distributionManagement>
```

这样，pom.xml中就可以动态获取settings.xml中的地址

除此之外，还要在settings.xml中配置鉴权账号，否则上传将报401鉴权错误

```
<server>
```

```
<id>deployment</id>
```

```
<username>deployment</username>
```

```
<password>deployment账号的密码</password>
```

```
</server>
```

二、命令

```
mvn deploy:deploy-file -DgroupId=groupId -DartifactId=artifactId -
Dversion=version -Dfile=本地jar包路径 -DrepositoryId=releases/snapshots -
Durl=仓库地址
```

举例：上传jmxri-1.2.1.jar，本地存放在D盘

```
mvn deploy:deploy-file -DgroupId=com.sun.jmx -DartifactId=jmxri -
Dversion=1.2.1 -Dfile=d:/jmxri-1.2.1.jar -DrepositoryId=releases -
Durl=http://ip/nexus/content/repositories/releases
```

分类：Maven

标签：maven, 环境搭建

好文要顶

关注我

收藏该文



bigshark

关注 - 0

粉丝 - 0

+加关注

1

0

« 上一篇：Maven基础配置—本地Maven配置

» 下一篇：Maven基础使用

posted on 2016-01-17 16:02 bigshark 阅读(2862) 评论(0) 编辑 收藏

[刷新评论](#) [刷新页面](#) [返回顶部](#)

注册用户登录后才能发表评论，请 [登录](#) 或 [注册](#)，[访问网站首页](#)。

【推荐】50万行VC++源码：大型组态工控、电力仿真CAD与GIS源码库

【集赞】参与H3BPM 朋友圈集赞活动，豪礼任性选

【推荐】Google+GitHub联手打造前端工程师课程

来自 facebook 的老司机 带你成为数据分析师

立即上车

每周直播 | 一对一指导 | 同步学习

最新IT新闻：

- 分期乐最快今年赴美IPO 融资约6亿美元
 - 刘庆峰：今年AI将迎来分水岭，不再忽悠概念，应用效果见分晓！
 - 滴滴要解决的是高峰出行问题，而不是争抢最后三公里
 - 微软最新的开源云硬件项目使用了Intel, AMD和ARM 芯片
 - 石墨烯化身“传声筒” 助聋哑人“开口说话”
- » 更多新闻...

H3 BPM

自开发 零实施的BPM

免费下载

最新知识库文章：

- 垃圾回收原来是这么回事
 - 「代码家」的学习过程和学习经验分享
 - 写给未来的程序媛
 - 高质量的工程代码为什么难写
 - 循序渐进地代码重构
- » 更多知识库文章...