

CS213: Software Systems Laboratory

Autumn 2023-24

Koteswararao Kondepu

k.kondepu@iitdh.ac.in

Recap



- Cascading Style Sheets
 - Background Image
 - Button Styling
 - Reusability of Rulesets
 - Multiple Class Names in HTML Elements

- Bootstrap Framework

- Flexbox properties
 - Flex Container

- flex-direction
 - flex-wrap
 - flex-flow
 - justify-content
 - align-items
 - align-content

Box Properties

- Height
- Width
- Margin
- Padding
- Boarder
 - border-radius
 - border-width

Background Properties

- background-image
- background-size
- background-color

Text Properties

- color
- font-size
- font-family
- font-weight
- font-style
- text-decoration
- text-align

Outline

- CSS Bootstrap: Forms

- Form controls
- Checks
- Range
- Floating labels
- Validation

- CSS Bootstrap: Components

- Alerts
- Dropdown
- Badge
- Collapse
- List group

<https://getbootstrap.com/docs/5.3/getting-started/introduction/>



CSS Bootstrap Forms

Overview

- Bootstrap's form controls expand on Rebooted form styles with classes.
- Use these classes to opt into their customized displays for a more consistent rendering across browsers and device

- Form controls
- Checks
- Range
- Floating labels
- Validation

<fieldset>

<legend>

<label>

<input>

<select>

<textarea>

<button>

CSS Bootstrap Forms

Form Controls

- Give textual form controls like `<input>`s and `<textarea>`s an upgrade with custom styles, sizing, focus states, and more.

Where *property* is one of:

- *m* - for classes that set *margin*
- *p* - for classes that set *padding*


`{property}{sides}-{size}`

`{property}{sides}-{breakpoint}-{size}`

Where *sides* is one of:

- *t* - for classes that set *margin-top* or *padding-top*
- *b* - for classes that set *margin-bottom* or *padding-bottom*
- *l* - for classes that set *margin-left* or *padding-left*
- *r* - for classes that set *margin-right* or *padding-right*

```
<div class="mb-3">
<label for="exampleFormControlInput1" class="form-label">Email address</label>
<input type="email" class="form-control" id="exampleFormControlInput1"
placeholder="name@example.com">
</div>
```




Email address

CSS Bootstrap Forms

Form Controls

- Give textual form controls *<textarea>*s an upgrade with custom styles, sizing, focus states, and more.

```
<div class="mb-3">  
<label for="exampleFormControlTextarea1" class="form-label">Example textarea  
</label>  
<textarea class="form-control" id="exampleFormControlTextarea1" rows="3">  
</textarea>  
</div>
```



- Sizing
- Disabled
- Readonly
- Readonly plain text
- File input
- Color
- Datalists

CSS Bootstrap Forms

Checks

- Create consistent cross-browser and cross-device checkboxes and radios with our completely rewritten checks component

```
<div class="form-check">  
  <input class="form-check-input" type="checkbox" value=""  
id="flexCheckDefault">  
  <label class="form-check-label" for="flexCheckDefault">
```

Default checkbox

```
</label>
```


```
</div>
```

```
<div class="form-check">  
  <input class="form-check-input" type="checkbox" value=""  
id="flexCheckChecked" checked>  
  <label class="form-check-label" for="flexCheckChecked">
```

Checked checkbox

```
</label>
```

```
</div>
```




- Indeterminate
- Disabled
- Radios
- Disabled
- Switches

CSS Bootstrap Forms

Range

- custom range inputs for consistent cross-browser styling and built-in customization.

```
<label for="customRange1" class="form-label">Example range</label>  
<input type="range" class="form-range" id="customRange1">
```



- Min and Max
- Step

```
<label for="customRange1" class="form-label">Example range</label>  
<input type="range" class="form-range" id="disabledRange" disabled>
```

```
<input type="range" class="form-range" min="0" max="5" id="customRange2">
```

```
<input type="range" class="form-range" min="0" max="5" step="0.5" id="customRange3">
```



CSS Bootstrap Forms

Floating Labels

- Create beautifully simple form labels that float over your input fields

```
<div class="form-floating mb-3">  
  <input type="email" class="form-control" id="floatingInput"  
placeholder="name@example.com">  
  <label for="floatingInput">Email address</label>  
</div>  
<div class="form-floating">  
  <input type="password" class="form-control"  
id="floatingPassword" placeholder="Password">  
  <label for="floatingPassword">Password</label>  
</div>
```

- Textareas
- Selects
- Layouts




CSS Bootstrap Forms

Floating Labels

- Create beautifully simple form labels that float over your input fields

```
<div class="form-floating mb-3">
  <input type="email" class="form-control"
id="floatingInput" placeholder="name@example.com">
  <label for="floatingInput">Email address</label>
</div>
<div class="form-floating">
  <input type="password" class="form-control"
id="floatingPassword" placeholder="Password">
  <label for="floatingPassword">Password</label>
</div>
```

- Textareas
- Selects
- Layouts



CSS Bootstrap Forms

Floating Labels

- Create beautifully simple form labels that float over your input fields

```
<div class="form-floating">
  <select class="form-select" id="floatingSelect"
aria-label="Floating label select example">
    <option selected>Open this select menu</option>
    <option value="1">One</option>
    <option value="2">Two</option>
    <option value="3">Three</option>
  </select>
  <label for="floatingSelect">Works with
selects</label>
</div>
```

```
<div class="row g-2">
  <div class="col-md">
  </div>
  <div class="col-md">
  </div>
</div>
```

- Textareas
- Selects
- Layouts

Works with selects

Open this select menu

Open this select menu

One

Two


Three

CSS Bootstrap Forms

Validation

- Create beautifully simple form labels that float over your input fields
 - The Bootstrap grid system has four classes: **xs (phones)**, **sm (tablets)**, **md (desktops)**, and **lg (larger desktops)**. The classes can be combined to create more dynamic and flexible layouts.

```
<form class="row g-3 needs-validation" novalidate>
  <div class="col-md-4">
    <label for="validationCustom01" class="form-label">First name</label>
    <input type="text" class="form-control" id="validationCustom01" value="Mark"
required>
    <div class="valid-feedback">
      Looks good!
    </div>
  </div>
</form>
```



The image shows a Bootstrap form with the following fields and layout:

- First name:** A text input field containing the value "Mark".
- Last name:** A text input field containing the value "Otto".
- Username:** A text input field containing the value "@".
- City:** A text input field.
- State:** A dropdown menu with the text "Choose..." and a downward arrow.
- Zip:** A text input field.
- Agree to terms and conditions:** A checkbox followed by the text "Agree to terms and conditions".
- Submit form:** A blue button with the text "Submit form".

The form is styled with Bootstrap's default form controls, including floating labels and a clean, modern design. The "First name" field is highlighted with a green border and a green checkmark, indicating it is valid.

Check the provided examples code

CSS Bootstrap Components

Alerts

- Provides contextual feedback messages for typical user actions with the handful of available and flexible alert messages.

```
<div class="alert alert-primary" role="alert">
```

A simple primary alert—check it out!

```
</div>
```

```
<div class="alert alert-secondary" role="alert">
```

A simple primary alert—check it out!

```
</div>
```

```
<div class="alert alert-success" role="alert">
```

A simple primary alert—check it out!

```
</div>
```

A simple primary alert—check it out!

A simple secondary alert—check it out!

A simple success alert—check it out!

- `class alert` takes care of height and width of the alert box
- `alert-<name>` takes care of the color

Primary

Secondary

Success

Danger

Warning


btn-primary

CSS Bootstrap Components

Dropdown

- Provides contextual feedback messages for typical user actions with the handful of available and flexible alert messages.

```
<div class="dropdown">
  <button class="btn btn-secondary dropdown-toggle" type="button"
id="dropdownMenuButton1" data-bs-toggle="dropdown" aria-
expanded="false">
    Departments
  </button>
  <ul class="dropdown-menu" aria-labelledby="dropdownMenuButton1">
    <li><a class="dropdown-item">Computer Science Engineering</a></li>
    <li><a class="dropdown-item">Electrical Engineering</a></li>
    <li><a class="dropdown-item">Mechanical Engineering</a></li>
  </ul>
</div>
```



CSS Bootstrap Components

Badge

- Badges can be used as part of links or buttons to provide a counter.

`<h1>CS-213 Midsem</h1>`

CS-213 **Midsem**

`<h3>CS-213 Quiz</h3>`

CS-213 **Quiz**

`<h5>CS-213 New Assignment</h5>`

CS-213 **New Assignment**

`` inline container used to mark up a part of a text, or a part of a document

CSS Bootstrap Components

Button group

- Group a series of buttons together on a single line or stack them in a vertical column

```
<div class="btn-group" role="group" aria-label="Basic mixed styles example">  
  <button type="button" class="btn btn-danger">Left</button>  
  <button type="button" class="btn btn-warning">Middle</button>  
  <button type="button" class="btn btn-success">Right</button>  
</div>
```



```
<div class="btn-toolbar" role="toolbar" aria-label="Toolbar with button groups">  
  <div class="btn-group me-2" role="group" aria-label="First group">  
    <button type="button" class="btn btn-primary">1</button>  
    <button type="button" class="btn btn-primary">2</button>  
    <button type="button" class="btn btn-primary">3</button>  
    <button type="button" class="btn btn-primary">4</button>  
  </div>  
</div>
```



CSS Bootstrap Components

Collapse

Link with href

- Toggle the visibility of content across your project with a few classes

```
<p class="d-inline-flex">  
  <a class="btn btn-primary" data-bs-toggle="collapse" href="#collapseExample"  
  role="button" aria-expanded="false" aria-controls="collapseExample">  
    Link with href  
  </a>  
</p>
```

```
<div class="collapse" id="collapseExample">  
  <div class="card card-body">
```

Some placeholder content for the collapse component. This panel is hidden by default but revealed when the user activates the relevant trigger.

```
</div>
```

Link with href

Some placeholder content for the collapse component. This panel is hidden by default but revealed when the user activates the relevant trigger.

CSS Bootstrap Components

List group

- List groups are a flexible and powerful component for displaying a series of content.

```
<ul class="list-group">  
  <li class="list-group-item active" aria-current="true">An active  
item</li>  
  <li class="list-group-item">A second item</li>  
  <li class="list-group-item">A third item</li>  
  <li class="list-group-item">A fourth item</li>  
  <li class="list-group-item">And a fifth one</li>  
</ul>
```

```
<div class="list-group">  
  <button type="button" class="list-group-item list-group-item-action active" aria-  
current="true">  
    The current button  
  </button>  
  <button type="button" class="list-group-item list-group-item-action">A second button  
item</button>  
  <button type="button" class="list-group-item list-group-item-action" disabled>A disabled  
button item</button>  
</div>
```

| |
|-----------------|
| An active item |
| A second item |
| A third item |
| A fourth item |
| And a fifth one |

thank you!

email:

k.kondepu@iitdh.ac.in