

```
remove(p,q,x);
// removes all occurrences of x from [p,q[, shifting (copying) the
// remaining elements to the left;
// invariant: the length of the segment remains unchanged;
```

#### EXAMPLE E.42 Testing the `remove()` Algorithm

```
int main()
{ char* s="All is flux, nothing is stationary."; // Heraclitus
  int l = strlen(s);
  int n = count(s,s+l,' ');
  cout << "l=" << l << '\n';
  cout << "n=" << n << '\n';
  remove(s,s+l,' ');
  cout << s << '\n';
  s[l-n] = 0; // truncate s
  cout << s << '\n';
}
l=35
n=5
Allisflux,nothingisstationaryonary.
Allisflux,nothingisstationary.
```

Since 5 blanks were removed, the last 5 letters remain after their copies were shifted left.

```
remove_copy(p,q,pp,x);
// copies all elements of [p,q[ that do not match x to [pp,pp+n[,
// where n is the number of nonmatching elements;
// returns pp+n;
// invariant: [p,q[ remains unchanged;
```

#### EXAMPLE E.43 Testing the `remove_copy()` Algorithm

```
int main()
{ char* s="All is flux, nothing is stationary."; // Heraclitus
  char buffer[80];
  int l = strlen(s);
  int n = count(s,s+l,' ');
  cout << "l=" << l << '\n';
  cout << "n=" << n << '\n';
  char* ss = remove_copy(s,s+l,buffer,' ');
  *ss = 0; // truncate buffer
  cout << s << '\n';
  cout << buffer << '\n';
  cout << ss-buffer << '\n';
}
l=35
n=5
All is flux, nothing is stationary.
Allisflux,nothingisstationary.
30
```

```
remove_copy_if(p,q,pp,P());
// copies all elements x of [p,q[ for which !P(x) to [pp,pp+n[,
// where n is the number of nonmatching elements;
// returns pp+n;
// invariant: [p,q[ remains unchanged;
```

#### EXAMPLE E.44 Testing the `remove_copy_if()` Algorithm

```
class Blank
{ public:
    bool operator()(char c) { return c == ' '; }
};

int main()
{ char* s="All is flux, nothing is stationary."; // Heraclitus
  char buffer[80];
  int l = strlen(s);
  int n = count(s,s+l,' ');
  cout << "l=" << l << '\n';
  cout << "n=" << n << '\n';
  char* ss = remove_copy_if(s,s+l,buffer,Blank());
  *ss = 0; // truncate buffer
  cout << s << '\n';
  cout << buffer << '\n';
  cout << ss-buffer << '\n';
}
l=35
n=5
All is flux, nothing is stationary.
Allisflux,nothingisstationary.
30
```

This is the same as Example E.43 except that a predicate is used.

```
remove_if(p,q,P());
// removes all x from [p,q[ for which !P(x), shifting (copying) the
// remaining elements to the left;
```

#### EXAMPLE E.45 Testing the `remove_if()` Algorithm

```
class Blank
{ public:
    bool operator()(char c) { return c == ' '; }
};

int main()
{ char* s="All is flux, nothing is stationary."; // Heraclitus
  int l = strlen(s);
  int n = count(s,s+l,' ');
  cout << "l=" << l << '\n';
  cout << "n=" << n << '\n';
  remove_if(s,s+l,Blank());
  cout << s << '\n';
  s[l-n] = 0;
```