ONCall Open API Documentation

ONCall Open API Integration

Create A Case

Description: This solution is designed to provide a standard to push a case into ONCall, so long as the required information for service has been provided.

HTTP Method: *POST*

URL: *https://extapi.testing.misp-solutions.com/oncall/cases*

Headers:

x-api-key	String value provided by Maestro
Content Type	Application/json

NOTE: Michelin Integrations team will provide API key for both TEST and PRODUCTION environments

Case Attributes:

Name	**Description**	**Required**
specialInstructions	Identifies special instructions or notes regarding the asset and product request. **NOTE: Special instructions should be used sparingly and is not intended to provide product information as the request row is used for this purpose.**	N
inboundProgramNumberId	Identifier for the inbound program submitting request within ONCall	Y
NOTE: the same Inbound Program number must be used for every POST call being made to ONCall. Michelin Integrations team will provide Inbound Program number that must be used within the call.		
DRIVER / CALLER		
name	Name of the contact	Y

	NOTE: Validation has been put in place to ensure that proper contact name and phone is received via the API.	
phone	Phone number for the contact	Y
NOTE: for contacts, at least one contact must be provided within the case for successful creation within ONCall		
LOCATION		
address	Breakdown address for the asset (address, city, state, ZIP)	N
highway	Highway location of the breakdown address	N
mileMarker	Nearest mile marker of the breakdown location	N
comments	Notes entered regarding asset breakdown location (ex. Behind McDonald's)	N
country	Country code for the asset breakdown address	N
latitude	Latitude of the breakdown location	Y
NOTE: latitude must be provided with a minimum of three digits to the right of the decimal (**ex.** '41.177')		
longitude	Longitude of the breakdown location	Y
NOTE: longitude must be provided with a minimum of three digits to the right of the decimal (**ex.** "-80.712")		
FLEET		
shipTo	Michelin Ship To account number for the fleet customer	Y
billTo	Michelin Bill To account number for the fleet customer	N
NOTE: billTo field is now an optional field when making a request. Please NOTE that is the incorrect BT that is associated with the ST is sent, the case will be rejected.		

ASSETS		
NOTE: more than one asset can be listed in the POST call. If multiple assets are listed in the call, one of these assets must be designated as the 'primary' asset.		
unitNumber	Unit Number	Y
type	Type of unit (ex. Tractor, trailer, etc.)	Y
Values: • AMBULANCE • BACKHOE • BOOM_TRUCK • BOX_TRUCK • BUS • CAR_HAULER • CHASSIS • CONTAINER • DOLLY • DUMP_TRUCK • FARM_TRACTOR • FIRE_TRUCK • FORK_LIFT • FRONT_END_LOADER • GARBAGE_TRUCK • MOFFITT • MOTOR_HOME • OTHER_COMMERCIAL_EQUIP • PACKAGE_CAR • PICKUP_TRUCK • ROLLOFF_TRUCK • STEP_VAN • STRAIGHT_TRUCK • TRACTOR • TRAILER • UTILITY_TRAILER		
droppedUnit	Indicates if the asset has been dropped off by the driver, awaiting repair (ex. Left at drop yard)	Y
unitPrimary	true / false	Y
NOTE: a single asset must be designated as the primary unit, even when sending over a single asset within the POST call		

PRODUCTS - TIRE		
type	TIRE	Y
NOTE: multiple product request rows can be sent within the POST call. The type that is sent across in the POST call will indicate whether the product request row will require tire or wheel related data to complete the record.		
unitNumber	Asset Number	Y
NOTE: the unit number entered here must match the unit number entered within the assets section of the POST call		
action	Action being requested by the customer (ex. Replace, Repair if possible, etc.)	Y
Values: • REPAIR_IF_POSSIBLE • REPLACE • REPLACE_WITH_SPARE • SPECIAL_INSTRUCTIONS • If this value is selected, you must populate the Special Instructions field with instructions		
position	Tire position of the tire being repaired/replaced NOTE: Tire Position will be validated against the axle type to indicate proper position.	Y
Values: • LF • RF • LR • RR • LFI • RFI • LFO • RFO • LRI • RRI • LRO • RRO • UNAVAILABLE		

• OTHER		
condition	Condition of the tire being repaired/replaced	N
Values: • BALD_TIRE • BLANK_CASE • BLOWN_TIRE • CORDS_SHOWING • FLAT_TIRE • FLAT_SPOTTED • LEAKING_AIR • OBJECT_IN_TIRE • OFF_THE_RIM • PEELED_CAP • RIM_DAMAGED • SHREDDED • SIDEWALL_CUT • STOLEN • TREAD_SEPARATION • WORN_OUT		
axle	Identifies the axle type for the asset	Y

Values (based on unit type):
• Trailer Unit Type
  ○ Trailer
  ○ Other
• Remaining Unit Types
  ○ Steer
  ○ Drive
  ○ Other		

brand	Brand of tire **NOTE: Only Michelin Family products will be accepted. Products outside of Michelin Family will be rejected.**	Y
NOTE: reference Middleware API for list of available values for this field		
type	Type of tire being requested	Y

Values:
• New
  ○ Based on the 'isRetread' flag set to false
• Retread
  ○ Based on the 'isRetread' flag set to true		

tread	Tread name of the tire	Y
NOTE: reference Middleware API for list of available values for this field		
size	Tire size	Y
NOTE: reference Middleware API for list of available values for this field		
loadRange	Load range	Y
NOTE: reference Middleware API for list of available values for this field		

PRODUCTS – WHEEL

Wheels are sent as a separate request from tires within the case payload. In these situations, the following payload should be sent to insert the record within Product Request section of the case.

```
"wheel": {
          "position": "LF",
          "size": "20",
          "offset": "",
          "axle": "STEER",
          "material": "Aluminum",
          "type": "Dayton"
        }
```

type	WHEEL	Y
NOTE: multiple product request rows can be sent within the POST call. The type that is sent across in the POST call will indicate whether the product request row will require tire or wheel related data to complete the record. **NOTE: if 'wheel' type is sent in the product request row, the product request will map this request as a 'Rim Replacement'**		
unitNumber	Asset Number	Y
NOTE: the unit number entered here must match the unit number entered within the assets section of the POST call		
position	Tire position of the wheel being replaced	Y
Values: • LF • RF • LR • RR • LFI • RFI • LFO • RFO • LRI • RRI • LRO • RRO • UNAVAILABLE		

• OTHER		
size	Rim size	Y
Values: • No selection • X One • 14 • 15 • 16 • 16.5 • 17 • 17.5 • 18 • 19.5 • 20 • 20.5 • 21 • 22 • 22.5 • 24 • 24.5 • 25		
offset	Rim offset	N
Values: • NA • 0 (default value) • 2		

axle	Identifies the axle type for the asset	N

Values (based on unit type):
• Trailer Unit Type
  ○ Trailer
  ○ Other
• Remaining Unit Types
  ○ Steer
  ○ Drive
  ○ Other
 	
NOTE: default to 'OTHER' if axle is not provided		

material	Rim material	Y
Values: • Aluminum • Steel		
type	Rim type	Y
Values: • Spoke • Hub Pilot • Stud Pilot • Budd • Dayton • UniMount		
BILLING INFO		
comment	Billing comments	N
poNumber	Identifies the PO Number provided by the customer	N
drNumber	Identifies the DR Number for the case	N
referenceNumber	Identifies a Reference Number for the case	N
invoiceNumber	Identifies the Invoice Number for the case	N
amount	Identifies a dollar Amount authorized by the customer	N
Credit Card Information*		

(NOT AVAILABLE IN PRODUCTION)		
name	Name on the card (string)	N
firstDigit	First digit of card number (string)	N
last4Digits	Last four digits of card number (string)	N
expirationMonth	Expiration Month on the card (integer)	N
expirationYear	Expiration Year on the card (integer)	N
* The credit card is mandatory when the Fleet is set up as "Credit Card Only" customer in Michelin. If an invalid card is used to make the request, the case will be rejected.		

Request:

```
curl --location --request POST 'https://extapi.testing.misp-solutions.com/oncall/cases' \
--header 'x-api-key: <YOUR_API_KEY>'
--header 'Content-Type: application/json' \
--data-raw '{
  "inboundProgramNumberId": "",
  "location": {
    "longitude": "-82.2007266",
    "latitude": "34.9289684",
    "country": "USA",
    "highway": null,
    "mileMarker": null,
    "timezone": null,
    "comments": null,
    "address": "450 Global Commerce Dr, Greer, SC 29651, USA"
  },
  "fleet": {
    "shipTo": "1368548",
    "billTo": "1207138"
  },
  "assets": [
    {
      "unitPrimary": true,
      "unitNumber": "1",
      "type": "TRAILER",
```

```
      "droppedUnit": false
    }
  ],
  "specialInstructions": "bring pizza, pepperoni, XL, extra cheese",
  "products": [
    {
      "type": "TIRE",
      "unitNumber": "1",
      "tire": {
        "action": "REPAIR_IF_POSSIBLE",
        "position": "LF",
        "condition": "BLANK_CASE",
        "axle": "STEER",
        "brand": "Michelin",
        "type": "New",
        "tread": "XZA1",
        "size": "275/80R22.5",
        "loadRange": "H"
      }
    },
    {
      "type": "TIRE",
      "unitNumber": "1",
      "tire": {
        "action": "REPAIR_IF_POSSIBLE",
        "position": "RRO",
        "condition": "BLANK_CASE",
        "axle": "STEER",
        "brand": "Michelin",
        "type": "New",
        "tread": "XZA1",
        "size": "275/80R22.5",
        "loadRange": "H"
      }
    },
    {
      "type": "WHEEL",
      "unitNumber": "1",
      "wheel": {
        "position": "LF",
        "size": "20",
        "offset": "0",
        "axle": "STEER",
        "material": "Aluminum",
        "type": "Dayton"
      }
    }
  ],
  "driver": {
    "phone": "+13617209339",
    "name": "TEstDriver"
  },
  "caller": {
    "phone": "+13617209339",
    "name": "other person"
  },
   "billingInfo": {
     "comment": "test",
     "poNumber": "123",
```

```
    "drNumber": "DR123204909",
    "referenceNumber": "ref1",
    "invoiceNumber": "345",
     "amount": "0.00"
  }
}'
```

Response:

Status: 200 OK

```
{
    "id": "D210842",
    "status": "NEW"
}
```

Status: 403 Forbidden

```
{
    "message": "Forbidden"
}
```

GET a Case Status

Description: This method returns the current status of the case, along with service provider, home office, and parent company information when the case has been dispatched.

HTTP Method: *GET*

URL: *https://extapi.testing.misp-solutions.com/oncall/cases/:id*

Headers:

x-api-key	String value provided by Maestro
Content Type	application/json

Response:

GET CASE INFORMATION	
Id	Case Number
dispatchedAt	Timestamp of when case is dispatched to service provider
status	Current case status within ONCall

Here are the possible ONCall statuses:
• Dispatch
  ○ Case has been created, but awaiting dispatch to service provider by ONCall agent
• Dispatched
  ○ Case has been dispatched to service provider
• En-Route
  ○ Service provider is enroute to breakdown location
• Arrived
  ○ Service provider has arrived at breakdown location
• Rolling
  ○ Service provider has completed service and asset is back on the road
• Closed
  ○ ONCall has reviewed the case and closed the case within their system
• Cancelled
  ○ Case has been cancelled by Agent
• Closed-Cancelled
  ○ Case was active but was cancelled by the agent.	

billTo	Michelin Bill To account number for the service provider
shipTo	Michelin Ship To account number for the Service Provider
eta	Estimated time of arrival provided by the Service Provider (range) • minMinutes • maxMinutes
Provider	Service Provider servicing the asset • name • address • street • city • state • country

	• zip
parent_company	Michelin Parent Company Number for the Service Provider
home_office	Michelin Home Office Number for the Service Provider

Request:

```
curl --location --request GET 'https://extapi.testing.misp-solutions.com/oncall/cases/D864528
--header 'accept: application/json' \
--header 'x-api-key: <YOUR_API_KEY>'
```

Response:

Status: 200


```
{
    "id": "D864528",
    "dispatchedAt": "2022-07-06T13:58:52Z",
    "status": "ROLLING",
    "billTo": "1386961",
    "shipTo": "1386963",
    "eta": {
        "minMinutes": "120",
        "maxMinutes": "150"
    },
    "provider": {
        "name": "Service Provider Name",
        "address": {
            "zip": "Postal Zip Code",
            "country": "Service Provider Country",
            "state": "Service Provider State",
            "city": "Service Provider City",
            "street": "Service Provider Address"
        }
    },
    "source": "Michelin Repository",
    "parent_company": null,
    "home_office": "1420403"
}
```

Status: 403 Forbidden

```
{
    "message": "Forbidden"
}
```

Status: 404 Not Found

```
{
    "error": "{name=NotFound, message=Page not found, code=404, className=not-found,
data={url=/oncall/cases/D207591}, errors={}}",
    "statusCode": 404
}
```

GET Multiple Case Statuses

Description: This method returns the current statuses for multiple cases, along with service provider, home office, and parent company information when the case has been dispatched.

HTTP Method: *GET*

URL: *https://extapi.testing.misp-solutions.com/oncall/cases/?$in_id=*

Headers:

x-api-key	String value provided by Maestro

Parameter:

?$in_id=	List of Case IDs after the =

Response:

GET CASE INFORMATION	
Id	Case Number

dispatchedAt	Timestamp of when case is dispatched to service provider
status	Current case status within ONCall

Here are the possible ONCall statuses:
• Dispatch
  ○ Case has been created, but awaiting dispatch to service provider by ONCall agent
• Dispatched
  ○ Case has been dispatched to service provider
• En-Route
  ○ Service provider is enroute to breakdown location
• Arrived
  ○ Service provider has arrived at breakdown location
• Rolling
  ○ Service provider has completed service and asset is back on the road
• Closed
  ○ ONCall has reviewed the case and closed the case within their system
• Cancelled
  ○ Case has been cancelled by Agent	

billTo	Michelin Bill To account number for the service provider
shipTo	Michelin Ship To account number for the Service Provider
eta	Estimated time of arrival provided by the Service Provider (range) • minMinutes • maxMinutes
Provider	Service Provider servicing the asset • name • address • street • city • state • country • zip
parent_company	Michelin Parent Company Number for the Service Provider

home_office	Michelin Home Office Number for the Service Provider

Request:

```
curl --location --request GET 'https://extapi.testing.misp-solutions.com/oncall/cases/
?$in_id=D869681,D869683,D869684'
--header 'accept: application/json' \
--header 'x-api-key: <YOUR_API_KEY>'
```

Response:

Status: 200


```
{
    "id": "D869681",
    "dispatchedAt": "2022-07-06T13:58:52Z",
    "status": "ROLLING",
    "billTo": "1386961",
    "shipTo": "1386963",
    "eta": {
        "minMinutes": "120",
        "maxMinutes": "150"
    },
    "provider": {
        "name": "Service Provider Name",
        "address": {
            "zip": "Postal Zip Code",
            "country": "Service Provider Country",
            "state": "Service Provider State",
            "city": "Service Provider City",
            "street": "Service Provider Address"
        }
    },
    "source": "Michelin Repository",
    "parent_company": null,
    "home_office": "1420403"
},
{
    "id": "D869683",
    "dispatchedAt": "2022-07-06T13:58:52Z",
    "status": "ROLLING",
    "billTo": "1386961",
    "shipTo": "1386963",
    "eta": {
        "minMinutes": "120",
        "maxMinutes": "150"
    },
    "provider": {
        "name": "Service Provider Name",
        "address": {
            "zip": "Postal Zip Code",
            "country": "Service Provider Country",
```

```
            "state": "Service Provider State",
            "city": "Service Provider City",
            "street": "Service Provider Address"
        }
    },
    "source": "Michelin Repository",
    "parent_company": null,
    "home_office": "1420403"
},
{
    "id": "D869684",
    "dispatchedAt": "2022-07-06T13:58:52Z",
    "status": "ROLLING",
    "billTo": "1386961",
    "shipTo": "1386963",
    "eta": {
        "minMinutes": "120",
        "maxMinutes": "150"
    },
    "provider": {
        "name": "Service Provider Name",
        "address": {
            "zip": "Postal Zip Code",
            "country": "Service Provider Country",
            "state": "Service Provider State",
            "city": "Service Provider City",
            "street": "Service Provider Address"
        }
    },
    "source": "Michelin Repository",
    "parent_company": null,
    "home_office": "1420403"
}
```


Status: 403 Forbidden


```
{
    "message": "Forbidden"
}
```


Status: 404 Not Found


```
{
    "error": "{name=NotFound, message=Page not found, code=404, className=not-found,
data={url=/oncall/cases/D869681}, errors={}}",
    "statusCode": 404
}
```

Update a Case

Description: This method is designed to update existing service requests within ONCall. Updates can be made against the following data sets up to the point of Dispatched:

- Fleet
- Location
- Assets
- Products

Note: for this method, send only those sections of the case requested for update (ex. Billing Information). There is the option to omit those sections where updates are not required as the case will retain the original values sent in the POST method. The exception to this is if an update to the Products section is needed, this update must also include the Assets section to validate the unit number that requires update.

Once the case moves into Dispatched status, the above data sets cannot be updated. Updates can continue to be made against the following request data after Dispatched, but before the case is Closed:

- Billing Information
    - PO Number
    - Ref Number
    - DR Number
    - Invoice Number
    - Amount

Note: If the case was already dispatched, only updates to the Billing Information section are allowed.

HTTP Method: *PATCH*

URL: *https://extapi.testing.misp-solutions.com/oncall/cases/:id*

Headers:

x-api-key	String value provided by Maestro
Content Type	Application/json

Case Attributes:

Name	**Description**	**Required**
specialInstructions	Identifies special instructions or notes regarding the asset and product request	N
DRIVER / CALLER **NOTE: for the PATCH, contact information is not required as this rule only applies to POST. In PATCH, if driver or caller is not specified, the case will keep the original driver/caller set in the POST.**		
name	Name of the contact	N
phone	Phone number for the contact	N
LOCATION		
address	Breakdown address for the asset (address, city, state, ZIP)	N
highway	Highway location of the breakdown address	N
mileMarker	Nearest mile marker of the breakdown location	N
comments	Notes entered regarding asset breakdown location (ex. Behind McDonald's)	N
country	Country code for the asset breakdown address	N
latitude	Latitude of the breakdown location	Y
NOTE: latitude must be provided with a minimum of nine digits, which includes the decimal (**ex.** '41.177600')		
longitude	Longitude of the breakdown location	Y
NOTE: longitude must be provided with a minimum of nine digits, which includes the decimal (**ex.** "-80.712813")		
FLEET		

NOTE: in PATCH, fleet is not specified, the case will keep the original fleet set in the POST		
shipTo	Michelin Ship To account number for the fleet customer	Y
billTo	Michelin Bill To account number for the fleet customer	Y
ASSETS		
NOTE: more than one asset can be listed in the PATCH call. If multiple assets are listed in the call, one of these assets must be designated as the 'primary' asset. In PATCH, if asset is not specified, the case will keep the original asset(s) set in the POST.		
unitNumber	Unit Number	Y
type	Type of unit (ex. Tractor, trailer, etc.)	Y
Values: • AMBULANCE • BACKHOE • BOOM_TRUCK • BOX_TRUCK • BUS • CAR_HAULER • CHASSIS • CONTAINER • DOLLY • DUMP_TRUCK • FARM_TRACTOR • FIRE_TRUCK • FORK_LIFT • FRONT_END_LOADER • GARBAGE_TRUCK • MOFFITT • MOTOR_HOME • OTHER_COMMERCIAL_EQUIP • PACKAGE_CAR • PICKUP_TRUCK • ROLLOFF_TRUCK • STEP_VAN • STRAIGHT_TRUCK • TRACTOR		

• TRAILER • UTILITY_TRAILER		
droppedUnit	Indicates if the asset has been dropped off by the driver, awaiting repair (ex. Left at drop yard)	Y
unitPrimary	true / false	Y
NOTE: a single asset must be designated as the primary unit, even when sending over a single asset within the POST call		
PRODUCTS - TIRE		
NOTE: in PATCH, if product is not specified, the case will keep the original product(s) set in the POST		
type	TIRE	Y
NOTE: multiple product request rows can be sent within the POST call. The type that is sent across in the POST call will indicate whether the product request row will require tire or wheel related data to complete the record.		
unitNumber	Asset Number	Y
NOTE: the unit number entered here must match the unit number entered within the assets section of the POST call		
action	Action being requested by the customer (ex. Replace, Repair if possible, etc.)	Y
Values: • REPAIR_IF_POSSIBLE • REPLACE • REPLACE_WITH_SPARE • SPECIAL_INSTRUCTIONS • If this value is selected, you must populate the Special Instructions field with instructions		
position	Tire position of the tire being repaired/replaced	Y

Values: • LF • RF • LR • RR • LFI • RFI • LFO • RFO • LRI • RRI • LRO • RRO • UNAVAILABLE • OTHER		
condition	Condition of the tire being repaired/replaced	N
Values: • BALD_TIRE • BLANK_CASE • BLOWN_TIRE • CORDS_SHOWING • FLAT_TIRE • FLAT_SPOTTED • LEAKING_AIR • OBJECT_IN_TIRE • OFF_THE_RIM • PEELED_CAP • RIM_DAMAGED • SHREDDED • SIDEWALL_CUT • STOLEN • TREAD_SEPARATION • WORN_OUT		
axle	Identifies the axle type for the asset	Y

Values (based on unit type):
• Trailer Unit Type
  ○ Trailer
  ○ Other
• Remaining Unit Types
  ○ Steer
  ○ Drive
  ○ Other		

brand	Brand of tire	Y
NOTE: reference Middleware API for list of available values for this field		
type	Type of tire being requested	Y

Values:
• New
  ○ Based on the 'isRetread' flag set to false
• Retread
  ○ Based on the 'isRetread' flag set to true		

tread	Tread name of the tire	Y
NOTE: reference Middleware API for list of available values for this field		
size	Tire size	Y
NOTE: reference Middleware API for list of available values for this field		
loadRange	Load range	Y
NOTE: reference Middleware API for list of available values for this field		

PRODUCTS – WHEEL

Wheels are sent as a separate request from tires within the case payload. In these situations, the following payload should be sent to insert the record within Product Request section of the case.

```
"wheel": {
          "position": "LF",
          "size": "20",
          "offset": "",
          "axle": "STEER",
          "material": "Aluminum",
          "type": "Dayton"
   }
```

NOTE: in PATCH, if wheel is not specified, the case will keep the original wheel set in the POST		
type	WHEEL	Y
NOTE: multiple product request rows can be sent within the POST call. The type that is sent across in the POST call will indicate whether the product request row will require tire or wheel related data to complete the record. **NOTE: if 'wheel' type is sent in the product request row, the product request will map this request as a 'Rim Replacement'**		
unitNumber	Asset Number	Y
NOTE: the unit number entered here must match the unit number entered within the assets section of the POST call		
position	Tire position of the wheel being replaced	Y
Values: • LF • RF • LR • RR • LFI • RFI • LFO • RFO • LRI • RRI • LRO • RRO • UNAVAILABLE • OTHER		
size	Rim size	Y

Values: • No selection • X One • 14 • 15 • 16 • 16.5 • 17 • 17.5 • 18 • 19.5 • 20 • 20.5 • 21 • 22 • 22.5 • 24 • 24.5 • 25		
offset	Rim offset	N
Values: • NA • 0 (default value) • 2		
axle	Identifies the axle type for the asset	N

Values (based on unit type):
• Trailer Unit Type
  ○ Trailer
  ○ Other
• Remaining Unit Types
  ○ Steer
  ○ Drive
  ○ Other
 	
NOTE: default to 'OTHER' if axle is not provided		

material	Rim material	Y
Values: • Aluminum • Steel		

type	Rim type	Y
Values: • Spoke • Hub Pilot • Stud Pilot • Budd • Dayton • UniMount		
BILLING INFO		
NOTE: in PATCH, if billing information is not specified, the case will keep the original billing information set in the POST		
comment	Billing comments	N
poNumber	Identifies the PO Number provided by the customer	N
drNumber	Identifies the DR Number for the case	N
referenceNumber	Identifies a Reference Number for the case	N
invoiceNumber	Identifies the Invoice Number for the case	N
amount	Identifies a dollar Amount authorized by the customer	N

Request:

```
curl --location --request PATCH 'https://extapi.testing.misp-
solutions.com/oncall/cases/D209769' \
--header 'x-api-key: <YOUR_API_KEY>' \
--header 'Content-Type: application/json' \
--data-raw '{
      "billingInfo": {
        "comment": "test",
        "poNumber": "poTest",
        "drNumber": "DR123204909",
        "referenceNumber": "ref1",
        "invoiceNumber": "345",
        "amount": "0.00"
      }
}'
```

Response:

Status: 200 OK

```
{
    "id": "D209769",
    "status": "EN_ROUTE"
}
```

Validate Credit Card

Description: This method is designed to validate an existing credit card returning true or false is the data is correct or not. It accepts 2 kinds of payload, credit card data or credit card token. Please note that to use the credit card functionality, customer must be either a credit card MANDATORY or OPTIONAL customer within the Michelin system. This is based at the ST level.

HTTP Method: *POST*

URL: *https://extapi.testing.misp-solutions.com/oncall/credit-card*

Headers:

x-api-key	String value provided by Maestro
Content Type	Application/json

Attributes to Credit Card Data:

Name	**Description**	**Required**
name	It is the holder credit card name	Y
firstDigit	Must be 1 digit number that indicates 1st digit of the credit card.	Y
Last4Digits	Must be 4 digit number that indicates the last 4 digits of the credit card.	Y

expirationMonth	Must be 1 or 2 digits for the month. For example, for January we would expect 1. For December we would expect 12.	Y
expirationYear	Must be 2 digits that indicate the year. For example, for 2025, we would expect 25.	Y

Attributes to Credit Card Token:

Name	**Description**	**Required**
cardToken	Must be 16 characters long alphanumeric string	Y

Request for credit card data:

```
curl --location --request POST 'https://extapi.testing.misp-solutions.com/oncall/credit-card' \
--header 'x-api-key: YOUR_API_KEY' \
--header 'Content-Type: application/json' \
--data-raw '{
    "name": "Test Card",
    "firstDigit": "4",
    "last4Digits": "8888",
    "expirationMonth": 1,
    "expirationYear": 25
}'
```

Request for credit card token:

```
curl --location --request POST 'https://extapi.testing.misp-solutions.com/oncall/credit-card' \
--header 'Authorization: <YOUR_API_TOKEN>' \
--header 'Content-Type: application/json' \
--data-raw '{
    "cardToken": "5CNRJMP6KSF40000"
}'
```

Response:

Status: 200 – Valid credit card

```
{
    "validCard": true,
    "detail": "The provided card data is valid"
}
```

Status: 200 – Invalid credit card

```
{
    "validCard": false,
    "detail": "The provided card data is not valid"
}
```