Engine Specifications

GENERAL SPECIFICATIONS

Application	In. (mm)
Corolla	
Displacement	
Cu. In.	96.8
Liters	1.6
Fuel System	2-Bbl.
HP @ RPM	70 @ 4800
Torque Ft. @ RPM	85 @ 2800
Compr. Ratio	9.0:1
Bore	3.19 (81.0)
Stroke	3.03 (77.0)
Tercel	
Displacement	
Cu. In.	88.6
Liters	1.5

Application	In. (mm)
Fuel System	2-Bbl.
HP @ RPM	62 @ 4800
Torque Ft. @ RPM	76 @ 2800
Compr. Ratio	9.0:1
Bore	3.05 (77.5)
Stroke	3.03 (77.0)

VALVE SPECIFICATIONS

Application	In. (mm)
Intake	
Head Diam.	N/A
Face Angle	44.5°
Seat Angle	45°
Seat Width	.047-.063 (1.20-1.60)
Stem Diameter	.2744-.2750 (6.970-6.985)
Stem Clearance	.0010-.0024 (.025-.060)
Valve Lift	N/A
Exhaust	
Head Diam.	N/A
Face Angle	44.5°
Seat Angle	45°
Seat Width	.047-.063 (1.20-1.60)

Application	In. (mm)
Stem Diameter	.2742-.2748 (6.965-6.980)
Stem Clearance	.0012-0026 (.030-.065)
Valve Lift	N/A

PISTONS, PINS & RINGS SPECIFICATIONS

Application	In. (mm)
1.5L	
Piston Clearance	.004-.005 (.10-.12)
Pins	
Piston Fit (1)	Press Fit
Rod Fit	Press Fit
Rings	
Ring No. 1	
End Gap	.008-.016 (.20-.40)
Side Clearance	.0016-.0031 (.04-.08)
Ring No. 2	
End Gap	.006-.014 (.15-.35)
Side Clearance	.0012-.0028 (.03-.07)
Oil Ring	
End Gap	.004-.024 (.10-.60)
Side Clearance	N/A

Application	In. (mm)
1.6L	
Piston Clearance	.004-.005 (.10-.12)
Pins	
Piston Fit (2)	Press Fit
Rod Fit	Press Fit
Rings	
Ring No. 1	
End Gap	.010-.014 (.25-.35)
Side Clearance	.0016-.0031 (.040-.080)
Ring No. 2	
End Gap	.006-.012 (.15-.30)
Side Clearance	.0012-.0028 (.030-.070)
Oil Ring	
End Gap	.008-.028 (.20-.70)
Side Clearance	N/A

(1)	Pistion and pins are available only as a set.
(2)	End gap for "TP" brand rings shown; for "Riken" brand, end gap is .008-.014" (.20-.35mm) for top ring, .006-.012" (.15-.30mm) for second ring and .012-.035" (.30-.90mm) for oil ring.

CRANKSHAFT MAIN & CONNECTING ROD BEARINGS SPECIFICATIONS

Application	In. (mm)
Main Bearings	
Journal Diam.	1.8892-1.8898 (47.985-48.000)
Clearance	.0005-0019(.012-049)
Thrust Bearing	Center
Crankshaft End Play	.0008-0073 (.202-.185)
Connecting Rod Bearings	
Journal Diam.	1.5742-15748 (39.985-40.000)
Clearance	.0008-0020 (.020-051)
Side Play	.006-.010 (.15-.25)

VALVE SPRING SPECIFICATIONS

Application	In. (mm)
Free Length	1.7565(44.60)
Pressure Lbs. @ In. (Kg @ mm)	
Valve Closed	52 @ 1.52 (23.6 @ 38.6
Valve Open	N/A

CAMSHAFT SPECIFICATIONS

Application	In. (mm)
Journal Diam.	1.139 (28.94)
Clearance	.0015-.0029 (.037-.073

Application	In. (mm)
Lobe Lift	N/A

scientia non olet · About LEMON Manuals