packages
ambiguous, 231–232
dependencies for, 232, 234–235, 381
descriptions of, 233
finding, 229–232
with command prompt, 229
on Web, 230
installing, 230–232
for installing OpenBSD software, 227, 228–232
limitations, 235
listing files installed, 230–231
preparing upgrades, 372–373
and *rc.d* scripts, 252
uninstalling, 234–235
updating installed, 380–382
packages directory, 21
packet filtering, 395. *See also /etc/pf.conf* file; firewall; `pf(4)`
activating rules, 409–410
basics, 398–401
blocking spoofed packets, 416
complete ruleset, 409
components, 401–403
control and configuration, 401
interface groups, 401–402
default accept vs. default deny, 399
as firewall, 397
limitations, 400–401
with lists, 413–414
with macros, 414–415
with NAT, 426–433
PF MIB for statistics, 316
reassembling packet, 416
rules, 403–411
default permit or default deny, 404
packet pattern matching, 404–409
and state table, 411–413
sanitizing traffic, 415–416
packets, 187
fragmentation, 399
parent queue, defining, 441
partition filesystems, 29
partitioning hard drive, data deleted for, 46
partitioning scheme, for multiple disks, 49
partitions, 25–29, 30–31
bootable, 131
cylinder boundary to end, 52
deleting, 51
disklabel, 31. *See also* disklabel partitions
displaying size in gigabytes, 51
displaying size in megabytes, 50
encrypted, 166–168
exporting, 156
finding for booting, 73–74
free space on, 142–144
MBR, 30
creating, 46, 130–131, 144
and `fdisk(8)`, 129–131
viewing, 130
MFS, creating, 149
modifying existing, 55
mount point for, 52
mounting and unmounting, 140–142
multiple exports for one, 159–160
removing, 131
setting not to mount, 138
unmounting, 141–142
viewing contents, 73–74
pass number, 128
passive FTP, 437
passphrase, for encrypted partition, 167, 168
`passwd` method for BSD authentication, 99
`passwd(1)` command, 58
`passwordcheck` password control, 98
`password-dead` password control, 99
passwords
files for, 265–268
for groups, 107
non-echoing prompt, 91
root, 44–45
`sudo` caching, 120–121
for user account, 87, 89
and batch mode, 90–92
options, 98–99
`passwordtime` password control, 98
`passwordtries` password control, 98
`password-warn` password control, 98
patches directory, 21
`path` variable, 97
in `default` class, 95
pathnames, tilde (~) in, 96
pausing boot process, 70
percent sign (`%`), for groups in user aliases, 114
per-host basis, `@` symbol to override `sudo` defaults, 118
permanently insecure mode, 178
`permission denied` error, 86
permissions
error from `ntrw`, 40
`setuid` or `setgid`, 25
TFTP use of, 311
viewing for existing files, 108

permissions scheme, file flags in, 175
persist keyword (PF), for table, 422
per-user basis, @ symbol to override sudo defaults, 118
PF mailing list, 9
pf(4) (PF), 270, 395
  anchors, 434
    adding rules, 434–435
  bandwidth management, 439–445
    queues for, 440–441
  configuration, and FTP proxy, 438–439
  enabling and configuring, 397–398
  FTP and, 437–439
  include files, 445
  logging, 446–448
  options, 417–420
    fragmented packets, 418
    set block-policy, 417
    set limit, 417–419
    set optimization, 419–420
    set skip, 420
    src-nodes limit, 418
    states limit, 418–419
  packet management, 421–448
    with tables, 422–426
  quick keyword, 446
  ruleset tracing, 448
  viewing active rules, 410–411
pf.conf(5), scrub keyword, 416
pfctl(8), 401, 409–410, 445
  for anchor rule changes, 435
  commands for tables, 423–424
  to view state table, 411–412
  viewing and flushing anchors with, 436
pflog0 (PF logging), 63
pflog(4) pseudo-device, 351
pflogd(8), 446
pflow(4) NetFlow exporter, 448
physical interface for disk drive, 33
physical layer (OSI), 184, 187
PID file, adding, 293
ping(8), 191, 196, 210–211
pkg_add(1), 228, 230, 246, 381
  verbose mode, 231
pkg_delete(1), 234–235
pkg_info(1), 229
pkglocatedb, 233
$PKG_PATH environment variable, 228, 380
pkill command, 83
Point-to-Point Protocol (PPP), 185
pointer movement commands, 337
portability of OpenBSD, xxxvi
portmap(8) daemon, 155
ports
  build stages, 243–246
  code snapshot for, 384
  customizing, 246–251
    local distfile mirrors, 246–249
    preferred collection mirrors, 247–248
  flavors, 249
    and dependencies, 250–251
    uninstalling, 251
  installing, 66
  subpackages, 251–252
  troubleshooting build failure, 242
  upgrading, 393
ports (TCP), 198–199
  determining which are open, 200–202
    with fstat, 202
    with netstat, 200–202
  filtering tcpdump on, 447
  reserved, 199–200
ports and packages system, 227–228
ports collection, 235–241, 385
  automation, 236
  building ports, 241–246
  finding software, 239–241
  secondary ports, 237–238
ports index, 239–240
ports tree, 66, 236–237
  read-only, 238–239
ports.tar.gz file, 21, 66, 236, 384
POSIX time zones, 60
PostgreSQL port, 372–373
PostScript, 306
power button, 179
power of Open BSD, xxxvi
power sensors, 297
PPP (Point-to-Point Protocol), 185
Preboot eXecution Environment (PXE) diskless booting method, 22, 450–451
preening of filesystems, 138
preferred collection mirrors, 247–248
primary mirror, 249
primary partitions, 30
print (fdisk), 130
printer capability file, 270
printer daemon (lpd), 306–307
printing disklabels, 50, 53
priority
  for log message, 284
  for queue, 442

priority queuing (PRIQ), 440
priority variable, 97
PRIQ (priority queuing), 440
private communities in SNMP agents, 314
private NAT addresses, 426–427
private networks, IP addresses for, 192
privilege, minimum level of, 86
privileged account, risks from regular use, 86
processors, 18
program name, sorting syslog messages by, 286
programs. *See* software
prompt
  boot loader, 70
  for disklabel(8), 50
  escaping to, 43
  for finding packages, 229
  in tmux, 328–329
  ukc> for kernel editor, 353
ProPolice, 173, 174
proprietary hardware, 17–18
proto keyword, for packet filtering, 405
pseudo-devices, 351
  custom kernel configuration for, 359–360
pseudo-terminals, 274
ptrmove, 337
public communities in SNMP agents, 314
PuTTY, 76
PXE (Preboot eXecution Environment) diskless booting method, 22, 450–451

Q

q command, to write disklabel to disk, 53–54
qemu, 19
queues for bandwidth management, 440–441
  assigning traffic to, 444
  child queue, 442
  match keyword, 444–445
  options, 442–443
  parent queue, 441
  priority for, 442
  viewing, 445
quit command
  with config, 353
  with fdisk, 131

R

RADIUS authentication, 99
  login classes for, 100–101
radius method for BSD authentication, 99
RAID (Redundant Array of Independent Disks)
  checking health status of devices in array, 164
  sensors for controllers, 297
  software, 160–166
  types, 161–162
RAM. *See* memory (RAM)
random early detection, of packet loss, 443
ranges of ports, pf(4) redirection of, 433
rarpd(8), for reverse ARP, 454–455
raw devices, 127
rbootd(8), 271
rc.d scripts, 82
  for third-party software, 83
rdist(1) program, 281
read-only mailing lists, 9–10
read-only mount (ro), 128
read-only mounts
  in FFS, 135–136
  in NFS, 157
read-only ports tree, 238–239
read-write (rw) mount option, 128
read-write mounts, in FFS, 136
reboot, 49
rebooting
  as part of upgrade, 380
  to test configuration, 57
redirecting email messages, 65
Redundant Array of Independent Disks. *See* RAID (Redundant Array of Independent Disks)
reinstalling OpenBSD, vs. upgrade, 371
reject method for BSD authentication, 99
relayd(8), 271
  anchors for, 434
release directories, 21–22
  contents after build, 391
$RELEASEDIR environment variable, 390, 391
releases of OpenBSD, 369–370
  building, 389–392
    bundling base system, 390–391
  indexing, 392
  using, 392
remote filesystem, mounting, 159
remote host, logging to, 288
remote machines, connecting with SSH, 334

remote magnetic tape command (rmt), 271
removable media, 153
removing. *See* deleting
repositories, for source code, 385–386
Request for Comments. See RFC (Request for Comments)
requirehome variable, 97
reserved ports (TCP), 199–200
resolver, 210
  vs. dynamic configuration, 212–213
resource limits, for user account, 96–97
responding to email, 14
restore(8), copying files with, 145
reverse ARP, rarpd(8) for, 454–455
RFC (Request for Comments)
  1918 on private networks, 192, 426
  5737 on IPv4 addresses, 426
RIP (Routing Information Protocol), 203
RIP daemon, 271
ripd(8), 271
rmoption keyword, 362–363
rmt (remote magnetic tape command), 271
rmuser(8), 92
rndc(8), 109
ro (read-only) mount option, 128
.rodata segments, 173
root (/) partition, 26–27, 46
  duplicating, 148
  multiple disks and, 49–50
  password, 44–45, 106
    setting, 58
  preparing for upgrade, 374
root account, 86, 105
  disallowing logins directly to, 275
  email alias for, 278
  emailing maintenance tasks results to local, 65
  hiding with sudo, 109–120
  for initial setup, 57
  secure console for, 275
roundrobin method, 221
route add command, 207
route delete command, 207
route(8), 204–207, 219
router advertisements, sysctl to control, 347
router discovery, 195
routing, 203
Routing Information Protocol (RIP), 203
routing table, 204–205
RPC, 272
Rufus, 457
run as alias, 114
  override sudo defaults, 119
rw (read-write) mount option, 128

S

salt for password, 90
sanitizing packet filtering traffic, 415–416
sappnd file flag, 175, 179
sasyncd(8) (security association synchronization daemon), 272
SATA drives, 29
/sbin/nologin shell, 102
scheduled tasks, 277–282
  custom scripts, 282
  daily maintenance, 278–281
  monthly maintenance, 282
  weekly maintenance, 282
schg file flag, 175, 179
screen
  blanking, 324–325
  locking in cwm, 333–334
  turning off display, 325
script kiddies, 170
script man page, 242
scripts
  for maintenance, 282
  startup system, 80–82
scrub keyword, 416
scrubbing, 399
SCSI drives, 29
SCSI multipathing feature, experimental, 362
search, 210–211
search domains, default, 210–211
search index, adding to routing table, 264
searching
  Internet, 11
  within man page, 5
    for cryptography, 10–11
  for man pages, 5–6
  for packages, 229–232
    with command prompt, 229
    on Web, 230
  for software, 239–241
    by keyword, 240
    with SQL, 240–241
  tables for packet filtering, 424
secondary ports, 237–238
sections in OpenBSD manual, 4
sectors, 31–32
  and disklabels, 32–34
  number for drive, 34
secure file transfer protocol (SFTP), 317
Secure Shell daemon. *See* SSH (Secure Shell) daemon (sshd),
Secure Sockets Layer (SSL) certificates, 273

securelevel(7), 177–181
determining appropriate, 180
in *rc.securelevel*, 81
weaknesses, 180–181
security, xxx, xxxviii–xxxix, 169–181
attackers, 170–172
bidirectional NAT and, 430
faulty sudo setup impact, 110
file flags, 175–177
memory protection, 172–175
partitions for, 25
for SNMP, 314
system clock and, 60
updates for, 368
user damage to, 85
security association synchronization daemon (sasyncd(8)), 272
security checks, in daily maintenance, 278–280
security-announce@OpenBSD.org, 9, 172
SEE ALSO section, in man pages, 7
segments, 187
Sendmail, 263
sensors in hardware, 272. *See also* hardware sensors
sensorsd(8), 298, 317
variables, 301
sensorsd.conf file, 299–300
serial connection, configuration, 271
serial consoles, 75–79
client serial port, 78–79
logins, 79
setup, 77
testing configuration, 77
Serial Line Internet Protocol (SLIP), 272
serial ports, 274
services, setup when installing OpenBSD, 44
sessions, in tmux, 327–328
set block-policy drop (PF), 417
set block-policy return (PF), 417
set keyword, 417
set limit option (PF), 417–419
set optimization option (PF) , 419–420
set skip option (PF), 420
set timeout command, 70
setenv variable, 97
setgid permissions, 25
set-option command (tmux), 329
setuid behavior, nosuid option disallowing, 138
setuid permissions, 25
setuid root wrapper, 110
setup after install, 57–84
booting to graphic console, 67
checking system errata, 58
hostname, 61–62
installing ports and source code, 66
keyboard mapping, 66
mail aliases and status mail, 65
networking, 62–65
default gateway, 64
dynamic configuration, 64
Ethernet interfaces, 62–64
name service servers, 65
root password setting, 58
software configuration, 59
time and date, 60–61
set-window-option command (tmux), 329
SFTP (secure file transfer protocol), 317
SGI (Silicon Graphics), 16
Shell option, in OpenBSD installer, 41
shell script
OpenBSD installer as, 41
variable assignments in, 59
shell variable, 97
shells
login forbidden for unprivileged users, 102
modifying environment, 97
for user account, 88, 92
configuring default, 87
shutdown, 179
of server software, 82
SIGHUP, 293
signal name, 293–294
signature in email, 13
Silicon Graphics (SGI), 16
Simple Mail Transfer Protocol (SMTP), 263
Simple Network Management Protocol (SNMP), 273
single-user mode
boot process in, 71–72
mounting disks in, 71–72
root partition mounting as read-only, 140
stackable mounts, 146
starting network in, 72
siteXX.tgz file, 373, 460
creating, 458–459
skey method for BSD authentication, 99
skilled attackers, 171–172
sleep, of screen, 325
SLIP (Serial Line Internet Protocol), 272
small-server handler (inetd), 304–305

SMDS (Switched Multimegabit Data Service), 185
SMTP (Simple Mail Transfer Protocol), 263
snapshots directory, 21
snapshots versions of OpenBSD, 369
  compressed tar files for, 384
`snk` method for BSD authentication, 99
SNMP client, `net-snmp` package of command-line tools, 313
SNMP (Simple Network Management Protocol), 273
`snmpd` (SNMP agent), 312–317
  configuring, 314–315
  debugging, 315–316
  getting information, 316–317
soft update mounts, in FFS, 137
`softraid(4)` devices, 160
  booting from, 166
  creating, 163–164
  deleting, 165
  failed volumes
    identifying, 164
    rebuilding, 164–165
  preparing disks for, 162–163
  reusing, 166
  status, 164
software
  collections, 248
  configuration, 59
  force-starting, 83–84
  logging to, 287
  making, 226
  management, 225–253
  removing during upgrade, 372
  source code for, 226–227
  startup scripts, 82–83
software RAID, 160–166
software serial console, 75
songs directory, 21
sorting
  `du` output, 143
  messages, `sylogd(8)` for, 284–287
source address, in filter rule, 406
source code, 226–227
  to build custom kernel, 358
  for OpenBSD, 28
  for operating system, installing, 66
  for ports, 241
  updating, 385–388
  for your own OpenBSD, 384
source port, in filter rule, 408–409
source routing, 179
sparc64, 16
spoofed packets, blocking, 416
`sqlports` package, 240
`src` (userland) collection, 385
`src-nodes` limit (PF), 418
src.tar.gz file, 21, 384
SSH (Secure Shell) daemon (`sshd`), 82–83, 273, 317–322
  connecting to remote machines with, 334
  disabling, 318
  disabling root logins over, 45
  enabling, 44
  host keys, 318
  network options, 318–319
sshd_config file, 321
SSL (Secure Sockets Layer) certificates, 273
-stable version of OpenBSD, 370
  building, 387–388
  source code for, 384
  tag for, 385
  updating to, 386–387
stackable mounts, 146
`stacksize` variable, 96
`staff` user class, 94
startup
  enabling time correction at, 61
  multiuser, 79–84
startup scripts, 80–82
  for packages, 252–253
  software, 82–83
`startx` command, 330
state table, 398–399
  filtering rules and, 411–413
stateful inspection, 398–399
stateful protocol, 197
stateless filtering, 399
stateless protocol, 197
statelessness of NFS, 155
states per source address, PF tracking of, 418
static IP address, 63–64, 216, 310
  DHCP vs., 42–43
static NAT, 429
statistics
  from operating system, SNMP for, 316
  of PF, 418
status bar in `tmux`, 326
  options for, 329
status mail, setup after install, 65
`stop` argument, for scripts at shutdown, 83
streaming protocol, TCP as, 197
striping (RAID-0), 161
striping data across disks (RAID-4), 161

striping with parity across drives (RAID-5), 161
su(1), 106
_subdir keyword, 265
subject, for email help request, 12–13
subnets, for IPv6 addresses, 194
subpackages, 251–252
sudo(8), 106, 109–120
  changing default behavior, 117–119
  configuring, 273
  disadvantages, 109–110
  and environment, 119–120
  exclusions, 122–123
  logs, 123, 293
  overview, 110
  password caching, 120–121
  reason to use, 109
  running commands, 121
sudoedit(8), 110, 121–122
$SUDO_EDITOR environment variable, 122
superblocks, in FFS, 134
swap partition, 52–53
swap space, 27
  encrypting data written to, 348
  mount point, 128
  splitting between drives, 30
Switched Multimegabit Data Service (SMDS), 185
switches, 213
  configuring for VLANS, 223
switching between visible cwm windows, 333
sylogd(8)
  and embedded systems, 289
  for sorting messages, 284–287
SYN (synchronization) request, 398
SYN+ACK packet, 398
synchronous mounts, in FFS, 136
SYNOPSIS section, in man pages, 7
sysadmin accounts, creating, 91
sysctl MIBs, 343–344
sysctl(8), 343
  for adjusting kernel, 340
sysctls (system controls), 178, 343–348
  changing values, 345
  setting at boot, 346–348
  sysctl MIBs, 343–344
  value types, 345–346
  viewing list of, 344–345
syslog facility, 283
syslog(3), 283
syslogd(8) (logging daemon), 273
  customizing, 288
sysmerge(8)
  to compare */etc* files, 376–378
  finishing, 380
  userland upgrade and, 389
sys.tar.gz file, 21, 384
systat pf, 418
systat states, 412
system controls. *See* sysctls (system controls)
system errata, checking after install, 58
system failures, swap space use in, 27
system groups, in user aliases, 114
system logs
  actions, 287–288
  adding timestamp, 286
  customizing syslogd, 288
  and embedded systems, 289
  excluding information from, 285
  facilities, 283–284
  priority, 284
  sorting messages with syslogd(8), 284–287
system maintenance, 277–301
  hardware sensors, 296–301
    configuring, 298–301
    device drivers for, 297–298
    triggering action, 300–301
  log file maintenance, 289–294
    adding PID file, 293
    monitoring, 293
    newsyslog.conf fields, 290–292
    signal name, 293–294
  scheduled tasks, 277–282
    custom scripts, 282
    daily maintenance, 278–281
    monthly maintenance, 282
    weekly maintenance, 282
  system logs, 282–289
    actions, 287–288
    customizing syslogd, 288
    and embedded systems, 289
    facilities, 283–284
    priority, 284
    sorting messages with syslogd(8), 284–287
  system time, 294–296
system message buffer, 340
system time, 294–296
system-level append-only flag, 175
system-level immutable flag, 175–176
systems administration team, directing mail sent to root to, 65
systrace(4) system, 273

T

table sysctl, 346
tables for packet filtering, 422–426
  and automation, 425–426
  changing, 424–425
  defining table, 422–423
  searching, 424
  using, 423
  viewing, 423–424
tag for repository version, 385
tar files, creating, 458–459
tar(1), copying files with, 145
tasks. *See* scheduled tasks
TCP (Transmission Control Protocol), 186, 197–198
  keep-alive feature, sysctl to control, 347
  open ports, 200–202
  ports, 198–199
  reserved ports, 199–200
  states, 411–412
tcpdump(8)
  binary format for PF logs, 447
  filtering, 447–448
TCP/IP, 183–207. *See also* IP addresses
  ICMP (Internet Control Message Protocol), 196
  IP routing, 202–207
    deleting routes, 207
    IPv4, 203–204
    route flags, 206–207
    route(8) for managing, 204–207
  network layers, 184–187
  network request, data transmission for, 187–188
  network stacks, 188–189
  TCP. *See* TCP (Transmission Control Protocol)
  UDP, 196–197
The TCP/IP Guide (Kozierok), 184, 397
tcsh(1)
  port for, 237
  system-wide defaults for, 257
tech@OpenBSD.org, 9
temperature sensors, 297
temporary root directories, 390
term variable, 97
termcap(5) database, 78
terminal emulator (tip(1)), 76
terminals, 274–276
  configuring, 275
  initializing, 79
  running virtual with tmux, 325–329
terminating windows in tmux, 327
testing
  configuration by rebooting, 57
  custom kernels, 364–365
  packet filtering rules, 410
  serial configuration, 77
  TFTP server, 311
text-based email reader, OpenBSD users, 13
TFTP (Trivial File Transfer Protocol), 310
  server setup for diskless install, 453
  testing server, 311
tftpd (TFTP daemon), 310–311
third parties, mailing lists, 9
third-party software, *rc.d* scripts for, 83
three-button mouse, emulating in X, 331
three-way handshake, 197, 398
thrsize for ALTQ, 441
tilde (~), in pathnames, 96
time and date, setting, 60–61
time formats, in log file, 291
time sensors, 295
time zone, setting, 45–46, 60
timeout
  boot idle, 70
  in PF, 399, 419
  setting for boot, 74
timestamp, adding to log file, 286
timestamp file, 21
timestamp_timeout option, for sudo password caching, 120
tip(1) (terminal emulator), 76
/tmp directory, 27
tmux attach, 328
tmux list-sessions, 328
tmux(1), 325–329
  command mode, 328–329
  commands, 326–327
  configuring, 329
  help for, 327
  sessions in, 327–328
  setting options, 329
  status bar and window names, 326
token bucket regulator size configuration, 441
token method for BSD authentication, 99
tools directory, 21, 22
traceroute(8), 196
tracing, pf ruleset, 448
tracks, on disk drives, 31
traffic interception, 433
Transmission Control Protocol. *See* TCP (Transmission Control Protocol)
transport layer (OSI), 186, 187
Trivial File Transfer Protocol. *See* TFTP (Trivial File Transfer Protocol)

troubleshooting
custom kernel build errors, 365–366
fsck for, 139
port build failure, 242
single-user mode for, 71
trunking, 221–222
tsch, installing from port, 242
tunnels, IPv6 addresses over, 224
tutorials, 4
in OpenBSD FAQ, 8
twm(1), 331

U

uappnd file flag, 175
uchg file flag, 176
UDP (User Datagram Protocol), 186, 196–197, 399
ports in netstat output, 201
states, 412–413
UFS (Unix File System), 133
UID (user ID), 88
NFS use of, 157
ukc> prompt (kernel editor), 353
umask setting, for user, 95
umask variable, 97
umount(8), 141–142
uname(1) command, 366, 381
undeadly.org, 8
underscore (_), for unprivileged user names, 103–104
UNetbootin, 457
uninstalling
flavored ports, 251
packages, 234–235
University of California, xxxii–xxxiii
UNIX, xxxi
development, xxxii
Unix File System (UFS), 133
Unix Systems Laboratories (USL), xxxii
Unix-like systems, boot floppies, 39–40
unmapping keyboard, 336
unmounting
decrypted partition, 167
partitions, 141–142
unprivileged user accounts, 102–104
creating, 104
uninstall packages and, 234
upgrade and install kernel, 72
upgrade.site script, 460
upgrading
customizing, 373, 460
installed packages update, 380–382
mounting filesystems, 376
from official media, 373–375
over network, 374–375
process for, 371–373
reasons for, 368
USB disk
booting installer from, 22
customizing media for installation, 457
USB keyboards, country code for, 66
user accounts
for administrators, creating, 91–92
authentication methods, 99–100
creating, 88–89
editing, 93–94
identifying group membership, 107
named, 102
nobody account, 103
password for, 87–88, 89
removing, 92
resource limits for, 96–97
restrictions, 92
temporarily disabling, 267
unprivileged, 102–104
user aliases, 114
user data partition, 25
User Datagram Protocol. *See* UDP (User Datagram Protocol)
user facility, 283
user ID (UID), 88
NSF use of, 157
user management, 85–104
root account, 86
user shells, as sudo exclusions, 122
userland, 340
building, 389
code snapshot for, 384
for diskless machine, 455
populating diskless, 456
user-level append-only flag, 175
user-level immutable flag, 176
usernames, 88
files for, 265–268
users
adding, 86–92
interactively, 87–89
noninteractively, 89–92
chrooting, 319–322
directing log messages to, 287
NFS and, 157–158
security problems from, 171
as security risk, 85
setting up first, 45
USL (Unix Systems Laboratories), xxxii
/usr partition, 28
/usr/local directory, 231
/usr/local partition, 28

/usr/mdec/ directory, 453
/usr/obj directory, for build, 384
/usr/obj partition, 28–29
/usr/ports directory, 66, 236
    for build, 384
/usr/ports/emulators file, 450
/usr/ports/INDEX file, 239
/usr/ports/sysutils/mtools, 151
/usr/share/zoneinfo directory, 60
/usr/src directory, for build, 384
/usr/src partition, 28
/usr/src/sys/arch file, 361
/usr/src/sys/arch/amd64 file, 365
/usr/src/sys/conf file, 360–361
/usr/X11R6 partition, 28
/usr/X11R6/share/X11/rgb.txt file, 335–336
/usr/xenocara directory, for build, 384
/usr/xobj directory, for build, 384
UTC (Coordinated Universal Time), 45
`uucp` facility, 283
`uvideo(4)`, 351

V

/var partition, 28
/var/backups file, 280
/var/db/pkg file, 232
/var/log/daemon file, 300
/var/log/pflog file, 447
/var/log/secure file, 123
/var/run/dmesg.boot file, 340
/var/www directory, 320
variables
    for *login.conf*, 95–96
    for ports collection, 238
verbose mode
    for `pkg_add(1)`, 231
    for `snmpd`, 315
versions of OpenBSD, 368–371
    -current, 368–369
        building, 392–393
        source code for, 384
        updating to, 387–388
    releases, 369–370
    snapshots, 369
    -stable, 370
        building, 387–388
        source code for, 384
        tag for, 385
        updating to, 386–387
    use decision, 370–371
`video` device, kernel support for, 351
`vipw(8)`, 94, 266
virtual consoles, 274
virtual local area network (VLAN), 223–224
    and OpenBSD install, 42
virtual memory, 27
virtual node. See vnode (virtual node)
Virtual PC, 450
virtual terminals, running with `tmux`, 325–329
VirtualBox (Oracle), 19, 450
virtualization, 19, 450
    USB installation for, 456
`$VISUAL` environment variable, 122
`visudo(8)` command, 110–111
VLAN (virtual local area network), 223–224
    and OpenBSD install, 42
`vmemoryuse` variable, 96
`vm.swapencrypt.enable` sysctl, 348
VMware, 19, 450
`vnconfig(8)`, 153, 154
vnode (virtual node). 151
    attaching to disk images, 154
    detaching from images, 154
    vs. inodes, 150–151
volumes in OpenBSD manual, 4

W

web applications, 461
web browser, `lynx(1)` text-mode, 262
web server
    installing OpenBSD from, 23
    on OpenBSD, 229
websites, on OpenBSD content, 8
weekly maintenance, 282
welcome message, default for user, 87
`welcome` variable, 97
`_whatdb` keyword, 264
`whatis(1)`, 5–6, 10
    database, 264
`wheel` group, 88–89, 106
    unlimited `sudo` access for, 114
wildcard, in command alias, 115
windows in `cwm`
    creating, 332–333
    managing, 333
windows in `tmux`
    changing current, 326–327
    names, 326, 327
    terminating, 327
Windows NT operating systems, disk images for, 40
word sysctls, 346
write caching, 136