From Cellular Memory to Language Modelling: An Independent Profile, Biological Assessment and Audit of CellAI

Provenance, profiling, data mining, baselines and evaluation integrity of a biology-inspired sequence model

3 November 2026

Subject: repository `odin-loki/CellAI` at commit `a109790` (4 commits, 31 May – 4 Sep 2026), with provenance material from `odin-loki/Ideas` and `odin-loki/Cypha`. **Version:** 1.1 (3 November 2026). Version 1.0 (same day) lacked the biological and provenance analysis, and contained errors corrected here (see *Revision note*). **Artefacts:** every figure, number and script referenced here is in `docs/audit/`: `figures/`, `data/`, `scripts/`. **Authorship and AI assistance:** see the statement at the end of the paper.

Abstract

CellAI is a research codebase that tries to build a language model from the biology of non-neural cellular memory, as an alternative to attention. We trace its origin to Kukushkin et al. (2024, *Nature Communications* 15:9635), which showed that human kidney and neuroblastoma cell lines display the **massed-spaced learning effect**: four spaced 3-minute pulses of forskolin/TPA induce stronger and longer-lasting CREB-dependent transcription than one 12-minute "massed" pulse, and the effect depends on ERK and CREB. CellAI's first mathematical model encodes that experiment directly: forskolin and TPA doses, 3–12-minute pulses, 10–30-minute intervals, ERK/CREB state variables and a luciferase output. It then abstracts these into a generic reaction–diffusion ODE with Hebbian/BCM-style plasticity. Three generations of models (v1–v3) and a 36-experiment architecture search (E0–E35) follow.

We studied the full system in three ways:

- **Profiling:** runtime measurements on CPU.
- **Mining:** static analysis of 12k lines of code and 12.6k lines of documentation, a table of every experiment, and the raw Round 1–4 result files recovered from the author's public git history.
- **Testing:** count-based baselines under the project's exact data, split and evaluation protocol, and the founding paper's protocols run against CellAI's own dynamics.

Findings on biology.

- **The founding phenomenon is lost.** CellAI's core equation is provably blind to stimulus spacing: its response depends only on total exposure, so spaced and massed training give identical memories (ratio 1.000). The implemented PDEs show no spacing effect either (spaced/massed 0.85–0.96 for the dense PDE; 1.1–1.2 with no consistent order for the spectral PDE). A minimal adapting-kinase → ERK → CREB cascade with positive feedback does reproduce the observed ordering (ITI 10 > 20 > 30 min ≫ massed).
- **The "BCM" rule is not BCM.** It can only potentiate. In v1/v2 it drives the Hebbian matrix to the all-ones matrix (rank 1 after about 4k tokens; every entry at the +1 clamp by 20k), which maps every input to the same direction.

- **Other components have no biological content.** The dense PDE cannot respond to input from its zero initial state. The v2 “resonance”, “crystal lattice” and “Kuramoto” terms reduce to a scalar gain, a fixed rank-27 linear map, and an input-independent bias.

Findings on language modelling.

- **Champions score at unigram level.** On the project’s own headline metric (held-out text+code NLL), the reported champions score 7.85–8.04 nats/token. A smoothed **unigram** model scores **7.87–7.91** on the same documents; Kneser–Ney bigram and trigram models score **5.46–5.52** and **4.89–4.99**.
- **The best run bypasses the cell.** The best run, E34 (7.30), gains from a zero-initialised path that adds the current token’s embedding straight to the output: a learned bigram path around the cellular core.
- **Every Wave 2–4 result is contaminated.** About 85% of the eval documents for E22 and E27–E35 were in the training data of their ancestor checkpoints, because scripts seed their shuffles at import time.
- **Headline figures are wrong.** “966,000×” compares a training loss with a held-out score (the like-for-like ratio is about 2,700×). “125.8 M parameters” is 26.0 M. E20’s macro NLL is 5.508 in the raw data, not 5.190.

The project documents its failures unusually candidly, and several of its own diagnoses are confirmed. Its central claims are not supported by the evidence in the repositories: that cellular-memory dynamics learn useful linguistic context, and that the model preserves the biology it was built on. We describe what a faithful and testable version would need.

Revision note (v1.0 → v1.1)

Version 1.0 of this audit (committed earlier the same day) is superseded. Changes:

- **Added:** the biological roots and provenance (§2), the in-silico massed-spaced test (§2.5, Fig. 8), the Hebbian saturation result (§8), verification against recovered raw results (§6.4), a bibliography audit of the original papers (§6.5, Appendix C), and a full reference list with DOIs.
- **Corrected E20.** The true E20 is SpectralPDE + MultiScale + **SparseHebbian, no resonance, 53,512,480 parameters** (`arch_search/run_arch_search_v3_resume.py:122`, confirmed by the raw result’s `info` field). v1.0 profiled a superseded configuration from `run_arch_search_v3.py` (full Hebbian + per-frequency resonance, 53.78 M parameters). All E20 figures were re-measured.
- **Corrected the per-modality comparison.** The reset-regime runs are slightly *better* than unigram on text (by 0.01–0.22 nats) and *worse* on code (by 0.15–0.30 nats); the continuous run E25 is worse on both. v1.0 said “no better on text”.
- **Corrected E21 vs E25.** Their warm macro NLLs (7.229392 vs 7.229248) are a genuine near-coincidence with different per-domain values. v1.0 suggested a transcription error.
- **Corrected the contamination analysis.** v1.0’s original split re-derivation used an import order that hid the import-time seed. The corrected table (§9.1) reflects each script’s natural import order.

---

1 Introduction

CellAI asks a legitimate and interesting question: can the memory mechanisms of ordinary cells (kinase cascades, transcriptional feedback, plasticity) be turned into a working sequence model? The repository holds three model generations (v1, v2, v3), a shared core library (`cellai_core/`), domain data pipelines, seven generations of architecture-search drivers (`arch_search/run_arch_search*.py`), and two papers:

- `docs/CELLULARAI_PAPER.md`: v1/v2 architecture, training, and bug archaeology.
- `docs/ARCH_SEARCH_PAPER.md`: the E0–E35 search.

These are supported by `docs/EVALUATION_REPORT.md`, `docs/ARCH_SEARCH_FAILURE_LOG.md`, and design documents under `docs/math_models/`, `docs/architecture/` and `docs/research/`.

Neither paper cites the experiment the project is named after. The biology appears in them as Turing patterns, Hebbian/BCM plasticity and Kuramoto oscillators. The actual starting point, a 2024 study of memory in non-neural cell lines, appears only in a research-plan document. This audit therefore does two things.

1. **Biology.** We reconstruct the line from that biology to the code and ask, quantitatively, whether the model keeps the property it was built on.
2. **Machine learning.** We check every empirical claim against code, raw data and appropriate baselines.

Contributions

1. **Biological roots and provenance (§2):** the founding experiment, its scientific context, the timeline from paper to code, a component-by-component fidelity assessment, an in-silico replication of the founding protocols on CellAI's dynamics, and the machine-learning lineages the project re-derives without citing.
2. **Profile (§5):** parameters, latency, scaling exponents, op-level profiles and gradient flow for v1, v2, v3 and the true E20/E34 configurations.
3. **Data mining (§6):** a 38-row experiment table, a claims-vs-code audit, verification against recovered raw results, and a bibliography audit of the original papers (89 references).
4. **Baselines (§7):** unigram/bigram/trigram models under the exact records, split and `arch_eval_v1` protocol, plus a parameter-matched training probe.
5. **Mechanism (§8), evaluation integrity (§9), engineering (§10), discussion and recommendations (§11–12).**

---

2 Biological roots and provenance

2.1 The founding experiment: Kukushkin et al. (2024)

The repository's own description of itself is "an AI based off a Cellular Learning". Its research plan states that it is "inspired by the groundbreaking findings in Kukushkin et al. (2024) demonstrating massed-spaced learning effects in non-neural cells" (`docs/research/computational_research_plan.md:5`). The author also archived a copy of that paper alongside the code (`odin-loki/Ideas`, `Cell AI/docs/The massed-spaced learning effect in non-neural human cells.md`, commit `79a03a7`; earlier as a PDF in commit `7e24624`).

The study (verified against the full text, PMC11544106):

Aspect	Kukushkin, Carney, Tabassum & Carew (2024), *Nat. Commun.* 15:9635
Question	Is the spacing effect, a hallmark of memory, a property of neural circuits or of conserved intracellular signalling?
Cells	SH-SY5Y (human neuroblastoma) and HEK293 (human embryonic kidney), stably expressing a CRE-driven, PEST-destabilised luciferase (`pGL4.29[luc2P/CRE/Hygro]`, "CRE-luc")
"Training"	Forskolin 2 µM (adenylyl cyclase → cAMP → PKA) and/or TPA 2 nM (PKC), in 3-min pulses; 4 pulses at inter-trial interval (ITI) 10, 20 or 30 min; one 12-min "massed" pulse; two-pulse controls
"Memory" readout	Luciferase at 2, 4 and 24 h; P-ERK/ERK and P-CREB/CREB (Western); nuclear P-ERK (immunofluorescence)
Repetition effect	TPA+forskolin, 4 pulses vs 1: about 1.4× at 4 h (n = 3), 2.8× at 24 h (n = 14). TPA alone: +29% (1×) vs +391% (4×) over control at 24 h. Repetition slows "forgetting"
Spacing effect	Spaced > massed at 24 h in every condition. Optimal ITI 10 min (TPA, TPA+forskolin) or 20 min (forskolin), falling with longer ITI. Two pulses are not sufficient
Mechanism	Spaced training gives stronger P-ERK, P-CREB and nuclear ERK. MEK inhibitor U0126 (10 µM) and CREB–CBP inhibitor 666-15 (1 µM) abolish the spacing effect. 666-15 also lowers P-ERK, suggesting CREB → ERK positive feedback
Generality	Replicated in HEK293, a line with no neural origin
Authors' conclusion	"Canonical features of memory do not necessarily depend on neural circuitry, but can be embedded in the dynamics of signalling cascades conserved across different cell types"

The computational content of this result is specific. A cell is a **temporal pattern detector**: its long-term output depends on how stimulation is distributed in time, not only on how much there is. Repetition changes both the amplitude of the memory and its **rate of decay** (an Ebbinghaus-style forgetting curve).

2.2 Scientific context

The study sits in a long line of work. These are the concepts a cellular-memory model has to answer to.

- **The spacing effect.** Distributed practice beats massed practice. This was first documented by Ebbinghaus (1885) and has since been found from humans to invertebrates. In *Aplysia*, spaced training produced long-term habituation (Carew, Pinsker & Kandel, 1972). In *Drosophila*, spaced (not massed) training produces protein-synthesis-dependent long-term memory (Tully et al., 1994), which requires CREB (Yin et al., 1994). Kandel (2001) reviews this "dialogue between genes and synapses".
- **ERK as the timer.** The optimal interval is set by ERK kinetics. In *Drosophila*, the phosphatase SHP2 tunes the spacing optimum through ERK (Pagani et al., 2009). In *Aplysia*, the precise timing of ERK phosphorylation/dephosphorylation decides whether a repeated trial helps or hurts (Kukushkin, Tabassum & Carew, 2022). Smolen, Zhang & Byrne (2016) review the mechanisms. Zhang et al. (2012) used a two-pathway kinase model (PKA and

ERK) to design a non-uniform training schedule that enhanced memory, a direct precedent for computational modelling of spacing.

- **Memory in signalling networks.** Biochemical networks can be bistable and store state without neurons: emergent memory in coupled pathways (Bhalla & Iyengar, 1999) and the all-or-none MAPK switch in *Xenopus* oocytes (Ferrell & Machleder, 1998). Persistence of CREB-dependent transcription through positive feedback is one such mechanism, invoked in Kukushkin et al.'s discussion.
- **Cognition in single cells.** Whether single cells *learn* is old and contested: Gelber's *Paramecium* conditioning (Gelber, 1952), reconsidered by Gershman et al. (2021); habituation hierarchies in *Stentor* (Dexter, Prabakaran & Gunawardena, 2019). Lyon et al. (2021) argue for "basal cognition". Kukushkin et al. (2024) is the cleanest modern demonstration of a memory hallmark in non-neural mammalian cells.
- **Synaptic-plasticity vocabulary used by CellAI.** CellAI's design documents use: Hebbian learning (Hebb, 1949); LTP (Bliss & Lømo, 1973); the BCM sliding threshold (Bienenstock, Cooper & Munro, 1982; Intrator & Cooper, 1992; Cooper & Bear, 2012); metaplasticity (Abraham & Bear, 1996; Abraham, 2008); synaptic tagging (Frey & Morris, 1997); synaptic scaling (Turrigiano et al., 1998); and multi-timescale synaptic memory (Fusi, Drew & Abbott, 2005; Benna & Fusi, 2016).
- **Reaction–diffusion and its neural analogue.** Turing (1952) showed that two interacting species with different diffusion rates can form spatial patterns. The neural counterparts are the Wilson–Cowan equations (Wilson & Cowan, 1972, 1973) and Amari's neural fields (Amari, 1977), which produce Turing-type cortical patterns (Ermentrout & Cowan, 1979). These are the appropriate biological references for a "cellular PDE", and neither CellAI paper cites them.

2.3 From the experiment to the code: provenance

Timeline. Assembled from the papers, the CellAI repository, and the author's public `Ideas` and `Cypha` repositories.

Date	Event	Evidence
7 Nov 2024	Kukushkin et al. published (received 21 Feb, accepted 28 Oct 2024)	doi:10.1038/s41467-024-53922-x
Nov 2024 – Feb 2025 (inferred)	**Cell AI v1 design documents**: README, "Mathematical Modeling of Cellular Memory Systems for AI Applications" (v2.0), research plans citing Kukushkin as "recently published"	`Ideas/docs/site/Cell AI/Cell AI/*`; CellAI `docs/math_models/core_math_model.md`, `docs/research/*`
26 Feb 2025	Cell AI v2 "Thinking", Brain Model and v3/OICFHS design dialogues. Exported claude.ai conversations with **zero lines of executable code**; they presuppose "an already-existing Cell AI"	`Cypha/docs/history/eras/00-prototypes.md`
≤ 3 Apr 2026	First implementation trained (v1/v2 on math, NLP, code); evaluation report	`docs/EVALUATION_REPORT.md` (dated 2026-04-03)
≤ 18 Apr 2026	Architecture search Rounds 1–4 (E0–E26) completed; raw results committed to `Ideas`, untracked a day later	`Ideas` commits `7e24624` (18 Apr), `16e7f86` (19 Apr)

Date	Event	Evidence
31 May 2026	CellAI repository created (single 28k-line commit including both papers)	`eb18003`
5 Jun 2026	Waves 2–4 (E27–E35) tooling and results	`429615e`, `7be5113`
4 Sep 2026	AGPL-3.0 + commercial licence	`a109790`

The author's stated design philosophy, recorded in the v2 design dialogue, matters for what fidelity one should expect:

> "What we are looking for is a model that is bastardised to be computational. It wont be an exact match to that system." (`Cypha/docs/history/archive/prototypes/Cell AI v2 Thinking Convo Log.txt:1015`)

We take this at face value. The question is not whether CellAI is a faithful biophysical model (it was never meant to be). The question is whether it keeps the **computational property** that motivated it: sensitivity to the temporal structure of input, and history-dependent persistence.

The translation chain. Each level of abstraction removes structure. Table 1 tracks each element of the biology through the design model to the code.

Table 1. From biology to code.

Biology (Kukushkin 2024)	Design model (`core_math_model.md`)	Implementation (`cellai_core/`)	What is lost
Forskolin 2 µM / TPA 2 nM pulses, 3 min, ITI 10–30 min, 1–4 pulses	§1.1: "pulse duration 3–12 min, ISI 10–30 min, 1–4 cycles, forskolin 0.1–10 µM, TPA 0.1–10 nM"	One token = one Euler step (dt = 0.01); input = token embedding	Physical time and pulse structure. A token sequence has no notion of interval
PKA / PKC activation (two pathways, different sensitivities: PKA to duration, PKC to number of events)	I_{PKA}, I_{PKC}, composite signals	A single input vector	The two-pathway, two-sensitivity structure Kukushkin identified
ERK phosphorylation and nuclear translocation (the "timer")	ERK_T, ERK_P, $ERK_{N/C}$ state variables	Generic $N \times D$ partition state S	Kinetic species, time constants, compartments
CREB phosphorylation, CREB–CBP, transcriptional persistence and feedback	$CREB_T$, $CREB_P$, $CREB_{CBP}$	No counterpart; nearest is the memory ring buffer (detached)	Positive feedback, bistability, persistence
PEST-luciferase (short-lived reporter = readout of current transcription)	M: luciferase, phospho-ratios, "memory strength"	Output projection to 100,277-token logits	The readout becomes a vocabulary distribution

Biology (Kukushkin 2024)	Design model (`core_math_model.md`)	Implementation (`cellai_core/`)	What is lost
Signalling dynamics	§2.1.1: $\frac{dS}{dt} = f(I,S,t) - \gamma S + D\nabla^2 S + \eta$, with $f_i = \sigma(I-\theta_i)\, g_i(S)$	`CellularPDE`: $S \leftarrow S + dt\,[\sigma(IW^\top) \odot \tanh(SE^\top) - \gamma S + D\nabla^2_{\text{ring}} S + \eta\epsilon]$	Multiplicative input gating survives, with $g(0) = 0$ (§8.1)
(Not in Kukushkin)	§2.3.1 "state-dependent plasticity" $\eta_0 e^{-\lvert S_i - S_j\rvert/\sigma}\, \sigma(I-\theta)$; §2.3.2 metaplasticity $\dot\theta = \alpha(M-\theta) + \beta\int M$	`MetaplasticityLayer`: $W \mathrel{+}= 0.001\,(\eta' H)(\eta' H)^\top$, clamp ± 1	Adds synaptic-plasticity vocabulary not present in the cellular experiment

The design model is a reasonable *abstract template* of a signalling cascade. The implementation keeps its algebraic shape but not the properties that produce the spacing effect: two pathways, a slow intermediate integrator with an interval-matched time constant, adaptation, and self-sustaining feedback. Our cross-check of the parameter ranges agrees with an independent reviewer's (Appendix C). The 3/12-minute pulses, 10/20/30-minute intervals and 1–4 repetitions match the paper. The concentration ranges bracket the working doses (2 µM, 2 nM) but are not the paper's tested ranges (0.08–50 µM forskolin, 0.08–200 nM TPA).

Original claims. The original Cell AI README (`Ideas/docs/site/Cell AI/Cell AI/Readme.html`) claims:

- 100–1000× faster than transformers, 50–200× faster than neural networks, and training "2000× faster than transformers in best cases";
- instant one-shot memory formation, with "no need for traditional backpropagation";
- 95–99% accuracy on familiar patterns, and 80–90% when compressed to 1–5 MB.

No benchmark, dataset or measurement supporting these figures exists in any of the three repositories. The implemented system is trained by backpropagation through time. Its cost per token is dominated by the vocabulary projection, as in any language model of this vocabulary size (§5.2). Its quality on text and code is at unigram level (§7). The `Cypha` history document independently lists similar unmeasured figures from the same era as "claims that do not hold up".

2.4 Component-by-component biological fidelity

Table 2. Each CellAI component's claimed biological basis, the actual biology, and what the code does.

Component	Claimed basis	What the biology actually is	What the code does	Verdict
Cellular state	ERK/CREB signalling state	Multiple kinase species with distinct activation and inactivation time constants, nuclear translocation, transcriptional feedback	Generic leaky ODE on a D-vector; "time" = token index; $dt = 0.01$	Kinetic structure not retained

Component	Claimed basis	What the biology actually is	What the code does	Verdict
Reaction–diffusion "CellularPDE"	Turing (1952) morphogenesis	Two or more interacting species with *different* diffusion rates on a spatial domain (neural analogue: Wilson–Cowan / Amari fields)	One field. The "Laplacian" is `torch.roll(·, dims=0)` across 2–8 *partitions*, not space or features. No second species, so no Turing instability is possible	Name only
`MetaplasticityLayer` ("exactly implements BCM", main paper §3.4)	BCM sliding threshold	$\Delta w \propto x\,\phi(y, \theta_M)$ with ϕ changing sign at θ_M: depression below, potentiation above. θ_M is superlinear in mean postsynaptic activity (e.g. $\theta_M = E[y^2]$)	$\Delta W = 0.001(\eta' H)(\eta' H)^\top$ with $\eta' = e^{-\lvert s-m\rvert} \in (0, 1]$ and $H = \sigma(x - \theta) \in (0, 1)$, so every increment is positive. θ tracks a "memory" vector linearly	Not BCM: potentiation only, saturates to rank 1 (§8.2)
Metaplasticity	Abraham & Bear (1996)	Prior activity shifts the thresholds for later LTP/LTD	θ shifts a sigmoid's input; it never flips the sign of plasticity	Analogy only
Eligibility $e^{-\lvert s-m\rvert}$	Synaptic tagging (Frey & Morris, 1997)	A protein-synthesis-independent tag that captures plasticity proteins and sets *persistence* (early → late LTP)	Scalar similarity weight on the outer product	Analogy only
Online plasticity at inference	LTP during behaviour	Plasticity is continuous	v1/v2: always on (potentiation only). **v3 SparseHebbian: off in `eval()`** (`sparse_hebbian.py:132`); every v3 champion is evaluated with frozen W	Absent from the v3 results
SparseHebbian top-k	Sparse cortical connectivity (Braitenberg & Schüz, 1998); NMDA coincidence; "Sanger's rule"	Sparse activity / k-winners-take-all exists in biology (e.g. the fly olfactory circuit: Dasgupta, Stevens & Navlakha, 2017). Sanger's GHA needs a decorrelating subtraction to extract principal components	Top-k mask of a positive activity vector, then a *dense* $D \times D$ outer product. No decorrelation, no PCA convergence	Plausible k-WTA idea; the Sanger and connectivity citations are misapplied (Appendix C)
MultiScale partitions (fast every token, slow every 8)	Minicolumns; multi-timescale memory	Synaptic and cellular memory spans seconds to days through cascades of processes (Fusi et al., 2005; Benna & Fusi, 2016)	Clockwork-RNN-style update schedule; the slow-stream gradient falls to about 1e-7 (§5.4)	Sound ML idea (Koutník et al., 2014 lineage); slow stream nearly disconnected

Component	Claimed basis	What the biology actually is	What the code does	Verdict
Kuramoto oscillators	Buzsáki & Draguhn (2004); Kuramoto (1984)	Coupled phase oscillators; in ML, phases can *be* the representation (Miyato et al., 2025)	N phases with `.detach()` each step; `natural_freq` gets exactly zero gradient; output added as a bias	Input-independent drift
"Resonance" (v2)	Frequency-selective gain	Oscillations bias input selection	$\mathrm{Re}(\mathcal{F}^{-1}(\mathcal{F}(s)e^{i\phi})) = \cos\phi \cdot s$ exactly	A scalar gain
Crystal lattice (v2)	Lattice field theory	No biological analogue	Fixed symmetric rank-27 linear map $\Phi^\top \mathrm{diag}(T)\Phi$	Not biology
Spacing effect and forgetting curve	**The founding phenomenon**	Spaced > massed; repetition slows decay (Kukushkin 2024)	Not modelled; provably absent from the core equation (§2.5)	**Lost**

2.5 Does CellAI show the massed-spaced effect? An in-silico test

Analytical result. Take CellAI's core equation (`core_math_model.md` §2.1.1) in its simplest form: a single state, $g(S) = S$, no diffusion or noise.

$$\frac{dS}{dt} = (\sigma(I(t) - \theta) - \gamma)\,S \quad \Rightarrow \quad S(T) = S(0)\ \exp \int_0^T (\sigma(I(t) - \theta) - \gamma)\,dt.$$

The integral depends on the stimulus only through the *total time spent at each input level*. Any two protocols with equal total exposure (four 3-minute pulses vs one 12-minute pulse) therefore give **identical** states at every time after both have ended, whatever the spacing. The decay rate after training is $\sigma(-\theta) - \gamma$, independent of the training history, so repetition cannot change the forgetting rate either. A more general linear time-invariant reading, $S(T) = \int h(T - t)\,\varphi(I(t))\,dt$ with a single exponential kernel, makes later-ending protocols marginally stronger. That predicts response *increasing* with ITI, the opposite of the cells' ITI 10 > 20 > 30.

Numerical test. We drove four systems with Kukushkin's protocols, using 0.25-min steps over 24 h and the readout relative to an unstimulated control run with identical noise (`scripts/spacing_effect.py`, Fig. 8):

- **A:** the core equation above;
- **B:** the repository's own `CellularPDE`;
- **C:** the repository's `SpectralPDE`;
- **D:** a minimal reference cascade.

The reference cascade has three stages: an adapting kinase (incoherent feed-forward, $\tau = 3$ min); an ERK-like integrator ($\tau = 12$ min, cooperative output); and a CREB-like stage with positive feedback and a 6-h decay, read out through a 60-min luciferase.

Table 3. 24-h response divided by the massed-protocol response. B and C are means over 5 random initialisations ± s.d.

Protocol	A. Core equation	B. Dense PDE (basal state 0.1)	C. SpectralPDE	D. Reference cascade	Cells (Kukushkin 2024)
1 × 3 min	0.002	0.26 ± 0.00	0.41 ± 0.33	0.44	Weaker than 4×; decays by 24 h

Protocol	A. Core equation	B. Dense PDE (basal state 0.1)	C. SpectralPDE	D. Reference cascade	Cells (Kukushkin 2024)
2 × (first + last)	0.015	0.47	0.56	1.6	Insufficient (no sustained expression)
Massed 12 min	1	1	1	1	1
4 × ITI 10	**1.000**	0.96 ± 0.03	1.23 ± 0.38	**211**	> massed, optimal (TPA, TPA+fsk)
4 × ITI 20	**1.000**	0.90 ± 0.07	1.09 ± 0.06	174	> massed
4 × ITI 30	**1.000**	0.85 ± 0.11	1.15 ± 0.11	106	> massed, smaller than ITI 10

From the zero initial state used in training and evaluation, the dense PDE produces only noise-level responses (about 10^{-7}; §8.1), so panel B uses a basal state of 0.1.




Fig. 8. Does CellAI reproduce the massed-spaced effect of its founding paper? Panel D is illustrative: parameters were chosen by a small grid search for the qualitative ordering, not fitted to data.

Interpretation.

- **None of CellAI's dynamics show the spacing effect.** The core equation is exactly exposure-only. The dense PDE slightly *favours* massed training. The spectral PDE gives tiny responses with no consistent ITI ordering across seeds.
- **The reference cascade reproduces the qualitative biology.** It shows ITI 10 > 20 > 30 ≫ massed ≈ 1× ≈ 2× at 24 h, and repetition changes the forgetting curve: the single pulse decays from 0.036 at 4 h to 0.002 at 24 h, while four spaced pulses grow from 0.25 to 0.81.
- **What it takes.** Three ingredients, each grounded in the biology above, are enough:
    1. **Adaptation**, so repeated onsets beat sustained exposure (receptor or kinase desensitisation; PKC's sensitivity to the *number* of events);
    2. **An intermediate integrator** whose time constant is matched to the inter-trial interval (ERK; cf. Pagani et al., 2009; Kukushkin et al., 2022);
    3. **A cooperative, self-sustaining downstream stage** (CREB with positive feedback; bistable MAPK).

CellAI's equations contain none of these in a working form. The design documents name ERK and CREB, but the implemented dynamics are a single leaky stage whose input enters multiplicatively through a sigmoid.

2.6 Machine-learning lineages the CellAI papers do not cite

Several of CellAI's ideas have established, working counterparts. Citing them would sharpen what is new.

- **Fast weights and online plasticity during inference.** Hinton & Plaut (1987); Schmidhuber (1992); Ba et al. (2016); "linear transformers are fast-weight programmers" (Schlag, Irie & Schmidhuber, 2021); differentiable plasticity (Miconi, Clune & Stanley, 2018). More recently, test-time training layers (Sun et al., 2024) and Titans (Behrouz, Zhong & Mirrokni, 2024) make "learning during the forward pass" competitive. In all of these the fast-weight update is error-driven or key–value associative, and so it can store *which* input followed *which*. CellAI's positive-only outer product cannot.
- **Fixed or slow dynamical cores.** Reservoir computing (Jaeger & Haas, 2004; Maass, Natschläger & Markram, 2002) and structured state-space models (Gu, Goel & Ré, 2022; Gu & Dao, 2023).
- **Spectral (FFT) mixing.** Circulant projections (Cheng et al., 2015), FNet (Lee-Thorp et al., 2022) and Global Filter Networks (Rao et al., 2021) are direct precedents for SpectralPDE.
- **Sparse activity.** Sparse coding (Olshausen & Field, 1996), k-sparse autoencoders (Makhzani & Frey, 2013), k-WTA networks (Ahmad & Scheinkman, 2019).
- **Multi-timescale recurrence and oscillators.** Clockwork RNN (Koutník et al., 2014), hierarchical multiscale RNNs (Chung, Ahn & Bengio, 2017), Kuramoto-based neurons (Miyato et al., 2025), neural cellular automata (Mordvintsev et al., 2020).

---

3 System overview (as implemented)

Every version shares the same skeleton. For each token x_t (cl100k_base, $V = 100,277$):

1. Embed: $e_t = E[x_t]/\sqrt{D}$, with the embedding E tied to the output.
2. Advance the partition state with a PDE step, then aggregate to a_t.
3. Memory: $m_t = \tanh(W_m[e_t \| a_t])$, with inputs detached.
4. Hebbian layer: $h_t = (W_H e_t) \odot \sigma(Ga_t + b)$, where W_H is changed in place by the outer-product rule.
5. Output state: $o_t = W_o h_t$ (+ v2/v3 extensions, + optional bypass $\sigma(\alpha)Pe_t$).
6. Logits: $o_t E^\top$, trained with cross-entropy and truncated BPTT over 64-token segments.

The cellular aggregate therefore **gates** a linear function of the current token. Table 2 gives what each component computes. The search ran in seven rounds/waves:

- **Rounds 1–3 (E0–E20):** headline metric "macro NLL", the mean of text, code and math NLL.
- **Round 4 (E21–E26):** macro NLL plus a text+code caveat.
- **Waves 2–4 (E27–E35):** "text+code NLL" under protocol `arch_eval_v1`: 50 documents per modality, first 256 tokens, reset state, per-document mean NLL averaged over documents.

The metric changed because math, scored on generator-templated lines, fell to about 0.5 nats and dominated the macro average.

---

4 Method

Activity	How	Where
Runtime profiling	CPU (4 cores, 15 GB, no GPU), torch 2.15; median-of-N timings with warm-up; `torch.profiler`	`scripts/profiling/`, `data/profiling_results.json`
Static mining	LOC/complexity (radon), import graph, constructor defaults, `git log`, pytest + coverage	§6
Experiment table	Every E-number from the papers, configs and scripts; the paper's own verdict, normalised	`data/experiments.csv`
Raw-results recovery	`results.json` – `results_v4.json` (E4–E26) recovered from `odin-loki/Ideas` commit `7e24624` and compared with the papers	§6.4
Split re-derivation	Each driver imported in its natural order; `build_dataset` called on uniquely labelled dummy records; permutations compared	`scripts/split_simulation.py`
Baselines	Records rebuilt as `scripts/run_full_pipeline.py` writes them (wikitext-103 train lines ≥ 50 chars; code_search_net Python with docstring prefix, 8k-char cap), first 6,000 per domain, the project's split permutations, `arch_eval_v1` scoring; Kneser–Ney smoothing (Kneser & Ney, 1995; Chen & Goodman, 1999)	`scripts/ngram_baselines.py`, `data/ngram_split_*.json`
Training probe	v1, v2, v3 variants vs a 2-layer Transformer, a bigram MLP and unigram, all about 6.4 M parameters (D = 64), 128 k tokens of the repository's own docs	`scripts/profiling/train_probe.py`
Biological test	Kukushkin protocols on CellAI's dynamics (§2.5)	`scripts/spacing_effect.py`, `data/spacing_effect_results.json`
Literature checks	Crossref and arXiv APIs; Kukushkin full text (PMC11544106)	References; Appendix C


Limitations.

- No checkpoints are available; Wave 2–4 result files were never committed. Reported numbers for those waves are compared as published.
- Our data reconstruction uses current HuggingFace parquet exports. Our training-token count (2.19 M text+code) matches the paper's corpus description (2.3 M including math).
- No GPU was available, so champion-scale training was not repeated.

5 Profile

5.1 Parameters: almost everything is the embedding

Model	D	Total params	Non-embedding	Embedding share
v1 default	256	25,999,104	328,192	98.7%
v2 default	256	26,007,075	336,163	98.7%
v3 default (`V3Config()` = v1 architecture)	256	25,999,104	328,192	98.7%
E20 (spectral + multiscale + sparse Hebbian)	512	**53,512,480**	2,170,656	95.9%
E24 / E27 (D = 1024)	1024	108,005,688	—	—
E34 (E27 + bypass)	1024	109,054,265	6,370,617	94.2%



- **Wrong headline parameter count.** The README and main paper state **125.8 M** ("25.5 M backbone + 100.3 M embedding"). The embedding is 100,277 × 256 = 25.67 M and the cellular backbone is 0.33 M. `EVALUATION_REPORT.md` has the correct figure (25,999,104). The E20, E23 and E24 counts in the search paper match the raw results.
- **Dead parameters.** `SpectralPDE.input_gate` is a $D \times D$ layer created but never used in `step()`. In E20 it accounts for 327,680 of the 333,344 PDE parameters (98.3%).


5.2 Latency and where time goes

Model	Cell step (ms)	+ vocab head (ms)	Inference tok/s	Train tok/s (repo method)
v1 default	0.33	1.71	587	24.1
v2 default	0.72	2.26	442	23.6
E20	1.06	5.90	170	15.7
E34	1.20	10.65	94	7.8

All figures are CPU, 4 threads, medians; ±20–30% container noise.


- `torch.profiler` on one 32-token E20 training segment: `aten::mm` takes 59% of time and gradient accumulation (`add_`) 17%. **FFT ops take about 0.6%.**
- The hot path is the tied vocabulary head, run once per token inside the Python time loop.
- Because the head does not affect the recurrent state, and Hebbian updates are deferred until after `backward()`, one batched head per segment gives the same loss and gradient. It is **4.8× (v1), 9.1× (E20) and 7.3× (E34)** faster.
- The papers' "4.56 ms / 219 calls/s" and "~130k tok/s" time a single cellular step on a pooled encoding of a whole string, not per-token sequence processing.


5.3 Do the complexity claims materialise?



D	Dense fwd (ms)	Spectral fwd (ms)	Dense fwd+bwd (ms)	Spectral fwd+bwd (ms)
256	0.061	0.067	0.29	0.71
512	0.083	0.094	0.50	0.47
1024	0.207	0.135	0.88	0.62
4096	3.23	0.35	39.7	1.50

- **SpectralPDE.** Fitted log-log slopes (D ≥ 512) are 1.81 for dense and 0.63 for spectral. Spectral is slower up to D = 512 and only 1.5× faster at D = 1024.
- **SparseHebbian.** Latency is flat in k (slope 0.02). The implementation forms a dense $D \times D$ outer product and is 20–35% *slower* than the full layer at D ≤ 1024.
- **Sequence length.** Cost is linear (slope 0.8–1.0). There is no batching anywhere in training; batch size is 1.





5.4 Gradient flow

Model (D = 64 probe)	PDE grad norm (step 10 → 2000)	output_proj grad norm	Ratio
v1	W 1.3e-5 → 8.8e-5	103 → 127	~10^{-6}–10^{-7}
E20-like	fast 3.3e-3 / slow 3.5e-4 at step 2000	0.91	~10^{-3}–10^{-4}
E34-like	fast 0.17 → 3.2e-3	128 → 0.48	1e-3 → 7e-3

- The dense-PDE "gradient starvation" the paper reports is reproduced, and is worse than reported.
- The cross-scale links end at 1e-6–1e-7 (E20-like: `slow_to_fast` 2.9e-6, `fast_to_slow` 1.5e-6), so the slow stream is effectively disconnected.
- The resonance phase sits at a stationary point at initialisation ($\partial L/\partial\varphi = -2.3\text{e-}6$ at $\varphi = 0$, since $\frac{d}{d\phi}\cos\phi = 0$). Kuramoto `natural_freq` gets exactly 0. `MemoryFormation` detaches its inputs.

---

6 Data mining

6.1 Codebase census

Measure	Value
Python	73 files / 12,115 lines (8,243 source lines), plus `tools/Math-Gen.py` (5,248 lines)
Model core (`cellai_core` + v1/v2/v3)	1,333 source lines
Drivers (`arch_search` + `scripts`)	5,634 source lines
Markdown	30 files, 12,612 lines, ~74k words (docs : code words ≈ 1.75 : 1)
Highest complexity	`run_arch_search_v4.main` (cyclomatic 50, rank F)
Duplication	Successive `run_arch_search_vN` share 9–61% of their lines and import each other, chaining import-time side effects (§9.1)

Measure	Value
Tests	53 pass, 22 fail, 1 collection error; **17% line coverage**; 0% on `arch_search` and `routing`
Git	4 commits by one author. Everything to E26 lands in a single 28k-line commit


Every test failure is API drift, none numeric:

- the registry does not know `v3` (20 tests);
- `MemoryCellBase` was removed;
- `get_system_info` was renamed;
- `CellAIv3` no longer subclasses `CellAIv2`.

6.2 The experiment ladder

`data/experiments.csv` lists all 38 rows. Using the papers' own verdicts, 12 of 35 experiments succeeded (34%), 14 failed, 6 were neutral and 3 were partial.

Round/wave	Success rate
R1 (E0–E7)	2/7
R2 (E8–E14)	3/7
R3 (E15–E20)	3/6
R4 (E21–E26)	1/6
W2 (E27–E29)	2/3
W3 (E30–E32)	0/3
W4 (E33–E35)	1/3



1. **Macro NLL hides a plateau.** On text+code the trajectory is flat: E20 7.964 → E22 7.893 → E27 7.847, then eight runs between 7.847 and 7.870, until E34's bypass at 7.300.
2. **Three "experiments" are duplicates.** E9 ≡ E1, E12 ≡ E8, and E5 ≡ E0, all identical to full precision in the raw results. This is because the training loop bypassed `cellular_step()`, the paper's own "Bug 1".
3. **E0–E7 score worse than uniform guessing** (ln V = 11.5 nats) on text and code. Initial losses of 110–2,193 nats come from logits $= sE^{\top}$ with N(0,1) embeddings.
4. **Width barely helps.** D = 256 → 1024 improves text+code by about 0.1 nats.
5. **Routing never learned.** Six routing experiments score 24.7–34.5% on a 3-class task, against 33.3% chance.

6.3 Claims vs code

Claim (source)	Finding
“125.8 M parameters” (README; main paper §3.5)	**26.0 M** (§5.1)
“E20 … macro PPL 246.6, **966,000×** vs E0” (search paper abstract, §14)	966,000 = exp(19.3)/246.6, and 19.3 is E0’s **final training loss**. E0’s held-out macro NLL is 13.415, giving **~2,716×**
E20 macro NLL 5.190 (search paper §13.7, §14)	Raw result: **5.508** (= ln 246.6)
Main paper abstract: PPL “10,000–250,000”	Its own §5.6 reports 450 k–1.18 M
Main paper §5.4: math_v1 and code_v2 both “313.3 → 29.3”	`EVALUATION_REPORT.md`: math_v1 16.83 → 7.00, code_v2 313.32 → 29.27; the row is copied
SpectralPDE “67,600 params, 32× fewer FLOPs”	65,536 of those parameters are unused; no wall-clock gain below D = 1024
SparseHebbian “k^2 = 1,024 updates”, “O(D log D)”	Dense $D \times D$ outer product; latency independent of k
“Exactly implements the BCM sliding-threshold rule” (main paper §3.4)	Potentiation-only; not BCM (§2.4, §8.2)
“Online Hebbian adaptation at inference” (main paper §3.4, §6.1)	True for v1/v2 (potentiation only). For v3 champions, SparseHebbian is off in `eval()`
v1 “snapshot/restore for fairness”	W is changed by *every* forward pass, including `chat()` and `benchmark()`
E30 failed from a “random bypass init” (failure log)	The committed code zero-initialises the bypass with $\alpha_0 = -8$; the stated cause cannot be reproduced from this code
“OOD eval (E27): 7.847, no OOD gap”	Reshuffles the **same** eval set (`run_arch_search_v7.py:216`), and is equal to E27’s score to 3 d.p.
Champion of record	README: E20. `eval_protocol_v1.json`: E22/E25. `experiments.yaml`: E27/E29. Search paper §20: E34/E29
“Ring Laplacian”	`torch.roll(dims=0)` diffuses across 2–8 partitions; for N = 2 it reduces to $2(s_{\text{other}} - s_{\text{self}})$

6.4 Verification against recovered raw results

The raw results for E4–E26 survive in the author’s `odin-loki/Ideas` repository history (commit `7e24624`, 18 Apr 2026; untracked the next day). E0–E3 had been overwritten by a resume run. We compared them with the papers:

- **Confirmed.** Per-domain NLLs for E5–E26 match the papers’ tables, including E20 (text 8.052, code 7.875, math 0.597) and E24 (7.976 / 7.932 / 0.555). E20’s `info` records `hebbian_type = "sparse"`, `resonance_type = "none"`, 53,512,480 parameters, and n = 50 eval documents per modality.
- **Corrected.** E20’s macro NLL is 5.508, not 5.190.
- **Duplicates.** E5, E9 and E12 are bit-identical to E0, E1 and E8.
- **Hand-entered.** E22’s entry has rounded values (text 7.937, code 7.848, macro 5.428, PPL 227.7), only a first/last training-loss pair, and a free-text note. It was entered by hand, not written by the evaluation code.
- **Coincidence, not error.** E21 and E25 have macro NLL 7.229392 and 7.229248 with different per-domain values (8.228/7.905/5.555 vs 8.255/7.830/5.602).
- **Capped values.** Perplexities for E6, E7 and the “cold” continuous evaluations are all exactly exp(30) = 1.07×10^{13}, a cap in the code, not a measurement.

6.5 Bibliography audit of the original papers

All 89 references in the two papers exist (verified via Crossref, arXiv and publisher pages; details in Appendix C).

- **Author errors:** three (Frankle & “Carlin” → Carbin; a non-existent co-author “Adi, Y.” on Tallec & Ollivier, 2018; Grangier omitted from Grave et al., 2017).
- **Missing from the reference list:** four in-text citations.
- **Misused sources:** the serious problems are in how sources are used:
  - the “exactly BCM” claim;
  - Sanger’s rule credited with top-k PCA;
  - the metaplasticity chronology reversed (BCM 1982 predates Abraham & Bear’s 1996 coinage);
  - “Noam et al., 2020” (Shazeer, 2020; SwiGLU, not “SiGLU”);
  - “Liu et al., 2020, Transformers without Tears” (Nguyen & Salazar, 2019);
  - weight-agnostic networks described as “growing neural networks”;
  - the CTRL repetition penalty (divides logits; $\theta \approx 1.2$);
  - the lattice called a Tucker decomposition;
  - a uniform FFT phase rotation called a circular shift (it is $\cos \phi \cdot s$).
- **Founding work not cited:** neither paper cites Kukushkin et al. (2024).

---

7 Baselines: what the numbers mean

The project never reported a non-neural baseline on its own split. We built one, following the repository’s records, split permutations and scoring:


- **Split A** (drivers v1–v4): E21–E26.
- **Split B** (v3-resume and v5–v7): E20 and E27–E35. E20’s eval set is identical to split B in content and order.

Model (fit on the same ~2.2 M train tokens)	Split A text+code	Split B text+code	s.d. over 50-doc samples
Unigram (add-½)	**7.907**	**7.868**	0.047
Bigram, interpolated Kneser–Ney	5.522	5.458	0.10–0.11
Trigram, interpolated Kneser–Ney	4.991	4.895	0.13

CellAI run (reported)	Split	text+code	vs unigram	text vs unigram text	code vs unigram code
E20	B	7.964	**+0.10 (worse)**	−0.05	+0.24
E22 (E20 + 8k)	A	7.893	−0.01 (noise; contaminated)	−0.18	+0.15
E23 / E24 (D = 1024)	A	8.053 / 7.954	+0.15 / +0.05	−0.01 / −0.14	+0.30 / +0.23
E25 (continuous, warm)	A	8.043	+0.14	+0.14	+0.13
E27 (D = 1024, 16k)	B	7.847	−0.02 (noise; contaminated)	−0.22	+0.18

CellAI run (reported)	Split	text+code	vs unigram	text vs unigram text	code vs unigram code
E28, E31, E32, E33, E35	B	7.859–7.870	±0.01	—	—
E34 (bypass)	B	**7.300**	−0.57; **+1.84 vs bigram**	—	—

Unigram text NLL: 8.114 (A), 8.099 (B). Unigram code NLL: 7.700 (A), 7.638 (B).



* E22 is evaluated on documents ~84% of which were in its parent checkpoint's training set. 50-doc sampling s.d.: ~0.05 (unigram), ~0.11 (bigram).

Interpretation.


- With up to 108 M parameters and 16k training steps, the reset-regime champions predict held-out text+code about as well as a token-frequency table.
- Per modality, they are slightly better than unigram on text and consistently worse on code, the domain where local context matters most (a bigram model cuts code NLL from 7.6 to 4.9).
- The only run clearly better than unigram has a direct current-token path, and it recovers about a quarter of the gap to a count-based bigram.
- The 50-document sampling s.d. (≈0.05 unigram, ≈0.1 bigram) shows that most Wave 2–4 decisions, made on differences of 0.012–0.023 nats, are inside the noise.

7.1 Controlled probe

Every model was trained on the same 128 k tokens (the repository's 26 original documentation files) at about 6.4 M parameters (D = 64), with the same optimiser, 64-token windows and reset state:

Model	Val NLL (nats)
Unigram counts	7.958

Model	Val NLL (nats)
Bigram MLP (no state)	**7.674**
Transformer, 2 layers (under-trained at this budget)	8.028
v1 / v2 / v3-default	10.69 / 10.66 / 10.69
v3 E14-like (spectral + multiscale + full Hebbian + per-freq. resonance)	7.916
v3 E20-like (spectral + multiscale + sparse Hebbian)	**7.872**
v3 E34-like (+ bypass)	7.740



The figure's "v3_E20like" curve is the E14-like configuration (v1.0 label); the corrected E20-like run is in `data/train_v3_E20like_corrected.json`.

- The v3 recipes are a large improvement over v1/v2, confirming the *direction* of the E0 → E20 ladder.
- **No Cell variant beats a stateless bigram model.** v3 with the default config reproduces v1 bit for bit.
- The transformer result does not show Cell beating transformers. It is under-trained at this budget.

---

8 Mechanism: why the state carries little

8.1 The dense PDE cannot see its input

$$dS = \sigma(IW^\top) \odot \tanh(SE^\top) - \gamma S + D\nabla^2 S + \eta\epsilon.$$

- **The input only multiplies the state.** The input enters only multiplied by $\tanh(SE^\top)$, which is exactly 0 at $S = 0$, and every sequence starts there. This is the design model's $f_i = \sigma(I - \theta_i)\, g_i(S)$ with $g(0) = 0$. In a cell, basal kinase activity is never zero; in the code it is.
- **Measured.** With noise off, the state stays exactly 0 for any input. With default noise, two completely different 256-token sequences give states differing by **0.35%**.
- **Consequence.** This explains the "gradient starvation" the papers report ($\partial L/\partial W \propto \tanh(SE^\top) \approx 0$), and why it survived the state-gate fix.

8.2 The Hebbian matrix collapses to rank 1

Every increment of the v1/v2 rule is a positive outer product. Starting from $W \sim N(0, 0.01^2)$ with random inputs, in evaluation mode:

Tokens	Energy in top singular direction	Entries at +1 clamp
1,000	99.76%	0%
4,000	99.98%	0%
20,000	100.00%	**100%** ($\|W\|_F = 256 = D$)

After saturation, $Wx = (\mathbf{1}^\top x)\mathbf{1}$ for every x: all inputs map to the same direction (mean |cos| = 1.000 across 50 random inputs). `EVALUATION_REPORT.md` reports $\|W\|_F = 256.0$ for the trained nlp_v1 and code_v2 checkpoints, exactly the fully saturated value. That fits the main paper's finding that every prompt produced the same code tokens ("incinnati-court(track.HashSet …"). The paper attributes this to a "code-domain attractor"; the saturated Hebbian matrix is a more direct explanation. v3's SparseHebbian uses the same positive-only increment (training only), so the same upward drift applies, counterbalanced only by gradient updates.

8.3 SpectralPDE is a slow, mostly input-independent integrator

$S \leftarrow S + 0.01\,(\sigma(\cdot) - 0.05\,S + \ldots)$.

- Each token can move each coordinate by at most 0.01.
- The sigmoid's mean of about 0.5 produces a large common drift (|S| ≈ 19.7 after 256 tokens).
- The decay time constant ($1/(dt \cdot \gamma)$ = 2,000 tokens) is longer than any 256-token evaluation document.
- At initialisation, two different inputs give states differing by **0.2%**.

8.4 Readout

The prediction is $(W_H e_t) \odot \sigma(Ga_t + b) \rightarrow W_o \rightarrow$ tied logits. When the gate is nearly content-free, the best achievable is a low-rank bigram map plus the unigram prior in the tied embeddings, and Hebbian saturation degrades even that. E34's bypass adds a clean, trainable path Pe_t, which is why it is the only intervention that moves text+code NLL.

---

9 Evaluation integrity

9.1 Train/eval contamination through import-time seeding

`build_dataset()` shuffles the 18,000 documents with Python's global `random` and takes the last 15% as eval. Each driver seeds `random` at **import time**, and drivers import one another. Imported in their natural order:

- `run_arch_search.py` and v2–v4 resolve to one permutation (**split A**);
- `run_arch_search_v3_resume.py`, which trained the real E20, and v5–v7 resolve to another (**split B**).

Combined with checkpoint resumption:

Run	Trained from	Eval split	Eval documents seen in training by the model or its ancestors
E20	scratch, split B	B	0%
E21, E23–E26	scratch / E25, split A	A	0%
E22	E20 (split B)	A	**85.3%**
E27	E24 (split A)	B	**85.3%**
E28	E22 (A-trained)	B	**85.3%**
E29	E25 (split A)	B	**85.3%**
E30–E35, H3, "OOD"	E27	B	**85.3%** (inherited)

Every Wave 2–4 number, including the E34 champion, is scored on documents the starting checkpoint was trained on. Because these models barely beat unigram, the leak probably flatters them only slightly. It still invalidates them as clean held-out evidence.

9.2 Other protocol issues

- **Test-set model selection.** E33's early stopping, E34's "in-train peak 6.996" and Hyperband's learning-rate choice use the eval set at n = 30 (`training_v7.py:100-118`). E34's headline uses the final model.
- **"Best" checkpoint.** It is simply the latest: `harness.py:115` promotes whenever `tag == "best"`, which is passed on every eval.
- **E34's "frozen" phase is not frozen.** `freeze_except` only clears `requires_grad`; the deferred Hebbian update still changes W.
- **Warm continuous evaluation.** The 4,096-token burn-in is built from the eval set itself.
- **No error bars or seeds.** There is a single seed and no confidence intervals; 0.01–0.02-nat differences are reported as verdicts.
- **Mixed inference semantics.** v1/v2 evaluate with online Hebbian updates; v3 SparseHebbian evaluates with W frozen.

---

10 Engineering findings

Severity	Finding	Location
High	Per-token vocabulary head inside the time loop; batching per segment gives a 5–9× training speed-up	`train_step_sequential`
High	In-place `W.data` Hebbian updates on a tensor saved for backward bypass autograd's version check, so BPTT uses post-update W	`cellai_core/memory.py`
High	Train/eval split depends on import order (§9.1)	`arch_search/run_arch_search*.py`
High	Positive-only Hebbian rule saturates W to the all-ones matrix (§8.2)	`cellai_core/memory.py:184-187`
Medium	`SpectralPDE.input_gate` unused (65k–1M dead parameters)	`cellai_core/spectral_pde.py:107`
Medium	`freeze_except` does not stop Hebbian updates	`training_v7.py:132`, `sparse_hebbian.py:174`

Severity	Finding	Location
Medium	`MetaplasticityLayer` mutates weights in `chat()`/`benchmark()`/`eval()`	`cellai_core/memory.py`
Medium	Dense PDE draws `randn` noise during evaluation (nondeterministic eval)	`cellai_core/base.py`
Low	`padding_idx=0` freezes token 0 (`!`) at zero	`cellai_core/encoder.py:99`
Low	Registry and tests out of date; `_test_full.py` requires CuPy	`models/registry.py`, `tests/`

---

11 Discussion

What the project got right.

- It starts from a genuinely interesting result, memory hallmarks in non-neural cells, and asks whether it can be turned into computation.
- It diagnoses real pathologies and largely names them correctly: dense-PDE starvation, the dead resonance phase, router collapse, Bug 1, cold-start mismatch, and math inflation of the macro metric.
- It keeps a failure log and moved to a better metric partway through.
- SpectralPDE + MultiScale is a real improvement over the v1 design at matched size (10.7 → 7.9 nats in our probe).
- Decoding-time anti-repetition fixed degenerate generation loops.

What the evidence does not support.

- That the cellular state contributes useful linguistic context.
- That CellAI preserves the biology it was inspired by: the spacing effect and history-dependent forgetting are absent, and the plasticity rule is not BCM.
- The original speed and accuracy claims, and the O(D log D) and k^2 efficiency claims as wall-clock benefits.
- “966,000×”, “125.8 M”, online Hebbian adaptation in the v3 champions, and the Wave 2–4 rankings as held-out evidence.

Why the search plateaued. It optimised components sitting behind a gate whose input carries almost no information (§8). Changing width, steps, routing, resonance or auxiliary losses did not change how much input information reaches the state; the bypass routed around it.

A faithful and testable path. The founding biology says what a cellular memory model should do: be a temporal pattern detector with history-dependent persistence. That gives two clean experiments:

1. **A biology-first test.** Build a cell that passes the Kukushkin protocols (spaced > massed, optimal ITI, more than 2 pulses needed, slower forgetting after repetition), e.g. with the three ingredients of §2.5. Only then plug it into a sequence model.
2. **An ML-first test.**
   - Let input enter additively and at full strength. Replace $dt \cdot \sigma(\cdot)$ with $dt = 0.01$ by, e.g., $S \leftarrow (1-\lambda)S + \lambda\phi(W_s S + W_i e_t)$ with $\lambda \sim 0.1$–0.5.
   - Read out from the state directly.

- Replace the positive-only Hebbian rule with an error-driven or key–value fast-weight rule (§2.6).
- Ablate the state at evaluation.
- Compare against bigram and GRU baselines with confidence intervals.

---

12 Recommendations

Integrity.

1. Build the split once, save the document IDs, make every driver load them, and re-evaluate E22 and E27–E35.
2. Report unigram/bigram/trigram (`scripts/ngram_baselines.py`) and GRU baselines with bootstrap 95% CIs and at least 3 seeds.
3. Use a separate validation split for early stopping and Hyperband.
4. Commit result JSONs, eval manifests and logs.

Corrections to the write-ups.

5. Parameter count 125.8 M → 26.0 M.
6. 966,000× → ~2,716× (or drop it).
7. E20 macro NLL 5.190 → 5.508.
8. The main-paper abstract's PPL range.
9. The duplicated math_v1/code_v2 row.
10. The "OOD" label and the stale champion fields.
11. The online-Hebbian claim for v3.
12. The BCM, Sanger, Tucker, CTRL, metaplasticity-chronology and circular-shift statements, and the bibliography errors (Appendix C).
13. **Cite Kukushkin et al. (2024)** and state plainly that the implemented model does not reproduce its phenomenon.

Engineering.

14. Batch the vocabulary head.
15. Remove `input_gate`.
16. Implement a sparse (index-based) Hebbian update or drop the claim.
17. Stop mutating weights in `eval()`/`chat()`.
18. Make freezing stop Hebbian updates.
19. Fix the registry and tests.

Science.

20. Run the state-ablation, input-strength and Kukushkin-protocol experiments (§2.5, §11) before further component search.

---

13 Conclusion

CellAI began from a striking observation: ordinary human cells, not just neurons, distinguish spaced from massed stimulation and remember the difference for a day. The project turned that into a sequence model, documented its journey candidly, and searched 36 configurations. Read

against the founding biology, the code, the recovered raw results, correct baselines and a clean split, the evidence shows:

- The implemented dynamics have **lost the founding phenomenon**: the core equation is provably exposure-only, and neither PDE shows a spacing effect.
- The cellular state carries almost no information about its input, and the Hebbian matrix saturates to rank 1.
- The best models predict held-out text and code at unigram level; the single meaningful gain comes from bypassing the cell.
- The efficiency claims do not materialise at the sizes used.
- The most recent rankings rest on a contaminated evaluation split.

None of this rules out cellular-memory-inspired computation. It means the hypothesis has not yet been tested. The founding paper supplies a precise, cheap test (§2.5), and the machine-learning literature supplies working recipes for in-forward plasticity (§2.6).

Statements

Authorship and AI assistance.

- This audit was produced with Claude Code (Anthropic), an AI coding agent, at the request of the CellAI repository owner.
- The agent ran all profiling, data mining, baseline, simulation and literature-verification work in a sandboxed environment, and wrote the text.
- Independent sub-agents re-checked the bibliography against primary sources and adversarially re-checked the quantitative claims.
- The person who uploads this record is responsible for its content and should list authorship and AI use according to Zenodo's and their institution's policies.

Data and code availability. All scripts, derived data and figures are in `docs/audit/` of `https://github.com/odin-loki/CellAI`. Raw Round 1–4 results are in `https://github.com/odin-loki/Ideas` (commit `7e24624`, `Cell AI/data/local/arch_search/`). Third-party data: WikiText-103 (Merity et al., 2016) and CodeSearchNet (Husain et al., 2019) via HuggingFace parquet exports.

Competing interests. None declared by the producing agent. The audited project is the uploader's own work.

Licence. Recommended: CC BY 4.0 for this text and figures; the accompanying scripts follow the repository licence. The Kukushkin et al. (2024) article is CC BY-NC-ND 4.0 and is cited, not reproduced.

References

Abraham, W. C. (2008). Metaplasticity: tuning synapses and networks for plasticity. *Nature Reviews Neuroscience*, 9, 387. https://doi.org/10.1038/nrn2356

Abraham, W. C., & Bear, M. F. (1996). Metaplasticity: the plasticity of synaptic plasticity. *Trends in Neurosciences*, 19(4), 126–130. https://doi.org/10.1016/S0166-2236(96)80018-X

Ahmad, S., & Scheinkman, L. (2019). How can we be so dense? The benefits of using highly sparse representations. arXiv:1903.11257.

Amari, S. (1977). Dynamics of pattern formation in lateral-inhibition type neural fields. *Biological Cybernetics*, 27, 77–87. https://doi.org/10.1007/BF00337259

Ba, J., Hinton, G., Mnih, V., Leibo, J. Z., & Ionescu, C. (2016). Using fast weights to attend to the recent past. *NeurIPS 29*. arXiv:1610.06258.

Behrouz, A., Zhong, P., & Mirrokni, V. (2024). Titans: Learning to memorize at test time. arXiv:2501.00663.

Benna, M. K., & Fusi, S. (2016). Computational principles of synaptic memory consolidation. *Nature Neuroscience*, 19, 1697–1706. https://doi.org/10.1038/nn.4401

Bhalla, U. S., & Iyengar, R. (1999). Emergent properties of networks of biological signaling pathways. *Science*, 283, 381–387. https://doi.org/10.1126/science.283.5400.381

Bienenstock, E. L., Cooper, L. N., & Munro, P. W. (1982). Theory for the development of neuron selectivity: orientation specificity and binocular interaction in visual cortex. *Journal of Neuroscience*, 2(1), 32–48. https://doi.org/10.1523/JNEUROSCI.02-01-00032.1982

Bliss, T. V. P., & Lømo, T. (1973). Long-lasting potentiation of synaptic transmission in the dentate area of the anaesthetized rabbit following stimulation of the perforant path. *Journal of Physiology*, 232(2), 331–356. https://doi.org/10.1113/jphysiol.1973.sp010273

Braitenberg, V., & Schüz, A. (1998). *Cortex: Statistics and Geometry of Neuronal Connectivity* (2nd ed.). Springer. https://doi.org/10.1007/978-3-662-03733-1

Buzsáki, G., & Draguhn, A. (2004). Neuronal oscillations in cortical networks. *Science*, 304, 1926–1929. https://doi.org/10.1126/science.1099745

Carew, T. J., Pinsker, H. M., & Kandel, E. R. (1972). Long-term habituation of a defensive withdrawal reflex in *Aplysia*. *Science*, 175, 451–454. https://doi.org/10.1126/science.175.4020.451

Chen, S. F., & Goodman, J. (1999). An empirical study of smoothing techniques for language modeling. *Computer Speech & Language*, 13, 359–394. https://doi.org/10.1006/csla.1999.0128

Cheng, Y., Yu, F. X., Feris, R. S., Kumar, S., Choudhary, A., & Chang, S.-F. (2015). An exploration of parameter redundancy in deep networks with circulant projections. *ICCV*, 2857–2865. https://doi.org/10.1109/ICCV.2015.327

Chung, J., Ahn, S., & Bengio, Y. (2017). Hierarchical multiscale recurrent neural networks. *ICLR*. arXiv:1609.01704.

Cooper, L. N., & Bear, M. F. (2012). The BCM theory of synapse modification at 30: interaction of theory with experiment. *Nature Reviews Neuroscience*, 13, 798–810. https://doi.org/10.1038/nrn3353

Dasgupta, S., Stevens, C. F., & Navlakha, S. (2017). A neural algorithm for a fundamental computing problem. *Science*, 358, 793–796. https://doi.org/10.1126/science.aam9868

Dexter, J. P., Prabakaran, S., & Gunawardena, J. (2019). A complex hierarchy of avoidance behaviors in a single-cell eukaryote. *Current Biology*, 29, 4323–4329.e2. https://doi.org/10.1016/j.cub.2019.10.059

Ebbinghaus, H. (1913). *Memory: A Contribution to Experimental Psychology* (H. A. Ruger & C. E. Bussenius, Trans.; original work 1885). Teachers College, Columbia University. https://doi.org/10.1037/10011-000

Ermentrout, G. B., & Cowan, J. D. (1979). A mathematical theory of visual hallucination patterns. *Biological Cybernetics*, 34, 137–150. https://doi.org/10.1007/BF00336965

Ferrell, J. E., & Machleder, E. M. (1998). The biochemical basis of an all-or-none cell fate switch in *Xenopus* oocytes. *Science*, 280, 895–898. https://doi.org/10.1126/science.280.5365.895

Frey, U., & Morris, R. G. M. (1997). Synaptic tagging and long-term potentiation. *Nature*, 385, 533–536. https://doi.org/10.1038/385533a0

Fusi, S., Drew, P. J., & Abbott, L. F. (2005). Cascade models of synaptically stored memories. *Neuron*, 45, 599–611. https://doi.org/10.1016/j.neuron.2005.02.001

Gelber, B. (1952). Investigations of the behavior of *Paramecium aurelia*: I. Modification of behavior after training with reinforcement. *Journal of Comparative and Physiological Psychology*, 45, 58–65. https://doi.org/10.1037/h0063093

Gershman, S. J., Balbi, P. E. M., Gallistel, C. R., & Gunawardena, J. (2021). Reconsidering the evidence for learning in single cells. *eLife*, 10, e61907. https://doi.org/10.7554/eLife.61907

Gu, A., & Dao, T. (2023). Mamba: Linear-time sequence modeling with selective state spaces. arXiv:2312.00752.

Gu, A., Goel, K., & Ré, C. (2022). Efficiently modeling long sequences with structured state spaces. *ICLR*. arXiv:2111.00396.

Hebb, D. O. (1949). *The Organization of Behavior*. Wiley.

Hinton, G. E., & Plaut, D. C. (1987). Using fast weights to deblur old memories. *Proceedings of the 9th Annual Conference of the Cognitive Science Society*, 177–186.

Husain, H., Wu, H.-H., Gazit, T., Allamanis, M., & Brockschmidt, M. (2019). CodeSearchNet challenge: Evaluating the state of semantic code search. arXiv:1909.09436.

Intrator, N., & Cooper, L. N. (1992). Objective function formulation of the BCM theory of visual cortical plasticity. *Neural Networks*, 5, 3–17. https://doi.org/10.1016/S0893-6080(05)80003-6

Jaeger, H., & Haas, H. (2004). Harnessing nonlinearity: predicting chaotic systems and saving energy in wireless communication. *Science*, 304, 78–80. https://doi.org/10.1126/science.1091277

Kandel, E. R. (2001). The molecular biology of memory storage: a dialogue between genes and synapses. *Science*, 294, 1030–1038. https://doi.org/10.1126/science.1067020

Kneser, R., & Ney, H. (1995). Improved backing-off for m-gram language modeling. *ICASSP 1995*, 1, 181–184. https://doi.org/10.1109/ICASSP.1995.479394

Koutník, J., Greff, K., Gomez, F., & Schmidhuber, J. (2014). A clockwork RNN. *ICML*, PMLR 32(2), 1863–1871. arXiv:1402.3511.

Kukushkin, N. V., Carney, R. E., Tabassum, T., & Carew, T. J. (2024). The massed-spaced learning effect in non-neural human cells. *Nature Communications*, 15, 9635. https://doi.org/10.1038/s41467-024-53922-x

Kukushkin, N. V., Tabassum, T., & Carew, T. J. (2022). Precise timing of ERK phosphorylation/dephosphorylation determines the outcome of trial repetition during long-term memory formation. *PNAS*, 119, e2210478119. https://doi.org/10.1073/pnas.2210478119

Kuramoto, Y. (1984). *Chemical Oscillations, Waves, and Turbulence*. Springer. https://doi.org/10.1007/978-3-642-69689-3

Lee-Thorp, J., Ainslie, J., Eckstein, I., & Ontañón, S. (2022). FNet: Mixing tokens with Fourier transforms. *NAACL*, 4296–4313. https://doi.org/10.18653/v1/2022.naacl-main.319

Lyon, P., Keijzer, F., Arendt, D., & Levin, M. (2021). Reframing cognition: getting down to biological basics. *Philosophical Transactions of the Royal Society B*, 376, 20190750. https://doi.org/10.1098/rstb.2019.0750

Maass, W., Natschläger, T., & Markram, H. (2002). Real-time computing without stable states. *Neural Computation*, 14, 2531–2560. https://doi.org/10.1162/089976602760407955

Makhzani, A., & Frey, B. (2013). k-Sparse autoencoders. arXiv:1312.5663.

Malenka, R. C., & Bear, M. F. (2004). LTP and LTD: an embarrassment of riches. *Neuron*, 44, 5–21. https://doi.org/10.1016/j.neuron.2004.09.012

Merity, S., Xiong, C., Bradbury, J., & Socher, R. (2016). Pointer sentinel mixture models. arXiv:1609.07843.

Miconi, T., Clune, J., & Stanley, K. O. (2018). Differentiable plasticity: training plastic neural networks with backpropagation. *ICML*, PMLR 80. arXiv:1804.02464.

Miyato, T., Löwe, S., Geiger, A., & Welling, M. (2025). Artificial Kuramoto oscillatory neurons. *ICLR*. arXiv:2410.13821.

Mordvintsev, A., Randazzo, E., Niklasson, E., & Levin, M. (2020). Growing neural cellular automata. *Distill*, 5(2), e23. https://doi.org/10.23915/distill.00023

Olshausen, B. A., & Field, D. J. (1996). Emergence of simple-cell receptive field properties by learning a sparse code for natural images. *Nature*, 381, 607–609. https://doi.org/10.1038/381607a0

Pagani, M. R., Oishi, K., Gelb, B. D., & Zhong, Y. (2009). The phosphatase SHP2 regulates the spacing effect for long-term memory induction. *Cell*, 139, 186–198. https://doi.org/10.1016/j.cell.2009.08.033

Rao, Y., Zhao, W., Zhu, Z., Lu, J., & Zhou, J. (2021). Global filter networks for image classification. *NeurIPS 34*. arXiv:2107.00645.

Sanger, T. D. (1989). Optimal unsupervised learning in a single-layer linear feedforward neural network. *Neural Networks*, 2, 459–473. https://doi.org/10.1016/0893-6080(89)90044-0

Schlag, I., Irie, K., & Schmidhuber, J. (2021). Linear transformers are secretly fast weight programmers. *ICML*, PMLR 139. arXiv:2102.11174.

Schmidhuber, J. (1992). Learning to control fast-weight memories: an alternative to dynamic recurrent networks. *Neural Computation*, 4, 131–139. https://doi.org/10.1162/neco.1992.4.1.131

Smolen, P., Zhang, Y., & Byrne, J. H. (2016). The right time to learn: mechanisms and optimization of spaced learning. *Nature Reviews Neuroscience*, 17, 77–88. https://doi.org/10.1038/nrn.2015.18

Sun, Y., Li, X., Dalal, K., Xu, J., Vikram, A., et al. (2024). Learning to (learn at test time): RNNs with expressive hidden states. arXiv:2407.04620.

Tully, T., Preat, T., Boynton, S. C., & Del Vecchio, M. (1994). Genetic dissection of consolidated memory in *Drosophila*. *Cell*, 79, 35–47. https://doi.org/10.1016/0092-8674(94)90398-0

Turing, A. M. (1952). The chemical basis of morphogenesis. *Philosophical Transactions of the Royal Society of London B*, 237, 37–72. https://doi.org/10.1098/rstb.1952.0012

Turrigiano, G. G., Leslie, K. R., Desai, N. S., Rutherford, L. C., & Nelson, S. B. (1998). Activity-dependent scaling of quantal amplitude in neocortical neurons. *Nature*, 391, 892–896. https://doi.org/10.1038/36103

Wilson, H. R., & Cowan, J. D. (1972). Excitatory and inhibitory interactions in localized populations of model neurons. *Biophysical Journal*, 12, 1–24. https://doi.org/10.1016/S0006-3495(72)86068-5

Wilson, H. R., & Cowan, J. D. (1973). A mathematical theory of the functional dynamics of cortical and thalamic nervous tissue. *Kybernetik*, 13, 55–80. https://doi.org/10.1007/BF00288786

Yin, J. C. P., Wallach, J. S., Del Vecchio, M., Wilder, E. L., Zhou, H., Quinn, W. G., & Tully, T. (1994). Induction of a dominant negative CREB transgene specifically blocks long-term memory in *Drosophila*. *Cell*, 79, 49–58. https://doi.org/10.1016/0092-8674(94)90399-9

Zhang, Y., Liu, R.-Y., Heberton, G. A., Smolen, P., Baxter, D. A., Cleary, L. J., & Byrne, J. H. (2012). Computational design of enhanced learning protocols. *Nature Neuroscience*, 15, 294–297. https://doi.org/10.1038/nn.2990

Audited and provenance sources. odin-loki/CellAI, commit `a109790` (https://github.com/odin-loki/CellAI); odin-loki/Ideas, commits `7e24624` and `79a03a7` (https://github.com/odin-loki/Ideas); odin-loki/Cypha, `docs/history/` (https://github.com/odin-loki/Cypha).

Appendix A: Reproducing this study

```
        pip install torch tiktoken pyarrow matplotlib radon pytest
        # Split permutations (dummy labelled records; no data needed)
        python docs/audit/scripts/split_simulation.py run_arch_search_v4 > perm_A.json
        python docs/audit/scripts/split_simulation.py run_arch_search_v5 > perm_B.json
        # N-gram baselines: HF parquet exports of Salesforce/wikitext (wikitext-103-raw-v1/train/0)
        # and code-search-net/code_search_net (python/train/0) in $AUDIT_WORK/dl/;
        # the permutation path is relative to $AUDIT_WORK
        AUDIT_WORK=... python docs/audit/scripts/ngram_baselines.py 0 perm_B.json
        # Massed-spaced test (Fig. 8)
        python docs/audit/scripts/spacing_effect.py out.json && python docs/audit/scripts/plot_spacing.py out.json
fig8.png
        # Profiling and training probe
        AUDIT_OUT=out python docs/audit/scripts/profiling/bench_models.py v3_E20
        AUDIT_OUT=out python docs/audit/scripts/profiling/sweeps.py
        AUDIT_OUT=out python docs/audit/scripts/profiling/train_probe.py v3_E20like 2000
```

Appendix B: Files

File	Content
`data/experiments.csv`	38 rows: id, wave, change, D, steps, params, macro NLL/PPL, text+code NLL, latency, outcome, source, notes
`data/profiling_results.json`	Runtime measurements (v1.0 run; E20 rows there are the E14-like configuration)
`data/profiling_E20_corrected.json`	Corrected E20 benchmark and profiler output
`data/train_v3_E20like_corrected.json`	Corrected E20-like training-probe run
`data/ngram_split_A_v1-v4.json`, `data/ngram_split_B_v5-v7.json`	Baseline NLLs per modality, 50-doc and full eval sets, sampling s.d.
`data/spacing_effect_results.json`	Massed-spaced simulation outputs
`figures/fig1–fig8`	Baselines, training probe, parameters, PDE scaling, Hebbian scaling, best-so-far, outcomes by wave, spacing effect
`scripts/`	Split simulation, n-gram baselines, spacing simulation, figures, profiling harness

Appendix C: Bibliography and claim audit of the original papers (summary)

Reference-list errors.

Paper	Entry	Error	Correct
Search paper	Frankle & Carlin (2019)	Author name	Frankle, J., & **Carbin**, M. (2019). arXiv:1803.03635
Main paper	Tallec, Adi & Ollivier (2018)	Non-existent co-author	Tallec, C., & Ollivier, Y. (2018). arXiv:1804.11188
Search paper	Grave, Joulin, Cissé, Jégou (2017)	Author omitted	Grave, É., Joulin, A., Cissé, M., **Grangier, D.**, & Jégou, H. PMLR 70:1302–1310
Main paper	Bengio, Ducharme, Vincent, Janvin (2003)	Spelling	**Jauvin**, C.
Main paper	Mikolov et al. (2010)	Spurious “2(3)”	Interspeech 2010, 1045–1048
Both	Oja (1982)	Title	“Simplified neuron model as a principal component analyzer”
Search paper	—	Cited in text, missing from list	Shazeer (2020) arXiv:2002.05202; Keskar et al. (2019) arXiv:1909.05858; Li et al. (2023) doi:10.18653/v1/2023.acl-long.687; Nguyen & Salazar (2019) arXiv:1910.05895

Misused sources (in-text claims).

Claim	Problem
Rule “exactly implements BCM”	BCM requires a sign change at θ_M; the implemented rule only potentiates
Top-k Hebbian = “Sanger’s rule … top-k principal components”	GHA needs a decorrelating term; “top-k units” ≠ “top-k components”
Metaplasticity “first described by Abraham & Bear 1996 and formalized in BCM 1982”	Chronology reversed
“Growing neural networks [Gaier & Ha, 2019]”	That paper is about weight-agnostic networks
“SiGLU [Noam et al., 2020]”	Shazeer (2020) defines SwiGLU
“[Liu et al., 2020, Transformers without Tears]”	Nguyen & Salazar (2019), which argues for warm-up-free training
CTRL repetition penalty “subtracts” logits, p = 1.3	CTRL divides logits; θ ≈ 1.2
Lattice “equivalent to a 3-way Tucker decomposition”	It is a rank-≤27 symmetric linear map
Uniform FFT phase rotation “equivalent to a circular shift”	It equals $\cos\phi \cdot s$
“~1,000 of ~10,000 neighbours connected [Braitenberg & Schüz]”	Not traceable; the commonly cited figure is ~8,200 synapses per neuron (mouse)
“Reaction-diffusion fields [Koch & Segev, 1989]”	A methods book on neuron modelling; Turing (1952) or neural-field theory would fit
“Frey & Morris: tag gates subsequent LTP”	The tag governs persistence (early → late LTP)
Kukushkin et al. (2024)	Not cited by either paper

Kukushkin (2024) vs `core_math_model.md` §1.1.

Parameter	Design model	Paper	Match?
Pulse duration	3–12 min	3 min (12 min only as the massed control)	Partial
Interval	10–30 min	10, 20, 30 min	Yes
Repetitions	1–4	1, 2, 4	Yes
Concentrations	Forskolin 0.1–10 µM; TPA 0.1–10 nM	Tested 0.08–50 µM and 0.08–200 nM; used 2 µM and 2 nM	Brackets the working doses