



Reseller Gateway API documentation

April 2025.

Abstract

This document provides detailed overview of Reseller Gateway API.

Note: Only Data related API operations are supported at this time (no voice or SMS).

Contents

1 Introduction	9
1.1 Authentication	9
1.2 Responses	9
1.3 Error Handling	9
2 Inventory	10
2.1 SIMS	10
2.1.1 Request	10
2.1.2 Response	10
2.1.3 Example	11
3 Subscribers	12
3.1 Add subscriber	12
3.1.1 Request	12
3.1.2 Response	12
3.1.3 Example	12
3.2 Get subscriber	13
3.2.1 Request	13
3.2.2 Response	13
3.2.3 Example	13
3.3 Update subscriber	13
3.3.1 Request	14
3.3.2 Response	14
3.3.3 Example	14
3.4 Query subscribers	14
3.4.1 Request	14
3.4.2 Response	15
3.4.3 Example	15
3.5 Add address	15
3.5.1 Request	15
3.5.2 Response	16
3.5.3 Example	16

3.6 Get addresses	16
3.6.1 Request	16
3.6.2 Response	16
3.6.3 Example	17
3.7 Get address	17
3.7.1 Request	17
3.7.2 Response	17
3.7.3 Example	17
3.8 Delete address	18
3.8.1 Request	18
3.8.2 Response	18
3.8.3 Example	18
4 Retail plans	19
4.1 Get retail plans	19
4.1.1 Request	19
4.1.2 Response	19
4.1.3 Example	19
4.2 Get retail plan	19
4.2.1 Request	19
4.2.2 Response	20
4.2.3 Example	20
5 Subscription	21
5.1 Validate devices	21
5.1.1 Request	21
5.1.2 Response	21
5.1.3 Response	22
5.1.4 Example	23
5.2 Validate service address	24
5.2.1 Request	24
5.2.2 Response	24
5.2.3 Example	25

5.3 Activate subscription	26
5.3.1 Request	26
5.3.2 Response	27
5.3.3 Example	27
5.4 Query subscription activations	28
5.4.1 Request	28
5.4.2 Response	28
5.4.3 Example	28
5.5 Get subscription activation status	29
5.5.1 Request	29
5.5.2 Response	29
5.5.3 Example	29
5.6 Modify subscription activation	30
5.6.1 Request	30
5.6.2 Response	30
5.6.3 Example	30
5.7 Cancel subscription activation	31
5.7.1 Request	31
5.7.2 Response	31
5.7.3 Example	31
5.8 Query subscriptions	31
5.8.1 Request	31
5.8.2 Response	32
5.8.3 Example	32
5.9 Get subscription information	32
5.9.1 Request	32
5.9.2 Response	33
5.9.3 Example	33
5.10 Modify subscription	34
5.10.1 Request	34
5.10.2 Response	34
5.10.3 Example	34

5.11 Suspend subscription.	34
5.11.1 REQUEST	34
5.11.2 Response	35
5.11.3 Example.	35
5.12 Restore subscription.	35
5.12.1 Request	35
5.12.2 Response.	35
5.12.3 Example.	35
5.13 Cancel subscription.	36
5.13.1 Request	36
5.13.2 Response	36
5.13.3 Example.	36
5.14 Get subscription plans	36
5.14.1 REQUEST	36
5.14.2 Response	36
5.14.3 Example.	37
5.15 Get subscription plan history.	37
5.15.1 REQUEST	37
5.15.2 Response.	37
5.15.3 Example.	37
5.16 Get subscription plan	38
5.16.1 Request.	38
5.16.2 Response	38
5.16.3 Example.	38
5.17 Add plan	39
5.17.1 Request	39
5.17.2 Response.	39
5.17.3 Example.	39
5.18 Expire plan	40
5.18.1 Request	40
5.18.2 Response.	40
5.18.3 Example.	40

5.19 Re-provision plan	40
5.19.1 Request	40
5.19.2 Response	40
5.19.3 Example	41
5.20 Add service	41
5.20.1 Request	41
5.20.2 Response	41
5.20.3 Example	41
5.21 Remove service	41
5.21.1 Request	42
5.21.2 Response	42
5.21.3 Example	42
5.22 Get subscription services	42
5.22.1 Request	42
5.22.2 Response	42
5.22.3 Example	43
5.23 Get subscription service	43
5.23.1 Request	43
5.23.2 Response	43
5.23.3 Example	43
5.24 Get network information	44
5.24.1 Request	44
5.24.2 Response	44
5.24.3 Example	44
5.25 Swap device	44
5.25.1 Request	45
5.25.2 Response	45
5.25.3 Example	45
6 NUMBER PORTABILITY	47
6.1 Check port-in eligibility	47
6.1.1 Request	47

6.1.2 Response.	47
6.1.3 Example.	47
6.2 Create port-in request	48
6.2.1 Request	48
6.2.2 Response.	48
6.2.3 Example.	49
6.3 Get port-in status request	49
6.3.1 Request.	49
6.3.2 Response.	50
6.3.3 Example.	52
6.4 Update port-in request	52
6.4.1 Request	52
6.4.2 Response.	53
6.4.3 Example.	53
6.5 Cancel port-in request	53
6.5.1 Request	53
6.5.2 Response.	53
6.5.3 Example.	53
6.6 Create port-out request	54
6.6.1 Request	54
6.6.2 Response.	54
6.6.3 Example.	54
6.7 Get port-out request	55
6.7.1 Request	55
6.7.2 Response.	55
6.7.3 Example.	55
6.8 Cancel port-out request	56
6.8.1 Request	56
6.8.2 Response.	56
6.8.3 Example.	56
6.9 Query port-out requests	57
6.9.1 Request	57

6.9.2 Response	57
6.9.3 Example	57
7 Notifications	58
7.1 Subscription activation status	* 2 2 2 2 2 2 3 3 8
7.1.1 Request	58
7.1.2 Example.	58
7.2 Subscription activated	59
7.2.1 Request	59
7.2.2 Example.	59
7.3 Usage notification.	59
7.3.1 Request	59
7.3.2 Example.	60
7.4 Threshold notification.	61
7.4.1 Request	61
7.4.2 Example.	61
7.5 Port-in status notification	61
7.5.1 Request	61
7.5.2 Example.	62
8 API Endpoints	63

1 Introduction

This chapter provides an overview of Reseller Gateway API.

1.1 Authentication

Reseller Gateway API uses token-based HTTP Authentication scheme.

For clients to authenticate, the token key should be included in the Authorization HTTP header. The key should be prefixed by the string literal "Token", with whitespace separating the two strings. For example:

```
Authorization: Token 9944b09199c62bcf9418ad846dd0e4bbdfc6ee4b
```

Listing 1: Authorization token

1.2 Responses

For each request, system returns a JSON-formatted response. The documentation for each API call contains an example JSON response for that function.

1.3 Error Handling

Reseller Gateway API uses standard HTTP status codes as well as system-specific error messages.

HTTP STATUS CODE	DESCRIPTION
200	Success
201	Created
204	No content
400	Bad request
404	Resource not found
500	Server error

Table 1: HTTP Status codes

2 Inventory

This chapter provides detailed documentation of Inventory APL

2.1 SIMS

This API call is used to retrieve all or subset of SIM inventory. You can query SIMs by type, status, carrier, ICCID or date added.

2.1.1 Request

GET /api/v1/inventory/sims{query parameters}

ELEMENT	REQUIRED	DESCRIPTION
---------	----------	-------------

Table 2: Query SIMS requests

PARAMETER	DESCRIPTION
type	Filter by SIM type. See table 5 for list of possible values
status	Filter by SIM status
iccid	Filter by ICCID or ICCIDS ending with parameter value
carrier	Filter by carrier
after	Return SIMs added after date specified in parameter value

Table 3: Query parameters

2.1.2 Response

/api/v1/inventory/sims

ELEMENT	REQUIRED	DESCRIPTION
count	YES	Total number of SIMs matching query
next	YES	URL where to get next page of results
previous	YES	URL where to get previous page of results
results	YES	List of SIMs.
iccid	YES	ICCID
type	YES	SIM type
carrier	NO	Downstream carrier
status	YES	SIM status
activation_code	NO	eSIM activation code

Table 4: Query SIMs response

SIM types are described in table 5.

TYPE	DESCRIPTION
esim	eSIM
physical	Physical SIM

Table 5: SIM types

2.1.1.3 Example

```
GET api/vl/inventory/sims
GET api/vl/inventory/sims?type=esim
GET api/vl/inventory/sims?status=inventory
GET api/vl/inventory/sims?type=esim&after=2022-06-01
```

Listing 2: Query SIMs request

```
{
  "count": 3,
  "next": null,
  "previous": null,
  "results": [
    {
      "iccid": "89405037176069199511",
      "type": "physical",
      "carrier": "TMO",
      "status": "Inventory",
    },
    {
      "Diccid": "89280011113651059446",
      "type": "physical",
      "carrier": "AT&T",
      "status": "Inventory",
    },
    {
      "Diccid": "89975111967191511974",
      "type": "esim",
      "carrier": "AT&T",
      "status": "Inventory",
      "Dactivation_code": "FKE: O$CUST-111-V4-FAKE-ATL2. GDSB.NET$555"
    }
  ]
}
```

Listing 3: Query SIMs response

3 Subscribers

This chapter provides detailed documentation of Subscribers Management APL

Subscriber represents MVNO's customer. Subscriber is uniquely identified by subscriber ID.

3.1 Add subscriber

This API call is used to add or register a subscriber.

3.1.1 Request

POST /api/v1/subscribers		
ELEMENT	REQUIRED	DESCRIPTION
username	NO	Username
first_name	YES	First name
middle_name	NO	Middle name
last_name	*YES	Last name
phone number	NO	Contact phone number
email	NO	Contact email
date_of_birth	NO	Date of birth

Table 6: Add subscriber request

3.1.2 Response

/api/v1/subscribers		
ELEMENT	REQUIRED	DESCRIPTION
id	YES	Subscriber ID

Table 7: Add subscriber response

3.1.3 Example

```
{
  "username": "jsmith@example.com",
  "first_name": "John",
  "last_name": "Smith",
}
```

Listing 4: Add subscriber request

```
{
  "id": "cbdc3bf6-6742-4f95-afc2-0744dab38bc2"
}
```

Listing 5: Add subscriber response

3.2 Get subscriber

This API call is used to retrieve subscriber information.

3.2.1 Request

GET /api/v1/subscribers/{subscriber id}		
ELEMENT	REQUIRED	DESCRIPTION

Table 8: Get subscriber request

3.2.2 Response

/api/v1/subscribers/{subscriber id}		
ELEMENT	REQUIRED	DESCRIPTION
username	YES	Username
first name	YES	First name
middle name	NO	Middle name
last name	YES	Last name
date of birth	NO	Date of birth
phone number	NO	Contact phone number
email	NO	Contact email

Table 9: Get subscriber response

3.2.3 Example

```
{
}
```

Listing 6: Get subscriber request

```
{
  "username": "jsmith@example.com",
  "first_name": "John",
  "last_name": "Smith",
  "email": "jsmith@example.com",
}
```

Listing 7: Get subscriber response

3.3 Update subscriber

This API call is used to update subscriber. Any attribute can be changed individually.

3.3.1 Request

PATCH /api/v1/subscribers/{subscriber id}		
ELEMENT	REQUIRED	DESCRIPTION
username	NO	Username
first name	NO	First name
middle name	NO	Middle name
last name	NO	Last name
phone number	NO	Contact phone number
email	NO	Contact email
date of birth	NO	Date of birth

Table 10: Update subscriber request

3.3.2 Response

/api/v1/subscribers/{subscriber id}		
ELEMENT	REQUIRED	DESCRIPTION

Table 11: Update subscriber response

3.3.3 Example

```
{
  "first_name": "John",
  "last_name": "Smith",
  "date_of_birth": "1999-01-08"
}
```

Listing 8: Update subscriber request

```
{
}
```

Listing 9: Update subscriber response

3.4 Query subscribers

This API call is used to retrieve subset of subscribers. You can query subscribers by username, first name, last name or email

3.4.1 Request

GET /api/v1/subscribers/{query parameters}		
ELEMENT	REQUIRED	DESCRIPTION

Table 12: Query subscribers requests

3.4.2 Response

/api/v1/subscribers/{query parameters}

ELEMENT	REQUIRED	DESCRIPTION
count	YES	Total number of subscribers matching query
next	YES	URL where to get next page of results
previous	YES	URL where to get previous page of results
results	YES	List of subscriber IDs.

Table 13: Query subscribers response

3.4.3 Example

GET api/v1/subscribers

GET api/v1/subscribers?username=j

GET api/v1/subscribers? email=j

Listing 10: Get subscriber request

```
{
  "COUNT": 1,
  "next": null,
  "previous": null,
  "results": [
    "709c13e6-6a81-479b-aff2-2f9251589f38"
  ]
}
```

Listing 11: Get subscriber response

3.5 Add address

This API call is used to associate address with subscriber.

3.5.1 Request

POST /api/v1/subscribers/{subscriber id}/addresses

ELEMENT	REQUIRED	DESCRIPTION
address_line_1	YES	Address line 1
address_line_2	NO	Address line 2
zone_code	YES	Zone code ie. state, province, prefecture etc.
postal_code	YES	ZIP code, postcode or postal code
city	YES	City
country	YES	Country code

Table 14: Add address request

3.5.2 Response

/api/v1/subscribers/{subscriber id}/addresses

ELEMENT	REQUIRED	DESCRIPTION
id	YES	Address ID

Table 15: Add address response

3.5.3 Example

```
{
  "address_line_1": "13991 Durango Drive",
  "zone_code": "CA",
  "postal_code": "92014",
  "city": "Del Mar",
  "country": "US"
}
```

Listing 12: Add address request

```
{
  "id": "d17317b8-5ae5-44a8-b4a0-6baf45ab83ba"
}
```

Listing 13: Add address response

3.6 Get addresses

This API call is used to retrieve all the addresses associated with subscriber.

3.6.1 Request

GET **/api/v1/subscribers/{subscriber id}/addresses**

ELEMENT	REQUIRED	DESCRIPTION
---------	----------	-------------

Table 16: Get addresses request

3.6.2 Response

/api/v1/subscribers/{subscriber id}/addresses

ELEMENT	REQUIRED	DESCRIPTION
addresses	YES	List of address IDs

Table 17: Get addresses response

3.6.3 Example

```
{
}
```

Listing 14: Get addresses request

```
{
  "addresses": [
    "d17317b8-5ae5-44a8-b4a0-6baf45ab83ba",
    "d42f177f-c34d-4b2e-8982-3fdc50aedd88",
    "9fac75b5-b40d-458f-8d3f-fa138d478be3"
  ]
}
```

Listing 15: Get addresses response

3.7 Get address

This API call is used to get address associated with subscriber.

3.7.1 Request

GET /api/v1/subscribers/{subscriber id}/addresses/{address id}		
ELEMENT	REQUIRED	DESCRIPTION

Table 18: Get address request

3.7.2 Response

/api/v1/subscribers/{subscriber id}/addresses/{address id}		
ELEMENT	REQUIRED	DESCRIPTION
address_line_1	YES	Address line 1
address_line_2	NO	Address line 2
zone_code	NO	Zone code ie. state, province, prefecture etc.
postal_code	YES	ZIP code, postcode or postal code
city	YES	City
country	YES	Country

Table 19: Get address response

3.7.3 Example

```
{
}
```

Listing 16: Get address request

```
{
  "address_line_1": "1 Cherry Court",
  "address_line_2": null,
  "postcode": "SO53 5PD",
  "zone_code": "Greater London",
  "city": "SOUTHAMPTON",
  "country": "UK"
}
```

Listing 17: Get address response

3.8 Delete address

This API call is used to delete address associated with subscriber.

3.8.1 Request

DELETE /api/v1/subscribers/{subscriber id}/addresses/{address id}

ELEMENT	REQUIRED	DESCRIPTION
---------	----------	-------------

Table 20: Delete address request

3.8.2 Response

/api/v1/subscribers (subscriber id)/addresses/{address id}

ELEMENT	REQUIRED	DESCRIPTION
---------	----------	-------------

Table 21: Delete address response

3.8.3 Example

```
{
}
```

Listing 18: Delete address request

```
{
}
```

Listing 19: Delete address response

4 Retail plans

4.1 Get retail plans

This API call is used to retrieve list of all retail plans available to the MVNO.

4.1.1 Request

GET /api/v1/plans		
ELEMENT	REQUIRED	DESCRIPTION

Table 22: Get retail plans request

4.1.2 Response

/api/v1/plans		
ELEMENT	REQUIRED	DESCRIPTION
plans	YES	List of available retail plan IDs

Table 23: Get retail plans response

4.1.3 Example

```
{
}
```

Listing 20: Get retail plans request

```
{
  "plans": [
    "1GB TEST PLAN"
  ]
}
```

Listing 21: Get retail plans response

4.2 Get retail plan

This API call is used to retrieve retail plan information.

4.2.1 Request

GET /api/v1/plans/{plan id}		
ELEMENT	REQUIRED	DESCRIPTION

Table 24: Get retail plan request

4.2.2 Response

/api/v1/plans/{plan id}		
ELEMENT	REQUIRED	DESCRIPTION
id	YES	Retail plan ID
name	YES	Plan name
quota	YES	Quota
data	YES	Plan data quota in bytes or octets
voice	YES	Plan voice quota in minutes
unlimited minutes	YES	Plan marked as unlimited minutes
credit	YES	Plan ILD and out-of-bundle credit
messages	YES	Plan messages quota
unlimited messages	YES	Plan marked as having unlimited mes-
		sages
currency	YES	Credit currency
duration	YES	Plan duration in days
duration_type	YES	Plan duration type

Table 25: Get retail plan response

Plan duration types are summarized in the table 26.

TYPE	DESCRIPTION
0	Fixed duration in days determined by duration parameter
1	Monthly plan that ends on the same day of month in the next calendar month, duration is ignored
2	Monthly plan that ends at the end of the calendar month, duration is ignored
3	Plan expiry date is set to current plan expiry date

Table 26: Plan duration types

4.2.3 Example

```
{
}
```

Listing 22: Get retail plan request

```

{
  "id": "1GB_TEST_PLAN",
  "NAME": "1GB DATA-ONLY TEST PLAN",
  "quota": {
    "messages": 0,
    "UNLIMITED_MESSAGES": FALSE,
    "voice": 0,
    "UNLIMITED_MINUTES": FALSE,
    "credit": 0.0,
    "DATA": 1073741824
  },
  "currency": "GBP",
  "duration": 30,
  "duration_type": 0
}

```

Listing 23: Get retail plan response

5 SUBSCRIPTION

5.1 Validate devices

This API is used to validate an ICCID and/or IMEI before it is activated. This is typically done before activation to ensure that subscription activation can complete successfully.

5.1.1 Request

POST /api/v1/devices/validate		
ELEMENT	REQUIRED	DESCRIPTION
devices	YES	List of devices
DEVICE	YES	Device identifier
type	YES	Device type

Table 27: Validate devices request

Device types are described in table 34.

5.1.2 Response

/api/v1/devices/validate		
ELEMENT	REQUIRED	DESCRIPTION
devices	YES	List of devices
DEVICE	YES	Device identifier
TYPE	YES	Device type
valid	YES	Device valid for activation
reason	NO	REASON WHY DEVICE IS NOT VALID
supported plans	NO	for activation List of supported plans

Table 28: Validate devices response

If API token is associated with multiple downstream carriers, Validate devices API will return validation result for each associated carrier as shown in 29.

5.1.3 Response

/api/v1/devices/validate

ELEMENT	REQUIRED	DESCRIPTION
devices	YES	List of devices
device	YES	Device identifier
type	YES	Device type
carriers	YES	Carriers
valid	YES	Device valid for activation
reason	NO	Reason why device is not valid for activation
supported_plans	NO	List of supported plans

Table 29: Validate devices response with multiple carriers

Field valid determines if device is valid for activation. If field valid is set to true device is valid for activation.

If device is not valid for activation field reason will be included in the response and contain description why device is not valid for activation. Reasons can include device not being in inventory, device being in invalid state etc.

If device is valid for activation but there are restrictions on plans it can be activated on, then those plans will be included in field supported_plans.

If device is valid but no response plans are returned in response then device can be activated on any plan available to the MVNO. This is shown in table 30.

VALID	SUPPORTED PLANS	DESCRIPTION
False	No	Device is not valid for activation
Valid	No	Device is valid; all plans supported
Valid	Yes	Device is valid but can only be activated on plans included in response

Table 30: Device validity and supported plans

5.1.4 Example

```
{
  "devices": [
    {
      "type": "iccid",
      "device": "89137717494915840618"
    },
    {
      "type": "imei",
      "device": "353053110085992"
    }
  ]
}
```

Listing 24: Validate devices request

```
{
  "devices": [
    {
      "device": "353053110085992",
      "supported plans": [
        "1GB_TEST_PLAN",
        "5GB_TEST_PLAN"
      ],
      "valid": true,
      "type": "imei"
    },
    {
      "device": "89137717494915840618",
      "reason": "Not found",
      "valid": false,
      "type": "iccid"
    }
  ]
}
```

Listing 25: Validate devices response

```
{
  "devices": [
    {
      "device": "353053110085992",
      "type": "imei",
      "carriers": {
        "Carrier0": {
          "reason": "device not eligible",
          "valid": false
        },
        "Carrier1": {
          "valid": true
        }
      }
    }
  ]
}
```

Listing 26: Validate devices response with multiple downstream carriers

5.2 Validate service address

This API is used to validate service addresses. This is typically done before activation to ensure that subscription activation can complete successfully.

Note that this API validates service address for service activation with downstream carrier and cannot be used as general-purpose address validation. Downstream carriers might validate only portion of service address or ignore mismatches in zone code and postal code. Put another way, successful service address validation does not guarantee that the actual address is valid, rather it means downstream carrier will accept that address for service activation.

Service address validation result from one downstream carrier cannot be applied to different downstream carrier.

Service address validation does not guarantee network coverage. Actual coverage may vary and is subject to change without notice. (Example: there may not be no coverage if device is used underground). Service address validation applies to areas within the domestic coverage areas. If the response is no, the user may still be able to get services if domestic roaming is enabled.

5.2.1 Request

POST /api/v1/address/validate		
ELEMENT	REQUIRED	DESCRIPTION
address_line_1	YES	Address line 1
address_line_2	NO	Address line 2
zone_code	YES	Zone code ie. state, province, prefecture etc.
postal_code	YES	ZIP code, postcode or postal code
city	YES	City
country	YES	Country code

Table 31: Validate service address request

5.2.2 Response

/api/v1/address/validate		
ELEMENT	REQUIRED	DESCRIPTION
carriers	YES	List of address validation results for each carrier
carrier	YES	Carrier name
valid	YES	Address validation result
reason	NO	Reason address failed validation
alternate_address	NO	Alternate address components, e.g postal_code, zone_code, etc.

Table 32: Validate service address response

Field valid determines if service address is valid for activation. If field valid is set to true service address can be added for activation

If service address is not valid but alternative exists, alternate address component such as postal_code, state etc., will be returned in alternate address field.

5.2.3 Example

```
{
  "address_line_1": "710 Camino Del Mar",
  "postal_code": "92014",
  "city": "Del Mar",
  "zone_code": "CA",
  "country": "US"
}
```

Listing 27: Validate service address request

```
[
  {
    "carrier": "T-Mobile",
    "valid": true
  },
  {
    "carrier": "AT&T",
    "valid": true
  }
]
```

Listing 28: Validate service address response

```
{
  "address_line_1": "331 Skyline Dr",
  "postal_code": "92328",
  "city": "Death Valley",
  "zone_code": "CA",
  "country": "US"
}
```

Listing 29: Validate service address request with alternate address

```
[
  {
    "alternate_address": {
      "postal_code": "92327"
    },
    "carrier": "T-Mobile",
    "valid": false
  },
  {
    "carrier": "AT&T",
    "valid": true
  }
]
```

Listing 30: Validate service address with alternate address response

```
{
  "address_line_1": "331 Skyline Dr",
  "postal code": "92328",
  "city": "Death Valley",
  "zone_code": "CX",
  "country": "US"
}
```

Listing 31: Validate service address request with invalid address

```
[
  {
    "reason": "invalid zone code",
    "carrier": "T-Mobile",
    "Bvalid": false
  },
  {
    "reason": "invalid zone code",
    "carrier": "AT&T",
    "valid": false
  }
]
```

Listing 32: Validate service address with invalid address response

5.3 Activate subscription

This API call is used to activate subscription based on the parameters included in the request. Custom fields are configured on per-customer basis and can be used only once configured.

Activate subscription response does not provide status of the activation. Capture the subscription activation ID returned with the response to poll for the status.

5.3.1 Request

POST /api/v1/subscriptions/activations		
ELEMENT	REQUIRED	DESCRIPTION
subscriber	YES	Subscriber ID
retail plan	YES	Retail plan ID
service address	YES	Service address ID
activation type	NO	Subscription activation type. Default is immediate.
devices	YES	List of devices
device	YES	Device identifier
type	YES	Device type
custom field name 1... 10	YES	Value for custom field 1...10

Table 33: Activate subscription request

Device types are described in table 34.

TYPE	DESCRIPTION
imei	IMEI
iccid	ICCID

Table 34: Device types

Activation types are described in table 35. Scheduled subscription activations have to either be started manually using Modify subscription activation API described in 5.6, admin UI or they are started through some automation rule, for example subscriber calling IVR. SIM state changes if supported by downstream carrier, etc. Automation rules are configured on a per-customer basis.

TYPE	DESCRIPTION
immediate	Subscription activation is started immediately
scheduled	Subscription activation scheduled but not started. Scheduled subscription activations need to be started at a later time either through API, admin UI or automation rules

Table 35: Subscription activation types

5.3.2 Response

/api/v1/subscriptions/activations		
ELEMENT	REQUIRED	DESCRIPTION
id	YES	Subscription activation ID

Table 36: Activate subscription response

5.3.3 Example

```
{
  "subscriber": "9d54dc5a-8258-4dad-9c0d-9a8169a3d946",
  "retail_plan": "1GB_TEST_PLAN",
  "service_address": "d17317b8-5ae5-44a8-b4a0-6baf45ab83ba",
  "devices": [
    {
      "type": "imei",
      "device": "355425073591786"
    },
    {
      "type": "iccid",
      "device": "89014104271886165668"
    }
  ]
}
```

Listing 33: Activate subscription request

```
{
  "id": "98fba846-47b2-44c7-9402-a884bd7427f2"
}
```

Listing 34: Activate subscription response

5.4 Query subscription activations

This API call is used to retrieve subset of subscription activations. You can query subscription activations by ICCID, IMSI, subscription ID or status.

5.4.1 Request

GET /api/v1/subscriptions/activations/{query parameters}		
ELEMENT	REQUIRED	DESCRIPTION

Table 37: Query subscription activations requests

5.4.2 Response

/api/v1/subscriptions/activations/{query parameters}		
ELEMENT	REQUIRED	DESCRIPTION
count	YES	Total number of subscriptions matching query
next	YBS	URL where to get next page of results
previous	YES	URL where to get previous page of results
results	YES	List of subscription activation IDs

Table 38: Query subscription activations response

5.4.3 Example

GET api/v1/subscriptions/activations

GET api/v1/subscriptions/activations?status=scheduled

GET api/v1/subscriptions/activations?iccid=89014104272959398350

GET api/v1/subscriptions/activations?subscription_id=bd451116-54v1-53f0-1259-5612fga12457

Listing 35: Query subscription activations request

```
{
  "count": 1,
  "next": null,
  "previous": null,
  "results": [
    "920e64e6-6a07-188b-atf2-109461778g41"
  ]
}
```

Listing 36: Query subscription activations response

5.5 Get subscription activation status

This API call retrieves information about subscription activation.

5.5.1 Request

GET /api/v1/subscriptions/activations/{activation id}

ELEMENT	REQUIRED	DESCRIPTION
---------	----------	-------------

Table 39: Get subscription activation status request

5.5.2 Response

/api/v1/subscriptions/activations/{activation id}

ELEMENT	REQUIRED	DESCRIPTION
status	YES	Subscription activation status
subscription_id	NO	Subscription ID if subscription activation completed successfully

Table 40: Get subscription activation status response

STATUS	DESCRIPTION
scheduled	Subscription is scheduled for activation
pending	Subscription activation pending
processing	Subscription activation processing
reserved	Number reserved
completed	Subscription activation completed
canceled	Subscription activation canceled
rejected	Subscription activation was rejected by the downstream carrier
failed	Subscription activation failed

Table 41: Subscription activation status codes

5.5.3 Example

```
{
}
```

Listing 37: Get subscription activation status request

```
{
  "status": "completed",
  "subscription_id": "ecala2aa-cde1-48ca-91c0-0a53beff2641"
}
```

Listing 38: Get subscription activation status response

5.6 Modify subscription activation

This API call is used to modify subscription activation. This can be used to start scheduled subscription activation, retry failed subscription activation or update subscription activation service address. Only subscription activation in scheduled or failed state can be modified

5.6.1 Request

PATCH /api/v1/subscriptions/activations/{activation id}		
ELEMENT	REQUIRED	DESCRIPTION
status	YES	Subscription activation status. Only allowed value is 'Pending'.
service_address	NO	New subscription activation service address.

Table 42: Modify subscription activation request

5.6.2 Response

/api/v1/subscriptions/activations/{activation id}		
ELEMENT	REQUIRED	DESCRIPTION
status	YES	Subscription activation status

Table 43: Modify subscription activation response

5.6.3 Example

```
{
  "status": "pending"
}
```

Listing 39: Modify subscription activation status request

```
{
  "status": "pending",
}
```

Listing 40: Modify subscription activation status response

```
{
  "status": "pending",
  "service_address": "e49d1581-26a8-4cea-8dd7-d36bf2167d77"
}
```

Listing 41: Modify subscription activation service address request

```
{
  "status": "pending",
}
```

Listing 42: Modify subscription activation service address response

5.7 Cancel subscription activation

This API call is used to cancel scheduled or pending subscription activation. When scheduled or pending subscription is canceled associated SIM card will be retired, subscription deactivated and retail plans expired, if any.

5.7.1 Request

DELETE /api/v1/subscriptions/activations/{activation id}		
ELEMENT	REQUIRED	DESCRIPTION

Table 44: Cancel subscription activation request

5.7.2 Response

/api/v1/subscriptions/activations/{activation id}		
ELEMENT	REQUIRED	DESCRIPTION

Table 45: Cancel subscription activation response

5.7.3 Example

```
{
}
```

Listing 43: Cancel subscription activation request

```
{
}
```

Listing 44: Cancel subscription activation response

5.8 Query subscriptions

This API call is used to retrieve subset of subscriptions. You can query subscriptions by ICCID, MSISDN, IMSI, status or any custom field.

5.8.1 Request

GET /api/v1/subscriptions/{query parameters}		
ELEMENT	REQUIRED	DESCRIPTION

Table 46: Query subscriptions requests

5.8.2 Response

/api/v1/subscriptions/{query parameters}		
ELEMENT	REQUIRED	DESCRIPTION
count	YES	Total number of subscriptions matching query
next	YES	URL where to get next page of results
previous	YES	URL where to get previous page of results
results	YES	List of subscription IDs.

Table 47: Query subscriptions response

5.8.3 Example

GET api/v1/subscriptions
 GET api/v1/subscriptions?iccid=89014104272959398350
 GET api/v1/subscriptions?status=active

Listing 45: Query subscriptions request

```
{
  "count": 1,
  "next": null,
  "previous": null,
  "results": [
    "810d24e6-6a81-479b-aff2-2f9251589f38"
  ]
}
```

Listing 46: Query subscriptions response

5.9 Get subscription information

This API call retrieves information about subscription.

5.9.1 Request

GET /api/v1/subscriptions/{subscription id}		
ELEMENT	REQUIRED	DESCRIPTION

Table 48: Get subscription information request

5.9.2 Response

/api/v1/subscriptions/{subscription id}		
ELEMENT	REQUIRED	DESCRIPTION
plan	YES	Active plan ID
msisdn	YES	MSISDN
status	YES	Status
subscriber	YES	Subscriber ID
pin1	YES	PIN1
puk1	YES	PUK1
pin2	YES	PIN2
puk2	YES	PUK2
devices	YES	List of devices
device	YES	Device identifier
type	YES	Device type

Table 49: Get subscription information response

Subscription status codes are summarized in the table 50. Device types are described in table 34.

STATUS	DESCRIPTION
active	Active
activation pending	Activation pending
deactivated	Deactivated/cancelled
suspended	Suspended

Table 50: Subscription status codes

5.9.3 Example

```
{
}
```

Listing 47: Get subscription information request

```
{
  "plan": "362c2512-fdf0-409f-b77c-bb80105dc266",
  "msisdn": "8582592913",
  "status": "active",
  "subscriber": "c24b7a34-56c2-46aa-95b6-4325e0782cd4",
  "pin1": "2380",
  "puk1": "122512878142",
  "pin2": "5494",
  "puk2": "107357410381",
  "devices": [
    {
      "device": "18944125646610156897",
      "type": "iccid"
    }
  ]
}
```

Listing 48: Get subscription information response

5.10 Modify subscription

This API call is used to modify subscription based on the parameters included in the request. This API call can be used to change subscription custom fields. Custom fields are configured on per-customer basis.

5.10.1 Request

PATCH /api/v1/subscriptions/{subscription id}

ELEMENT	REQUIRED	DESCRIPTION
custom field name 1..10	NO	Value for custom field 1..10

Table 51: Modify subscription request

5.10.2 Response

/api/v1/subscriptions/{subscription id}

ELEMENT	REQUIRED	DESCRIPTION
---------	----------	-------------

Table 52: Modify subscription response

5.10.3 Example

```
{
  "customer_specific_field_name0": "Test data",
  "customer_specific_field_name1": "More data",
}
```

Listing 49: Modify subscription request

```
{
}
```

Listing 50: Modify subscription response

5.11 Suspend subscription

This API is used to suspend subscription.

5.11.1 Request

PUT /api/v1/subscriptions/{subscription id}/suspend

ELEMENT	REQUIRED	DESCRIPTION
---------	----------	-------------

Table 53: Suspend subscription request

5.11.2 Response

/api/v1/subscriptions/{subscription id}/suspend

ELEMENT	REQUIRED	DESCRIPTION
---------	----------	-------------

Table 54: Suspend subscription response

5.11.3 Example

```
{
}
```

Listing 51: Suspend subscription request

```
{
}
```

Listing 52: Suspend subscription response

5.12 Restore subscription

This API is used to restore suspended subscription.

5.12.1 Request

PUT /api/v1/subscriptions/{subscription id}/restore

ELEMENT	REQUIRED	DESCRIPTION
---------	----------	-------------

Table 55: Restore subscription request

5.12.2 Response

/api/v1/subscriptions/{subscription id}/restore

ELEMENT	REQUIRED	DESCRIPTION
---------	----------	-------------

Table 56: Restore subscription response

5.12.3 Example

```
{
}
```

Listing 53: Restore subscription request

```
{
}
```

Listing 54: Restore subscription response

5.13 Cancel subscription

This API is used to cancel subscription. **WARNING:** subscription cannot be restored once canceled.

5.13.1 Request

DELETE /api/v1/subscriptions/{subscription id}		
ELEMENT	REQUIRED	DESCRIPTION

Table 57: Cancel subscription request

5.13.2 Response

/api/v1/subscriptions/{subscription id}		
ELEMENT	REQUIRED	DESCRIPTION

Table 58: Cancel subscription response

5.13.3 Example

```
{
}
```

Listing 55: Cancel subscription request

```
{
}
```

Listing 56: Cancel subscription response

5.14 Get subscription plans

This API call is used to retrieve list of all non-expired plans for subscription.

5.14.1 Request

GET /api/v1/subscriptions/{subscription id}/plans		
ELEMENT	REQUIRED	DESCRIPTION

Table 59: Get subscription plans request

5.14.2 Response

/api/v1/subscriptions/{subscription id}/plans		
ELEMENT	REQUIRED	DESCRIPTION
plans	YES	List of plan IDs

Table 60: Get subscription plans response

5.14.3 Example

```
{
}
```

Listing 57: Get subscription plans request

```
{
  "plans": [
    "8179e7b0-943f-4e61-944a-e86c9401f906"
  ]
}
```

Listing 58: Get subscription plans response

5.15 Get subscription plan history

This API call is used to retrieve list of all expired plans for subscription.

5.15.1 Request

GET /api/v1/subscriptions/{subscription id}/plans/history		
ELEMENT	REQUIRED	DESCRIPTION

Table 61: Get subscription plan history request

5.15.2 Response

/api/v1/subscriptions/{subscription id}/plans/history		
ELEMENT	REQUIRED	DESCRIPTION
plans	YES	List of plan IDs

Table 62: Get subscription plan history response

5.15.3 Example

```
{
}
```

Listing 59: Get subscription plan history request

```
{
  "plans": [
    "8d2da232-1a00-4fa3-b970-148f119d39cd",
    "017c67a5-a7ee-4516-88ee-b0cfa6b572fb",
    "c242bcb1-1d37-409f-bae0-5e284b546a98",
    "c1216d15-86e5-4dd7-b732-8b11fd377fb9",
    "ae1b72f9-6ffa-4f3b-a3dd-995f24e75ca0"
  ]
}
```

Listing 60: Get subscription plan history response

5.16 Get subscription plan

This API call is used to retrieve subscription plan information.

5.16.1 Request

GET /api/v1/subscriptions/{subscription id}/plans/{plan id}

ELEMENT	REQUIRED	DESCRIPTION
---------	----------	-------------

Table 63: Get subscription plan request

5.16.2 Response

/api/v1/subscriptions/{subscription id}/plans/{plan id}

ELEMENT	REQUIRED	DESCRIPTION
id	YES	Plan ID
retail_plan	YES	Retail plan ID
effective_date	YES	Plan effective date
expiration_date	YES	Plan expiration date
balance	YES	Plan balance
data	YES	Plan data balance in bytes or octets
voice	YES	Plan voice balance in minutes
credit	YES	Remaining plan ILD and out-of-bundle credit balance in retail plan currency
quota	messages	Plan messages balance
		Quota
	data	Plan data quota in bytes or octets
	voice	Plan voice quota in minutes
	credit	Plan ILD and out-of balance credit
	messages	Plan messages quota

Table 64: Get subscription plan response

5.16.3 Example

```
{
}
```

Listing 61: Get subscription plan request

```
{
  "id": "1089f0c4-d4e1-4b0c-b0da-26cfab4e3f1f",
  "retail_plan": "8d2da232-1a00-4fa3-b970-148f119d39cd",
  "effective_date": "2021-02-13T00:00:00Z",
  "expiration_date": "2021-03-13T00:00:00Z",
  "balance": {
    "data": 268435456,
    "voice": 0,
    "messages": 0
  },
  "quota": {
    "data": 1073741824,
    "voice": 0,
    "messages": 0
  }
}
```

Listing 62: Get subscription plan response

5.17 Add plan

This API call is used to add a plan to subscription.

5.17.1 Request

PUT /api/v1/subscriptions/{subscription id}/plans		
ELEMENT	REQUIRED	DESCRIPTION
retail_plan	YES	Retail plan ID

Table 65: Add plan to subscription request

5.17.2 Response

/api/v1/subscriptions/{subscription id}/plans		
ELEMENT	REQUIRED	DESCRIPTION
plan	YES	New plan ID

Table 66: Add plan to subscription response

5.17.3 Example

```
{
  "retail_plan": "1GB_TEST_PLAN"
}
```

Listing 63: Add plan request

```
{
  "id": "8179e7b0-943f-4061-944a-e86c9401f906"
}
```

Listing 64: Add plan response

5.18 Expire plan

This API call is used to expire subscription plan.

5.18.1 Request

DELETE /api/v1/subscriptions/{subscription id}/plans/{plan id}		
ELEMENT	REQUIRED	DESCRIPTION

Table 67: Expire subscription plan request

5.18.2 Response

/api/v1/subscriptions/{subscription id}/plans/{plan id}		
ELEMENT	REQUIRED	DESCRIPTION

Table 68: Expire subscription plan response

5.18.3 Example

```
{
}
```

Listing 65: Expire subscription plan request

```
{
}
```

Listing 66: Expire subscription plan response

5.19 Re-provision plan

This API call is used to re-provision the subscription plan on the downstream carrier. Use cases include fixing plan provisioning problems or troubleshooting subscriber-reported service delivery issues.

5.19.1 Request

POST /api/v1/subscriptions/{subscription id}/plans/{plan id}/reprovision		
ELEMENT	REQUIRED	DESCRIPTION

Table 69: Re-provision subscription plan request

5.19.2 Response

/api/v1/subscriptions/{subscription id}/plans/{plan id}/reprovision		
ELEMENT	REQUIRED	DESCRIPTION

Table 70: Re-provision subscription plan response

5.19.3 Example

```
{
}
```

Listing 67: Re-provision subscription plan request

```
{
}
```

Listing 68: Re-provision subscription plan response

5.20 Add service

This API call is used to add service to subscription. Result is effective service ID.

5.20.1 Request

POST /api/v1/subscriptions/{subscription id}/services		
ELEMENT	REQUIRED	DESCRIPTION
service	YES	Service ID

Table 71: Add service request

5.20.2 Response

/api/v1/subscriptions/{subscription id}/services		
ELEMENT	REQUIRED	DESCRIPTION
service_id	YES	New service ID

Table 72: Add service response

5.20.3 Example

```
{
  "service": "DATABLOCK"
}
```

Listing 69: Add service request

```
{
  "id": "e28428c8-6bf6-55b9-c5b1-6baf45ab83ba"
}
```

Listing 70: Add service response

5.21 Remove service

This API call is used to remove effective service from subscription

5.21.1 Request

DELETE /api/v1/subscriptions/{subscription id}/services/{id}

ELEMENT	REQUIRED	DESCRIPTION
---------	----------	-------------

Table 73: Remove service request

5.21.2 Response

/api/v1/subscriptions/{subscription id}/services/{id}

ELEMENT	REQUIRED	DESCRIPTION
---------	----------	-------------

Table 74: Remove service response

5.21.3 Example

```
{
}
```

Listing 71: Remove service request

```
{
}
```

Listing 72: Remove service response

5.22 Get subscription services

This API call is used to retrieve list of all effective services for subscription.

5.22.1 Request

GET /api/v1/subscriptions/{subscription id}/services

ELEMENT	REQUIRED	DESCRIPTION
---------	----------	-------------

Table 75: Get subscription services request

5.22.2 Response

/api/v1/subscriptions/{subscription id}/services

ELEMENT	REQUIRED	DESCRIPTION
services	YES	List of service IDs

Table 76: Get subscription services response

5.22.3 Example

```
{
}
```

Listing 73: Get subscription services request

```
{
  "services": [
    "7080f8a1-832e-5e72-833a-e86c9401f906"
  ]
}
```

Listing 74: Get subscription plans response

5.23 Get subscription service

This API call is used to retrieve subscription service information.

5.23.1 Request

GET /api/v1/subscriptions/{subscription id}/services/{id}		
ELEMENT	REQUIRED	DESCRIPTION

Table 77: Get subscription service request

5.23.2 Response

/api/v1/subscriptions/{subscription id}/subscriptions/{id}		
ELEMENT	REQUIRED	DESCRIPTION
id	YES	Plan ID
service	YES	Service ID
effective date	YES	Plan effective date
expiration_date	NO	Plan expiration date

Table 78: Get subscription service response

5.23.3 Example

```
{
}
```

Listing 75: Get subscription service request

```
{
  "id": "1089f0c4-d4e1-4b0c-b0da-26cfab4e3f1f",
  "service": "DATABLOCK",
  "effective_date": "2021-02-13T00:00:00Z",
}
```

Listing 76: Get subscription service response

5.24 Get network information

This API call is used to fetch subscription network information.

5.24.1 Request

GET /api/v1/subscriptions/{subscription id}/network-information		
ELEMENT	REQUIRED	DESCRIPTION

Table 79: Get network information request

5.24.2 Response

/api/v1/subscriptions/{subscription id}/network-information		
ELEMENT	REQUIRED	DESCRIPTION
status	YES	Status
msisdn	YES	MSISDN
imei	YES	IMEI as reported by the network
iccid	YES	ICCID as reported by the network

Table 80: Get network information

5.24.3 Example

```
{
}
```

Listing 77: Get network information request

```
{
  "msisdn": "3484756863",
  "status": "Active",
  "imei": "358934292295126",
  "iccid": "5351329852765744651"
}
```

Listing 78: Get network information response

5.25 Swap device

This API call is used to swap subscription device. Device types that can be swapped are described in table 81.

DEVICE TYPE	DESCRIPTION
imei	Swap subscription IMEI
iccid	Swap subscription ICCID
msisdn	Swap subscription MSISDN

Table 81: Swap device types

5.25.1 Request

PATCH /api/v1/subscriptions/{subscription id}/swap/{device type}		
ELEMENT	REQUIRED	DESCRIPTION
device	NO	New device i.e. ICCID or IMEI
service address	NO	Service address ID used in MSISDN swap.

Table 82: Swap device request

5.25.2 Response

/api/v1/subscriptions/{subscription id}/swap/{device type}		
ELEMENT	REQUIRED	DESCRIPTION
msisdn	YES	MSISDN
devices	YES	List of devices
device	YES	Device identifier
type	YES	Device type

Table 83: Swap device response

5.25.3 Example

```
{
  "device": "5351329852765744651"
}
```

Listing 79: Swap ICCID request

```
{
  "msisdn": "3484756863",
  "devices": [
    {
      "device": "5351329852765744651",
      "type": "iccid"
    },
    {
      "device": "358934292295126",
      "type": "imei"
    }
  ]
}
```

Listing 80: Swap ICCID response

```
{
  "device": "358934292295126"
}
```

Listing 81: Swap IMEI request

```
{
  "msisdn": "3484756863",
  "devices": [
    {
      "device": "89137717494915840618",
      "type": "iccid"
    },
    {
      "device": "358934292295126",
      "type": "imei"
    }
  ]
}
```

Listing 82: Swap IMEI response

```
{
  "service_address": "489ddd74-0197-4bd4-8e0e-ce266f964d5f"
}
```

Listing 83: Swap MSISDN request

```
{
  "msisdn": "8582611601",
  "devices": [
    {
      "device": "89014104272959398350",
      "type": "iccid"
    },
    {
      "device": "359407085473829",
      "type": "imei"
    }
  ]
}
```

Listing 84: Swap MSISDN response

6 Number portability

Note: pages 47 to 57 are omitted for data only offers.

7 Notifications

Notification mechanism sends usage events to MVNO configured endpoint. Notifications are sent as HTTP POST requests with notification data encoded using JSON. Notifications will have Content-Type entity header set to application/json

NOTIFICATION TYPE	DESCRIPTION
Subscription activation status	Sent whenever subscription activation status changes
Subscription activated	Sent when subscription activation completes
Usage	Sent when session reports usage
Threshold notifications	Sent when plan usage falls below threshold level
Port-in status	Sent whenever port-in request status changes

Table 103: Notification types

7.1 Subscription activation status

Subscription activation notification is sent whenever subscription activation status changes. See table 41 for possible values for subscription activation status.

Successful subscription activation will go through 'pending' -> 'processing' -> 'reserved' -> 'completed' states and generate two subscription activation notifications.

Rejected subscription activation can go through multiple 'processing' -> 'rejected' -> 'pending' -> 'processing' cycles before eventually completing successfully and transitioning to 'completed' state

7.1.1 Request

ELEMENT	REQUIRED	DESCRIPTION
notification_id	YES	Notification ID
subscription_activation_id	YES	Subscription activation ID
status	YES	New subscription activation status
status_description	NO	Subscription activation status description. Normally, set do the error message reported by the downstream carrier for failed subscription activations
subscription_id	NO	Subscription ID if subscription activation completed successfully

Table 104: Subscription activation status request

7.1.2 Example

```
{
  "notification_id": "ae3d7336-4d05-4e54-9500-529d86362bd7",
  "subscription_activation_id": "bcbc6023-a009-4075-aa81-ccc475a39b77",
  "status": "pending"
}
```

Listing 105: Subscription activation status notification

7.2 Subscription activated

Subscription activation notification is sent when subscription activation completes successfully.

7.2.1 Request

ELEMENT	REQUIRED	DESCRIPTION
notification_id	YES	Notification ID
subscription_activation_id	YES	Subscription activation ID
subscription_id	YES	Subscription ID

Table 105: Subscription activation completed request

7.2.2 Example

```
{
  "notification_id": "ae3d7336-4d05-4e54-9500-529d86362bd7",
  "subscription_activation_id": "bcb6023-a009-4075-aa81-ccc475a39b77",
  "subscription_id": "b99706f0-c525-4069-ba9b-670202de81c0"
}
```

Listing 106: Subscription activation notification

7.3 Usage notification

Usage notification is sent whenever session reports usage. Data usage is reported in bytes or octets. Call duration is reported in number of seconds. Usage for SMS events are reported as number of messages sent or received. Date and time fields are formatted as ISO 8601.

7.3.1 Request

ELEMENT	REQUIRED	DESCRIPTION
notification_id	YES	Notification id
timestamp	YES	Event timestamp
msisdn	YES	MSISDN
subscription_id	YES	Subscription ID
type	YES	Usage event type
usage	YES	Units used
plan	YES	Effective plan ID
calling_number	NO	Calling number
called_number	NO	Called number

Table 106: Usage notification request

EVENT TYPE	DESCRIPTION
SMS	SMS events
VOICE	Voice call usage
DATA	Data usage

Table 107: Usage event types

EVENT TYPE	DESCRIPTION
SMS	SMS events
VOICE	Seconds
DATA	Bytes or octets

Table 108: Usage units

7.3.2 Example

```
{
  "notification_id": "5aaa09e5-e373-4a2e-9cac-17ceae2546f5",
  "timestamp": "2021-04-18T12:20:00+00:00",
  "msisdn": "2092003933",
  "subscription_id": "4adf9433-a0fe-4998-9528-2e8fd95118a1",
  "type": "DATA",
  "usage": 10485760,
  "plan": "bf485602-2f88-4aee-821a-a71397d79a07",
}
```

Listing 107: Data Usage notification

```
{
  "notification_id": "1ac69ce4-b1be-4f5a-8980-ac1bf1d9d439",
  "timestamp": "2021-04-18T12:20:00+00:00",
  "msisdn": "2092003933",
  "subscription_id": "4adf9433-a0fe-4998-9528-2e8fd95118a1",
  "type": "VOICE",
  "usage": 180,
  "plan": "bf485602-2f88-4aee-821a-a71397d79a07",
  "calling number": "2092003933",
  "called number": "4152014071"
}
```

Listing 108: Voice Usage notification

```
{
  "notification_id": "f62123fa-d067-4351-8d46-5cb37f9eb872",
  "timestamp": "2021-04-18T12:20:00+00:00",
  "msisdn": "2092003933",
  "subscription_id": "4adf9433-a0fe-4998-9528-2e8fd95118a1",
  "type": "SMS",
  "usage": 1,
  "plan": "bf485602-2f88-4aee-821a-a71397d79a07",
  "calling number": "2092003933",
  "called number": "4152014071"
}
```

Listing 109: SMS Usage notification

7.4 Threshold notification

Threshold notification is sent when retail plan quota falls below notifications threshold. Multiple thresholds can be configured per retail plan, for example at 80%, 50% and 10%.

7.4.1 Request

ELEMENT	REQUIRED	DESCRIPTION
notification_id	YES	Notification id
msisdn	YES	MSISDN
timestamp	YES	Event timestamp
threshold	YES	Threshold triggered
plan	YES	Plan ID
balance	YES	Plan balance
data	YES	Plan data balance in bytes or octets
voice	YES	Plan voice balance in minutes
messages	YES	Plan messages balance

Table 109: Threshold notification request

7.4.2 Example

```
{
  "notification_id": "f7b7f23e-6221-4dd0-bf69-a04e611ed255",
  "msisdn": "8582592913",
  "timestamp": "2021-04-21T18:41:43.122028+00:00",
  "plan": "312f4606-5c5c-4bf4-a694-74ae6f45bb9e",
  "threshold": 52428800,
  "balance": {
    "messages": 0,
    "voice": 0,
    "data": 52428800
  }
}
```

Listing 110: Threshold notification

7.5 Port-in status notification

Port-in status notification is sent whenever port-in request status is updated

7.5.1 Request

ELEMENT	REQUIRED	DESCRIPTION
notification_id	YES	Notification id
msisdn	YES	MSISDN
subscription_id	NO	Subscription ID
port_in_request_id	YES	Port-in request ID
port_request_status	YES	Port-in request status

Table 110: Port-in status notification request

7.5.2 Example

```
{  
  "notification_id": "dab11165-21b8-4ecf-adff-b93fe684f88d",  
  "msisdn": "8582592913",  
  "subscription_id": "84dd253e-3e6c-4aa0-9b6c-814f4e96cf09",  
  "port_in_request_id": "697b49b0-ab34-4d86-8114-0b37a7591ca0",  
  "port_request_status": "Confirmed",  
}
```

Listing III: Port-in status notification

8 API Endpoints

ENVIRONMENT	ENDPOINT
Staging	https://staging.24mobileconnect.com/api/v1
Production	https://api.24mobileconnect.com/api/v1

Table 111: API URLs