

## FLUTTER INSTABILITY OF PIEZOELECTRIC FLUTTERING PLATES USED AS FLOW-ENERGY HAVERSTERS

Olivier Doaré<sup>1,\*</sup>, Sébastien Michelin<sup>2</sup>, Miguel Piñeirua<sup>1</sup>, Yifan Xia<sup>2</sup>


<sup>1</sup>Unité de Mécanique, ENSTA-Paristech, 91120, Palaiseau, France

<sup>2</sup>LadHyX, École Polytechnique, 91128, Palaiseau, France

\* [olivier.doare@ensta-paristech.fr](mailto:olivier.doare@ensta-paristech.fr)

**Abstract** In this work, the fluid-solid-electric coupling of piezoelectric fluttering plates in axial flows is studied experimentally and numerically. Keywords: flag flutter, energy-harvesting, piezoelectric coupling, fluid-structure interaction, instability.

Rectangular cantilevered plates are known to display large amplitude oscillations once a critical value of the flow velocity is reached, a phenomenon commonly referred to as “flag flutter” [1], which results from an instability of straight position of the plate, due to aerodynamic reactions forces. This system was the subject of a considerable number of numerical and experimental research works in the last decade [2]. Drawing profit from these oscillations to harvest kinetic energy of a flow received a growing attention recently. We are interested here in the energy harvesting potential of a cantilevered plate in a flow equipped with a distributed series of small piezoelectric elements, as sketched on Figure 1. Each of the piezoelectric pairs is connected to an energy harvesting circuit. In our work, various kinds of such circuits are considered, such as simple resistive circuits [3, 4, 5], inductive circuits [6] or active switching circuits [7]. We show how the piezoelectric coupling can modify the stability properties of the system, and present parametric studies of the efficiency of the system.



**Figure 1.** Schematic view of a plate in axial flow equipped with piezoelectric patches pairs.

## References

- [1] Kornecki, A., Dowell, E. H., & O'Brien, J. (1976). On the aeroelastic instability of two-dimensional panels in uniform incompressible flow. *Journal of Sound and Vibration*, 47(2), 163-178.
- [2] Shelley, M. J., & Zhang, J. (2011). Flapping and bending bodies interacting with fluid flows. *Annual Review of Fluid Mechanics*, 43, 449-465.
- [3] Doaré, O., & Michelin, S. (2011). Piezoelectric coupling in energy-harvesting fluttering flexible plates: linear stability analysis and conversion efficiency. *Journal of Fluids and Structures*, 27(8), 1357-1375.
- [4] Michelin, S., & Doaré, O. (2013). Energy harvesting efficiency of piezoelectric flags in axial flows. *Journal of Fluid Mechanics*, 714, 489-504.
- [5] Piñeirua, M., Doaré, O., & Michelin, S. (2015). Influence and optimization of the electrodes position in a piezoelectric energy harvesting flag, to appear in *Journal of Sound and Vibration*.
- [6] Y. Xia, S. Michelin & Doaré, O. (2015). Fluid-Solid-Electric Lock-In of Energy-Harvesting Piezoelectric Flags, *Physical Review Applied*, 3(1), 014009.
- [7] Guyomar, D., Badel, A., Lefeuvre, E. & Richard, C. (2005). Toward energy harvesting using active materials and conversion improvement by nonlinear processing. *Ultrasonics, Ferroelectrics, and Frequency Control*, IEEE Transactions on, 52(4), 584-595.