



Search by keyword, manufacturer part no. or RS part no.



MPN



Login / Register



Basket

Abrasives,
Engineering
Materials &
Adhesives

Adhesives,
Sealants &
Tapes

Cables,
Fasteners
& Fixings

Electrical &
Automation

Electronics,
Components &
Conductors

Hand
Tools &
Power
Tools

Hydraulics &
Pneumatics

Plumbing
& Pipeline

Power Supplies,
Transformers &
Transmission

Safety,
Security &
Facilities
Equipment

Test &
Measurement



RS PRO PT100 RTD Sensor, 4mm Dia, 100mm Long, 4 Wire, Probe, Class B

+250°C Max

RS Stock No.: 1235590

Brand: RS PRO



✓ In stock

83 in stock, 2-6 working days for dispatch from SG

IDR 767,899.69

—

1

+

Add to basket

Price Each

Unit(s)	Per Unit(IDR)
1	767,899.69

*price per unit indicative

Technical Reference

[Manufacturer Information](#)

[RS PRO Cables Guide](#)

[RS PRO Connectors Guide](#)

[RS PRO PRT Guide](#)

[RS PRO PRT Selection Guide](#)

[RS PRO Selection](#)

[RS PRO Thermocouple Selection Guide](#)

[RS Pro Datasheet](#)



Need help to find products?

[Contact us now](#) We'll get back to you shortly



Butuh bantuan dalam mencari produk?

[Hubungi Kami](#) Kami akan segera membantu Anda

Legislation and Compliance

RoHS Certificate of Compliance	▼
Statement of Conformity	▼

Country of Origin: GB

Product Details

RS Pro General Purpose 4 Wire Pt100 PRT Probe with Screened Teflon Lead

From RS Pro a high-quality and reliable Pt100 PRT (Platinum Resistance Thermometer) or RTD (Resistance Temperature Detector) sensing probe. This RTD probe has a robust construction with the sensing element encased in a rigid 316 stainless steel sheath. The leads have a durable and flexible Teflon insulation and are screened for protection against electromagnetic interference. This platinum resistance thermometer provides accurate and reliable temperature measurement for a wide range of applications.

What is an RTD?

An RTD is a type of temperature sensor based on the correlation between metals and temperature. As the temperature of a metal increases so does its resistance to the flow of electricity. This resistance can be measured and converted to a temperature reading. In a Pt100 RTD 'Pt' stands for platinum (platinum wire or film) and '100' means that the temperature sensor has a resistance of 100 Ohms at 0°C. Platinum is the most reliable metal due to its linear resistance to temperature relationship over a large temperature range.

What is a Pt100 Probe?

A Pt100 probe is the most rugged form of RTD. The Pt100 temperature sensor element is mounted inside a metal sheath or probe. This protects it from being damaged by the surrounding environment when it is inserted into the process to be measured. The other end of the probe is terminated by an insulated lead comprising of 4 wire tails which are connected to the temperature measuring equipment.

Features and Benefits

- High stability sensing element with a precision output
- IEC 60751 Class B accuracy/tolerance
- Temperature measurement range of -50 to +250°C
- 4 lead wires for accurate readings
- Leads connect to any 2 3 or 4 wire PT100 instrument
- Rigid 316 corrosion resistant stainless steel sheath for protection of sensing element
- Flexible Teflon insulation provides thermal and electrical insulation, impact strength and protects against moisture, corrosion and abrasive chemicals even in extreme temperatures
- Screened cable for protection against electromagnetic interference

Applications

These Pt100 PRT sensor probes with their robust design are ideal for use in many general purpose industrial applications including the following:

- Air conditioning and refrigeration
- Chemical industry
- Plastics processing
- Stoves and grills
- Air, gas and liquid temperature measurement
- Exhaust gas temperature measurement
- Food processing
- Laboratories

Frequently Asked Questions

How Does a PRT Temperature Sensor Work?

The PRT temperature sensor works by placing the sensor element (or process end) into the equipment or process that requires temperature measurement. As the temperature of the platinum resistance thermometer increases it's resistance to the flow of electricity increases. For every increase per degree of temperature the electrical resistance also changes by a set ratio, this is called the temperature coefficient. For platinum, this ratio is .00385 ohm/ohm/°C which means for a Pt100 with a 100 ohm resistance the increase in resistance per degree of temperature would be 0.385 ohms. The total resistance reading can, therefore, be measured and converted into temperature.

How is the Resistance Measured?

The resistance generated by the temperature sensor is measured by passing current through one of the wires to produce a voltage. This voltage is then measured using a suitable bridge or voltmeter and the resistance calculated in ohms using Ohm's Law (R=V/I). Once the resistance is known you can convert it to a temperature reading using a calibration equation or a Pt100 table. A temperature measurement device or calibrator can also be connected to the leads of the probe that will automatically convert the measured resistance into a temperature reading.

Specifications

Attribute	Value
Brand	RS PRO
Thermocouple Type	PT 100
Sensor Type	PT100
Probe Diameter	4 mm
Probe Length	100 mm
Probe Material	Stainless Steel
Maximum Temperature Sensed	+250 °C
Minimum Temperature Sensed	-50 °C
Termination Type	Cable
Cable Length	2 m
Process Connection	Probe
Number Of Wires	4
Accuracy	Class B

Support

Placing an Order
Payment
Delivery Method
Returns
Product Support

Our Services

Delivery Options
DesignSpark

About RS

About RS
Contact Us
RS Worldwide
Corporate Group

Hot Topics



Contact us

📞 (65) 6865 3433

✉ Orders.ID@rs.rsgroup.com

© RS Components Pte Ltd Robinson Road, PO Box 1582, Singapore 903132

[Terms and Conditions of Sales](#) [Data Protection](#) [Export Compliance](#) [Privacy Policy](#) [Email Security](#) [Cookie Policy](#)

[Website Terms](#)