



µLab worksheet • Kubernetes in one container

Group _____ Date _____ Time _____

Driver (types) _____ Mapper (looks up) _____ Referee (demos) _____

Hand this in at the end of the round. The referee presents this work in 90 seconds at the caucus, so the referee has to follow it, not just watch it.

1 • THE CORE, IN FIVE STEPS • TEN MINUTES

1 ☐ Start a cluster

```
docker run -d --name k8s --privileged --tmpfs /run --tmpfs /var/run \
-p 6443:6443 rancher/k3s:v1.31.5-k3s1 server --disable=traefik
```

Then `docker exec -it k8s sh` and stay there: `kubectl` is already installed inside.

Why `--disable=traefik`? k3s normally installs Traefik, an **ingress controller**: the component that takes HTTP traffic arriving from outside and routes it to the right service inside the cluster. It claims ports 80 and 443 on your machine and adds time to the start. Nothing today arrives from outside, so we tell k3s to skip it.

2 ☐ Ask the cluster to keep a whale running

```
kubectl create deployment whale --image=ghcr.io/oesteban/whalesay --replicas=3
```

A **Deployment** says: this many of these should exist, at all times. You do not say when to start anything.

3 ☐ Look at what the controller made

```
kubectl get pods — once straight away, once about a minute later.
```

This lists the **Pods** the Deployment created on your behalf. Two columns matter: **STATUS**, what the pod is doing right now, and **RESTARTS**, how many times the container inside it has been started again. Write both readings in panel 3.

4 ☐ Ask for the same image to run once, instead of forever

```
kubectl create job whale --image=ghcr.io/oesteban/whalesay -- cowsay 'a cluster ran me'
```

A **Job** says: run this to completion, once. Same image, same cluster, same command — only the kind of object is different.

5 ☐ Read what it printed

```
kubectl logs job/whale
```

`kubectl logs` prints whatever a container wrote to its output. You did not have to find the pod: naming the Job was enough, and `kubectl` found it for you.

2 • WHAT YOU STARTED

From `kubectl get nodes`:

NAME	_____	VERSION	_____
STATUS	_____	AGE when first Ready	_____

3 • THE TWO READINGS, AND THE REASON

First reading

STATUS _____

RESTARTS _____

A minute later

STATUS _____

RESTARTS _____

The container did not crash. It printed its whale and exited **successfully**. So why is Kubernetes starting it again?

The Job in step 4 used **the same image** and did not do this. What did you change, in one sentence?

4 • WHAT THE LOGS WILL TELL YOU

Logs are the first place you look when something is wrong, and they are not only for things that are wrong. Try all four, inside the cluster.

`kubectl logs deploy/whale`

There are three pods. Which one did it pick, and how do you know?

`kubectl logs <pod> --previous`

The container that **already died**. Why would that ever be the only copy left?

`kubectl logs -l app=whale --prefix`

All three at once. What does the prefix tell you?

`kubectl logs <pod> --timestamps`

Now you can see **when**. How far apart are the restarts?

A pod is gone and you want to know why. Which of those four do you reach for, and what would you have lost if you had waited an hour?

Reached this line? Then you have solved the challenge.



Referee: tick the box on the left now, and write the time. Do not wait for the caucus. Then carry on below — the extensions are not optional, they are the rest of the round.

Solved at _____ Referee's initials _____

5 • NOW USE THE IMAGE YOU BUILT ON FRIDAY

Everything so far ran **someone else's** image. Repeat step 2 with your own, the one your GitHub Actions workflow published on Friday:

`kubectl create deployment mine --image=ghcr.io/<your-handle>/whalesay`

Your handle _____ Did it pull? _____

If it did not, `kubectl describe pod` will name the reason. Write it down, then fix it.

Nobody told the cluster where `ghcr.io` is, and nobody gave it a password. So: what **is** a registry, and what had to be true of your package for this to work at all?

On Friday you pushed to **GHCR**. When you type `docker pull alpine` you get an image from **Docker Hub**, and you never type a registry name. Where did that default come from, and what is the full name your `alpine` actually has?

6 • MAKE THE CLUSTER EXPLAIN ITSELF

First, the node's NAME from panel 2 is not a hostname anybody chose. Where does it come from, and what does that tell you about what a "node" is here?

`kubectl describe pod <one of the whale pods>` and read the **Events** block at the very bottom. Copy the two most recent event lines.

Then `kubectl get events --sort-by=.lastTimestamp | tail -5`. Whose account of the morning is this — yours, or the controller's?

7 • TWO IMAGE STORES, ONE NAME

Inside the cluster: `crictl images`.

On your laptop, in another terminal: `docker images`.

whalesay in `crictl`? _____ in `docker`? _____

Nobody copied anything from your laptop into the cluster. So how did the image get there?

8 • A WISH IS NOT A COMMAND

`kubectl scale deployment whale --replicas=5`, wait, then `kubectl scale deployment whale --replicas=0`. Count the pods after each.

pods at 5 _____ pods at 0 _____

Now delete the **Job's** pod: `kubectl delete pod <the job pod>`. Does it come back? Does a Deployment's pod come back? Why are the answers different?

9 • EXTRA MILE • SATISFY THE DEPLOYMENT INSTEAD OF ABANDONING IT

In step 4 you stopped the restarting by changing the **object**. There is a second way that leaves it a Deployment: same image, no rebuild, no re-push, sitting at `RESTARTS 0` and `Running`. Write the command.

You have now satisfied a Deployment two ways. Which would you use for a web server, and which for a nightly report?

No hint. The image runs one program and then stops; nothing says it has to.

Done when the referee can say, without reading this sheet, why the same image restarts forever as a Deployment and finishes as a Job.