

```

#include <stdio.h>
#include <string.h>
struct employee {
    char name[500];
    char post[500];
    int empid;
    float salary;
};

int main(){
    struct employee emp[500];
    int i,n;
    float max;

    max = 0.0;
    printf("Enter the number of records of employees you want to enter: ");
    scanf("%d", &n);

    for(i=0; i<n; i++){
        printf("Employee record no: %d\n", i+1);
        printf("Enter the name of the employee: ");
        scanf("%s", emp[i].name);
        printf("Enter the post of the employee: ");
        scanf("%s", emp[i].post);
        printf("Enter the employee id: ");
        scanf("%d", &emp[i].empid);
        printf("Enter the salary of the employee: ");
        scanf("%f", &emp[i].salary);
    }

    for(i=0; i<n; i++){
        if(emp[i].salary > max){
            max = emp[i].salary;
        }
    }
    printf("The records of the employee having the maximum salary is\n %.2lf: ", max);
    for(i=0; i<n; i++){
        if(emp[i].salary == max){

            printf("name %s\n\n:", emp[i].name);
            printf("Employee id %d\n\n:", emp[i].empid);
            printf("post %s\n\n:", emp[i].post);
            printf("Salary is %.2lf\n\n", emp[i].salary);
        }
    }
    return 0;
}

```