TempoBench-Grounded Human/AI Benchmark Game Family (GF-01): Standalone Formal Specification with Decision and Hypothesis Glossary

Bobby Veihman
Project Specification

Last edited: March 22, 2026

Abstract

This document gives a standalone formal specification for the current TempoBench-grounded benchmark family `GF-01` (see Definition 9). Ground truth is defined over a canonical substrate: *(HOA/reactive-system object, finite trace, explicit intervention semantics)*. Primary scoring is machine-checkable through structured certificates rather than free-form explanation. To keep the document readable without access to repository-internal notes, all referenced decision labels (DEC-*), hypothesis labels (HYP-*), and renderer labels (GF-01-R*) are explicitly defined here.

Public implementation repository. A publishable mirror of the benchmark implementation artifacts is available at https://github.com/official-Auralin/Benchmark-game.

1 Reading Guide and Label Glossary

1.1 What the labels mean

- **DEC-***: locked project decisions that are normative in this specification.
- **HYP-***: explicit hypotheses (not yet treated as facts), each with a validation plan.
- **Q-***: question-lineage items (open, deferred, or resolved), with status maintained in the decision/open-question logs.
- **EVAL-***: evaluation-condition tracks (closed-book, tool-augmented, oracle-ceiling).
- **MET-***: metric/scoring regimes.
- **Code/field identifiers**: shown in monospace (e.g., `family_id`, `eval_track`).

1.2 Renderer labels used in this document (see Definition 9)

- **GF-01-R1**: canonical causal-board single-agent renderer with explicit timestep progression; interventions for timestep t are chosen before advancing to $t + 1$.
- **Future renderer variants**: not active in the current repo; any future labels require explicit parity/leakage/reporting amendments before activation.

2 Objective and Evidence Anchors

2.1 Objective

The benchmark is designed to evaluate temporal causality reasoning, aligned with TempoBench TCE-style tasks where the model must recover causally relevant interventions over time [4].

2.2 Evidence policy

Nontrivial factual claims in this document are backed by cited sources. Project-policy locks are identified by DEC labels. Statements not yet established empirically are marked as HYP labels.

3 Canonical Substrate and Formal Notation

3.1 Finite-trace benchmark scope

TempoBench defines task objects over automata and finite traces for temporal reasoning and temporal causality [4]. Coenen et al. formalize temporal causality in reactive systems in an ω-trace setting with explicit counterfactual structure [3]. This benchmark intentionally uses a finite-trace operational scope while keeping formal causality checks machine-verifiable.

Definition 1 (System and proposition partition)**.** *Each instance uses a system object A with atomic propositions*

$$AP = AP_{\text{in}} \uplus AP_{\text{out}},$$

where AP_{in} are intervenable input propositions and AP_{out} are observable output propositions.

Definition 2 (Base trace)**.** *Let*

$$\tau = (\tau_0, \ldots, \tau_{T-1}), \qquad T \geq 1,$$

where each $\tau_t : AP_{\text{in}} \to \{0, 1\}$ is an input valuation.

Intuition. τ is the default input schedule. The player/agent edits this schedule via interventions (see Definition 3, Definition 4, and Definition 5).

3.2 Intervention semantics

Definition 3 (Intervention atom)**.** *An intervention atom is (t, a, v) with $t \in \{0, \ldots, T-1\}$, $a \in AP_{\text{in}}$, $v \in \{0, 1\}$.*

Definition 4 (Certificate)**.** *A certificate is a finite set*

$$C \subseteq \{0, \ldots, T-1\} \times AP_{\text{in}} \times \{0, 1\}.$$

Definition 5 (Apply operator)**.** *Define the intervened trace $\tau[C] = \text{Apply}(\tau, C)$ (`Apply`) by*

$$\tau[C]_t(a) = \begin{cases} v, & \text{if } (t, a, v) \in C, \\ \tau_t(a), & \text{otherwise.} \end{cases}$$

Malformed certificates with conflicting assignments to the same (t, a) are rejected by structural validation.

Intuition. "Unchanged" is represented by omission: if no atom targets (t, a), base trace value $\tau_t(a)$ remains.

3.3 Run and canonical observation object

Definition 6 (Run)**.**

$$\rho = \mathrm{Run}(A, \tau[C])$$

*denotes the benchmark rollout under the intervened trace (**Run**). For a fixed instance bundle and evaluator version, rollout semantics are replay-deterministic (DEC-024, DEC-031).*

Definition 7 (Canonical observation object)**.** *At timestep t, the canonical agent-facing object is*

$$O(s_t) = \{t, y_t, \texttt{effect_status}_t, b_T^{\mathrm{rem}}, b_A^{\mathrm{rem}}, C_{\leq t}, \mathrm{mode}, t^*\},$$

with hidden internal state omitted. All renderers must be semantics-preserving maps from this canonical object.

Definition 8 (Canonical exposure set)**.** *Define the renderer/agent exposure set as*

$$I(s_t) = O(s_t) \cup \{\textit{static mission metadata}\},$$

where static mission metadata includes objective description, mode semantics, and declared budgets.

Parity lock. By DEC-100t and DEC-100x, any renderer-facing summaries (wave strips, tile threat overlays, deployment feedback, and inspector views) must be derivable from Definition 8 and committed action history only; no hidden-state-only fields may be shown.

4 Instance Definition and Game Interpretation

4.1 What GF-01 means (family-level definition)

Definition 9 (GF-01 benchmark family)**.** *GF-01 is a forward-time, intervention-driven benchmark family in which:*

1. *the environment evolves over discrete timesteps $t = 0, \ldots, T-1$,*
2. *at each timestep, an agent (human or AI) can apply do-style edits to input propositions in AP_{in},*
3. *the episode objective is to achieve a formal effect predicate e with a certificate that passes machine-checkable causal-validity tests (sufficiency + minimality),*
4. *scoring is computed from structured artifacts (intervention logs and final certificate), not from natural-language explanation.*

Plain-language interpretation. GF-01 is the core game family name for this benchmark. The active renderer (GF-01-R1) and any future renderer variants are just different user interfaces over the same formal game: same state semantics, same intervention rules, same ground truth, and same evaluator.

Definition 10 (GF-01 instance)**.** *A GF-01 instance is*

$$I = (A, AP_{\mathrm{in}}, AP_{\mathrm{out}}, \tau, T, e, t^*, \mathrm{mode}, w(I), B_T, \mathrm{meta}).$$

Field meanings.

- e: machine-checkable effect predicate,
- t^*: target timestep for effect objective,
- mode $\in \{\text{normal}, \text{hard}\}$,
- $w(I)$: trailing window size used in normal mode,
- B_T: primary timestep intervention budget.

This object is the formal instance contract used throughout the evaluator (see Definition 10).

4.2 Mode-specific effect objective

$$E_{\text{hard}}(\rho, e, t^*) := [\rho_{t^*} \models e],$$
$$E_{\text{norm}}(\rho, e, t^*, w) := \exists t \in [\max(0, t^* - w), t^*]\ [\rho_t \models e].$$
$$E_I(\rho) = \begin{cases} E_{\text{norm}}(\rho, e, t^*, w(I)), & \text{mode} = \text{normal}, \\ E_{\text{hard}}(\rho, e, t^*), & \text{mode} = \text{hard}. \end{cases}$$

This normal/hard split is locked by DEC-014.

4.3 Normal-mode window scaling policy

Current locked default:

$$w(I) = \text{clamp}(w_{\min}, w_{\max}, \text{round}(\alpha_0 + \alpha_T T + \alpha_C z(I))),$$

with provisional defaults (DEC-014b): $\alpha_0 = 1$, $\alpha_T = 0$, $\alpha_C = 2$, $w_{\min} = 1$, $w_{\max} = 6$, and equal-weight normalized complexity composite $z(I)$ based on TempoBench-linked structural factors [4].

Complexity policy lock (DEC-058). The composite score definition above is the normative calibration signal under `gf01.complexity_policy.v1`. Per-knob predictive statistics are reported as machine-checkable diagnostics in `pilot-analyze` but do not replace composite-score trigger semantics in DEC-014d.

5 Ground-Truth Causality Contract

Definition 11 (Sufficiency)**.**

$$\text{Suff}_I(C) := \mathbf{1}[E_I(\text{Run}(A, \tau[C])) = 1].$$

Definition 12 (Normative minimality (singleton-removal))**.**

$$\text{Min1}_I(C) := \mathbf{1}\Big[\forall c \in C : E_I(\text{Run}(A, \tau[C \setminus \{c\}])) = 0\Big].$$

Definition 13 (Normative validity)**.**

$$\text{Valid}_I(C) := \text{Suff}_I(C) \wedge \text{Min1}_I(C).$$

Definition 14 (Ground-truth certificate set)**.**

$$\mathcal{M}(I) := \{C \mid \text{Valid}_I(C) = 1\}.$$

Multiple distinct valid minimal certificates are allowed.

Normative policy. DEC-012 locks singleton-removal minimality as normative scorer behavior.

5.1 Optional stronger diagnostic

Optional (non-scoring) exact subset-minimality diagnostic:

Definition 15 (Optional exact subset-minimality diagnostic)**.**

$$\mathrm{SubsetMin}_I(C) := \mathbf{1}[\nexists C' \subset C \ \textit{with}\ \mathrm{Suff}_I(C') = 1].$$

By policy (DEC-012a, DEC-012b), this diagnostic is optional and exact-only when run.

6 Coenen Alignment and Scope Divergence

Coenen et al. define causality with explicit PC1/PC2/PC3 structure, contingencies, and strict-subset/property-level minimality [3]. This benchmark intentionally diverges in normative scoring by using finite intervention certificates with singleton-removal minimality. The divergence is explicit and policy-locked (centered on DEC-012), not implicit.

7 Evaluation Tracks and Metric Regimes

7.1 Evaluation-condition tracks

- `EVAL-CB`: closed-book (no external tools beyond model-internal reasoning/scratchpad).
- `EVAL-TA`: tool-augmented with predeclared allowlist and full tool logging.
- `EVAL-OC`: solver-oracle ceiling track, reported separately.

Track separation is mandatory (DEC-001, DEC-001a). Tool metadata policy is mandatory (DEC-053):

- `EVAL-CB`: `tool_allowlist_id=none`, `tool_log_hash=""`.
- `EVAL-TA`: `tool_allowlist_id=local-planner-v1` and non-empty `tool_log_hash`.
- `EVAL-OC`: `tool_allowlist_id=oracle-exact-search-v1` and non-empty `tool_log_hash`.

Adaptation metadata policy is mandatory (DEC-055):

- `adaptation_condition=no_adaptation` requires `adaptation_budget_tokens=0`, `adaptation_data_scope=none`, `adaptation_protocol_id=none`.
- `adaptation_condition in {prompt_adaptation, weight_finetune}` requires `adaptation_budget_tokens>0`, `adaptation_data_scope != none`, and non-empty `adaptation_protocol_id`.

7.2 Metric regimes

The symbols in this section reuse formal objects from Definition 11, Definition 12, Definition 13, and Definition 14.

MET-C (Certified Causality).

$$\text{Score}_C(I) = \mathbf{1}[\text{Valid}_I(C_a) = 1].$$

where the implementation artifact name is `Score_C`.

MET-M (Multi-objective). For agent certificate C_a:

$$M(I) = \mathbf{1}[\text{Valid}_I(C_a) = 1], \quad G(I) = \mathbf{1}[\text{Suff}_I(C_a) = 1],$$

$$\text{Eff}_t(I) = |\text{TS}(C_a)|, \quad \text{TS}(C) = \{t \mid \exists a, v : (t, a, v) \in C\},$$

$$\text{Eff}_a(I) = |C_a|.$$

Per-instance lexicographic key:

$$\kappa(I) = \big(M(I), G(I), -\text{Eff}_t(I), -\text{Eff}_a(I)\big).$$

with implementation key name `kappa`.

Intuition. The scoring priority is: valid minimal causality first, then effect success, then fewer intervention timesteps.

7.3 AP/TS precision-recall-F1 under non-unique minima

TempoBench reports AP/TS causality metrics [4]. With non-unique $\mathcal{M}(I)$ (Definition 14), deterministic best-match target is (DEC-025):

$$C^*(I, C_a) = \arg\max_{C \in \mathcal{M}(I)} F1_{AP}(C_a, C),$$

then tie-break by $F1_{TS}$, then lower Eff_t, then canonical atom hash order.

7.4 Required reporting dimensions

Official reports must stratify by:

```
(family_id, eval_track, renderer_track,
renderer_profile_id,
play_protocol, scored_commit_episode,
adaptation_condition, adaptation_budget_tokens,
adaptation_data_scope, adaptation_protocol_id,
difficulty_slice, split_id)
```

No cross-track pooling is allowed. Under DEC-046, official runs currently fix:

```
play_protocol=commit_only
scored_commit_episode=true
```

but fields remain explicit to prevent silent protocol mixing if policy is amended. This follows evidence that aggregate single scores can hide major failures [6] and that contamination/governance choices can distort benchmark conclusions [1, 9, 10].

Split governance policy. Publication-governance split policy is locked by DEC-054. The default official ratio target is:

```
public_dev=0.20, public_val=0.20, private_eval=0.60
```

with default absolute tolerance 0.05 checked per split by `split-policy-check`. This policy is reported separately from pilot-only freezes and is intended to reduce contamination risk while preserving reproducibility slices.

Release rotation and contamination policy. Cross-cycle release governance is additionally locked by DEC-067. The machine-checkable command `release-governance-check` combines `gf01.split_policy.v1` checks with rotation safeguards:

- prior-cycle `private_eval` instances must not appear in current `public_*` splits;
- current public-set novelty versus prior public set must exceed a configurable threshold (default 0.10).

This operationalizes contamination-risk controls from [9, 10] while retaining procedural-refresh pressure motivated by [2, 5].

Baseline panel policy. Anti-shortcut baseline policy is locked by DEC-056. Default campaign enforcement level is `full`, requiring `random,greedy,search,tool,oracle`. An explicit `core` level is available for fast internal smoke checks and requires `random,greedy,oracle`. This follows the anti-shortcut principle that release evaluations must include heuristic-stress and ceiling references rather than a single easy baseline. At release time, DEC-068 enforces this policy with `release-report-check`, which fails if required baseline agents or required eval tracks are missing from any manifest `(split_id, mode)` slice.

Integrated release-candidate command and CI policy. By DEC-072, release-governance, release-report, and release-package checks are additionally composable through one machine-checkable command, `release-candidate-check`, which outputs explicit stage-level pass/fail payloads. By DEC-074, CI executes this integrated command as a required status check alongside the one-shot gate. Hosted branch protection therefore requires both:

```
GF01 Gate / gate
GF01 Gate / release-candidate
```

By DEC-082, workflow jobs additionally publish these exact context names as commit statuses on the PR head SHA (fallback `github.sha`) to avoid pending-state mismatches between required-check configuration and reported status contexts. Activation guidance for remote repository settings is captured by DEC-075.

8 Generator Contract and Difficulty Scaling

8.1 Canonical formal input object

$$G_{\text{formal}} = (A, \tau, AP_{\text{in}}, AP_{\text{out}}, F, \text{meta}).$$

Legacy development generation may additionally use implementation-facing `seed/cfg` fields, but official semantic identity is the normalized formal content rather than the seed value itself. Formal ingestion is defined for any finite trace length $T \geq 1$. Candidates are accepted only if exact normative checking confirms $\mathcal{M}(I) \neq \emptyset$ (see Definition 14).

8.2 Determinism lock

For fixed normalized formal content and normalization/checker versions, output must be bit-identical. Legacy development generation additionally requires bit-identical output for fixed $(A, \tau, AP_{\text{in}}, AP_{\text{out}}, F, \text{seed}, \text{cfg}, \text{generator_version})$. No wall-clock or system-entropy randomness is permitted in either path.

8.3 Connection to TempoBench generation evidence

TempoBench describes a formal generation/evaluation pipeline using specification-to-automaton synthesis and causal extraction over generated traces [4]. Repo-side benchmark-runner artifacts provide AP/TS-scored execution/logging behavior [8]. Solver-validated generation as a general methodology is also supported by SATBench-style design [11].

9 Optional-Diagnostic Infeasibility Policy

Normative exact checks are always required. Only optional diagnostics may be marked infeasible (DEC-019).

Hybrid policy (DEC-020):

- platform/runtime caps P_{ref},
- algorithmic-budget caps A_{ref}.

Initial cap freeze timing is aligned with DEC-021 checkpoint; derivation uses dual-threshold rule from DEC-022 with provisional defaults $p = 0.90$, $k = 3$ (DEC-023).

10 Partial Observability and No-Query Rule

Hidden state is allowed but not directly exposed. Agents gather information only from passive observations and intervention consequences. Explicit query actions are excluded. The agent-facing channel is the canonical observation object in Definition 7. This aligns with interactive-agent evaluation practices that require explicit environment protocols rather than static one-shot prompts [7, 12].

Identifiability acceptance policy. To prevent low-signal partially observable instances, acceptance is gated by a machine-checkable identifiability policy. By DEC-059:

```
policy_version = gf01.identifiability_policy.v1
metric_id = single_atom_observation_divergence.v1
min_response_ratio = 0.60
min_unique_signatures = 8
```

These checks are enforced at generation time and are auditable on bundle artifacts using `identifiability-check`. They remain explicit policy constants (rather than implicit heuristics) so amendments must be tracked via decision-log updates.

11 Renderer Policy and Current Priority

11.1 Renderer parity requirement

Renderer variants are allowed only if they preserve canonical $O(s)$ semantics, intervention semantics, and scoring outcomes (see Definition 7 and Definition 13). By DEC-057, the active renderer-policy mapping is:

- `renderer_track=json` → `renderer_profile_id=canonical-json-v1`,
- `renderer_track=visual` → `renderer_profile_id=GF-01-R1`.

Any additional renderer profile is out of scope for current official runs until an explicit amendment records parity/leakage gate evidence. Within `GF-01-R1`, interaction backends may differ (`text` terminal snapshot vs `pygame` graphical view) while remaining under the same renderer profile and canonical scoring semantics (DEC-100).

11.2 Current lock

By DEC-038, implementation priority is:

- active canonical renderer: `GF-01-R1` (causal-board, spatial-board single-agent renderer),
- any future deferred renderer candidate is promoted only after DEC-038a gates pass: semantic parity, leakage-audit parity, and track-separated reporting.

11.3 Interaction protocol lock (`GF-01-R1`)

By DEC-045, the baseline human-playable protocol is:

1. a visible static goal panel from episode start (including target output proposition, target timestep, and mode semantics),
2. one scored commit episode as the normative benchmark run.

Scoring contract under `DEC-045`. Only the commit episode contributes to official machine-checkable metrics (Definition 13, Definition 14). Official run artifacts carry fixed `play_protocol=commit_only` and `scored_commit_episode=true` values.

Why exploration is excluded from official runs. Interactive evaluation requires explicit environment protocols and logging [7, 12]. Keeping official runs commit-only avoids confounding score outcomes with unbounded rehearsal opportunities that can distort benchmark conclusions [6].

12 Active Hypotheses and Validation Plans

- **HYP-005**: exact subset-minimal diagnostics may be costly at scale. Validation: runtime/cost curves versus instance complexity.
- **HYP-006**: forward-time defensive gameplay can preserve TCE fidelity while improving engagement. Validation: matched human/agent pilot.

- **HYP-007/HYP-008**: complexity-scaled normal windows and current trigger constants are useful but provisional. Validation: post-pilot recalibration audit.
- **HYP-011/HYP-012**: current family ranking and decision matrix are inference-first and require empirical backfill.
- **HYP-013/HYP-014**: hybrid infeasibility caps improve cross-lab comparability when frozen from pilot evidence.
- **HYP-015/HYP-016/HYP-020**: calibration/discrimination and Python-first feasibility remain monitored under protocol-scale reruns and structural hardening changes.
- **HYP-017**: a future renderer variant may scale better than the current causal-board `GF-01-R1` on high-complexity slices. Validation: matched-seed parity/usability pilot versus R1.

13 Resolved Deferred Item and Current Risk Note

- **Q-033 (resolved):** larger stratified profiling/closure rerun completed under structural setting `min_witness_atoms=2`; both replicates passed pre-registered global and stratified gates with `close_q033=true`.
- Optional-diagnostic coverage comparability depends on successful cap freeze execution and transparent run metadata.

14 Summary

This specification locks the current normative benchmark contract while keeping hypotheses and question-lineage status explicitly labeled. The document is self-contained: all key labels and renderer identifiers used in formal sections are defined in this document, with normative decisions collected in Appendix A.

A Normative decisions referenced in this spec

`DEC-001`
: report `EVAL-CB`, `EVAL-TA`, and `EVAL-OC` separately; do not mix tracks.

`DEC-001a`
: keep naming separation: `EVAL-*` for conditions, `MET-*` for metric regimes.

`DEC-002`
: interventions occur online during play.

`DEC-003`
: intervention semantics are ternary per (t, AP): set 0, set 1, unchanged.

`DEC-004`
: primary efficiency cost is number of distinct intervened timesteps; legacy atom-count metadata may be reported diagnostically but is not part of official validity.

`DEC-005`
: action availability must not leak hidden state.

`DEC-012`
: normative minimality is singleton-removal.

`DEC-012a`
: subset-minimality is optional and non-scoring.

`DEC-012b`
: subset-minimality diagnostics must be exact-only when run.

`DEC-014`
: hard mode uses exact-time objective; normal mode uses windowed objective.

`DEC-014a`
: normal-mode window scales with complexity.

`DEC-014b`
: current normal-window coefficients are fixed defaults, pending post-pilot calibration.

`DEC-014c`
: coefficient recalibration follows a pre-registered dual-trigger rule (threshold anomaly or fixed-sample checkpoint).

`DEC-014d`
: current provisional recalibration constants are locked as: sample target $N = 240$, discrimination threshold $\Delta_{Q1,Q4} = 0.12$, hard-quartile floor $M_{Q4} = 0.10$, shortcut-goal threshold 0.40, and shortcut-certified floor 0.05.

`DEC-016`
: renderer variants are allowed only under semantic parity.

`DEC-018`
: per-timestep intervention cardinality is unrestricted, constrained by global budgets.

`DEC-019`
: exact normative checks are always mandatory.

`DEC-020`
: optional-diagnostic infeasibility uses hybrid caps (P_{ref}, A_{ref}).

`DEC-021`
: initial cap freeze timing is tied to the scheduled pilot checkpoint.

`DEC-022`
: cap derivation uses a dual-threshold rule.

`DEC-023`
: current provisional dual-threshold defaults are $p = 0.90$, $k = 3$.

`DEC-024`
: generator determinism is mandatory for fixed input tuple.

`DEC-025`
: AP/TS PRF under non-unique minima uses deterministic best-match mapping.

DEC-031
run artifact schemas are versioned and metadata-rich.

DEC-038
implementation priority is `GF-01-R1` first.

DEC-038a
`GF-01-R3` promotion requires pre-registered parity/leakage/reporting gates.

DEC-045
`GF-01-R1` uses visible-goal + single scored commit run; exploration episodes are not part of official scoring protocol.

DEC-046
run artifacts must include `play_protocol/scored_commit_episode` with fixed `commit_only/true` values for official runs.

DEC-053
`tool_allowlist_id` is track-constrained under `gf01.tool_policy.v1`: `EVAL-CB` requires `none`/empty hash, `EVAL-TA` requires `local-planner-v1`+non-empty hash, and `EVAL-OC` requires `oracle-exact-search-v1`+non-empty hash.

DEC-054
publication split governance is locked by `gf01.split_policy.v1` with official labels `public_dev/public_val/private_eval`, target ratio `0.20/0.20/0.60`, and machine-checkable policy validation via `split-policy-check`.

DEC-066
reproducibility bundling is enforced via `release-package`: package creation requires strict run+manifest validation and emits hash-addressed artifact manifests plus rerun instructions.

DEC-067
release rotation/contamination governance is locked by `gf01.rotation_policy.v1` and checked with `release-governance-check`: prior private instances are forbidden in current public splits, and public novelty versus prior public set must exceed a configured minimum ratio.

DEC-055
adaptation/fine-tuning reporting is locked by `gf01.adaptation_policy.v1`: condition labels are `no_adaptation/prompt_adaptation/weight_finetune`, and budget/scope/protocol fields must satisfy condition-specific constraints.

DEC-056
anti-shortcut baseline panel policy is locked by `gf01.baseline_panel_policy.v1`: official publication campaigns use full panel `{random,greedy,search,tool,oracle}`; optional core smoke policy requires `{random,greedy,oracle}`.

DEC-068
release report policy is machine-checkable via `release-report-check`: required baseline-agent and required eval-track coverage must be present for each manifest `(split_id, mode)` slice.

DEC-072
integrated release-candidate policy composition is machine-checkable via `release-candidate-check`, which emits explicit stage-level outcomes for governance/report/package checks.

DEC-074

CI must execute integrated release-candidate checks and branch protection must require both status checks: `GF01 Gate / gate` and `GF01 Gate / release-candidate`.

DEC-082

CI must publish explicit commit-status contexts for those required checks on the PR head commit (fallback current workflow SHA), so hosted ruleset enforcement binds to reported contexts, not only check-run names.

DEC-075

remote branch-protection activation uses an explicit checklist handoff artifact when local execution cannot apply hosted policies directly.

DEC-057

renderer freedom is locked by `gf01.renderer_policy.v1`: `renderer_track=json` maps to `canonical-json-v1`; `renderer_track=visual` maps to `GF-01-R1`; other profiles are disallowed until explicit amendment.

DEC-099

active human-playable visual direction is a causal-board and spatial-board first for `GF-01-R1`; curated missions are onboarding-only and must remain generator-derived.

DEC-099a

canonical visual-plan governance uses a single active plan artifact; conflicting split plans are not allowed (current active authority: `spec/plan.md`).

DEC-100

`play` supports `visual_backend={text,pygame}` for `renderer_track=visual`; non-visual tracks must use `visual_backend=text`.

DEC-100d

`GF-01-R1` pygame renderer includes observation-safe output-delta feedback derived only from successive observed outputs, with no hidden-state exposure.

DEC-100e

`GF-01-R1` pygame renderer supports deterministic keyboard AP toggles (‘1..9‘, ‘0‘) over the visible AP page with cycle semantics `unset -> 1 -> 0 -> unset`.

DEC-100f

`GF-01-R1` pygame renderer supports deterministic AP-density controls (‘+‘ / ‘-‘) with bounded page-size range `[4, 16]` for readability scaling.

DEC-100g

`GF-01-R1` pygame renderer supports an in-session quick-help overlay toggle (‘H‘) with deterministic control guidance text.

DEC-100s

map semantics are spatial-board first (square/rectangular topology); time progression is encoded by turn transitions $S_t \to S_{t+1}$, not a required spatial time axis.

DEC-100t

human/agent information-equivalence is locked as $I(s) = O(s)+$ static mission metadata; renderers may derive overlays only from this set plus committed player actions.

DEC-100u
interaction remains indirect and semantics-preserving: global command panel edits current-step AP values; commit advances one step.

DEC-100v
board-scaling parameters are deterministic functions of instance complexity metadata (no per-level manual tuning in official runs).

DEC-100w
large-board navigation policy may use deterministic pan/zoom/minimap affordances under the same parity constraints.

DEC-100x
visual mode includes an in-session canonical observation inspector and explicit command→sector correspondence cues, both constrained to observation-safe fields.

DEC-101
internal alpha (`P0`) is a required pre-participant stage with deterministic seed-backed execution and blocker/clarity gates before formal participant stage (`P1`).

DEC-101a
`p0-feedback-check` is the machine-checkable gate command for P0 advancement.

DEC-101b
`p0-feedback-template` + fixed command chain define the canonical P0 execution path.

DEC-101e
`p0-init` is the one-shot deterministic setup command that materializes both required P0 setup artifacts (feedback template + seed pack) while preserving the same policy semantics.

DEC-101f
`p0-session-check` is the machine-checkable artifact-coverage validation step that must pass before `p0-feedback-check` is interpreted for P0 advancement.

DEC-101g
`p0-gate` is the canonical sequential wrapper for P0 advancement checks, enforcing `p0-session-check` before `p0-feedback-check` in one deterministic command.

DEC-058
complexity-knob governance is locked by `gf01.complexity_policy.v1`: normative calibration uses fixed equal-weight normalized composite score, while `pilot-analyze` must emit per-knob diagnostics (including constant-knob detection and per-agent slices) as non-normative audit fields.

DEC-059
partial-observability identifiability governance is locked by `gf01.identifiability_policy.v1`: use metric `single_atom_observation_divergence.v1` with thresholds `min_response_ratio=0.60` and `min_unique_signatures=8`, enforced in generation and machine-checkable `identifiability-check` validation.

DEC-060
first-cycle review of `DEC-014d` constants: after checkpoint-scale evidence (`N=240` normal-mode

unique instances), constants remain unchanged in this cycle; calibration action should target coefficient/hardness tuning under the same trigger policy.

References

[1] Zerui Cheng, Stella Wohnig, Ruchika Gupta, Samiul Alam, Tassallah Abdullahi, Jose Alves Ribeiro, et al. Benchmarking is broken - don't let ai be its own judge. In *NeurIPS Datasets and Benchmarks Track*, 2025. URL https://arxiv.org/abs/2510.07575. source_id: SRC-020.

[2] Karl Cobbe, Christopher Hesse, Jacob Hilton, and John Schulman. Leveraging procedural generation to benchmark reinforcement learning. *arXiv preprint arXiv:1912.01588*, 2020. URL https://arxiv.org/abs/1912.01588. source_id: SRC-010.

[3] Norine Coenen, Bernd Finkbeiner, Hadar Frenkel, Christopher Hahn, Niklas Metzger, and Julian Siber. Temporal causality in reactive systems. In *Automated Technology for Verification and Analysis (ATVA)*, volume 13505 of *Lecture Notes in Computer Science*, pages 208–224, 2022. doi: 10.1007/978-3-031-19992-9_13. URL https://doi.org/10.1007/978-3-031-19992-9_13. source_id: SRC-003.

[4] Nikolaus Holzer, William Fishell, Baishakhi Ray, and Mark Santolucito. Mechanics of learned reasoning 1: Tempobench, a benchmark for interpretable deconstruction of reasoning system performance. *arXiv preprint arXiv:2510.27544*, 2025. doi: 10.48550/arXiv.2510.27544. URL https://arxiv.org/abs/2510.27544. source_id: SRC-001.

[5] Douwe Kiela, Max Bartolo, Yixin Nie, Divyansh Kaushik, Atticus Geiger, et al. Dynabench: Rethinking benchmarking in nlp. In *Proceedings of NAACL-HLT 2021*, 2021. doi: 10.18653/v1/2021.naacl-main.324. URL https://doi.org/10.18653/v1/2021.naacl-main.324. source_id: SRC-009.

[6] Percy Liang, Rishi Bommasani, Tony Lee, et al. Holistic evaluation of language models. *arXiv preprint arXiv:2211.09110*, 2022. URL https://arxiv.org/abs/2211.09110. source_id: SRC-017.

[7] Xiao Liu, Hao Yu, Hanchen Zhang, Yifan Xu, Xuanyu Lei, et al. Agentbench: Evaluating llms as agents. In *International Conference on Learning Representations (Datasets and Benchmarks Track)*, 2024. URL https://openreview.net/forum?id=zAdUB0aCTQ. source_id: SRC-008.

[8] nik-hz and contributors. Tempobench github repository. https://github.com/nik-hz/tempobench, 2025. URL https://github.com/nik-hz/tempobench. source_id: SRC-002.

[9] Weijia Shi, Sewon Min, Maria Lomeli, Chunting Zhou, Margaret Li, et al. Open source data contamination in gpt-4 and other llms. *arXiv preprint arXiv:2310.17589*, 2023. URL https://arxiv.org/abs/2310.17589. source_id: SRC-019.

[10] Soham, Anik Santikary, and Ruoxi Jia. A survey on the impact of data contamination in the evaluation of large language models. *arXiv preprint arXiv:2406.04244*, 2024. URL https://arxiv.org/abs/2406.04244. source_id: SRC-018.

[11] Anjiang Wei, Yuheng Wu, Yingjia Wan, Tarun Suresh, Huanmi Tan, Zhanke Zhou, Sanmi Koyejo, Ke Wang, and Alex Aiken. Satbench: Benchmarking llms' logical reasoning via automated puzzle generation from sat formulas. In *Proceedings of the 2025 Conference on*

Empirical Methods in Natural Language Processing, 2025. doi: 10.18653/v1/2025.emnlp-main.1716. URL https://doi.org/10.18653/v1/2025.emnlp-main.1716. source_id: SRC-004.

[12] Shuyan Zhou, Frank F. Xu, Hao Zhu, Xuhui Zhou, et al. Webarena: A realistic web environment for building autonomous agents. *arXiv preprint arXiv:2307.13854*, 2023. URL https://arxiv.org/abs/2307.13854. source_id: SRC-015.