

Suitable for 100mm (4") borewell Approx performance chart at 2880 RPM, 350 to 420V (T.P), 160 to 230V (S.P.), 50Hz AC Supply

DP-1C

DP SP/TP - TUBRO MOTOR WITH COPPER ROTOR

OUTLET SIZ	OUTLET SIZE:- 32 MM			Pri	ce₹		DISCHARGE IN LPM									
Model	Motor	Rating	STAGE	Single Phase	Three											
No.	Kw	H.P	SIAGE		Phase	0	15	20	25	35	45	50	60			
DP1C-5010	0.37	0.5	10	12718		60	55	50	45	40	35	25	15			
DP1C-7512	0.55	0.75	12	14:	332	72	66	60	54	48	42	30	18			
DP1C-7515	0.55	0.75	15	14616		90	82	75	68	60	53	38	23			
DP1C-116	0.75	1.00	16	16925		96	88	80	72	64	56	40	24			
DP1C-118	0.75	1.00	18	17	109	108	99	90	81	72	63	45	27			
DP1C-1525	1.10	1.50	25	20:	232	150	136	125	112	100	88	63	38			
DP1C-230	1.50	2.00	30	24	762	180	165	150	135	120	105	75	45			
DP1C-235	1.50	2.00	35	26300		210	192	175	158	140	120	88	53			
DP1C-245	2.20	3.00	45	32008		270	248	225	203	180	158	113	68			

DP-2C

OUTLET SIZE	OUTLET SIZE:- 32 MM				ce₹		DISCHARGE IN LPM							
Model	Moto	r Rating	STAGE	Single	Three				SCHAR	or IIV EI				
No.	Kw	H.P	STAGE	Phase	Phase	0	25	35	45	50	55	60	70	
DP2C-508	0.37	0.5	8	12	633	48	44	40	36	32	28	20	8	
DP2C-7510	0.55	0.75	10	14:	276	60	55	50	45	40	35	25	10	
DP2C-113	0.75	1.00	13	16868		78	72	65	59	52	46	33	13	
DP2C-115	0.75	1.00	15	17037		90	83	75	68	60	53	38	15	
DP2C-1520	1.1	1.50	20	19226		120	110	100	90	80	70	50	20	
DP2C-225	1.50	2.00	25	23	828	150	138	125	113	100	88	63	25	
DP2C-330	2.20	3.00	30	28	814	180	165	150	135	120	105	75	30	
DP2C-335	2.20	3.00	35	29	841	210	193	175	158	140	123	88	35	
DP2C-340	2.20	3.00	40	309	903	240	200	180	160	140	120	100	40	
DP2C-545	3.70	5.00	45	39	731	270	225	203	180	158	135	113	45	
DP2C-550	3.70	5.00	50	40	576	300	250	225	200	175	150	125	50	
DP2C-655	3.70	6.00	55	47	913	330	275	248	220	193	165	138	55	
DP2C-660	4.50	6.00	60	489	972	360	300	270	240	210	180	150	60	
DP2C-770	5.60	7.50	70	544	413	420	385	350	315	280	245	175	70	





Suitable for 100mm (4") borewell Approx performance chart at 2880 RPM, 350 to 420V (T.P), 160 to 230V (S.P.), 50Hz AC Supply

DP-4C

DP SP/TP - TUBRO MOTOR WITH COPPER ROTOR

OUTLET SIZ	E:- 32 MM	(1.25")		Prio	ce₹		DISCHARGE IN LPM							
Model	Motor	Rating	STAGE	Single	Three	DISCHARGE IN ET W								
No.	Kw	H.P	SIAGE	Phase	Phase	0	45	55	70	80	90	100	120	
DP4C-505	0.37	0.5	5	12!	590	30	25	23	20	18	15	10	5	
DP4C-758	0.55	0.75	8	14	14106		40	36	32	28	24	16	8	
DP4C-110	0.75	1.00	10	16740		60	50	45	40	35	30	20	10	
DP4C-112	0.75	1.00	12	16925		72	60	54	48	42	36	24	12	
DP4C-1515	1.10	1.50	15	19305		90	75	68	60	53	45	30	15	
DP4C-220	1.50	2.00	20	230	099	120	100	90	80	70	60	40	20	
DP4C-325	2.20	3.00	25	274	433	150	125	113	100	88	75	50	25	
DP4C-535	3.70	5.00	35	368	851	210	175	158	140	123	105	70	35	
DP4C-540	3.70	5.00	40	389	905	240	200	180	160	140	120	80	40	
DP4C-645	4.50	6.00	45	458	45845		225	203	180	158	135	90	45	
DP4C-650	4.50	6.00	50	46893		300	250	225	200	175	150	100	50	
DP4C-760	5.60	7.50	60	52:	52346		300	270	240	210	180	120	60	

DP-5C

OUTLET SIZE	OUTLET SIZE:- 40 MM (1.5")			Pri	ce₹		DISCHARGE IN LPM								
Model	Motor	Rating	STAGE	Single	Single Three		DISCHARGE IN EI III								
No.	Kw	H.P	SIAGE	Phase	Phase	0	60	75	85	90	105	135	150		
DP5C-18	0.75	1.00	8	16457		48	40	36	32	28	24	16	8		
DP5C-1512	1.10	1.50	12	19176		72	60	54	48	42	36	24	12		
DP5C-215	1.50	2.00	15	22930		90	75	68	60	53	45	30	15		
DP5C-320	2.20	3.00	20	268	26803		100	90	80	70	60	40	20		
DP5C-322	2.20	3.00	22	270	023	132	110	99	88	77	66	44	22		
DP5C-530	3.70	5.00	30	359	903	180	150	135	120	105	90	60	30		
DP5C-640	4.50	6.00	40	448	825	240	200	180	160	140	120	80	40		
DP5C-745	5.60	7.50	45	49	740	270	225	203	180	158	135	90	45		
DP5C-750	5.60	7.50	50	504	50448		250	225	200	175	150	100	50		









Suitable for 100mm (4") borewell Approx performance chart at 2880 RPM, 350 to 420V (T.P), 160 to 230V (S.P.), 50Hz AC Supply

DP-7C

OUTLET SIZE:- 40 MM (1.5")				Pri	ce₹	DISCHARGE IN LPM										
Model	Motor	Rating	STAGE	Single Phase	Single Three		DISCHARGE IN EL IN									
No.	Kw	H.P	SIAGE		Phase	0	65	75	100	110	130	155	180			
DP7C-17	0.75	1.00	7	16358		42	35	32	28	25	21	14	7			
DP7C-1510	1.10	1.50	10	18	950	60	50	45	40	35	30	20	10			
DP7C-214	1.50	2.00	14	22	930	84	70	63	56	49	42	28	14			
DP7C-318	2.20	3.00	18	26	655	108	90	81	72	63	54	36	18			
DP7C-525	3.70	5.00	25	35045		150	125	113	100	88	75	50	25			
DP7C740	5.60	7.50	40	48	890	240	200	180	160	140	120	80	40			

DP-10C

OUTLET SIZE:	- 50 MM	Prid	ce₹		DISCHARGE IN LPM												
Model	Motor I	Rating	STAGE		Single	Single Three		DISCHMINGE IN EI III									
No.	Kw	H.P	STAGE		Phase	0	120	130	140	150	165	185	200				
DP10C-15	0.75	1.00	5	16457		30	25	23	20	18	15	10	5				
DP10C-158	1.10	1.50	8	19 ⁻	184	48	40	36	32	28	24	16	8				
DP10C-210	1.50	2.00	10	230	099	60	50	45	40	35	30	20	10				
DP10C-315	2.20	3.00	15	26	26796		75	68	60	53	45	30	15				
DP10C-520	3.70	5.00	20	33	736	120	100	90	80	70	60	40	20				

DP-12C

OUTLET SIZE:	OUTLET SIZE:- 50 MM (2.0")				ce₹		DISCHARGE IN LPM							
Model	Motor	Rating	STAGE	Single Three		DISCHARGE IN EL III								
No.	Kw	H.P	SIAGE	Phase	Phase	0	135	145	170	180	200	220	240	
DP12C-156	1.10	1.50	6	19445		36	30	27	24	21	18	12	6	
DP12C-28	1.50	2.00	8	23	283	48	40	36	32	28	24	16	8	
DP12C-312	2.20	3.00	12	26	26045		60	54	48	42	36	24	12	
DP12C-516	3.70	5.00	16	32702		96	80	72	64	56	48	32	16	

DP-18C

OUTLET SIZE:	T SIZE:- 50 MM (2.0")			Prid	ce₹	DISCHARGE IN LPM									
Model	Motor I	Rating	STAGE	Single Three Phase Phase O	Three	DISCHARGE IN EL III									
No.	Kw	H.P	STAGE		0	130	180	220	250	310	350	410			
DP18C-26	1.50	2.00	6	25705		30	27	24	21	18	12	9	6		
DP18C-38	1.50	3.00	8	284	467	40	36	32	28	24	16	12	8		
DP18C-310	2.20	3.00	10	29:	331	50	45	40	35	30	20	15	10		
DP18C-512	3.70	5.00	12	36682		60	54	48	42	36	24	18	12		