

V4 REGULAR MODEL CORA SERIES 20 FEET HEAD VERTICAL BOREWELL SUBMERSIBLE PUMPSET



Suitable for 100mm (4") borewell
Approx performance chart at 2880 RPM, 350 to 420V (T.P), 160 to 230V (S.P), 50Hz AC Supply

DP - 1 C

DP SP/TP - TUBRO MOTOR WITH COPPER ROTOR

OUTLET SIZE:- 32 MM				Price ₹		DISCHARGE IN LPM							
Model No.	Motor Rating		STAGE	Single Phase	Three Phase								
	Kw	H.P.				0	15	20	25	35	45	50	60
DP1C-5010	0.37	0.5	10		12718	60	55	50	45	40	35	25	15
DP1C-7512	0.55	0.75	12		14332	72	66	60	54	48	42	30	18
DP1C-7515	0.55	0.75	15		14616	90	82	75	68	60	53	38	23
DP1C-116	0.75	1.00	16		16925	96	88	80	72	64	56	40	24
DP1C-118	0.75	1.00	18		17109	108	99	90	81	72	63	45	27
DP1C-1525	1.10	1.50	25		20232	150	136	125	112	100	88	63	38
DP1C-230	1.50	2.00	30		24762	180	165	150	135	120	105	75	45
DP1C-235	1.50	2.00	35		26300	210	192	175	158	140	120	88	53
DP1C-245	2.20	3.00	45		32008	270	248	225	203	180	158	113	68

DP - 2 C

OUTLET SIZE:- 32 MM				Price ₹		DISCHARGE IN LPM							
Model No.	Motor Rating		STAGE	Single Phase	Three Phase								
	Kw	H.P.				0	25	35	45	50	55	60	70
DP2C-508	0.37	0.5	8		12633	48	44	40	36	32	28	20	8
DP2C-7510	0.55	0.75	10		14276	60	55	50	45	40	35	25	10
DP2C-113	0.75	1.00	13		16868	78	72	65	59	52	46	33	13
DP2C-115	0.75	1.00	15		17037	90	83	75	68	60	53	38	15
DP2C-1520	1.1	1.50	20		19226	120	110	100	90	80	70	50	20
DP2C-225	1.50	2.00	25		23828	150	138	125	113	100	88	63	25
DP2C-330	2.20	3.00	30		28814	180	165	150	135	120	105	75	30
DP2C-335	2.20	3.00	35		29841	210	193	175	158	140	123	88	35
DP2C-340	2.20	3.00	40		30903	240	200	180	160	140	120	100	40
DP2C-545	3.70	5.00	45		39731	270	225	203	180	158	135	113	45
DP2C-550	3.70	5.00	50		40576	300	250	225	200	175	150	125	50
DP2C-655	3.70	6.00	55		47913	330	275	248	220	193	165	138	55
DP2C-660	4.50	6.00	60		48972	360	300	270	240	210	180	150	60
DP2C-770	5.60	7.50	70		54413	420	385	350	315	280	245	175	70

V4 REGULAR MODEL CORA SERIES 20 FEET HEAD VERTICAL BOREWELL SUBMERSIBLE PUMPSET



POWERZONE
PUMPS

Suitable for 100mm (4") borewell

Approx performance chart at 2880 RPM, 350 to 420V (T.P), 160 to 230V (S.P), 50Hz AC Supply

DP - 4 C

DP SP/TP - TUBRO MOTOR WITH COPPER ROTOR

OUTLET SIZE:- 32 MM (1.25")				Price ₹		DISCHARGE IN LPM							
Model No.	Motor Rating		STAGE	Single Phase	Three Phase								
	Kw	H.P.				0	45	55	70	80	90	100	120
DP4C-505	0.37	0.5	5		12590	30	25	23	20	18	15	10	5
DP4C-758	0.55	0.75	8		14106	48	40	36	32	28	24	16	8
DP4C-110	0.75	1.00	10		16740	60	50	45	40	35	30	20	10
DP4C-112	0.75	1.00	12		16925	72	60	54	48	42	36	24	12
DP4C-1515	1.10	1.50	15		19305	90	75	68	60	53	45	30	15
DP4C-220	1.50	2.00	20		23099	120	100	90	80	70	60	40	20
DP4C-325	2.20	3.00	25		27433	150	125	113	100	88	75	50	25
DP4C-535	3.70	5.00	35		36851	210	175	158	140	123	105	70	35
DP4C-540	3.70	5.00	40		38905	240	200	180	160	140	120	80	40
DP4C-645	4.50	6.00	45		45845	270	225	203	180	158	135	90	45
DP4C-650	4.50	6.00	50		46893	300	250	225	200	175	150	100	50
DP4C-760	5.60	7.50	60		52346	360	300	270	240	210	180	120	60

DP - 5 C

OUTLET SIZE:- 40 MM (1.5")				Price ₹		DISCHARGE IN LPM							
Model No.	Motor Rating		STAGE	Single Phase	Three Phase								
	Kw	H.P.				0	60	75	85	90	105	135	150
DP5C-18	0.75	1.00	8		16457	48	40	36	32	28	24	16	8
DP5C-1512	1.10	1.50	12		19176	72	60	54	48	42	36	24	12
DP5C-215	1.50	2.00	15		22930	90	75	68	60	53	45	30	15
DP5C-320	2.20	3.00	20		26803	120	100	90	80	70	60	40	20
DP5C-322	2.20	3.00	22		27023	132	110	99	88	77	66	44	22
DP5C-530	3.70	5.00	30		35903	180	150	135	120	105	90	60	30
DP5C-640	4.50	6.00	40		44825	240	200	180	160	140	120	80	40
DP5C-745	5.60	7.50	45		49740	270	225	203	180	158	135	90	45
DP5C-750	5.60	7.50	50		50448	300	250	225	200	175	150	100	50

V4 REGULAR MODEL CORA SERIES 20 FEET HEAD VERTICAL BOREWELL SUBMERSIBLE PUMPSET



Suitable for 100mm (4") borewell
Approx performance chart at 2880 RPM, 350 to 420V (T.P), 160 to 230V (S.P), 50Hz AC Supply

DP - 7 C

OUTLET SIZE:- 40 MM (1.5")				Price ₹		DISCHARGE IN LPM							
Model No.	Motor Rating		STAGE	Single Phase	Three Phase								
	Kw	H.P.				0	65	75	100	110	130	155	180
DP7C-17	0.75	1.00	7		16358	42	35	32	28	25	21	14	7
DP7C-1510	1.10	1.50	10		18950	60	50	45	40	35	30	20	10
DP7C-214	1.50	2.00	14		22930	84	70	63	56	49	42	28	14
DP7C-318	2.20	3.00	18		26655	108	90	81	72	63	54	36	18
DP7C-525	3.70	5.00	25		35045	150	125	113	100	88	75	50	25
DP7C740	5.60	7.50	40		48890	240	200	180	160	140	120	80	40

DP - 10 C

OUTLET SIZE:- 50 MM (2.0")				Price ₹		DISCHARGE IN LPM							
Model No.	Motor Rating		STAGE	Single Phase	Three Phase								
	Kw	H.P.				0	120	130	140	150	165	185	200
DP10C-15	0.75	1.00	5		16457	30	25	23	20	18	15	10	5
DP10C-158	1.10	1.50	8		19184	48	40	36	32	28	24	16	8
DP10C-210	1.50	2.00	10		23099	60	50	45	40	35	30	20	10
DP10C-315	2.20	3.00	15		26796	90	75	68	60	53	45	30	15
DP10C-520	3.70	5.00	20		33736	120	100	90	80	70	60	40	20

DP - 12 C

OUTLET SIZE:- 50 MM (2.0")				Price ₹		DISCHARGE IN LPM							
Model No.	Motor Rating		STAGE	Single Phase	Three Phase								
	Kw	H.P.				0	135	145	170	180	200	220	240
DP12C-156	1.10	1.50	6		19445	36	30	27	24	21	18	12	6
DP12C-28	1.50	2.00	8		23283	48	40	36	32	28	24	16	8
DP12C-312	2.20	3.00	12		26045	72	60	54	48	42	36	24	12
DP12C-516	3.70	5.00	16		32702	96	80	72	64	56	48	32	16

DP - 18 C

OUTLET SIZE:- 50 MM (2.0")				Price ₹		DISCHARGE IN LPM							
Model No.	Motor Rating		STAGE	Single Phase	Three Phase								
	Kw	H.P.				0	130	180	220	250	310	350	410
DP18C-26	1.50	2.00	6		25705	30	27	24	21	18	12	9	6
DP18C-38	1.50	3.00	8		28467	40	36	32	28	24	16	12	8
DP18C-310	2.20	3.00	10		29331	50	45	40	35	30	20	15	10
DP18C-512	3.70	5.00	12		36682	60	54	48	42	36	24	18	12