Source Code

```
#!/usr/bin/env bash
echo "SSH client:"
ssh -V 2>&1
echo
echo "SSH server service status (read-only):"
if command -v systemctl >/dev/null 2>&1; then
  systemctl --no-pager --full status ssh 2>&1 | head -n 8 ||
  systemctl --no-pager --full status sshd 2>&1 | head -n 8 || true
else
  echo "systemctl not available"
fi
echo
echo "Common SSH hardening settings in config (if readable):"
if [[ -r /etc/ssh/sshd_config ]]; then
  grep -E
'^[[:space:]]*(PermitRootLogin|PasswordAuthentication|PubkeyAuthe
ntication|MaxAuthTries)' /etc/ssh/sshd_config || echo "No matching
explicit settings; defaults/includes may apply"
else
  echo "Server configuration not readable or not present"
fi
```

Output :

```
sahil@HP:~/BCA-Linux-Project$ nano ssh_audit_readonly.sh
sahil@HP:~/BCA-Linux-Project$ chmod +x ssh_audit_readonly.sh
sahil@HP:~/BCA-Linux-Project$ ./ssh_audit_readonly.sh
SSH client:
OpenSSH_10.2p1 Ubuntu-2ubuntu3.6, OpenSSL 3.5.5 27 Jan 2026

SSH server service status (read-only):
Unit ssh.service could not be found.
```