JADE COATINGS · SURFACE PREPARATION

Universal Cleaner

Eco-friendly 3-in-1 aqueous cleaner that cleans and prepares metal, masonry, rubber and wooden surfaces for paint application.

COVERAGE	DILUTION	DRY BEFORE PAINT	SUBSTRATES	SHELF LIFE
10 – 12 m²/L	**10 – 20% water**	**1 – 2 hours**	**Multi-surface**	**12 months**

DESCRIPTION

JADE Universal Cleaner is an eco-friendly 3-in-1 aqueous product formulated to clean and prepare metal, masonry, rubber and wooden substrates for paint application. It removes rust, algae, fungi, oil and grease, and enhances adhesion of the subsequent paint coating.

It is a safe alternative to flammable solvents and dangerous caustic degreasers.

IMPORTANT: This product will not prevent re-occurring rust, fungal and algal growth. Apply a suitable coat soon after the cleaning process.

FEATURES & BENEFITS

- Removes **algae, fungi and dirt** on masonry.
- Removes **rust, oil and grease** on metal.
- Acts as a **substrate conditioner** and enhances adhesion of subsequent water-based or solvent-based paint coatings on metal and masonry.

APPLICATION

- **Dilute up to 10% – 20%** with clean water.
- Apply the cleaner with a **piece of rag, roller or brush**.
- **Repeat the application at a right angle** to the first application to make sure the entire substrate area is treated.
- **Wash properly with clean water** and allow **1 – 2 hours** to dry the surface before applying paint.

COVERAGE & THINNING

- Approximately **10 – 12 m² per litre**. Coverage depends on surface porosity, texture and application technique.
- Dilute **10% – 20%** with clean water prior to application.

CURING TIME

- Once treated with JADE Universal Cleaner, the substrate has to be **cleaned thoroughly with water** and left to dry.

APPLICATION AT A GLANCE

01	02	03	04	05	06
Dilute	**Apply**	**Repeat**	**Wash**	**Dry**	**Paint**
10 – 20% with clean water	Rag, roller or brush	At a right angle to the first pass	Thoroughly with clean water	1 – 2 hours	Coat soon after cleaning

TECHNICAL DATA

Product Type	Eco-friendly 3-in-1 aqueous cleaner and substrate conditioner
Substrates	Metal, masonry, rubber and wooden surfaces
Removes	Rust, algae, fungi, dirt, oil and grease
Coverage	Approximately 10 – 12 m² per litre. Coverage depends on surface porosity, texture and application technique.
Application Method	Rag, roller or brush
Thinning	Dilute 10% – 20% with clean water prior to application
Drying Time	Wash thoroughly with water and allow 1 – 2 hours to dry before painting
Compatible Paints	Subsequent water-based or solvent-based paint coatings on metal and masonry
Shelf Life	12 months if kept and stored in a cool, dry place, out of direct sunlight

CLEAN UP & DISPOSAL

- Do not pour contents down drains or sinks. Dispose of in accordance with your local council regulations.

SAFETY

- As with all chemical products, wear protective clothing and eyewear.
- Use under sufficient ventilation.

DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependent upon its correct preparation, application onto a sound surface and attention to the instructions.

JADE COATINGS (PVT) LTD.
424/1/B, Kottunna Road, Biyagama, Sri Lanka
T: 077 377 4340 E: info@colourmax.lk W: www.jadecoatings.lk