JADE COATINGS · MASONRY & CLAY

Masoguard All In One

Water-based, eco-friendly two-in-one colour and finish coat for interior and exterior masonry and clay surfaces.

COVERAGE	TOUCH DRY	FULL CURE	FINISH	SHELF LIFE
6 – 8 m²/L	**30 minutes**	**24 hours**	**Semi-gloss**	**2 years**

DESCRIPTION

JADE Masoguard All In One is a water-based, eco-friendly colour finish designed for interior and exterior masonry and clay substrates, for instance cement, concrete, fibre cement board and terracotta. This two-in-one product offers both colour and finish coat, replacing the need to apply two separate coats of colour and top coat. It is available in many popular colours.

KEY BENEFITS

- **Two-in-one** colour and finish coat – no separate top coat required.
- Easy to use, with optimum **durability** and **water resistance**.
- **Salt spray** and **UV resistance** for long-lasting exterior performance.
- **Algae & fungal resistance**, with excellent **colour retention** and longevity.

SURFACE PREPARATION

- Surface preparation is important. All surfaces should be free from **oil, grease, dust** and other contaminants.
- Fill **nail holes, uneven areas and joints** with a proper masonry putty, sand the areas with **320 grit sandpaper** and dust off thoroughly.
- All previous **solvent-based paints and varnish must be removed** before coating with JADE Masoguard All In One.
- If in doubt, test on a small area of the existing coating to check adhesion.

APPLICATION

- Apply the first coat of **JADE Masoguard Primer Grey** by brush, foam roller or spray and allow **1 – 2 hours** to dry. If further priming is required, apply a second coat on the whole surface or where necessary and allow one hour to dry.
- Apply **two coats of JADE Masoguard All In One** by brush, foam roller or spray, allowing **2 hours** drying between coats for interior applications. Exterior applications need **two to three coats**.
- If necessary, use **two coats of JADE Masoguard Top Coat – Clear** for further protection.
- Do not apply on exterior surfaces if **rain is expected within 24 hours**, as this could lead to whitening and reduced service life of the coating.

DRYING & RE-COATING

- Normally **touch dry in 30 minutes**. Drying may take longer in cold or humid weather and may be shorter on sunny days.
- **Full cure: 24 hours.**
- Apply the second coat in **1 – 2 hours** on normal sunny days for good inter-coat adhesion; on very hot sunny days apply it **within 45 minutes**.
- Sand lightly between coats with **320 grit** worn sandpaper.

JADE COATINGS (PVT) LTD.
424/1/B, Kottunna Road, Biyagama, Sri Lanka
T: 077 377 4340 E: info@colourmax.lk W: www.jadecoatings.lk

APPLICATION AT A GLANCE

01	02	03	04	05	06
Prepare	**Prime**	**Coat 1**	**Coat 2**	**Coat 3**	**Cure 24 hrs**
Fill, sand 320 grit, dust off	Masoguard Primer Grey, 1 – 2 hrs	All In One, brush, roller or spray	After 1 – 2 hrs, lightly sand	Exterior only, as required	Optional clear top coat

TECHNICAL DATA

Substrates	Interior and exterior masonry and clay: cement, concrete, fibre cement board, terracotta
Coverage	Approximately 6 – 8 m² per litre. Coverage depends on surface porosity, substrate type and application technique.
Application Method	Brush, foam roller or spray
Thinning	Up to 20% dilution with water is recommended when applying under hot conditions
Gloss Level	Semi-gloss
Shelf Life	2 years if kept and stored in a cool, dry place, out of direct sunlight

COLOURS

Larch Teak	Burma Teak	Mahogany
Dark Teak	Walnut	Titanium

Swatches are indicative only; please refer to the JADE colour card for actual shades.

CLEAN UP & DISPOSAL

- Clean all equipment promptly with water. Do not pour contents or washings down drains or sinks; dispose of in accordance with your local council regulations.

SAFETY

- JADE Masoguard All In One is classified as a **non-hazardous material** according to the criteria of NOHSC Australia.
- As with all chemical products, wear protective clothing and eyewear, and use under sufficient ventilation.

DISCLAIMER
The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependent upon its correct preparation, application onto a sound surface and attention to the instructions.

JADE COATINGS (PVT) LTD.
424/1/B, Kottunna Road, Biyagama, Sri Lanka
T: 077 377 4340 E: info@colourmax.lk W: www.jadecoatings.lk