JADE COATINGS · ROOF & WALL PROTECTION

Roof & Wall Shield

Water-based, eco-friendly, hard-wearing decorative coating that protects and stabilises exterior walls and roofing materials.

COVERAGE	TOUCH DRY	FULL CURE	FINISH	SHELF LIFE
6 – 8 m²/L	**45 minutes**	**24 hours**	**Matt**	**2 years**

DESCRIPTION

JADE Roof & Wall Shield is a water-based, eco-friendly, hard-wearing decorative coating designed to protect exterior walls and roofing materials. It can be applied on interior and exterior walls and roofing materials such as cement, terracotta and clay roof tiles and asbestos sheets. It enhances the appearance of the substrate, is dust-proof and stabilises the substrate, helping to prevent the generation of asbestos fibre dust and degradation of the roof due to ingress of water.

KEY BENEFITS

- **Self-cleaning ability** thanks to excellent dirt pick-up resistance.
- Easy to use, with optimum **durability** and **water resistance**.
- **Salt spray** and **UV resistance** for long-lasting exterior performance.
- **Algae & fungal resistance**, with excellent **colour retention** and longevity on masonry and clay surfaces.

SURFACE PREPARATION

- Surface preparation is important. All surfaces should be free from **oil, grease, dust** and other contaminants.
- Fill **nail holes, uneven areas and joints** with a proper masonry putty, sand the areas with **320 grit sandpaper** and dust off thoroughly.
- All previous **solvent-based paints, varnish and loose paint must be removed** before coating with JADE Roof & Wall Shield.
- If in doubt, test on a small area of the existing coating to check adhesion.

APPLICATION

- Apply the **first coat as a primer** (dilution – paint 1 : water 1) by brush, roller or airless spray and allow **2 – 3 hours** to dry. If a further coat is required, apply on the whole surface or where necessary and allow 2 hours to dry.
- Apply the **second and third coats** by brush, roller or spray, allowing **2 hours** drying between coats.
- Do not apply on exterior surfaces if **rain is expected within 24 hours**, as this could lead to whitening and reduced service life of the coating.

DRYING & RE-COATING

- Normally **touch dry in 45 minutes**. Drying may take longer in cold or humid weather and may be shorter on sunny days. **Full cure: 24 hours.**
- **Minimum 2 hours** between coats.

JADE COATINGS (PVT) LTD.
424/1/B, Kottunna Road, Biyagama, Sri Lanka
T: 077 377 4340 E: info@colourmax.lk W: www.jadecoatings.lk

APPLICATION AT A GLANCE

01	02	03	04	05	06
Prepare	**Primer coat**	**Coat 2**	**Coat 3**	**Touch dry**	**Full cure**
Fill, sand 320 grit, dust off	Paint 1 : water 1; dry 2 – 3 hrs	Paint 3 : water 1; after 2 hrs	Paint 3 : water 1; after 2 hrs	45 minutes	24 hours

TECHNICAL DATA

Product Type	Water-based decorative roof and wall coating
Substrates	Interior and exterior walls and roofing: cement, terracotta and clay roof tiles, asbestos sheets
Coverage	Approximately 6 – 8 m² per litre. Coverage depends on surface porosity, type of surface and application technique.
Application Method	Brush, roller or spray (airless spray for the primer coat)
Thinning	First coat (primer): paint 1 : water 1. Second and third coats: paint 3 : water 1.
Gloss Level	Matt
Shelf Life	2 years if kept and stored in a cool, dry place, out of direct sunlight

COLOURS

White
Tile Red
Roof Red
Coffee Brown
Spruce

Swatches are indicative only; please refer to the JADE colour card for actual shades.

CLEAN UP & DISPOSAL

- Clean all equipment promptly with water. Do not pour contents or washings down drains or sinks; dispose of in accordance with your local council regulations.

SAFETY

- JADE Roof & Wall Shield is classified as a **non-hazardous material** according to the criteria of NOHSC Australia.
- As with all chemical products, wear protective clothing and eyewear, and use under sufficient ventilation.

DISCLAIMER
The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependent upon its correct preparation, application onto a sound surface and attention to the instructions.

JADE COATINGS (PVT) LTD.
424/1/B, Kottunna Road, Biyagama, Sri Lanka
T: 077 377 4340 E: info@colourmax.lk W: www.jadecoatings.lk