JADE COATINGS · PAVING & MASONRY

# Wet Look Paving Sealer

Eco-friendly, water-based, hard-wearing clear sealer that enriches colour and protects pavers, stone and tiles.

| COVERAGE | TOUCH DRY | FULL CURE | FINISH | SHELF LIFE |
|---|---|---|---|---|
| **5 – 10 m²/L** | **2 hrs @ 25°C** | **24 hours** | **Low sheen** | **12 months** |

## DESCRIPTION

JADE Wet Look Paving Sealer is an eco-friendly, water-based, hard-wearing clear sealer designed to repel moisture and water from construction materials. It can be applied on cement pavers, natural stone surfaces, slate, terracotta and clay tiles. The sealer forms a clear film on the substrate that helps protect against efflorescence, staining, soiling and algal & fungal growth, in addition to its water repellence.

### KEY BENEFITS

- Gives a **wet look** and enhances the natural colour of the substrate.
- Prevents **efflorescence** – the unsightly white salt deposit on pavers caused by environmental conditions.
- Ideal for **interior and exterior**, natural and reconstituted, highly trafficable surfaces.
- Excellent **hot tyre pick-up resistance** – ideal for driveways.
- Excellent **chemical and alkali resistance**; can also be applied on new concrete.
- **Self-cleaning ability** thanks to excellent dirt pick-up resistance.

**IMPORTANT:** Always test the product on a small area first to ensure the coating has not caused the surface to become slippery.

## SURFACE PREPARATION

Surface preparation is very important.

- Ensure all surfaces to be sealed are **clean, dry and free from dust** and other contaminants. Areas affected by grease, oil, stains or mould should be cleaned before applying the sealer.
- **Efflorescence** (white salt deposit): simply wipe down with a wet rag and allow to dry for 20 – 30 minutes, then apply the sealer as usual.
- A surface cleaned with a **high-pressure water jet** may appear dry, but should be allowed to dry for about **2 – 3 days** before sealing, as the substrate may still contain moisture.
- Surfaces cleaned with **acid-based products** must be totally neutralised or completely washed away, as acid residue may attack the sealer.

## APPLICATION

- Stir the contents well before and during use. **Do not shake** – shaking produces air bubbles which may become trapped on the surface.
- Apply by **low-pressure spray, brush or roller**.
- Apply the **second coat after 4 hours**. Over-application may increase sheen and slip level.
- A **third coat** on porous substrates will enhance the durability of the coating.
- Do not apply if **rain is expected within 24 hours**, as this could lead to whitening of the coating.

JADE COATINGS (PVT) LTD.
424/1/B, Kottunna Road, Biyagama, Sri Lanka
T: 077 377 4340 E: info@colourmax.lk W: www.jadecoatings.lk

## APPLICATION AT A GLANCE

| 01 | 02 | 03 | 04 | 05 | 06 |
|---|---|---|---|---|---|
| **Prepare** | **Coat 1** | **Wait 4 hrs** | **Coat 2** | **Coat 3** | **Cure 24 hrs** |
| Clean, dry, dust-free surface | Spray, brush or roller | Before the second coat | Avoid over-application | Porous surfaces, for durability | Then open to heavy traffic |

## TECHNICAL DATA

| | |
|---|---|
| Product Type | Water-based clear paving sealer |
| Coverage | Approximately 5 – 10 m² per litre. Coverage depends on surface porosity, texture and application technique. |
| Application Method | Low-pressure spray, brush or roller |
| Recoat Interval | 4 hours (second coat); third coat recommended on porous substrates |
| Drying Time | Touch dry in 2 hours @ 25°C. Full cure may take 24 hours. |
| Traffic | Avoid heavy traffic for at least 24 hours |
| Gloss Level | Low sheen. Over-application may result in a semi-gloss level. |
| Colour | White in container; dries to clear |
| Thinning | Not recommended. Thinning may reduce slipperiness on dense substrates but will reduce the expected service life of the coating. |
| Clean Up | Clean all equipment promptly with water |
| Shelf Life | 12 months if kept and stored in a cool, dry place, out of direct sunlight |

## CLEAN UP & DISPOSAL

- Clean all equipment promptly with water.
- Do not pour contents or washings down drains or sinks. Dispose of in accordance with your local council regulations.

## SAFETY

- JADE Wet Look Paving Sealer is classified as a **non-hazardous material** according to the criteria of NOHSC Australia.
- As with all chemical products, wear protective clothing and eyewear.
- Use under sufficient ventilation.

**DISCLAIMER**
The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependent upon its correct preparation, application onto a sound surface and attention to the instructions.

JADE COATINGS (PVT) LTD.
424/1/B, Kottunna Road, Biyagama, Sri Lanka
T: 077 377 4340 E: info@colourmax.lk W: www.jadecoatings.lk