JADE COATINGS · WOOD CARE

Woodshield Stain

Water-based, eco-friendly, high-performance interior and exterior wood stain in a wide range of popular colours.

COVERAGE	TOUCH DRY	RECOAT	COLOURS	SHELF LIFE
6 – 8 m²/L	**20 min @ 25°C**	**After 1 hour**	**11 shades**	**2 years**

DESCRIPTION

JADE Woodshield Stain is a water-based, eco-friendly, high-performance stain for interior and exterior wooden products such as doors, windows, furniture and structures. It is available in many popular colours and is designed to be applied prior to the JADE Woodshield Interior & Exterior Clear Top Coat.

KEY BENEFITS

- Easy-to-use, user-friendly coating system with optimum **durability**.
- Excellent **water resistance** and **block resistance**.
- Superior **colour retention** and **longevity** on wooden surfaces.
- Wide choice of **11 colours**, from natural wood tones to Black, Green and Red.

SURFACE PREPARATION

- Surface preparation is important. All surfaces should be free from **oil, grease, dust** and other contaminants. **Sand the surface properly** and dust off.
- All previous **solvent-based paints and varnish must be removed** before coating with JADE Woodshield Stain and Clear Top Coat.
- If in doubt, test on a small area of the existing coating to check for proper adhesion.

APPLICATION

- Apply the **first coat** of JADE Woodshield Stain and allow **1 hour** to dry. If further colour development is required, apply a **second coat** on the whole surface or where necessary and allow one hour to dry.
- Then apply **two coats of JADE Woodshield Interior & Exterior Clear Top Coat**, allowing **2 hours** drying between coats for interior applications. Exterior applications need **two to three coats**.
- Do not apply on exterior surfaces if **rain is expected within 24 hours**, as this could lead to whitening and reduced service life of the coating.

DRYING & RE-COATING

- Woodshield Stain **touch dries in 20 minutes @ 25°C**. Drying may take longer under low temperature and humid conditions.
- Subsequent coats can be applied after **1 hour**.

JADE COATINGS (PVT) LTD.
424/1/B, Kottunna Road, Biyagama, Sri Lanka
T: 077 377 4340 E: info@colourmax.lk W: www.jadecoatings.lk

APPLICATION AT A GLANCE

01	02	03	04	05	06
Prepare	**Stain coat 1**	**Stain coat 2**	**Clear top coat**	**Exterior**	**Touch dry**
Clean, sand and dust off	Allow 1 hour to dry	If more colour is needed	2 coats, 2 hrs apart (interior)	2 – 3 clear top coats	20 min @ 25°C

TECHNICAL DATA

Product Type	Water-based interior and exterior wood stain
Substrates	Interior and exterior wooden products: doors, windows, furniture and structures
Coverage	Approximately 6 – 8 m² per litre. Coverage depends on surface porosity, type of wood and application technique.
Thinning	Not recommended
Drying Time	Touch dry in 20 minutes @ 25°C; may take longer in low temperature and humid conditions
Recoat Interval	1 hour
Shelf Life	2 years if kept and stored in a cool, dry place, out of direct sunlight

COLOURS

Natural	Jak Wood	Larch Teak	Burma Teak
Mahogany	Dark Teak	Walnut	Dark Walnut
Black	Green	Red	

Swatches are indicative only; please refer to the JADE colour card for actual shades.

CLEAN UP & DISPOSAL

- Clean all equipment promptly with water. Do not pour contents or washings down drains or sinks; dispose of in accordance with your local council regulations.

SAFETY

- JADE Woodshield Stain is classified as a **non-hazardous material** according to the criteria of NOHSC Australia.
- As with all chemical products, wear protective clothing and eyewear, and use under sufficient ventilation.

DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependent upon its correct preparation, application onto a sound surface and attention to the instructions.

JADE COATINGS (PVT) LTD.
424/1/B, Kottunna Road, Biyagama, Sri Lanka
T: 077 377 4340 E: info@colourmax.lk W: www.jadecoatings.lk