JADE COATINGS · MASONRY PROTECTION

Masoguard Primer

Eco-friendly, water-based pigmented primer that seals masonry, prevents efflorescence and promotes excellent inter-coat adhesion.

COVERAGE	TOUCH DRY	HARD DRY	FINISH	SHELF LIFE
6 – 8 m²/L	**30 minutes**	**24 hours**	**Matt**	**12 months**

DESCRIPTION

JADE Masoguard Primer is an eco-friendly, water-based pigmented coating designed to protect masonry surfaces by preventing efflorescence – the unsightly white deposit that forms on masonry due to environmental conditions – while priming and sealing the surface.

This innovative product dries quickly while offering excellent adhesion and hardness. It is based on a blend of resins and additives specially chosen for excellent substrate binding on masonry.

FEATURES & BENEFITS

- Excellent **adhesion to masonry**.
- Promotes excellent **inter-coat adhesion**.
- Helps **prevent efflorescence**.
- Good **exterior durability**.
- **Eco-friendly** and **APEO free**.
- Easy to use, easy clean-up and **non-toxic**.

SURFACE PREPARATION

- Surface preparation is important. All surfaces should be free from **oil, grease, dust** and other contaminants.
- Fill **nail holes, uneven areas and joints** with a proper masonry putty, sand the areas with **320 grit sandpaper** and dust off thoroughly.

APPLICATION

- **Shake** the contents well before use.
- Apply by **low-pressure spray or brush**.
- If necessary, recoat after **1 hour**, at which the product offers optimum film hardness.

COVERAGE

- Approximately **6 – 8 m² per litre**. Coverage depends on the nature of the substrate and application technique.

APPLICATION AT A GLANCE

01	02	03	04	05	06
Prepare	**Shake**	**Apply**	**Recoat**	**Touch dry**	**Hard dry**
Fill, sand 320 grit, dust off	Shake contents well before use	Low-pressure spray or brush	After 1 hour, if necessary	30 minutes	24 hours

TECHNICAL DATA

Product Type	Water-based pigmented masonry primer and sealer
Coverage	Approximately 6 – 8 m² per litre. Coverage depends on the nature of the substrate and application technique.
Application Method	Low-pressure spray or brush
Recoat Interval	1 hour, if necessary
Drying Time	Touch dry in 30 minutes; hard dry in 24 hours. Depends on environmental conditions.
Gloss Level	Matt
Thinning	Not recommended
Colour	Grey
Shelf Life	12 months if kept and stored in a cool, dry place, out of direct sunlight

CLEAN UP & DISPOSAL

- Clean all equipment promptly with water.
- Do not pour contents or washings down drains or sinks. Dispose of in accordance with your local council regulations.

SAFETY

- JADE Masoguard Primer is classified as **non-hazardous**.
- As with all chemical products, wear protective clothing and eyewear.
- Use under sufficient ventilation.

DISCLAIMER
The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependent upon its correct preparation, application onto a sound surface and attention to the instructions.

JADE COATINGS (PVT) LTD.
424/1/B, Kottunna Road, Biyagama, Sri Lanka
T: 077 377 4340 E: info@colourmax.lk W: www.jadecoatings.lk