JADE COATINGS · METAL PROTECTION

Metashield Anti Corrosive

Eco-friendly, water-based pigmented metal primer providing corrosion resistance, excellent adhesion and hardness.

COVERAGE	TOUCH DRY	HARD DRY	FINISH	SHELF LIFE
6 – 8 m²/L	**1.5 – 2 hours**	**24 hours**	**Semi-gloss**	**6 months**

DESCRIPTION

JADE Metashield Anti Corrosive is an eco-friendly, water-based pigmented coating designed to provide corrosion resistance, excellent adhesion and hardness to metal substrates.

FEATURES & BENEFITS

- Excellent **adhesion to metal**.
- Promotes excellent **inter-coat adhesion**.
- Good **exterior durability**.
- **Eco-friendly** and **APEO free**.
- Easy to use, easy clean-up and **non-toxic**.

SURFACE PREPARATION

- Surface preparation is very important. Ensure the surface is **clean, dry and free from rust** and other contaminants.
- Areas affected by rust, grease, dust, oil or stain should be **thoroughly buffed and cleaned** before applying the primer.

APPLICATION

- Use a **stirrer** to mix well before use.
- Apply by **low-pressure spray or brush**.
- **Three coats** are recommended to achieve the desired performance.
- Recoating time is **2 hours**, at which the product offers optimum film hardness. A shorter recoating time may be acceptable if it still meets the user's desired level of film properties.

DRYING & RE-COATING

- **Touch dry in 1 hour 30 minutes – 2 hours** and **hard dry in 24 hours**, depending on environmental conditions.
- Any accelerated testing is recommended to be done after **120 hours**.

JADE COATINGS (PVT) LTD.
424/1/B, Kottunna Road, Biyagama, Sri Lanka
T: 077 377 4340 E: info@colourmax.lk W: www.jadecoatings.lk

APPLICATION AT A GLANCE

01	02	03	04	05	06
Prepare	**Mix**	**Coat 1**	**Coat 2**	**Coat 3**	**Hard dry**
Clean, dry, rust-free, buffed	Stir well before use	Low-pressure spray or brush	After 2 hours	Recommended for performance	24 hours

TECHNICAL DATA

Product Type	Water-based pigmented anti-corrosive metal primer
Substrates	Metal
Coverage	Approximately 6 – 8 m² per litre. Coverage depends on the nature of the substrate and application technique.
Application Method	Low-pressure spray or brush
Thinning	If necessary, dilute up to 5% with distilled water to adjust the required viscosity
Recoat Interval	2 hours
Drying Time	Touch dry in 1 hr 30 min – 2 hrs; hard dry in 24 hours. Depends on environmental conditions.
Gloss Level	Semi-gloss
Shelf Life	6 months if kept and stored in normal environmental conditions at 27°C, in a dry place and out of direct sunlight

COLOUR

Black

CLEAN UP & DISPOSAL

- Clean all equipment promptly with water.
- Do not pour contents or washings down drains or sinks. Dispose of in accordance with your local council regulations.

SAFETY

- JADE Metashield Anti Corrosive is classified as **non-hazardous**.
- As with all chemical products, wear protective clothing and eyewear.
- Use under sufficient ventilation.

DISCLAIMER
The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependent upon its correct preparation, application onto a sound surface and attention to the instructions.

JADE COATINGS (PVT) LTD.
424/1/B, Kottunna Road, Biyagama, Sri Lanka
T: 077 377 4340 E: info@colourmax.lk W: www.jadecoatings.lk