JADE COATINGS · WOOD CARE

Woodshield Top Coat

Water-based, eco-friendly, high-performance clear finish for interior and exterior wooden products.

COVERAGE	TOUCH DRY	RECOAT	FINISH	SHELF LIFE
9 – 11 m²/L	**30 min @ 25°C**	**After 2 hours**	**Gloss & Matt**	**2 years**

DESCRIPTION

JADE Woodshield Top Coat (Interior & Exterior Clear Top Coat) is a water-based, eco-friendly, high-performance clear finish for interior and exterior wooden products such as doors, windows, furniture and structures. It is designed to be applied over JADE Woodshield Stain, which is available in many popular colours.

KEY BENEFITS

- Easy-to-use, user-friendly coating system with optimum **durability**.
- Excellent **water resistance** and **block resistance**.
- Superior **colour retention** and **longevity** on wooden surfaces.
- Available in **Gloss** and **Matt** finishes.

SURFACE PREPARATION

- Surface preparation is important. All surfaces should be free from **oil, grease, dust** and other contaminants. **Sand the surface properly** and dust off.
- All previous **solvent-based paints and varnish must be removed** before coating with JADE Woodshield Stain and Top Coat.
- If in doubt, test on a small area of the existing coating to check adhesion.

APPLICATION

- Apply the **first coat of JADE Woodshield Stain** and allow **1 hour** to dry. If further colour development is required, apply a second coat on the whole surface or where necessary and allow one hour to dry.
- **Stir well** and apply by **soft paint brush or spray**.
- Apply **two coats of Woodshield Top Coat**, allowing **2 hours** drying between coats for interior applications. Exterior applications need **two to three coats**.
- Do not apply on exterior surfaces if **rain is expected within 24 hours**, as this could lead to whitening and reduced service life of the coating.

DRYING & RE-COATING

- **Touch dry in 30 minutes @ 25°C.** Drying may take longer under low temperature and humid conditions. **Full cure may take 24 hours.**
- Subsequent coats can be applied after **2 hours**.

JADE COATINGS (PVT) LTD.
424/1/B, Kottunna Road, Biyagama, Sri Lanka
T: 077 377 4340 E: info@colourmax.lk W: www.jadecoatings.lk

APPLICATION AT A GLANCE

01	02	03	04	05	06
Prepare	**Stain**	**Stir**	**Top coat 1**	**Top coat 2**	**Full cure**
Clean, sand and dust off	Woodshield Stain, 1 hr per coat	Stir well before use	Brush or spray	After 2 hrs; 2 – 3 coats outdoors	Up to 24 hours

TECHNICAL DATA

Product Type	Water-based clear finish for interior and exterior wood
Substrates	Interior and exterior wooden products: doors, windows, furniture and structures
Coverage	Approximately 9 – 11 m² per litre. Coverage depends on surface porosity, type of wood and application technique.
Application Method	Soft paint brush or spray
Thinning	Recommended mixing ratio is 3 parts product to 1 part water. A higher level of dilution may reduce gloss level and durability.
Gloss Level	Available in Gloss and Matt
Drying Time	Touch dry in 30 minutes @ 25°C; full cure may take 24 hours. May take longer in low temperature and humid conditions.
Recoat Interval	2 hours
Shelf Life	2 years if kept and stored in a cool, dry place, out of direct sunlight

COLOUR

Pink in the container

Clear finish when dry

CLEAN UP & DISPOSAL

- Clean all equipment promptly with water. Do not pour contents or washings down drains or sinks; dispose of in accordance with your local council regulations.

SAFETY

- JADE Woodshield Top Coat is classified as a **non-hazardous material** according to the criteria of NOHSC Australia.
- As with all chemical products, wear protective clothing and eyewear, and use under sufficient ventilation.

DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependent upon its correct preparation, application onto a sound surface and attention to the instructions.

JADE COATINGS (PVT) LTD.
424/1/B, Kottunna Road, Biyagama, Sri Lanka
T: 077 377 4340 E: info@colourmax.lk W: www.jadecoatings.lk