JADE COATINGS · TYRE CARE

Tyreshield All In One

Eco-friendly, water-based pigmented coating for masking minor cosmetic defects and touch-up repairs on cured tyres.

COVERAGE	TOUCH DRY	HARD DRY	FINISH	SHELF LIFE
6 – 8 m²/L	**30 – 45 min**	**24 hours**	**Matt**	**6 months**

DESCRIPTION

JADE Tyreshield All In One is an eco-friendly, water-based pigmented coating designed for masking minor cosmetic defects, touch-up buffing and repairs on cured tyres.

This innovative product dries quickly while offering excellent fixing, covering and adhesion, and is compatible with different types of rubber compounds. It is based on a blend of binders and additives specially chosen for good substrate binding on rubber.

FEATURES & BENEFITS

- Good **adhesion** and **covering**.
- Promotes excellent **inter-coat adhesion** and **exterior durability**.
- **Compatible** with different types of rubber compounds.
- Easy to use, and **easy clean-up with water**.

SURFACE PREPARATION

- Surface preparation is important. All surfaces should be free from **oil, grease, dust** and other contaminants.

APPLICATION

- **Shake** the contents well before use.
- Apply by **low-pressure spray or brush**.
- **1 to 2 coats** are recommended.
- If necessary, recoat after **2 hours**, at which the product offers optimum film hardness.

DRYING

- **Touch dry in 30 – 45 minutes.** Drying may take longer under low temperature and humid conditions.
- **Hard dry in 24 hours.**

COVERAGE & THINNING

- Approximately **6 – 8 m² per litre**. Coverage depends on the nature of the substrate and application technique.
- If necessary, **dilute up to 20%** with water.

JADE COATINGS (PVT) LTD.
424/1/B, Kottunna Road, Biyagama, Sri Lanka
T: 077 377 4340 E: info@colourmax.lk W: www.jadecoatings.lk

APPLICATION AT A GLANCE

01	02	03	04	05	06
Prepare	**Shake**	**Coat 1**	**Coat 2**	**Touch dry**	**Hard dry**
Free from oil, grease and dust	Shake contents well	Low-pressure spray or brush	If necessary, after 2 hours	30 – 45 minutes	24 hours

TECHNICAL DATA

Product Type	Water-based pigmented coating for cured tyres
Substrates	Rubber (cured tyres); compatible with different rubber compounds
Coverage	Approximately 6 – 8 m² per litre. Coverage depends on the nature of the substrate and application technique.
Application Method	Low-pressure spray or brush
Number of Coats	1 to 2 coats recommended
Recoat Interval	2 hours, if necessary
Thinning	If necessary, dilute up to 20% with water
Drying Time	Touch dry in 30 – 45 minutes; hard dry in 24 hours. May take longer in low temperature and humid conditions.
Gloss Level	Matt
Shelf Life	6 months if kept and stored in a cool, dry place, out of direct sunlight

COLOURS

- White
- Black
- Grey
- Beige Light
- Beige Dark

Swatches are indicative only; please refer to the JADE colour card for actual shades.

CLEAN UP & DISPOSAL

- Clean all equipment promptly with water.
- Do not pour contents or washings down drains or sinks. Dispose of in accordance with your local council regulations.

SAFETY

- JADE Tyreshield All In One is classified as **non-hazardous**.
- As with all chemical products, wear protective clothing and eyewear.
- Use under sufficient ventilation.

DISCLAIMER
The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependent upon its correct preparation, application onto a sound surface and attention to the instructions.

JADE COATINGS (PVT) LTD.
424/1/B, Kottunna Road, Biyagama, Sri Lanka
T: 077 377 4340 E: info@colourmax.lk W: www.jadecoatings.lk