JADE COATINGS · WOOD CARE

Woodshield All In One

Water-based, eco-friendly two-in-one colour and finish coat for interior and exterior wooden surfaces.

COVERAGE	TOUCH DRY	RECOAT	FULL CURE	SHELF LIFE
6 – 8 m²/L	**45 minutes**	**1 – 2 hours**	**24 hours**	**2 years**

DESCRIPTION

JADE Woodshield All In One is a water-based, eco-friendly colour finish designed for interior and exterior wooden surfaces. This All In One product offers both colour and finish coat, replacing the need to apply two separate coats of colour and top coat. It is available in many popular colours.

KEY BENEFITS

- **Two-in-one** colour and finish coat – no separate top coat required.
- Easy to use, with optimum **durability** and **water resistance**.
- **Salt spray** and **UV resistance** for long-lasting performance.
- **Algae & fungal resistance**, with excellent **colour retention** and longevity on timber decking.

SURFACE PREPARATION

- Surface preparation is important. All surfaces should be free from **oil, grease, dust** and other contaminants. **Sand the surface properly** and dust off.
- All previous **solvent-based paints and varnish must be removed** before coating with JADE Woodshield All In One.
- If in doubt, test on a small area of the existing coating to check for proper adhesion.

APPLICATION

- Apply the **first coat** (dilute up to **20%** with clean water) and allow **1 – 2 hours** to dry.
- Apply a **second coat**, if required, diluted up to 20% with water.
- If further colour development is required, apply a **third coat** on the whole surface or where necessary and allow **2 hours** to dry.
- **Sand lightly** with 320 grit worn sandpaper and clean properly before the second and third coats.
- Apply by **brush, foam roller or spray**.
- Do not apply on exterior surfaces if **rain is expected within 24 hours**, as this could lead to whitening and reduced service life of the coating.

DRYING & RE-COATING

- Normally **touch dry in 45 minutes**. Drying may take longer in cold or humid weather and may be shorter on sunny days. **Full cure: 24 hours.**
- Apply the second coat in **1 – 2 hours** on normal sunny days for good inter-coat adhesion.
- Sand lightly with 320 grit worn sandpaper and clean properly between coats.

JADE COATINGS (PVT) LTD.
424/1/B, Kottunna Road, Biyagama, Sri Lanka
T: 077 377 4340 E: info@colourmax.lk W: www.jadecoatings.lk

APPLICATION AT A GLANCE

01	02	03	04	05	06
Prepare	**Coat 1**	**Coat 2**	**Sand & clean**	**Coat 3**	**Full cure**
Sand and dust off	Dilute up to 20%; dry 1 – 2 hrs	If required; dilute up to 20%	320 grit, before coats 2 & 3	If more colour is needed; dry 2 hrs	24 hours

TECHNICAL DATA

Product Type	Water-based colour and finish coat for interior and exterior wood
Substrates	Interior and exterior wooden surfaces, including timber decking
Coverage	Approximately 6 – 8 m² per litre. Coverage depends on surface porosity, type of wood and application technique.
Application Method	Brush, foam roller or spray
Thinning	If necessary, dilute up to 20% with clean water
Drying Time	Touch dry in 45 minutes; full cure 24 hours. May take longer in cold or humid conditions.
Recoat Interval	1 – 2 hours on normal sunny days
Shelf Life	2 years if kept and stored in a cool, dry place, out of direct sunlight

COLOURS

Jak Wood	Larch Teak	Burma Teak
Mahogany	Dark Teak	Walnut
Black	Dark Mahogany	Dark Walnut

Swatches are indicative only; please refer to the JADE colour card for actual shades.

CLEAN UP & DISPOSAL

- Clean all equipment promptly with water. Do not pour contents or washings down drains or sinks; dispose of in accordance with your local council regulations.

SAFETY

- JADE Woodshield All In One is classified as a **non-hazardous material** according to the criteria of NOHSC Australia.
- As with all chemical products, wear protective clothing and eyewear, and use under sufficient ventilation.

DISCLAIMER
The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependent upon its correct preparation, application onto a sound surface and attention to the instructions.

JADE COATINGS (PVT) LTD.
424/1/B, Kottunna Road, Biyagama, Sri Lanka
T: 077 377 4340 E: info@colourmax.lk W: www.jadecoatings.lk