

A

Task №1

In this task we will use service [draw-sql](#)



Task №2

```
CREATE SCHEMA IF NOT EXISTS travels;
```

```
CREATE TABLE travels.Employee (  
    id INT PRIMARY KEY,  
    employee_name VARCHAR(10),  
    company_id INT  
);
```

```
CREATE TABLE travels.Company (  
    id INT PRIMARY KEY,  
    company_name VARCHAR(10)  
);
```

```
CREATE TABLE travels.Trip (  
    id INT PRIMARY KEY,  
    employee_id INT,  
    startdate DATE,  
    enddate DATE,  
    cancelationdate DATE,  
    hotel_id INT,  
    ticket_1_id INT,  
    ticket_2_id INT,  
    branch_id INT  
);
```

```
CREATE TABLE travels.Flight (  
    flight_number INT PRIMARY KEY,  
    oigin_city_id INT,  
    destination_city_id INT,  
    air_company VARCHAR(10),  
    departure TIMESTAMP,  
    ticket_price FLOAT  
);
```

```
CREATE TABLE travels.Hotel (  
    id INT PRIMARY KEY,  
    hotel_name VARCHAR(10),  
    hotel_address VARCHAR(10),  
    city_id INT,
```

```
        room_charge FLOAT
    );

CREATE TABLE travels.City (
    id INT PRIMARY KEY,
    city_name VARCHAR(10),
    branch_id INT
);

CREATE TABLE travels.Branch (
    id INT PRIMARY KEY,
    branch_name VARCHAR(10)
);

ALTER TABLE travels.Employee ADD FOREIGN KEY (company_id) REFERENCES
travels.Company (id);

ALTER TABLE travels.Trip ADD FOREIGN KEY (employee_id) REFERENCES
travels.Employee (id);

ALTER TABLE travels.Trip ADD FOREIGN KEY (hotel_id) REFERENCES
travels.Hotel (id);

ALTER TABLE travels.Trip ADD FOREIGN KEY (branch_id) REFERENCES
travels.Branch (id);

ALTER TABLE travels.Trip ADD FOREIGN KEY (ticket_1_id) REFERENCES
travels.Flight (flight_number);

ALTER TABLE travels.Trip ADD FOREIGN KEY (ticket_2_id) REFERENCES
travels.Flight (flight_number);

ALTER TABLE travels.Hotel ADD FOREIGN KEY (city_id) REFERENCES
travels.City (id);

ALTER TABLE travels.Flight ADD FOREIGN KEY (origin_city_id) REFERENCES
travels.City (id);

ALTER TABLE travels.Flight ADD FOREIGN KEY (destination_city_id)
REFERENCES travels.City (id);

ALTER TABLE travels.City ADD FOREIGN KEY (branch_id) REFERENCES
travels.Branch (id);
```

Task №3

```
SELECT DISTINCT
    travels.Hotel.id,
    travels.Hotel.hotel_name
FROM
```

```
travels.Employee,
travels.Trip,
travels.Flight,
travels.City AS from_city,
travels.City AS to_city,
travels.Hotel
WHERE travels.Employee.id = travels.Trip.employee_id
AND travels.Trip.ticket_1_id = travels.Flight.flight_number

-- Employees who travel from Berlin to Paris
AND travels.Flight.origin_city_id = from_city.id
AND travels.Flight.destination_city_id = from_city.id
AND from_city.name LIKE "%Berlin%"
AND to_city.name LIKE "%Paris%"

-- Employees who travel this year and their flights were not cancelled
AND travels.Trip.canceled_date IS NULL
AND date_part('year', travels.Trip.startdate) = date_part('year',
NOW())

-- Hotels booked in these flights
AND travels.Trip.hotel_id = travels.Hotel.id;
```

Task №4

```
SELECT DISTINCT
travels.Company.id,
travels.company.company_name
FROM
travels.Company,
travels.Employee,
travels.Trip
WHERE travels.Employee.comapny_id = travels.Company.id
AND travels.Trip.employee_id = travels.Employee.id
GROUP BY travels.Trip.hotel_id;
```

Task №5

```
SELECT DISTINCT
travels.Company.id,
travels.company.company_name
FROM
travels.Company,
travels.Employee,
travels.Trip,
travels.Flight
WHERE travels.Employee.comapny_id = travels.Company.id
AND travels.Trip.employee_id = travels.Employee.id
AND travels.enddate > NOW() - INTERVAL '1 month'
```

```
AND travels.Trip.ticket_2_id = travels.Flight.flight_number  
GROUP BY travels.Flight.origin_city_id;
```

Task №6

```
SELECT travels.Branch.id, travels.Branch.branch_name  
FROM  
    travels.Branch,  
    travels.Trip  
WHERE travels.Trip.branch_id = travels.Branch.id  
    AND travels.Trip.startdate - travels.Trip.cancelationdate <= INTERVAL  
    '3 days'  
GROUP BY travels.Trip.branch_id  
ORDER BY COUNT(*)  
LIMIT 3;
```

Task №7

```
SELECT DISTINCT  
    emp1.id,  
    emp1.employee_name  
    emp2.id,  
    emp2.employee_name  
FROM  
    travels.Employee AS emp1  
    travels.Employee AS emp2  
    travels.Trip AS trip1  
    travels.Trip AS trip2  
    travels.Flight AS flight1  
    travels.Flight AS flight2  
WHERE trip1.employee_id = emp1  
    AND trip2.employee_id = emp2  
    AND  
    (  
        (  
            trip1.ticket_1_id = flight1.flight_number  
            AND trip2.ticket_1_id = flight2.flight_number  
  
            AND flight1.origin_city_id = flight2.origin_city_id  
            AND flight1.destination_city_id = flight2.destination_city_id  
  
            AND flight1.flight_number != flight2.flight_number  
        )  
        OR  
        (  
            trip1.ticket_2_id = flight1.flight_number  
            AND trip2.ticket_2_id = flight2.flight_number  
  
            AND flight1.origin_city_id = flight2.origin_city_id
```

```
        AND flight1.destination_city_id = flight2.destination_city_id  
        AND flight1.flight_number != flight2.flight_number  
    )  
);
```