

7- Header.jsx

```
import React from 'react'
import { NavLink } from 'react-router-dom'

function Header() {
  return (<>
    <h1>Bibliotheque</h1>
    <nav>
      <ul>
        <li> <NavLink to="/">Accueil</NavLink> </li>
        <li> <NavLink to="/details-livre">Details</NavLink> </li>
      </ul>
    </nav>
  </>
)
}

export default Header
```

8- Store.js

```
import { createStore } from "redux";
const Ajouter = (p) => {
  return { type: "Ajouter", payload: p };
};
const Supprimer = (p) => {
  return { type: "Supprimer", payload: p };
};

const InitialState = [];
const rdcr = (state = InitialState, action) => {
  if (action.type == "Ajouter" && state.indexOf(action.payload) == -1)
    return [...state, action.payload];
  else if (action.type == "Supprimer")
    return state.filter((el) => el.ISBN != action.payload);
  else return state;
};
const panier = createStore(rdcr);
export { Ajouter, Supprimer, panier };
```

8-App.js

```
import "../App.css";
import Header from "../Header";
import axios from "axios";
import { useEffect, useState } from "react";
import { Ajouter, Supprimer } from "../store";
import { useDispatch, useSelector } from "react-redux";

import "bootstrap/dist/css/bootstrap.css";
import "bootstrap/dist/js/bootstrap.js";

function App() {
  const dispatch = useDispatch();
  const panier = useSelector((state) => state);
  const [Livres, setLivres] = useState([]);
  const [GenreSelectionne, setGenreSelectionne] = useState("");
  useEffect(() => {
    axios.get("Livres.json").then((resp) => {
      console.log(resp);
      setLivres(resp.data);
    });
  }, []);

  return (
    <>
      <Header />
      <select
        onChange={(ev) => {
          setGenreSelectionne(ev.target.value);
        }}
      >
        {Livres.map((el, ind) => {
          return <option key={ind}>{el.Genre}</option>;
        })}
      </select>
      {GenreSelectionne && <h6> Livres du Genre {GenreSelectionne} </h6>}
      <table>
        <thead>
          <tr>
            <th>ISBN</th>
            <th>Titre</th>
            <th>Auteur</th>
            <th>Prix</th>
            <th>Genre</th>
            <th>Action</th>
          </tr>
        </thead>
        <tbody>
```

```

    {Livres.filter(
      (el) => GenreSelectionne && el.Genre == GenreSelectionne
    ).map((el, ind) => {
      return (
        <tr key={ind}>
          <td>{el.ISBN}</td>
          <td>{el.Titre}</td>
          <td>{el.Auteur}</td>
          <td>{el.Prix}</td>
          <td>{el.Genre}</td>
          <td>
            <button
              className="btn btn-success"
              onClick={() => {
                dispatch(Ajouter(el));
              }}
            >
              Ajouter Au Panier
            </button>
          </td>
        </tr>
      );
    })}
  </tbody>
</table>

<h1>Panier</h1>
<ul>
  {panier.map((el) => (
    <li>
      {el.Titre}- {el.Prix}{" "}
      <button
        className="btn btn-warning"
        onClick={() => dispatch(Supprimer(el.ISBN))}
      >
        Supprimer
      </button>
    </li>
  ))}
</ul>
<h3>
  Total {panier.reduce((Somme, el) => Somme + parseFloat(el.Prix), 0)}
</h3>
</>
);
}

export default App;

```

9- DetailsLivres.jsx

```
import React from 'react'
import { useSelector } from 'react-redux';
import Header from './Header';

function DetailsLivres() {
  const panier = useSelector((state) => state);

  return (<>
    <Header/>
    <div>Details Livres</div>

    <table>
      <thead>
        <tr>
          <th>ISBN</th>
          <th>Titre</th>
          <th>Auteur</th>
          <th>Prix</th>
          <th>Genre</th>

          </tr>
        </thead>
        <tbody>
          {panier.map((el, ind) => {
            return (
              <tr key={ind}>
                <td>{el.ISBN}</td>
                <td>{el.Titre}</td>
                <td>{el.Auteur}</td>
                <td>{el.Prix}</td>
                <td>{el.Genre}</td>

                </tr>
              );
            })}
          </tbody>
        </table></>
    )
  }

  export default DetailsLivres
```

10- Index.js

```
import React from "react";
```

```

import ReactDOM from "react-dom/client";
import "./index.css";
import App from "./App";
import reportWebVitals from "./reportWebVitals";
import { panier } from "./store";
import { Provider } from "react-redux";
import DetailsLivres from "./DetailsLivres";
import { BrowserRouter, Routes, Route } from "react-router-dom";

const root = ReactDOM.createRoot(document.getElementById("root"));
root.render(
  <BrowserRouter>
    <Provider store={panier}>
      <Routes>
        <Route path="/" element={<App />}></Route>
        <Route path="/details-livre" element={<DetailsLivres />}></Route>
      </Routes>

      { /* <App /> */ }
    </Provider>
  </BrowserRouter>
);

// If you want to start measuring performance in your app, pass a function
// to log results (for example: reportWebVitals(console.log))
// or send to an analytics endpoint. Learn more: https://bit.ly/CRA-vitals
reportWebVitals();

```

11- Intégration Bootstrap :

Importation(App.js) :

```

import "bootstrap/dist/css/bootstrap.css";
import "bootstrap/dist/js/bootstrap.js";

```

Utilisation :

```

<button
  className="btn btn-success"
  onClick={() => {
    dispatch(Ajouter(el));
  }}
>
  Ajouter Au Panier
</button>

```

```

<button
  className="btn btn-warning"

```

```
      onClick={() => dispatch(Supprimer(e1.ISBN))}  
    >  
      Supprimer  
    </button>
```