

Web Data Integration

Student project report

presented by
Oliver Frendo (1510432),
Dandan Li (),
Zehui Wang () *and*
Yi-Ru Cheng ()

submitted to the
Data and Web Science Group
Prof. Dr. Christian Bizer
University of Mannheim

November 28, 2015

Contents

1	Introduction to data and use case	1
2	Data translation	1
2.1	Data collection	1
2.1.1	Forbes: Company	1
2.1.2	DBpedia: Company	1
2.1.3	Freebase: Company	2
2.1.4	DBpedia: Location	2
2.2	Integrated schema	2
2.3	Data transformations	3
3	Identity resolution	4
3.1	Gold standards	4
3.1.1	Forbes \leftrightarrow Freebase	4
3.1.2	Freebase \leftrightarrow DBpedia companies	4
3.1.3	DBpedia companies \leftrightarrow DBpedia locations	4
3.2	Matching rules	5
3.3	Blocking functions	6
3.4	Learning matching rules	7
4	Data fusion	8
4.1	Input data	8
4.2	Gold standard	8
4.3	Conflict resolution functions	8
4.4	Accuracy	8

List of Figures

List of Tables

1	Basic Profile of Each Dataset	2
2	Integrated Schema	3
3	Matching rule accuracies	5
4	Blocking functions	7

1 Introduction to data and use case

2 Data translation

2.1 Data collection

In order to collect suitable data we tried different data service providers such as Datahub, finally we have collected total four datasets from three different sources and in three different formats, including:

2.1.1 Forbes: Company

The Forbes offers a .xls file with a list of Top 2000 companies during the period 2000 to 2014 which were published in Forbes magazine because of great performance in terms of business achievements. This dataset describes the basic information about these top 2000 companies. For example, location shows where this company is founded, industry depicts what fields the company focus on and so on.

2.1.2 DBpedia: Company

The information of company is extracted from DBpedia, since it provides relatively complete information. To access information from DBpedia we used the public SPARQL endpoint (at <http://dbpedia.org/sparql>). Figure 1.1 is our query for company, actually there is total 764398 companies in DBpedia, which would be too much for us and also not easy to handle it in terms of processing time and space. In order to reduce the number of data, we limit the company types to "company" and "public company" and only extract the companies that provide attributes "LocationCity" and "LocationCountry", these two attributes can also be related with Location Information, that's why we consider them as necessary and others are optional. On the other hand, if all these attributes are necessary, there will be only few thousands companies extracted, because not all companies have all these nine attributes, in this case few overlapping data will be in the final integration results. In addition to this, as many attributes such as KeyPeople, locationCity have multiple values which result in the same company would appear more than one times, to avoid these duplicates we used "group_concat", a function in Sparql, to group many value together. There are also many values for Revenue but without date notation, so we just took the maximum value.

```

SELECT  ?company
group_concat(distinct str(?keyPeople);separator=";;") as ?keyPeople
....
WHERE {
{?company rdf:type dbo:Company}
UNION
{?company dbr:type dbr:Public_company} .
optional{?company dbp:keyPeople ?keyPeople .}
?company dbp:locationCity ?locationCity.
.....
}ORDER BY ?company|

```

Figure 1: DBpedia Query For Company

2.1.3 Freebase: Company

Freebase, like DBpedia, offers a web service which can be queried for data. Instead of SPARQL, however, the service is used by sending JSON requests. Like DBpedia this lets us select certain companies, or companies with certain attributes.

2.1.4 DBpedia: Location

We also extracted Location information from DBpedia with the same method as Company. Figure 1.2 is the query for location. For the same reason as Company, we limit the location types to "city" and "AdministrativeRegion", which are more relevant to our company dataset. Also some attributes have many values without extra information, it's hard to identify which one represents the current state, thus, we just took the maximum number of them among multiple values. Furthermore, the name of locations are provide in different languages, while in our project we just focus on english, so we filtered language as english.

Table 1: Basic Profile of Each Dataset

	Source	Format	Class	#Entities	#Attributes
	List of Attributes				
Forbes Global	forbes.com	xlsx	company	2000	7
	Company,country,industry,revenue,assets,marketvalue,profit				
DBpedia	dbpedia.org/sparql	csv	company	16051	9
	Company,country,industry,revenue,numberOfemployees, foundingYear,assets,keyPeople,location				
Freebase	freebase.com/query	json	company		9
	Company,country,industry,revenue,numberOfemployees, foundingYear,profit,keyPeople,location				
Dbpeida	dbpedia.org/sparql	csv	location	3270	5
	Location,country,population,area,elevation				

2.2 Integrated schema

We looked into four datasets and did the following Integrated Schema. In this table we use prefix dataset 1, 2, 3, 4 respectively represent Forbes, DBpedia(company), Freebase and DBpedia(Location)

Class Name	Attributes Name	Datasets in which the attribute is found
company	(company) name	dataset 1, 2, 3
company, location	country	dataset 1, 2, 3, 4
company	industries	dataset 1, 2, 3
company	revenue	dataset 1, 2, 3
company	numberOfEmployees	dataset 2, 3
company	dateFounded	dataset 2, 3
company	assets	dataset 1, 2
company	marketValue	dataset 1
company	profit	dataset 1, 3
company	continent	dataset 1
company	keyPeople	dataset 2, 3
company, location	(location) name	dataset 2, 3, 4
location	population	dataset 4
location	area	dataset 4
location	elevation	dataset 4

Table 2: Integrated schema

2.3 Data transformations

Transformations were applied at two different points in this phase. The first was applied during mapping while the second was applied in the Java project. To begin with, numeric attributes with big values such as revenue or assets were often retrieved in scientific notation. Accordingly a function within MapForce was used to convert the numbers into a decimal notation. Secondly the datasets did not possess an ID attribute. Because it was going to be used later, it was generated with "GenerateID" in MapForce.

The next transformations occurred in Java. Many values, especially from the two DBpedia datasets, were loaded in the form of a URL due to our SPARQL query. As such the URL was parsed and only the actual value was kept. In addition, punctuation and symbols such as "_" were removed. Lastly we normalized country values, which was an important step for the blocking functions used later on in identity resolution. Especially values for the USA were transformed from spellings such as "US", "USA", "United States" to "United States of America".

3 Identity resolution

3.1 Gold standards

As described that we have four datasets in total, we made three types of gold standards. For the convenience of matching, entities in smaller size dataset are compared to the bigger one and all gold standards are selected by stratified distribution in ascending order. The corner cases in our project are mainly about companies which are very similar but not the same and companies have different names but are the same entity.

Forbes and Freebase are compared by the shared attributes: company name, country, industries, and revenue. The gold standard has 220 pairs in total with 120 false and 100 true. Types of corner cases are divided into abbreviation, Incomplete name, Similar name and Same name with different countries or industries. We took some examples as following:

Abbreviation: Bank of China V.S. Industrial and Commercial Bank of China (Asia), TRUE

Incomplete name: Chevron V.S. Chevron Corporation, TRUE

Similar name: BP V.S. TNK-BP, FALSE

different country/industry: Makita (U.S) V.S. Makita (Japan)

Freebase and DBpedia companies

DBpedia companies and DBpedia locations has two shared attributes: location

city and location country . Because city name extracted from DBPedia Location has multiple values due to multi-districts in one city , we defined the city without specific district name as the only true value for integration . The total gold standards size for this part is 270 pairs with 190 false and 80 true.

Example of corner cases:

New York V.S. New York City , TRUE New York V.S. Syracuse, New York , FALSE http://dbpedia.org/resource/New_York_City V.S. <http://dbpedia.org/resource/Syracuse>, New York, FALSE

3.2 Matching rules

This section explains the matching rules we tried in order to generate correspondences accurately. We matched the following datasets with each other:

- Forbes vs Freebase
- Freebase vs DBpedia
- DBpedia companies vs DBpedia locations

Attribute	MatchingRule	P	R	F1
Forbes vs Freebase				
name	Equals	1,0000	0,7500	0,8571
	Levenshtein	0,8571	1,0000	0,9231
countries	Equals	0,8571	1,0000	0,9231
	Jaccard	0,8571	1,0000	0,9231
	Highest Jaccard	0,8571	1,0000	0,9231
industries	Jaccard	0,9091	0,8333	0,8696
	Combination of Jaccard and Levenshtein	0,8571	1,0000	0,9231
revenue/ profit	PercentageSimilarity (max_percentage=0.5)	0,8571	1,0000	0,9231
Freebase vs DBpedia				
revenue/ numberOfEmployees	PercentageSimilarity (max_percentage=0.5)	0,9167	0,9167	0,9167
dateFounded	YearSimilarity (maxDifference=20)	0,9167	0,9167	0,9167
keyPeople	Jaccard	0,9167	0,9167	0,9167
	Combination of Jaccard and Levenshtein	0,9167	0,9167	0,9167
locations	Jaccard	0,9167	0,9167	0,9167
	Highest Jaccard	0,9167	0,9167	0,9167
DBpedia companies vs DBpedia locations				
countries	Highest Jaccard	0,9706	0,9429	0,9565
locations	Jaccard	0,9630	0,7429	0,8387
	Highest Jaccard	0,9706	0,9429	0,9429

Table 3: Matching rule accuracies

In particular the rules for `name`, `industries` and `locations` show different results. For `name` we chose to use Levenshtein because of misspellings, or because of the company type (e.g. "Inc." or "PLC"). However, this also in-

roduces some problematic cases such as "West Japan Railway" and "East Japan Railway", which are different companies but possess very similar attribute values and also generate a very high Levenshtein similarity. For `industries` we tried Jaccard first. This however is not an accurate measure of similarity because of slight differences like "Transport" and "Transportation". As such we chose to use a combination of Jaccard and Levenshtein which led to better results:

$$sim_{Jaccard+Levenshtein} = \frac{\sum_{x,y} max(sim_{Levenshtein}(x,y))}{|x| + |y| - \sum_{x,y} max(sim_{Levenshtein}(x,y))}$$

To give an example of two companies with two industries each: "Computer, Transportation" and "Computers, Transport" would generate a similarity of 0 with Jaccard but 0.75 with our approach. We used the same approach for comparing `keyPeople`, where misspellings of names are more important. `locations` and `countries` were compared using *Highest Jaccard*: This means we compared each location of an entity with each location of another entity using Jaccard and then picked the highest value. To give an example: Comparing a company with two locations "New York" and "London" with another company with only one location "New York City" would give bad results using *Equals* or *Levenshtein*, which is why we chose to use the highest Jaccard value. Very often there were entities with multiple countries or locations but only single intersections. Due to the sparsity and potential unreliability of Freebase and DBpedia we wanted the similarity to reflect this. Lastly we compared numeric attributes such as `Revenue` using the *PercentageSimilarity*: However numeric data from Freebase and DBpedia is too sparse, unreliable or outdated. Learning a matching rule via linear regression confirms this by assigning weights of 0 to both these attributes.

3.3 Blocking functions

Table 4 shows the blocking functions we tried and used in our project. For the comparison of the Forbes and Freebase datasets a partitioning by `countries` shows good results, which is consistent with the high density of the attribute in both datasets. We also tried a sorted neighbourhood approach on the same attribute which seemed to be less effective. Using a cross product approach for comparing Freebase with DBpedia was impossible due to the large size of DBpedia. As such we tried partitioning by `countries`, `dateFounded` (where the blocking key is *year/20*) and a combination of the two. The combination reflects our own implementation of a partitioning blocker, where we generate a match to be evaluated if the one of the two blocking keys are the same. This shows the best results because both attributes are relatively, but not completely, dense in both datasets, which is

why the reduction ratio is lower then when using only one of the two. When comparing companies with locations from the DBpedia datasets `countries` is the only possible blocking key.

Dataset Comparison	Blocking function	Time	Match	Ratio	P	R	F1
Forbes vs Freebase	CrossProduct	00:32	509	1,00	0,86	1,00	0,92
	SortedNeigh. (Country)	00:05	319	6,80	0,87	0,58	0,70
	Partitioning (Country)	00:02	425	20,19	0,86	1,00	0,92
Freebase vs DBpedia	Partitioning (Country)	00:44	576	15,92	0,90	0,75	0,82
	Partitioning (DateFounded)	00:39	496	9,43	0,89	0,67	0,76
	Partitioning (Combination)	01:22	671	6,13	0,92	0,92	0,92
Companies vs Locations	Partitioning (Country)	00:41	7.921	4,11	0,97	0,94	0,96

Table 4: Blocking functions

3.4 Learning matching rules

We were able to improve the results of our identity resolution by learning the weights for a linear matching rule from a linear regression in RapidMiner over our handwritten rules. To give an example, the learned weights for the datasets from Freebase and DBpedia are as follows. Interestingly, both `keyPeople` and `locations` seem to be important, while the weights for both numeric attributes `revenue` and `numberOfEmployees` is assigned a weight of 0, indicating the attributes are not very useful for an accurate comparison. Lastly the `name` attribute has the highest weight, as expected.

<code>name</code>	0.689	<code>revenue</code>	0.000
<code>countries</code>	0.088	<code>numberOfEmployees</code>	0.000
<code>industries</code>	0.025	<code>keyPeople</code>	0.377
<code>dateFounded</code>	0.170	<code>locations</code>	0.218
<i>intercept</i>	-0.135		

4 Data fusion

4.1 Input data

Table ?? contains the attribute densities and consistencies for each dataset. One notable attribute is `countries`, which has a density of 1 in all datasets except for Freebase. This is due to the nature of Freebase: We query for company locations, which very often returns a city for which the country is not defined (see ¹ for an example). The density of `locations` for Freebase, however, shows a density of 1, supporting this. It also explains why a cross product blocking function returns more matches than partitioning by country when comparing Freebase to another dataset (see table 4).

Attribute	Forbes	Freebase	DBpedia	Consistencies	Fused
name	1,00	1,00	1,00	0,97	1,00
countries	1,00	0,40	1,00	1,00	1,00
industries	0,98	0,54	0,61	0,93	0,65
revenue	1,00	0,16	0,15	1,00	0,21
numberOfEmployees	0,00	1,00	0,32	1,00	0,38
dateFounded	0,00	0,81	0,79	0,99	0,82
assets	1,00	0,00	0,06	1,00	0,12
marketValue	1,00	0,00	0,00	1,00	0,06
profit	0,98	0,13	0,00	1,00	0,07
continent	1,00	0,00	0,00	1,00	0,06
keyPeople	0,00	0,31	0,55	0,97	0,59
locations	0,00	1,00	1,00	0,90	1,00

Table 5: Attribute densities and consistencies per dataset

For this project we used the source as provenance data, as querying additional metadata (such as the author or the most recent date modified) for both Freebase and DBpedia would have made the data collection considerably more time consuming.

4.2 Gold standard

Our fused file contains five entities and each entity involves 15 attributes. For a company the revenue, numberOfEmployees, assets, marketValue and profit are al-

¹<http://www.freebase.com/m/0c0bbxc>

ways changing over time, in order to get the latest data, we searched for different external sources. Take APPLE for example, we went to the homepage of APPLE to read the latest financial statement² and to get the revenue. And then went to statista³ to acquire numberOfEmployees. And we got assets, marketValue and keyPeople went from Forbes⁴. By comparison, Forbes offers a higher quality data than Freebase and Dbpedia. Because of the same reason, we also searched for relatively fresh data on wikipedia⁵ for some attributes of Location, such as population, area and elevation. In a nut shell, DBpedia offers an outdated data and updating frequency is a little low.

²<http://www.apple.com/pr/library/2015/10/27Apple-Reports-Record-Fourth-Quarter-Results.html>

³<http://www.statista.com/statistics/273439/number-of-employees-of-apple-since-2005/>

⁴<http://www.forbes.com/companies/apple/>

⁵<https://en.wikipedia.org>

4.3 Conflict resolution functions

Attributes Name	Datasets in which the attribute is found	Conflict resolution function	Accuracy
name	dataset 1, 2, 3	FavourSources	0,94
		Voting	0,94
		LongestString	0,94
country	dataset 1, 2, 3, 4	Voting	0,94
industries	dataset 1, 2, 3	Intersection	0,88
		Union	0,94
revenue	dataset 1, 2, 3	FavourSources	0,94
numberOfEmployees	dataset 2, 3	Average	0,94
		Max	0,93
dateFounded	dataset 2, 3	MostComplete (date)	0,94
		MostComplete (sample)	0,94
		Combination	0,94
assets	dataset 1, 2	FavourSources	0,93
		Max	0,94
<i>marketValue</i>	<i>dataset 1</i>	<i>SingleSource</i>	<i>0,94</i>
profit	dataset 1, 3	FavourSources	0,94
		Max	0,94
<i>continent</i>	<i>dataset 1</i>	<i>SingleSource</i>	<i>0,94</i>
keyPeople	dataset 2, 3	Intersection	0,93
		Union	0,94
locationName	dataset 2, 3, 4	Intersection+ FavourSources	0,93
		Union+ FavourSources	0,94
<i>population</i>	<i>dataset 4</i>	<i>SingleSource</i>	<i>0,94</i>
<i>area</i>	<i>dataset 4</i>	<i>SingleSource</i>	<i>0,94</i>
<i>elevation</i>	<i>dataset 4</i>	<i>SingleSource</i>	<i>0,94</i>

Table 6: Conflict resolution functions: Datasets 1, 2, 3 and 4 correspond to Forbes, DBpedia, Freebase and DBpedia locations

The 0.06 accuracy missing is due to data not existing in any of the four datasets or very outdated data

Numeric attributes Because of the age of the Forbes dataset and the unreliability of DBpedia/Freebase a high max percentage difference was used to evaluate whether they were equal

Industries: Intersection had very few values left at the end of fusion because the industries from different sources were often very different. Number of Employees: logically Max should be better, since companies want to be growing (same as profit should be positive). Looking deeper into this, the company IBM had a lower number of employees in reality than what was recorded in DBpedia, indicating outdated values in DBpedia.

Intersection vs UNION Interestingly: Intersection seemed to work better with keyPeople than with industries

OWN IMPLEMENTATIONS: write here

4.4 Accuracy

Ehrenwörtliche Erklärung

Ich versichere, dass ich die beiliegende Master-/Bachelorarbeit ohne Hilfe Dritter und ohne Benutzung anderer als der angegebenen Quellen und Hilfsmittel angefertigt und die den benutzten Quellen wörtlich oder inhaltlich entnommenen Stellen als solche kenntlich gemacht habe. Diese Arbeit hat in gleicher oder ähnlicher Form noch keiner Prüfungsbehörde vorgelegen. Ich bin mir bewusst, dass eine falsche Erklärung rechtliche Folgen haben wird.

Mannheim, November 28, 2015

Unterschrift