



Audit log file format

StorageGRID

NetApp
March 02, 2022

This PDF was generated from <https://docs.netapp.com/us-en/storagegrid-116/audit/using-audit-explain-tool.html> on March 02, 2022. Always check docs.netapp.com for the latest.

Table of Contents

- Audit log file format 1
 - Use audit-explain tool 3
 - Use audit-sum tool 4

Audit log file format

The audit log files are found on every Admin Node and contain a collection of individual audit messages.

Each audit message contains the following:

- The Coordinated Universal Time (UTC) of the event that triggered the audit message (ATIM) in ISO 8601 format, followed by a space:

YYYY-MM-DDTHH:MM:SS.UUUUUU, where *UUUUUU* are microseconds.

- The audit message itself, enclosed within square brackets and beginning with `AUDT`.

The following example shows three audit messages in an audit log file (line breaks added for readability). These messages were generated when a tenant created an S3 bucket and added two objects to that bucket.

2019-08-07T18:43:30.247711

```
[AUDT:[RSLT(FC32):SUCS][CNID(UI64):1565149504991681][TIME(UI64):73520][SAI
P(IPAD):"10.224.2.255"][S3AI(CSTR):"17530064241597054718"]
[SACC(CSTR):"s3tenant"][S3AK(CSTR):"SGKH9100SCkNB8M3MTWNt-
PhoTDwB9JOk7PtyLkQmA=="][SUSR(CSTR):"urn:sgws:identity::175300642415970547
18:root"]
[SBAI(CSTR):"17530064241597054718"][SBAC(CSTR):"s3tenant"][S3BK(CSTR):"buc
ket1"][AVER(UI32):10][ATIM(UI64):1565203410247711]
[ATYP(FC32):SPUT][ANID(UI32):12454421][AMID(FC32):S3RQ][ATID(UI64):7074142
142472611085]]
```

2019-08-07T18:43:30.783597

```
[AUDT:[RSLT(FC32):SUCS][CNID(UI64):1565149504991696][TIME(UI64):120713][SA
IP(IPAD):"10.224.2.255"][S3AI(CSTR):"17530064241597054718"]
[SACC(CSTR):"s3tenant"][S3AK(CSTR):"SGKH9100SCkNB8M3MTWNt-
PhoTDwB9JOk7PtyLkQmA=="][SUSR(CSTR):"urn:sgws:identity::175300642415970547
18:root"]
[SBAI(CSTR):"17530064241597054718"][SBAC(CSTR):"s3tenant"][S3BK(CSTR):"buc
ket1"][S3KY(CSTR):"fh-small-0"]
[CBID(UI64):0x779557A069B2C037][UUID(CSTR):"94BA6949-38E1-4B0C-BC80-
EB44FB4FCC7F"][CSIZ(UI64):1024][AVER(UI32):10]
[ATIM(UI64):1565203410783597][ATYP(FC32):SPUT][ANID(UI32):12454421][AMID(F
C32):S3RQ][ATID(UI64):8439606722108456022]]
```

2019-08-07T18:43:30.784558

```
[AUDT:[RSLT(FC32):SUCS][CNID(UI64):1565149504991693][TIME(UI64):121666][SA
IP(IPAD):"10.224.2.255"][S3AI(CSTR):"17530064241597054718"]
[SACC(CSTR):"s3tenant"][S3AK(CSTR):"SGKH9100SCkNB8M3MTWNt-
PhoTDwB9JOk7PtyLkQmA=="][SUSR(CSTR):"urn:sgws:identity::175300642415970547
18:root"]
[SBAI(CSTR):"17530064241597054718"][SBAC(CSTR):"s3tenant"][S3BK(CSTR):"buc
ket1"][S3KY(CSTR):"fh-small-2000"]
[CBID(UI64):0x180CBD8E678EED17][UUID(CSTR):"19CE06D0-D2CF-4B03-9C38-
E578D66F7ADD"][CSIZ(UI64):1024][AVER(UI32):10]
[ATIM(UI64):1565203410784558][ATYP(FC32):SPUT][ANID(UI32):12454421][AMID(F
C32):S3RQ][ATID(UI64):13489590586043706682]]
```

In their default format, the audit messages in the audit log files are not easy to read or interpret. You can use the `audit-explain` tool to obtain simplified summaries of the audit messages in the audit log. You can use the `audit-sum` tool to summarize how many write, read, and delete operations were logged and how long these operations took.

Related information

[Use audit-explain tool](#)

[Use audit-sum tool](#)

Use audit-explain tool

You can use the `audit-explain` tool to translate the audit messages in the audit log into an easy-to-read format.

What you'll need

- You must have specific access permissions.
- You must have the `Passwords.txt` file.
- You must know the IP address of the primary Admin Node.

About this task

The `audit-explain` tool, available on the primary Admin Node, provides simplified summaries of the audit messages in an audit log.



The `audit-explain` tool is primarily intended for use by technical support during troubleshooting operations. Processing `audit-explain` queries can consume a large amount of CPU power, which might impact StorageGRID operations.

This example shows typical output from the `audit-explain` tool. These four SPUT audit messages were generated when the S3 tenant with account ID 92484777680322627870 used S3 PUT requests to create a bucket named "bucket1" and add three objects to that bucket.

```
SPUT S3 PUT bucket bucket1 account:92484777680322627870 usec:124673
SPUT S3 PUT object bucket1/part1.txt tenant:92484777680322627870
cbid:9DCB157394F99FE5 usec:101485
SPUT S3 PUT object bucket1/part2.txt tenant:92484777680322627870
cbid:3CFBB07AB3D32CA9 usec:102804
SPUT S3 PUT object bucket1/part3.txt tenant:92484777680322627870
cbid:5373D73831ECC743 usec:93874
```

The `audit-explain` tool can process plain or compressed audit logs. For example:

```
audit-explain audit.log
```

```
audit-explain 2019-08-12.txt.gz
```

The `audit-explain` tool can also process multiple files at once. For example:

```
audit-explain audit.log 2019-08-12.txt.gz 2019-08-13.txt.gz
```

```
audit-explain /var/local/audit/export/*
```

Finally, the `audit-explain` tool can accept input from a pipe, which allows you to filter and preprocess the input using the `grep` command or other means. For example:

```
grep SPUT audit.log | audit-explain
```

```
grep bucket-name audit.log | audit-explain
```

Since audit logs can be very large and slow to parse, you can save time by filtering parts that you want to look at and running `audit-explain` on the parts, instead of the entire file.



The `audit-explain` tool does not accept compressed files as piped input. To process compressed files, provide their file names as command-line arguments, or use the `zcat` tool to decompress the files first. For example:

```
zcat audit.log.gz | audit-explain
```

Use the `help` (`-h`) option to see the available options. For example:

```
$ audit-explain -h
```

Steps

1. Log in to the primary Admin Node:

- a. Enter the following command: `ssh admin@primary_Admin_Node_IP`
- b. Enter the password listed in the `Passwords.txt` file.

2. Enter the following command, where `/var/local/audit/export/audit.log` represents the name and the location of the file or files you want to analyze:

```
$ audit-explain /var/local/audit/export/audit.log
```

The `audit-explain` tool prints human-readable interpretations of all messages in the specified file or files.



To reduce line lengths and to aid readability, timestamps are not shown by default. If you want to see the timestamps, use the `timestamp (-t)` option.

Related information

[SPUT: S3 PUT](#)

Use audit-sum tool

You can use the `audit-sum` tool to count the write, read, head, and delete audit messages and to see the minimum, maximum, and average time (or size) for each

operation type.

What you'll need

- You must have specific access permissions.
- You must have the `Passwords.txt` file.
- You must know the IP address of the primary Admin Node.

About this task

The `audit-sum` tool, available on the primary Admin Node, summarizes how many write, read, and delete operations were logged and how long these operations took.



The `audit-sum` tool is primarily intended for use by technical support during troubleshooting operations. Processing `audit-sum` queries can consume a large amount of CPU power, which might impact StorageGRID operations.

This example shows typical output from the `audit-sum` tool. This example shows how long protocol operations took.

message group	count	min(sec)	max(sec)
average(sec)			
=====	=====	=====	=====
=====			
IDEL	274		
SDEL	213371	0.004	20.934
0.352			
SGET	201906	0.010	1740.290
1.132			
SHEA	22716	0.005	2.349
0.272			
SPUT	1771398	0.011	1770.563
0.487			

The `audit-sum` tool provides counts and times for the following S3, Swift, and ILM audit messages in an audit log:

Code	Description	Refer to
ARCT	Archive Retrieve from Cloud-Tier	ARCT: Archive Retrieve from Cloud-Tier
ASCT	Archive Store Cloud-Tier	ASCT: Archive Store Cloud-Tier
IDEL	ILM Initiated Delete: Logs when ILM starts the process of deleting an object.	IDEL: ILM Initiated Delete
SDEL	S3 DELETE: Logs a successful transaction to delete an object or bucket.	SDEL: S3 DELETE

Code	Description	Refer to
SGET	S3 GET: Logs a successful transaction to retrieve an object or list the objects in a bucket.	SGET: S3 GET
SHEA	S3 HEAD: Logs a successful transaction to check for the existence of an object or bucket.	SHEA: S3 HEAD
SPUT	S3 PUT: Logs a successful transaction to create a new object or bucket.	SPUT: S3 PUT
WDEL	Swift DELETE: Logs a successful transaction to delete an object or container.	WDEL: Swift DELETE
WGET	Swift GET: Logs a successful transaction to retrieve an object or list the objects in a container.	WGET: Swift GET
WHEA	Swift HEAD: Logs a successful transaction to check for the existence of an object or container.	WHEA: Swift HEAD
WPUT	Swift PUT: Logs a successful transaction to create a new object or container.	WPUT: Swift PUT

The `audit-sum` tool can process plain or compressed audit logs. For example:

```
audit-sum audit.log
```

```
audit-sum 2019-08-12.txt.gz
```

The `audit-sum` tool can also process multiple files at once. For example:

```
audit-sum audit.log 2019-08-12.txt.gz 2019-08-13.txt.gz
```

```
audit-sum /var/local/audit/export/*
```

Finally, the `audit-sum` tool can also accept input from a pipe, which allows you to filter and preprocess the input using the `grep` command or other means. For example:

```
grep WGET audit.log | audit-sum
```



```
grep bucket1 audit.log | audit-sum
```

```
grep SPUT audit.log | grep bucket1 | audit-sum
```



This tool does not accept compressed files as piped input. To process compressed files, provide their file names as command-line arguments, or use the `zcat` tool to decompress the files first. For example:

```
audit-sum audit.log.gz
```

```
zcat audit.log.gz | audit-sum
```

You can use command-line options to summarize operations on buckets separately from operations on objects or to group message summaries by bucket name, by time period, or by target type. By default, the summaries show the minimum, maximum, and average operation time, but you can use the `size (-s)` option to look at object size instead.

Use the `help (-h)` option to see the available options. For example:

```
$ audit-sum -h
```

Steps

1. Log in to the primary Admin Node:
 - a. Enter the following command: `ssh admin@primary_Admin_Node_IP`
 - b. Enter the password listed in the `Passwords.txt` file.
2. If you want to analyze all messages related to write, read, head, and delete operations, follow these steps:
 - a. Enter the following command, where `/var/local/audit/export/audit.log` represents the name and the location of the file or files you want to analyze:

```
$ audit-sum /var/local/audit/export/audit.log
```

This example shows typical output from the `audit-sum` tool. This example shows how long protocol operations took.

message group	count	min(sec)	max(sec)
average(sec)			
=====	=====	=====	=====
=====			
IDEL	274		
SDEL	213371	0.004	20.934
0.352			
SGET	201906	0.010	1740.290
1.132			
SHEA	22716	0.005	2.349
0.272			
SPUT	1771398	0.011	1770.563
0.487			

In this example, SGET (S3 GET) operations are the slowest on average at 1.13 seconds, but SGET and SPUT (S3 PUT) operations both show long worst-case times of about 1,770 seconds.

- b. To show the slowest 10 retrieval operations, use the `grep` command to select only SGET messages and add the long output option (`-l`) to include object paths: `grep SGET audit.log | audit-sum -l`

The results include the type (object or bucket) and path, which allows you to `grep` the audit log for other messages relating to these particular objects.

```

Total:          201906 operations
Slowest:        1740.290 sec
Average:        1.132 sec
Fastest:        0.010 sec
Slowest operations:
    time(usec)      source ip      type      size(B) path
    =====
1740289662  10.96.101.125      object  5663711385
backup/r9010aQ8JB-1566861764-4519.iso
1624414429  10.96.101.125      object  5375001556
backup/r9010aQ8JB-1566861764-6618.iso
1533143793  10.96.101.125      object  5183661466
backup/r9010aQ8JB-1566861764-4518.iso
70839      10.96.101.125      object    28338
bucket3/dat.1566861764-6619
68487      10.96.101.125      object    27890
bucket3/dat.1566861764-6615
67798      10.96.101.125      object    27671
bucket5/dat.1566861764-6617
67027      10.96.101.125      object    27230
bucket5/dat.1566861764-4517
60922      10.96.101.125      object    26118
bucket3/dat.1566861764-4520
35588      10.96.101.125      object    11311
bucket3/dat.1566861764-6616
23897      10.96.101.125      object    10692
bucket3/dat.1566861764-4516

```

From this example output, you can see that the three slowest S3 GET requests were for objects about 5 GB in size, which is much larger than the other objects. The large size accounts for the slow worst-case retrieval times.

3. If you want to determine what sizes of objects are being ingested into and retrieved from your grid, use the size option (-s):

```
audit-sum -s audit.log
```

message group average (MB)	count	min (MB)	max (MB)
=====	=====	=====	=====
IDEL 1654.502	274	0.004	5000.000
SDEL 1.695	213371	0.000	10.504
SGET 14.920	201906	0.000	5000.000
SHEA 2.967	22716	0.001	10.504
SPUT 2.495	1771398	0.000	5000.000

In this example, the average object size for SPUT is under 2.5 MB, but the average size for SGET is much larger. The number of SPUT messages is much higher than the number of SGET messages, indicating that most objects are never retrieved.

4. If you want to determine if retrievals were slow yesterday:

- a. Issue the command on the appropriate audit log and use the group-by-time option (`-gt`), followed by the time period (for example, 15M, 1H, 10S):

```
grep SGET audit.log | audit-sum -gt 1H
```

message group average(sec)	count	min(sec)	max(sec)
=====	=====	=====	=====
2019-09-05T00 1.254	7591	0.010	1481.867
2019-09-05T01 1.115	4173	0.011	1740.290
2019-09-05T02 1.562	20142	0.011	1274.961
2019-09-05T03 1.254	57591	0.010	1383.867
2019-09-05T04 1.405	124171	0.013	1740.290
2019-09-05T05 1.562	420182	0.021	1274.511
2019-09-05T06 5.562	1220371	0.015	6274.961
2019-09-05T07 2.002	527142	0.011	1974.228
2019-09-05T08 1.105	384173	0.012	1740.290
2019-09-05T09 1.354	27591	0.010	1481.867

These results show that S3 GET traffic spiked between 06:00 and 07:00. The max and average times are both considerably higher at these times as well, and they did not ramp up gradually as the count increased. This suggests that capacity was exceeded somewhere, perhaps in the network or in the grid's ability to process requests.

- b. To determine what size objects were being retrieved each hour yesterday, add the size option (`-s`) to the command:

```
grep SGET audit.log | audit-sum -gt 1H -s
```

message group average(B)	count	min(B)	max(B)
=====	=====	=====	=====
2019-09-05T00 1.976	7591	0.040	1481.867
2019-09-05T01 2.062	4173	0.043	1740.290
2019-09-05T02 2.303	20142	0.083	1274.961
2019-09-05T03 1.182	57591	0.912	1383.867
2019-09-05T04 1.528	124171	0.730	1740.290
2019-09-05T05 2.398	420182	0.875	4274.511
2019-09-05T06 51.328	1220371	0.691	5663711385.961
2019-09-05T07 2.147	527142	0.130	1974.228
2019-09-05T08 1.878	384173	0.625	1740.290
2019-09-05T09 1.354	27591	0.689	1481.867

These results indicate that some very large retrievals occurred when the overall retrieval traffic was at its maximum.

- c. To see more detail, use the `audit-explain` tool to review all the SGET operations during that hour:

```
grep 2019-09-05T06 audit.log | grep SGET | audit-explain | less
```

If the output of the `grep` command is expected to be many lines, add the `less` command to show the contents of the audit log file one page (one screen) at a time.

5. If you want to determine if SPUT operations on buckets are slower than SPUT operations for objects:

- a. Start by using the `-go` option, which groups messages for object and bucket operations separately:

```
grep SPUT sample.log | audit-sum -go
```

message group average(sec)	count	min(sec)	max(sec)
=====	=====	=====	=====
SPUT.bucket 0.125	1	0.125	0.125
SPUT.object 0.236	12	0.025	1.019

The results show that SPUT operations for buckets have different performance characteristics than SPUT operations for objects.

- b. To determine which buckets have the slowest SPUT operations, use the `-gb` option, which groups messages by bucket:

```
grep SPUT audit.log | audit-sum -gb
```

message group average(sec)	count	min(sec)	max(sec)
=====	=====	=====	=====
SPUT.cho-non-versioning 1.571	71943	0.046	1770.563
SPUT.cho-versioning 1.415	54277	0.047	1736.633
SPUT.cho-west-region 1.329	80615	0.040	55.557
SPUT.ldt002 0.361	1564563	0.011	51.569

- c. To determine which buckets have the largest SPUT object size, use both the `-gb` and the `-s` options:

```
grep SPUT audit.log | audit-sum -gb -s
```

message group average (B)	count	min (B)	max (B)
=====	=====	=====	=====
=====			
SPUT.cho-non-versioning 21.672	71943	2.097	5000.000
SPUT.cho-versioning 21.120	54277	2.097	5000.000
SPUT.cho-west-region 14.433	80615	2.097	800.000
SPUT.ldt002 0.352	1564563	0.000	999.972

Related information

[Use audit-explain tool](#)

Copyright Information

Copyright © 2022 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.