

autolisp-test Test Corpus

Codex

May 24, 2026

This directory holds the AutoLISP / Visual LISP conformance tests.

Tests are written in pure AutoLISP and use the registration helpers defined in `harness/rt.lisp` (`deftest`, `deftest-eq`, `deftest-pred`, `deftest-error`, `deftest-skip`).

Layout

Tests are grouped by language area, then by operator or narrowly related family:

reader/ reader-syntax conformance (literals, symbols, lists, dotted pairs, quote)

variables/ standardised variables (NIL, T, PI, PAUSE, *ERROR*)

types/ TYPE and the type system

special-forms/ every special form already implemented in clautolisp

equality/ EQ, EQUAL, NULL, ATOM, LISTP, NUMBERP, ZEROP, MINUSP

list/ list / CXXR / MAPCAR / VL-EVERY / VL-SOME / VL-MEMBER-IF /
VL-REMOVE-IF / VL-SORT / REMOVE / VL-POSITION / VL-LIST-LENGTH

numeric/ arithmetic, comparison, bitwise, math, FIX / FLOAT / FLOOR /
CEILING / ROUND

string/ STRCAT, STRLEN, SUBSTR, STRCASE, ASCII / CHR, ATOI, ATOF, ITOA,
RTOS, WCMATCH, XSTRCASE, SNVALID, VL-STRING-*

symbol/ VL-SYMBOLP, VL-SYMBOL-NAME, VL-SYMBOL-VALUE, BOUNDP, ATOMS-FAMILY

namespace/ VL-BB-*, VL-DOC-*, DEFUN-Q-LIST-*

control/ EVAL, APPLY

error/ VL-CATCH-ALL-*, VL-EXIT-WITH-*

printer/ PRIN1, PRINC, PRINT, TERPRI, VL-PRIN1-TO-STRING, VL-PRINC-TO-STRING

file/ OPEN, CLOSE, READ-LINE, WRITE-LINE, READ-CHAR, WRITE-CHAR, FINDFILE,
VL-FILE-*, VL-FILENAME-*, VL-DIRECTORY-FILES, VL-MKDIR

geometry/ DISTANCE, ANGLE, POLAR, INTERS

divergent/ Phase D: vendor-divergent twin tests

deferred/ Phase E: stubs for areas requiring a mock host or vendor-specific
runtime (DCL, COM/VLAX, VLA, VLR, OBJECTDBX, Express Tools,
DOSLib, ARX, BRX)

Test metadata

Every test carries a meta alist with at minimum:

OPERATOR the spec entry name being tested (string)

AREA the language area (string)

PROFILE one of STRICT, AUTOCAD, BRICSCAD

Optional fields:

PLATFORM-TAGS list of required platform symbols

RUNTIME-TAGS list of required runtime symbols

AUTHORITY DOCUMENTED (default), TESTED-AUTOCAD, TESTED-BRICSCAD, TESTED-BOTH,
INFERRED

Adding a new test file

1. Drop the file under the appropriate `tests/<area>/` directory.
2. Add its relative path to `*autolisp-test-files*` in `harness/test-loader.lsp` so it is loaded at run time.
3. The next (`autolisp-test-run-all`) picks it up.

Adding a vendor-divergent twin

When a function's behaviour differs between AutoCAD and BricsCAD, write **two** tests:

- one `:profile autocad` with the AutoCAD-attested result;
- one `:profile bricscad` with the BricsCAD-attested result;
- optionally a narrowed `:profile strict` test for the still-shared subset.

The harness reports each twin under its own profile, so the verdict matrix shows the divergence by name.