

# autolisp-test Test Corpus

Codex

June 24, 2026

This directory holds the AutoLISP / Visual LISP conformance tests.

Tests are written in pure AutoLISP and use the registration helpers defined in `harness/rt.lisp` (`deftest`, `deftest-eq`, `deftest-pred`, `deftest-error`, `deftest-skip`).

## Layout

Tests are grouped by language area, then by operator or narrowly related family:

**reader/** reader-syntax conformance (literals, symbols, lists, dotted pairs, quote)

**variables/** standardised variables (NIL, T, PI, PAUSE, \*ERROR\*)

**types/** TYPE and the type system

**special-forms/** every special form already implemented in clautolisp

**equality/** EQ, EQUAL, NULL, ATOM, LISTP, NUMBERP, ZEROP, MINUSP

**list/** list / CXXR / MAPCAR / VL-EVERY / VL-SOME / VL-MEMBER-IF /  
VL-REMOVE-IF / VL-SORT / REMOVE / VL-POSITION / VL-LIST-LENGTH

**numeric/** arithmetic, comparison, bitwise, math, FIX / FLOAT / FLOOR /  
CEILING / ROUND

**string/** STRCAT, STRLEN, SUBSTR, STRCASE, ASCII / CHR, ATOI, ATOF, ITOA,  
RTOS, WCMATCH, XSTRCASE, SNVALID, VL-STRING-\*

**symbol/** VL-SYMBOLP, VL-SYMBOL-NAME, VL-SYMBOL-VALUE, BOUNDP, ATOMS-FAMILY

**namespace/** VL-BB-\*, VL-DOC-\*, DEFUN-Q-LIST-\*

**control/** EVAL, APPLY

**error/** VL-CATCH-ALL-\*, VL-EXIT-WITH-\*

**printer/** PRIN1, PRINC, PRINT, TERPRI, VL-PRIN1-TO-STRING, VL-PRINC-TO-STRING

**file/** OPEN, CLOSE, READ-LINE, WRITE-LINE, READ-CHAR, WRITE-CHAR, FINDFILE,  
VL-FILE-\*, VL-FILENAME-\*, VL-DIRECTORY-FILES, VL-MKDIR

**geometry/** DISTANCE, ANGLE, POLAR, INTERS

**divergent/** Phase D: vendor-divergent twin tests

**deferred/** Phase E: stubs for areas requiring a mock host or vendor-specific  
runtime (DCL, COM/VLAX, VLA, VLR, OBJECTDBX, Express Tools,  
DOSLib, ARX, BRX)

## Test metadata

Every test carries a meta alist with at minimum:

**OPERATOR** the spec entry name being tested (string)

**AREA** the language area (string)

**PROFILE** one of STRICT, AUTOCAD, BRICSCAD

Optional fields:

**PLATFORM-TAGS** list of required platform symbols

**RUNTIME-TAGS** list of required runtime symbols

**AUTHORITY** DOCUMENTED (default), TESTED-AUTOCAD, TESTED-BRICSCAD, TESTED-BOTH,  
INFERRED

## Adding a new test file

1. Drop the file under the appropriate `tests/<area>/` directory.
2. Add its relative path to `*autolisp-test-files*` in `harness/test-loader.lsp` so it is loaded at run time.
3. The next (`autolisp-test-run-all`) picks it up.

## Adding a vendor-divergent twin

When a function's behaviour differs between AutoCAD and BricsCAD, write **two** tests:

- one `:profile autocad` with the AutoCAD-attested result;
- one `:profile bricscad` with the BricsCAD-attested result;
- optionally a narrowed `:profile strict` test for the still-shared subset.

The harness reports each twin under its own profile, so the verdict matrix shows the divergence by name.