

C28SOI_IO_EXT_CSF_BASIC_EG Databook

August 2016

EMPTYCELL_EXT_CSF_FC_INNER

Cell Description

EMPTYCELL_EXT_CSF_FC_INNER

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 3632.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
i alametei	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000

ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000
ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	3.104e-08
typ 1.00 25	0.000e+00	2.928e-08
worst 0.90 125	0.000e+00	8.318e-08



EMPTYCELL_EXT_CSF_FC_OUTER

Cell Description

EMPTYCELL_EXT_CSF_FC_OUTER

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 8307.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Farameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	3.104e-08
typ 1.00 25	0.000e+00	2.928e-08
worst 0.90 125	0.000e+00	8.318e-08



FILLCELL_1GRID_EXT_CSF_CL_LIN

Cell Description

FILLCELL_1GRID_EXT_CSF_CL_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 10.630

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_1GRID_EXT_CSF_FC_2ROWS

Cell Description

FILLCELL_1GRID_EXT_CSF_FC_2ROWS

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 18.460

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_1GRID_EXT_CSF_FC_INNER

Cell Description

FILLCELL_1GRID_EXT_CSF_FC_INNER

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 9.080

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_1GRID_EXT_CSF_FC_LIN

Cell Description

FILLCELL_1GRID_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 9.080

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_1GRID_EXT_CSF_FC_OUTER

Cell Description

FILLCELL_1GRID_EXT_CSF_FC_OUTER

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 9.380

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_1UM_EXT_CSF_CL_LIN

Cell Description

FILLCELL_1UM_EXT_CSF_CL_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 106.300

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_1UM_EXT_CSF_FC_2ROWS

Cell Description

FILLCELL_1UM_EXT_CSF_FC_2ROWS

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 184.600

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Farameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_1UM_EXT_CSF_FC_INNER

Cell Description

FILLCELL_1UM_EXT_CSF_FC_INNER

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 90.800

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_1UM_EXT_CSF_FC_LIN

Cell Description

FILLCELL_1UM_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 90.800

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Farameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_1UM_EXT_CSF_FC_OUTER

Cell Description

FILLCELL_1UM_EXT_CSF_FC_OUTER

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 93.800

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Farameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_5UM_EXT_CSF_CL_LIN

Cell Description

FILLCELL_5UM_EXT_CSF_CL_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 531.500

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125	
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100	
ASRCN[0] Max Load	10000.000	10000.000	10000.000	
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100	
ASRCN[1] Max Load	10000.000	10000.000	10000.000	
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100	
ASRCN[2] Max Load	10000.000	10000.000	10000.000	
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100	
ASRCN[3] Max Load	10000.000	10000.000	10000.000	
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100	
ASRCN[4] Max Load	10000.000	10000.000	10000.000	
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100	
ASRCN[5] Max Load	10000.000	10000.000	10000.000	
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100	
ASRCN[6] Max Load	10000.000	10000.000	10000.000	
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100	
ASRCP[0] Max Load	10000.000	10000.000	10000.000	
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100	
ASRCP[1] Max Load	10000.000	10000.000	10000.000	
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100	
ASRCP[2] Max Load	10000.000	10000.000	10000.000	
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100	
ASRCP[3] Max Load	10000.000	10000.000	10000.000	



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_5UM_EXT_CSF_FC_2ROWS

Cell Description

FILLCELL_5UM_EXT_CSF_FC_2ROWS

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 923.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_5UM_EXT_CSF_FC_INNER

Cell Description

FILLCELL_5UM_EXT_CSF_FC_INNER

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 454.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_5UM_EXT_CSF_FC_LIN

Cell Description

FILLCELL_5UM_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 454.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_5UM_EXT_CSF_FC_OUTER

Cell Description

FILLCELL_5UM_EXT_CSF_FC_OUTER

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 469.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_10UM_EXT_CSF_CL_LIN

Cell Description

FILLCELL_10UM_EXT_CSF_CL_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 1063.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_10UM_EXT_CSF_FC_2ROWS

Cell Description

FILLCELL_10UM_EXT_CSF_FC_2ROWS

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 1846.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Farameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_10UM_EXT_CSF_FC_INNER

Cell Description

FILLCELL_10UM_EXT_CSF_FC_INNER

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 908.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_10UM_EXT_CSF_FC_LIN

Cell Description

FILLCELL_10UM_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 908.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Farameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_10UM_EXT_CSF_FC_OUTER

Cell Description

FILLCELL_10UM_EXT_CSF_FC_OUTER

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 938.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Farameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_END_LEFT_EXT_CSF_CL_LIN

Cell Description

FILLCELL_END_LEFT_EXT_CSF_CL_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 1807.100

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[0] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[0] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[1] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[1] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[2] Input	0.0100	0.0100	0.0100
Cap.			



AODONOODEIOIMaaalaaal	40000 000	40000 000	40000 000
ASRCNCORE[2] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[3] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[3] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[4] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[4] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[5] Input	0.0100	0.0100	0.0100
Сар.			
ASRCNCORE[5] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[6] Input	0.0100	0.0100	0.0100
Сар.			
ASRCNCORE[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000
ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[0] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[0] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[1] Input	0.0100	0.0100	0.0100
Сар.			
ASRCPCORE[1] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[2] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[2] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[3] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[3] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[4] Input	0.0100	0.0100	0.0100
Сар.			
ASRCPCORE[4] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[5] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[5] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[6] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOACORE Input Cap.	0.0100	0.0100	0.0100
REFIOACORE Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
INET TOD ITIPUT Cap.	0.0100	0.0100	0.0100



REFIOB Max Load	10000.000	10000.000	10000.000
REFIOBCORE Input Cap.	0.0100	0.0100	0.0100
REFIOBCORE Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	7.662e-09
typ 1.00 25	0.000e+00	6.934e-09
worst 0.90 125	0.000e+00	8.943e-08



FILLCELL_END_LEFT_EXT_CSF_FC_2ROWS

Cell Description

FILLCELL_END_LEFT_EXT_CSF_FC_2ROWS

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 3876.600

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[0] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[0] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[1] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[1] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[2] Input	0.0100	0.0100	0.0100
Сар.			



ASPCNCOPEI31 May Load	10000.000	10000.000	10000.000
ASRCNCORE[2] Max Load ASRCNCORE[3] Input	0.0100	0.0100	0.0100
Cap.	0.0100	0.0100	0.0100
ASRCNCORE[3] Max Load	10000.000	10000.000	10000.000
	0.0100	0.0100	0.0100
ASRCNCORE[4] Input	0.0100	0.0100	0.0100
Cap. ASRCNCORE[4] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[5] Input	0.0100	0.0100	0.0100
Cap. ASRCNCORE[5] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[5] Max Load ASRCNCORE[6] Input			
	0.0100	0.0100	0.0100
Cap. ASRCNCORE[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000
ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[0] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[0] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[1] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[1] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[2] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[2] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[3] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[3] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[4] Input	0.0100	0.0100	0.0100
Cap.	40000 000	10000 000	40000
ASRCPCORE[4] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[5] Input	0.0100	0.0100	0.0100
Cap.	40000 000	40000 000	40000 000
ASRCPCORE[5] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[6] Input	0.0100	0.0100	0.0100
Cap.	10000 000	10000 000	10000 000
ASRCPCORE[6] Max Load	10000.000	10000.000	10000.000
REFIOA May Land	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOACORE Input Cap.	0.0100	0.0100	0.0100
REFIOACORE Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100



REFIOB Max Load	10000.000	10000.000	10000.000
REFIOBCORE Input Cap.	0.0100	0.0100	0.0100
REFIOBCORE Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	7.712e-09
typ 1.00 25	0.000e+00	7.477e-09
worst 0.90 125	0.000e+00	2.289e-07



FILLCELL_END_LEFT_EXT_CSF_FC_INNER

Cell Description

FILLCELL_END_LEFT_EXT_CSF_FC_INNER

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 1543.600

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[0] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[0] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[1] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[1] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[2] Input	0.0100	0.0100	0.0100
Cap.			



ASRCNCORE[2] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[3] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[3] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[4] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[4] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[5] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[5] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[6] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000
ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[0] Input	0.0100	0.0100	0.0100
Сар.			
ASRCPCORE[0] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[1] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[1] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[2] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[2] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[3] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[3] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[4] Input	0.0100	0.0100	0.0100
Cap.	40000 000	40000 000	10000 000
ASRCPCORE[4] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[5] Input	0.0100	0.0100	0.0100
Cap.	40000 000	10000 000	10000 000
ASRCPCORE[5] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[6] Input	0.0100	0.0100	0.0100
Cap.	10000 000	10000 000	10000 000
ASRCPCORE[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA CORE Input Con	10000.000	10000.000	10000.000
REFIOACORE Input Cap.	0.0100	0.0100	0.0100
REFIOACORE Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100



REFIOB Max Load	10000.000	10000.000	10000.000
REFIOBCORE Input Cap.	0.0100	0.0100	0.0100
REFIOBCORE Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	7.657e-09
typ 1.00 25	0.000e+00	6.896e-09
worst 0.90 125	0.000e+00	8.230e-08



FILLCELL_END_LEFT_EXT_CSF_FC_LIN

Cell Description

FILLCELL_END_LEFT_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 1543.600

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[0] Input	0.0100	0.0100	0.0100
Сар.			
ASRCNCORE[0] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[1] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[1] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[2] Input	0.0100	0.0100	0.0100
Cap.			



AODONIOODEIOI Massilla ad	10000 000	40000 000	40000 000
ASRCNCORE[2] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[3] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[3] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[4] Input	0.0100	0.0100	0.0100
Сар.			
ASRCNCORE[4] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[5] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[5] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[6] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000
ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[0] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[0] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[1] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[1] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[2] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[2] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[3] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[3] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[4] Input	0.0100	0.0100	0.0100
Cap.	0.0100	0.0.00	0.0.00
ASRCPCORE[4] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[5] Input	0.0100	0.0100	0.0100
Cap.	0.0100	0.0100	0.0100
ASRCPCORE[5] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[6] Input	0.0100	0.0100	0.0100
	0.0100	0.0100	0.0100
Cap.	10000 000	10000 000	10000 000
ASRCPCORE[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOACORE Input Cap.	0.0100	0.0100	0.0100
REFIOACORE Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100



REFIOB Max Load	10000.000	10000.000	10000.000
REFIOBCORE Input Cap.	0.0100	0.0100	0.0100
REFIOBCORE Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	7.657e-09
typ 1.00 25	0.000e+00	6.896e-09
worst 0.90 125	0.000e+00	8.230e-08



FILLCELL_END_RIGHT_EXT_CSF_CL_LIN

Cell Description

FILLCELL_END_RIGHT_EXT_CSF_CL_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 1807.100

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[0] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[0] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[1] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[1] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[2] Input	0.0100	0.0100	0.0100
Cap.			



ASRCNCORE[2] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[3] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[3] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[4] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[4] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[5] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[5] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[6] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000
ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[0] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[0] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[1] Input	0.0100	0.0100	0.0100
Cap.	40000 000	40000 000	40000 000
ASRCPCORE[1] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[2] Input	0.0100	0.0100	0.0100
Cap. ASRCPCORE[2] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[3] Input	0.0100	0.0100	0.0100
Cap.	0.0100	0.0100	0.0100
ASRCPCORE[3] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[4] Input	0.0100	0.0100	0.0100
Cap.	0.0100	0.0100	0.0100
ASRCPCORE[4] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[5] Input	0.0100	0.0100	0.0100
Cap.	2.2.00		
ASRCPCORE[5] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[6] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOACORE Input Cap.	0.0100	0.0100	0.0100
REFIOACORE Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100



REFIOB Max Load	10000.000	10000.000	10000.000
REFIOBCORE Input Cap.	0.0100	0.0100	0.0100
REFIOBCORE Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	7.662e-09
typ 1.00 25	0.000e+00	6.934e-09
worst 0.90 125	0.000e+00	8.943e-08



FILLCELL_END_RIGHT_EXT_CSF_FC_2ROWS

Cell Description

FILLCELL_END_RIGHT_EXT_CSF_FC_2ROWS

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 3876.600

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[0] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[0] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[1] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[1] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[2] Input	0.0100	0.0100	0.0100
Сар.			



ASRCNCORE[2] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[3] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[3] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[4] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[4] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[5] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[5] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[6] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000
ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[0] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[0] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[1] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[1] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[2] Input	0.0100	0.0100	0.0100
Сар.			
ASRCPCORE[2] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[3] Input	0.0100	0.0100	0.0100
Сар.			
ASRCPCORE[3] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[4] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[4] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[5] Input	0.0100	0.0100	0.0100
Сар.			
ASRCPCORE[5] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[6] Input	0.0100	0.0100	0.0100
Сар.			
ASRCPCORE[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOACORE Input Cap.	0.0100	0.0100	0.0100
REFIOACORE Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100



REFIOB Max Load	10000.000	10000.000	10000.000
REFIOBCORE Input Cap.	0.0100	0.0100	0.0100
REFIOBCORE Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	7.712e-09
typ 1.00 25	0.000e+00	7.477e-09
worst 0.90 125	0.000e+00	2.289e-07



FILLCELL_END_RIGHT_EXT_CSF_FC_INNER

Cell Description

FILLCELL_END_RIGHT_EXT_CSF_FC_INNER

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 1543.600

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[0] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[0] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[1] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[1] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[2] Input	0.0100	0.0100	0.0100
Cap.			



ASRCNCORE[2] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[3] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[3] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[4] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[4] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[5] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[5] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[6] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000
ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[0] Input	0.0100	0.0100	0.0100
Сар.			
ASRCPCORE[0] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[1] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[1] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[2] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[2] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[3] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[3] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[4] Input	0.0100	0.0100	0.0100
Cap.	40000 000	40000 000	10000 000
ASRCPCORE[4] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[5] Input	0.0100	0.0100	0.0100
Cap.	40000 000	10000 000	10000 000
ASRCPCORE[5] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[6] Input	0.0100	0.0100	0.0100
Cap.	10000 000	10000 000	10000 000
ASRCPCORE[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA CORE Input Con	10000.000	10000.000	10000.000
REFIOACORE Input Cap.	0.0100	0.0100	0.0100
REFIOACORE Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100



REFIOB Max Load	10000.000	10000.000	10000.000
REFIOBCORE Input Cap.	0.0100	0.0100	0.0100
REFIOBCORE Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	7.657e-09
typ 1.00 25	0.000e+00	6.896e-09
worst 0.90 125	0.000e+00	8.230e-08



FILLCELL_END_RIGHT_EXT_CSF_FC_LIN

Cell Description

FILLCELL_END_RIGHT_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 1543.600

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[0] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[0] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[1] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[1] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[2] Input	0.0100	0.0100	0.0100
Сар.			



AODONOODEIOI Maaalaaad	40000 000	40000 000	40000 000
ASRCNCORE[2] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[3] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[3] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[4] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[4] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[5] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[5] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[6] Input	0.0100	0.0100	0.0100
Сар.			
ASRCNCORE[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000
ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[0] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[0] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[1] Input	0.0100	0.0100	0.0100
Сар.			
ASRCPCORE[1] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[2] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[2] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[3] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[3] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[4] Input	0.0100	0.0100	0.0100
Сар.			
ASRCPCORE[4] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[5] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[5] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[6] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOACORE Input Cap.	0.0100	0.0100	0.0100
REFIOACORE Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
INET TOB IMPUT Cap.	0.0100	0.0100	0.0100



REFIOB Max Load	10000.000	10000.000	10000.000
REFIOBCORE Input Cap.	0.0100	0.0100	0.0100
REFIOBCORE Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	7.657e-09
typ 1.00 25	0.000e+00	6.896e-09
worst 0.90 125	0.000e+00	8.230e-08



FILLCELL_FEEDTHROUGH_40UM_EXT_CSF_CL_LIN

Cell Description

FILLCELL_FEEDTHROUGH_40UM_EXT_CSF_CL_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 4252.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Farameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	3.352e-08
typ 1.00 25	0.000e+00	2.991e-08
worst 0.90 125	0.000e+00	1.489e-07



FILLCELL_REFASRC_EXT_CSF_CL_LIN

Cell Description

FILLCELL_REFASRC_EXT_CSF_CL_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 903.550

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Farameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[0] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[0] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[1] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[1] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[2] Input	0.0100	0.0100	0.0100
Cap.			



ASRCNCORE[2] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[3] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[3] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[4] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[4] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[5] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[5] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[6] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000
ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[0] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[0] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[1] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[1] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[2] Input	0.0100	0.0100	0.0100
Сар.			
ASRCPCORE[2] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[3] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[3] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[4] Input	0.0100	0.0100	0.0100
Cap.	40000 000	40000 000	40000 000
ASRCPCORE[4] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[5] Input	0.0100	0.0100	0.0100
Cap. ASRCPCORE[5] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[5] Max Load ASRCPCORE[6] Input	0.0100	0.0100	0.0100
Cap.	0.0100	0.0100	0.0100
ASRCPCORE[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOACORE Input Cap.	0.0100	0.0100	0.0100
REFIOACORE Input Cap. REFIOACORE Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100



REFIOB Max Load	10000.000	10000.000	10000.000
REFIOBCORE Input Cap.	0.0100	0.0100	0.0100
REFIOBCORE Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	7.612e-09
typ 1.00 25	0.000e+00	6.533e-09
worst 0.90 125	0.000e+00	1.282e-08



FILLCELL_REFASRC_EXT_CSF_FC_2ROWS

Cell Description

FILLCELL_REFASRC_EXT_CSF_FC_2ROWS

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 1569.100

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter —		Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125	
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100	
ASRCN[0] Max Load	10000.000	10000.000	10000.000	
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100	
ASRCN[1] Max Load	10000.000	10000.000	10000.000	
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100	
ASRCN[2] Max Load	10000.000	10000.000	10000.000	
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100	
ASRCN[3] Max Load	10000.000	10000.000	10000.000	
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100	
ASRCN[4] Max Load	10000.000	10000.000	10000.000	
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100	
ASRCN[5] Max Load	10000.000	10000.000	10000.000	
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100	
ASRCN[6] Max Load	10000.000	10000.000	10000.000	
ASRCNCORE[0] Input	0.0100	0.0100	0.0100	
Cap. ASRCNCORE[0] Max Load	10000.000	10000.000	10000.000	
ASRCNCORE[1] Input	0.0100	0.0100	0.0100	
Cap.	0.0100	5.5100	0.0100	
ASRCNCORE[1] Max Load	10000.000	10000.000	10000.000	
ASRCNCORE[2] Input	0.0100	0.0100	0.0100	
Cap.				



ASPCNCOPEI31 May Load	10000.000	10000.000	10000.000
ASRCNCORE[2] Max Load ASRCNCORE[3] Input	0.0100	0.0100	0.0100
Cap.	0.0100	0.0100	0.0100
ASRCNCORE[3] Max Load	10000.000	10000.000	10000.000
	0.0100	0.0100	0.0100
ASRCNCORE[4] Input	0.0100	0.0100	0.0100
Cap. ASRCNCORE[4] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[5] Input	0.0100	0.0100	0.0100
Cap. ASRCNCORE[5] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[5] Max Load ASRCNCORE[6] Input			
· · · ·	0.0100	0.0100	0.0100
Cap. ASRCNCORE[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000
ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[0] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[0] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[1] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[1] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[2] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[2] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[3] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[3] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[4] Input	0.0100	0.0100	0.0100
Cap.	40000 000	10000 000	40000 000
ASRCPCORE[4] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[5] Input	0.0100	0.0100	0.0100
Cap.	40000 000	10000 000	10000 000
ASRCPCORE[5] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[6] Input	0.0100	0.0100	0.0100
Cap.	40000.000	40000 000	40000 000
ASRCPCORE[6] Max Load	10000.000	10000.000	10000.000
REFIOA May Land	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOACORE Input Cap.	0.0100	0.0100	0.0100
REFIOACORE Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100



REFIOB Max Load	10000.000	10000.000	10000.000
REFIOBCORE Input Cap.	0.0100	0.0100	0.0100
REFIOBCORE Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_REFASRC_EXT_CSF_FC_LIN

Cell Description

FILLCELL_REFASRC_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 771.800

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[0] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[0] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[1] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[1] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[2] Input	0.0100	0.0100	0.0100
Cap.			



ASRCNCORE[2] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[3] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[3] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[4] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[4] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[5] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[5] Max Load	10000.000	10000.000	10000.000
ASRCNCORE[6] Input	0.0100	0.0100	0.0100
Cap.			
ASRCNCORE[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000
ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[0] Input	0.0100	0.0100	0.0100
Cap.			
ASRCPCORE[0] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[1] Input	0.0100	0.0100	0.0100
Cap.	10000	10000	40000 000
ASRCPCORE[1] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[2] Input	0.0100	0.0100	0.0100
Cap. ASRCPCORE[2] Max Load	10000 000	40000 000	40000 000
	10000.000	10000.000	10000.000
ASRCPCORE[3] Input	0.0100	0.0100	0.0100
Cap. ASRCPCORE[3] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[3] Max Load ASRCPCORE[4] Input	0.0100	0.0100	0.0100
Cap.	0.0100	0.0100	0.0100
ASRCPCORE[4] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[5] Input	0.0100	0.0100	0.0100
Cap.	0.0100	0.0100	0.0100
ASRCPCORE[5] Max Load	10000.000	10000.000	10000.000
ASRCPCORE[6] Input	0.0100	0.0100	0.0100
Cap.	0.0.00	3.3.33	3.3.33
ASRCPCORE[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOACORE Input Cap.	0.0100	0.0100	0.0100
REFIOACORE Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
I · · · · · · · · · · · · ·		1	



REFIOB Max Load	10000.000	10000.000	10000.000
REFIOBCORE Input Cap.	0.0100	0.0100	0.0100
REFIOBCORE Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_VDDE_GNDE_EXT_CSF_CL_LIN

Cell Description

FILLCELL_VDDE_GNDE_EXT_CSF_CL_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 903.550

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter —	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_VDDE_GNDE_EXT_CSF_FC_2ROWS

Cell Description

FILLCELL_VDDE_GNDE_EXT_CSF_FC_2ROWS

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 1569.100

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Farameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCELL_VDDE_GNDE_EXT_CSF_FC_LIN

Cell Description

FILLCELL_VDDE_GNDE_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 771.800

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCUTCELL_ALL_EXT_CSF_FC_2ROWS

Cell Description

FILLCUTCELL_ALL_EXT_CSF_FC_2ROWS

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 2584.400

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Default Leakage Power (mW)	vdderight
best 1.10 -40	5.450e-08
typ 1.00 25	5.228e-08
worst 0.90 125	1.834e-07



FILLCUTCELL_ALL_EXT_CSF_FC_LIN

Cell Description

FILLCUTCELL_ALL_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 1271.200

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Default Leakage Power (mW)	vdderight
best 1.10 -40	3.105e-08
typ 1.00 25	2.938e-08
worst 0.90 125	9.440e-08



FILLCUTCELL_GNDE_EXT_CSF_CL_LIN

Cell Description

FILLCUTCELL_GNDE_EXT_CSF_CL_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 170.080

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Farameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCUTCELL_GNDE_EXT_CSF_FC_2ROWS

Cell Description

FILLCUTCELL_GNDE_EXT_CSF_FC_2ROWS

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 295.360

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Farameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCUTCELL_GNDE_EXT_CSF_FC_LIN

Cell Description

FILLCUTCELL_GNDE_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 145.280

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Doromotor	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCUTCELL_REFASRC_EXT_CSF_CL_LIN

Cell Description

FILLCUTCELL_REFASRC_EXT_CSF_CL_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 170.080

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCUTCELL_REFASRC_EXT_CSF_FC_2ROWS

Cell Description

FILLCUTCELL_REFASRC_EXT_CSF_FC_2ROWS

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 295.360

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCUTCELL_REFASRC_EXT_CSF_FC_LIN

Cell Description

FILLCUTCELL_REFASRC_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 145.280

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	0.000e+00
typ 1.00 25	0.000e+00	0.000e+00
worst 0.90 125	0.000e+00	0.000e+00



FILLCUTCELL_VDD_EXT_CSF_CL_LIN

Cell Description

FILLCUTCELL_VDD_EXT_CSF_CL_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 170.080

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Farameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdde
best 1.10 -40	0.000e+00
typ 1.00 25	0.000e+00
worst 0.90 125	0.000e+00



FILLCUTCELL_VDD_EXT_CSF_FC_2ROWS

Cell Description

FILLCUTCELL_VDD_EXT_CSF_FC_2ROWS

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 295.360

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdde
best 1.10 -40	0.000e+00
typ 1.00 25	0.000e+00
worst 0.90 125	0.000e+00



FILLCUTCELL_VDD_EXT_CSF_FC_LIN

Cell Description

FILLCUTCELL_VDD_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 145.280

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Farameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdde
best 1.10 -40	0.000e+00
typ 1.00 25	0.000e+00
worst 0.90 125	0.000e+00



FILLCUTCELL_VDDE_EXT_CSF_CL_LIN

Cell Description

FILLCUTCELL_VDDE_EXT_CSF_CL_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 372.050

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Farameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd
best 1.10 -40	0.000e+00
typ 1.00 25	0.000e+00
worst 0.90 125	0.000e+00



FILLCUTCELL_VDDE_EXT_CSF_FC_2ROWS

Cell Description

FILLCUTCELL_VDDE_EXT_CSF_FC_2ROWS

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 295.360

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd
best 1.10 -40	0.000e+00
typ 1.00 25	0.000e+00
worst 0.90 125	0.000e+00



FILLCUTCELL_VDDE_EXT_CSF_FC_LIN

Cell Description

FILLCUTCELL_VDDE_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 145.280

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	
best 1.10 -40	0.000e+00	
typ 1.00 25	0.000e+00	
worst 0.90 125	0.000e+00	



FILLCUTCELL_VDDE_GNDE_EXT_CSF_CL_LIN

Cell Description

FILLCUTCELL_VDDE_GNDE_EXT_CSF_CL_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 372.050

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd
best 1.10 -40	0.000e+00
typ 1.00 25	0.000e+00
worst 0.90 125	0.000e+00



FILLCUTCELL_VDDE_GNDE_EXT_CSF_FC_2ROWS

Cell Description

FILLCUTCELL_VDDE_GNDE_EXT_CSF_FC_2ROWS

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 295.360

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd
best 1.10 -40	0.000e+00
typ 1.00 25	0.000e+00
worst 0.90 125	0.000e+00



FILLCUTCELL_VDDE_GNDE_EXT_CSF_FC_LIN

Cell Description

FILLCUTCELL_VDDE_GNDE_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 145.280

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd
best 1.10 -40	0.000e+00
typ 1.00 25	0.000e+00
worst 0.90 125	0.000e+00



GND_EXT_CSF_CL_LIN

Cell Description

GND_EXT_CSF_CL_LIN

- The cell has "dont_use" attribute set in the Synopsys STF
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 4252.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	1.041e-06	0.000e+00
typ 1.00 25	1.356e-05	0.000e+00
worst 0.90 125	1.400e-03	0.000e+00



GND_EXT_CSF_FC_LIN

Cell Description

GND_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 3632.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	1.039e-06	0.000e+00
typ 1.00 25	1.356e-05	0.000e+00
worst 0.90 125	1.400e-03	0.000e+00



GND_VDD_EXT_CSF_FC_2ROWS

Cell Description

GND_VDD_EXT_CSF_FC_2ROWS

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 8307.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Farameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	2.079e-06	0.000e+00
typ 1.00 25	2.712e-05	0.000e+00
worst 0.90 125	2.799e-03	0.000e+00



GNDE_EXT_CSF_CL_LIN

Cell Description

GNDE_EXT_CSF_CL_LIN

- The cell has "dont_use" attribute set in the Synopsys STF
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 4252.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	4.045e-04
typ 1.00 25	0.000e+00	5.646e-05
worst 0.90 125	0.000e+00	2.821e-04



GNDE_EXT_CSF_FC_INNER

Cell Description

GNDE_EXT_CSF_FC_INNER

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 3632.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Farameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	4.045e-04
typ 1.00 25	0.000e+00	5.646e-05
worst 0.90 125	0.000e+00	2.821e-04



GNDE_EXT_CSF_FC_LIN

Cell Description

GNDE_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 3632.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	4.045e-04
typ 1.00 25	0.000e+00	5.646e-05
worst 0.90 125	0.000e+00	2.821e-04



GNDE_EXT_CSF_FC_OUTER

Cell Description

GNDE_EXT_CSF_FC_OUTER

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 8307.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	1.965e-29	4.045e-04
typ 1.00 25	3.016e-29	5.645e-05
worst 0.90 125	0.000e+00	2.821e-04



LBCORNERCELL_EXT_CSF_FC_2ROWS

Cell Description

LBCORNERCELL_EXT_CSF_FC_2ROWS

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 34077.200

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	2.041e-29	8.318e-04
typ 1.00 25	0.000e+00	1.160e-04
worst 0.90 125	0.000e+00	5.794e-04



LBCORNERCELL_EXT_CSF_FC_LIN

Cell Description

LBCORNERCELL_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 8244.640

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	4.159e-04
typ 1.00 25	0.000e+00	5.800e-05
worst 0.90 125	0.000e+00	2.897e-04



LTCORNERCELL_EXT_CSF_FC_2ROWS

Cell Description

LTCORNERCELL_EXT_CSF_FC_2ROWS

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 34077.200

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Farameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	8.318e-04
typ 1.00 25	0.000e+00	1.160e-04
worst 0.90 125	0.000e+00	5.794e-04



LTCORNERCELL_EXT_CSF_FC_LIN

Cell Description

LTCORNERCELL_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 8244.640

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Farameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	4.159e-04
typ 1.00 25	0.000e+00	5.800e-05
worst 0.90 125	0.000e+00	2.897e-04



RBCORNERCELL_EXT_CSF_FC_2ROWS

Cell Description

RBCORNERCELL_EXT_CSF_FC_2ROWS

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 34077.200

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	1.780e-29	8.318e-04
typ 1.00 25	0.000e+00	1.160e-04
worst 0.90 125	0.000e+00	5.794e-04



RBCORNERCELL_EXT_CSF_FC_LIN

Cell Description

RBCORNERCELL_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 8244.640

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Doromotor		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	4.159e-04
typ 1.00 25	0.000e+00	5.800e-05
worst 0.90 125	0.000e+00	2.897e-04



RTCORNERCELL_EXT_CSF_FC_2ROWS

Cell Description

RTCORNERCELL_EXT_CSF_FC_2ROWS

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 34077.200

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter -	Value(pF)		
	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	1.796e-29	8.318e-04
typ 1.00 25	0.000e+00	1.160e-04
worst 0.90 125	0.000e+00	5.794e-04



RTCORNERCELL_EXT_CSF_FC_LIN

Cell Description

RTCORNERCELL_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 8244.640

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	4.159e-04
typ 1.00 25	0.000e+00	5.800e-05
worst 0.90 125	0.000e+00	2.897e-04



VDD_EXT_CSF_CL_LIN

Cell Description

VDD_EXT_CSF_CL_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 4252.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	1.041e-06	0.000e+00
typ 1.00 25	1.356e-05	0.000e+00
worst 0.90 125	1.400e-03	0.000e+00



VDD_EXT_CSF_FC_LIN

Cell Description

VDD_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 3632.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



 ${\tt VDD_EXT_CSF_FC_LIN}$

ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	1.039e-06	0.000e+00
typ 1.00 25	1.356e-05	0.000e+00
worst 0.90 125	1.400e-03	0.000e+00



VDD_GND_EXT_CSF_FC_2ROWS

Cell Description

VDD_GND_EXT_CSF_FC_2ROWS

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 8307.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	2.079e-06	0.000e+00
typ 1.00 25	2.712e-05	0.000e+00
worst 0.90 125	2.799e-03	0.000e+00



VDDE_EXT_CSF_CL_LIN

Cell Description

VDDE_EXT_CSF_CL_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 4252.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Farameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	4.045e-04
typ 1.00 25	0.000e+00	5.646e-05
worst 0.90 125	0.000e+00	2.821e-04



VDDE_EXT_CSF_FC_INNER

Cell Description

VDDE_EXT_CSF_FC_INNER

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 3632.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	4.045e-04
typ 1.00 25	0.000e+00	5.646e-05
worst 0.90 125	0.000e+00	2.821e-04



VDDE_EXT_CSF_FC_LIN

Cell Description

VDDE_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STE.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 3632.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	0.000e+00	4.045e-04
typ 1.00 25	0.000e+00	5.646e-05
worst 0.90 125	0.000e+00	2.821e-04



VDDE_EXT_CSF_FC_OUTER

Cell Description

VDDE_EXT_CSF_FC_OUTER

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 8307.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000



ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	1.968e-29	4.045e-04
typ 1.00 25	3.020e-29	5.645e-05
worst 0.90 125	0.000e+00	2.821e-04



WIRECELL_50OHMS_EXT_CSF_CL_LIN

Cell Description

WIRECELL_50OHMS_EXT_CSF_CL_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 4252.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ANAIOPAD Input Cap.	1.0000	1.0000	1.0000
ANAIOPAD Max Load	10000.000	10000.000	10000.000
ANAZI Input Cap.	0.0100	0.0100	0.0100
ANAZI Max Load	10000.000	10000.000	10000.000
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000



ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000
ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Pin	Doromotor	Value		
Pin	Parameter	best 1.10	typ 1.00	worst 0.90
ANAIOPAD (Input)	Min Transition (ns)	0.002	0.002	0.002
ANAIOPAD (Input)	Max Transition (ns)	0.675	0.675	0.675
ANAIOPAD (Input)	Swing (V)	0.0 - 1.95	0.0 - 1.8	0.0 - 1.65
ANAIOPAD (Input)	Delay thres. rising (V)	0.975	0.9	0.825
ANAIOPAD (Input)	Delay thres. falling (V)	0.975	0.9	0.825
ANAIOPAD (Input)	Slope thres. low (V)	-	-	-
ANAIOPAD (Input)	Slope thres. high (V)	-	-	-
ANAIOPAD (Output)	Min Transition (ns)	-	-	-
ANAIOPAD (Output)	Max Transition (ns)	-	-	-
ANAIOPAD (Output)	Swing (V)	0.0 - 1.95	0.0 - 1.8	0.0 - 1.65
ANAIOPAD (Output)	Delay thres. rising (V)	0.975	0.9	0.825
ANAIOPAD (Output)	Delay thres. falling (V)	0.975	0.9	0.825
ANAIOPAD (Output)	Slope thres. low (V)	0.585	0.54	0.495
ANAIOPAD (Output)	Slope thres. high (V)	1.365	1.26	1.155

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	1.891e-14	9.559e-08
typ 1.00 25	0.000e+00	5.568e-08
worst 0.90 125	0.000e+00	3.652e-07



WIRECELL_50OHMS_EXT_CSF_FC_INNER

Cell Description

WIRECELL_50OHMS_EXT_CSF_FC_INNER

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 3632.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Falameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ANAIOPAD Input Cap.	1.0000	1.0000	1.0000
ANAIOPAD Max Load	10000.000	10000.000	10000.000
ANAZI Input Cap.	0.0100	0.0100	0.0100
ANAZI Max Load	10000.000	10000.000	10000.000
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000



ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000
ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Pin Parameter		Value		
Pin	Parameter	best 1.10	typ 1.00	worst 0.90
ANAIOPAD (Input)	Min Transition (ns)	0.002	0.002	0.002
ANAIOPAD (Input)	Max Transition (ns)	0.675	0.675	0.675
ANAIOPAD (Input)	Swing (V)	0.0 - 1.95	0.0 - 1.8	0.0 - 1.65
ANAIOPAD (Input)	Delay thres. rising (V)	0.975	0.9	0.825
ANAIOPAD (Input)	Delay thres. falling (V)	0.975	0.9	0.825
ANAIOPAD (Input)	Slope thres. low (V)	-	-	-
ANAIOPAD (Input)	Slope thres. high (V)	-	-	-
ANAIOPAD (Output)	Min Transition (ns)	-	-	-
ANAIOPAD (Output)	Max Transition (ns)	-	-	-
ANAIOPAD (Output)	Swing (V)	0.0 - 1.95	0.0 - 1.8	0.0 - 1.65
ANAIOPAD (Output)	Delay thres. rising (V)	0.975	0.9	0.825
ANAIOPAD (Output)	Delay thres. falling (V)	0.975	0.9	0.825
ANAIOPAD (Output)	Slope thres. low (V)	0.585	0.54	0.495
ANAIOPAD (Output)	Slope thres. high (V)	1.365	1.26	1.155

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	1.814e-14	8.796e-08
typ 1.00 25	0.000e+00	4.901e-08
worst 0.90 125	0.000e+00	3.301e-07



WIRECELL_50OHMS_EXT_CSF_FC_LIN

Cell Description

WIRECELL_50OHMS_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 3632.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ANAIOPAD Input Cap.	1.0000	1.0000	1.0000
ANAIOPAD Max Load	10000.000	10000.000	10000.000
ANAZI Input Cap.	0.0100	0.0100	0.0100
ANAZI Max Load	10000.000	10000.000	10000.000
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000
ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000



ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000
ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Pin	Parameter		Value	
PIII	Parameter	best 1.10	typ 1.00	worst 0.90
ANAIOPAD (Input)	Min Transition (ns)	0.002	0.002	0.002
ANAIOPAD (Input)	Max Transition (ns)	0.675	0.675	0.675
ANAIOPAD (Input)	Swing (V)	0.0 - 1.95	0.0 - 1.8	0.0 - 1.65
ANAIOPAD (Input)	Delay thres. rising (V)	0.975	0.9	0.825
ANAIOPAD (Input)	Delay thres. falling (V)	0.975	0.9	0.825
ANAIOPAD (Input)	Slope thres. low (V)	-	-	-
ANAIOPAD (Input)	Slope thres. high (V)	-	-	-
ANAIOPAD (Output)	Min Transition (ns)	-	-	-
ANAIOPAD (Output)	Max Transition (ns)	-	-	-
ANAIOPAD (Output)	Swing (V)	0.0 - 1.95	0.0 - 1.8	0.0 - 1.65
ANAIOPAD (Output)	Delay thres. rising (V)	0.975	0.9	0.825
ANAIOPAD (Output)	Delay thres. falling (V)	0.975	0.9	0.825
ANAIOPAD (Output)	Slope thres. low (V)	0.585	0.54	0.495
ANAIOPAD (Output)	Slope thres. high (V)	1.365	1.26	1.155

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	1.814e-14	8.796e-08
typ 1.00 25	0.000e+00	4.901e-08
worst 0.90 125	0.000e+00	3.301e-07



WIRECELL_EXT_CSF_CL_LIN

Cell Description

WIRECELL_EXT_CSF_CL_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 4252.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Farameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ANAIO Input Cap.	0.0100	0.0100	0.0100
ANAIO Max Load	10000.000	10000.000	10000.000
ANAIOPAD Input Cap.	1.0000	1.0000	1.0000
ANAIOPAD Max Load	10000.000	10000.000	10000.000
ANAZI Input Cap.	0.0100	0.0100	0.0100
ANAZI Max Load	10000.000	10000.000	10000.000
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000



ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000
ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Pin Parameter			Value	
PIII	Parameter	best 1.10	typ 1.00	worst 0.90
ANAIOPAD (Input)	Min Transition (ns)	0.002	0.002	0.002
ANAIOPAD (Input)	Max Transition (ns)	0.675	0.675	0.675
ANAIOPAD (Input)	Swing (V)	0.0 - 1.95	0.0 - 1.8	0.0 - 1.65
ANAIOPAD (Input)	Delay thres. rising	0.975	0.9	0.825
	(V)			
ANAIOPAD (Input)	Delay thres. falling	0.975	0.9	0.825
	(V)			
ANAIOPAD (Input)	Slope thres. low (V)	=	-	-
ANAIOPAD (Input)	Slope thres. high (V)	-	-	-
ANAIOPAD (Output)	Min Transition (ns)	=	-	-
ANAIOPAD (Output)	Max Transition (ns)	-	-	-
ANAIOPAD (Output)	Swing (V)	0.0 - 1.95	0.0 - 1.8	0.0 - 1.65
ANAIOPAD (Output)	Delay thres. rising	0.975	0.9	0.825
	(V)			
ANAIOPAD (Output)	Delay thres. falling	0.975	0.9	0.825
	(V)			
ANAIOPAD (Output)	Slope thres. low (V)	0.585	0.54	0.495
ANAIOPAD (Output)	Slope thres. high (V)	1.365	1.26	1.155

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	3.924e-14	9.559e-08
typ 1.00 25	0.000e+00	5.568e-08
worst 0.90 125	0.000e+00	3.652e-07



WIRECELL_EXT_CSF_FC_INNER

Cell Description

WIRECELL_EXT_CSF_FC_INNER

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 3632.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter	Value(pF)		
Parameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ANAIO Input Cap.	0.0100	0.0100	0.0100
ANAIO Max Load	10000.000	10000.000	10000.000
ANAIOPAD Input Cap.	1.0000	1.0000	1.0000
ANAIOPAD Max Load	10000.000	10000.000	10000.000
ANAZI Input Cap.	0.0100	0.0100	0.0100
ANAZI Max Load	10000.000	10000.000	10000.000
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000



0.0100	0.0100	0.0100
10000.000	10000.000	10000.000
0.0100	0.0100	0.0100
10000.000	10000.000	10000.000
0.0100	0.0100	0.0100
10000.000	10000.000	10000.000
0.0100	0.0100	0.0100
10000.000	10000.000	10000.000
0.0100	0.0100	0.0100
10000.000	10000.000	10000.000
0.0100	0.0100	0.0100
10000.000	10000.000	10000.000
0.0100	0.0100	0.0100
10000.000	10000.000	10000.000
0.0100	0.0100	0.0100
10000.000	10000.000	10000.000
	10000.000 0.0100 10000.000 0.0100 10000.000 0.0100 10000.000 0.0100 10000.000 0.0100 10000.000 0.0100 10000.000 0.0100 0.0100	10000.000 10000.000 0.0100 0.0100 10000.000 10000.000 0.0100 0.0100 10000.000 10000.000 0.0100 0.0100 10000.000 10000.000 0.0100 0.0100 10000.000 10000.000 0.0100 0.0100 10000.000 10000.000 0.0100 0.0100 10000.000 10000.000 0.0100 0.0100

Pin	Doromotor	Value		
PIII	Pin Parameter	best 1.10	typ 1.00	worst 0.90
ANAIOPAD (Input)	Min Transition (ns)	0.002	0.002	0.002
ANAIOPAD (Input)	Max Transition (ns)	0.675	0.675	0.675
ANAIOPAD (Input)	Swing (V)	0.0 - 1.95	0.0 - 1.8	0.0 - 1.65
ANAIOPAD (Input)	Delay thres. rising	0.975	0.9	0.825
	(V)			
ANAIOPAD (Input)	Delay thres. falling	0.975	0.9	0.825
	(V)			
ANAIOPAD (Input)	Slope thres. low (V)	-	-	-
ANAIOPAD (Input)	Slope thres. high (V)	-	-	-
ANAIOPAD (Output)	Min Transition (ns)	-	-	-
ANAIOPAD (Output)	Max Transition (ns)	-	-	-
ANAIOPAD (Output)	Swing (V)	0.0 - 1.95	0.0 - 1.8	0.0 - 1.65
ANAIOPAD (Output)	Delay thres. rising	0.975	0.9	0.825
	(V)			
ANAIOPAD (Output)	Delay thres. falling	0.975	0.9	0.825
	(V)			
ANAIOPAD (Output)	Slope thres. low (V)	0.585	0.54	0.495
ANAIOPAD (Output)	Slope thres. high (V)	1.365	1.26	1.155

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	3.844e-14	8.796e-08
typ 1.00 25	0.000e+00	4.901e-08
worst 0.90 125	0.000e+00	3.301e-07



WIRECELL_EXT_CSF_FC_LIN

Cell Description

WIRECELL_EXT_CSF_FC_LIN

- The cell has "dont_use" attribute set in the Synopsys STF.
- The cell has "dont_touch" attribute set in the Synopsys STF.


Physical Dimensions

Area(um2): 3632.000

Glossary

Tr : Input Transition time C : Output (capacitive) load

R : Rising edge F : Falling edge



Parameter		Value(pF)	
Farameter	best 1.10 -40	typ 1.00 25	worst 0.90 125
ANAIO Input Cap.	0.0100	0.0100	0.0100
ANAIO Max Load	10000.000	10000.000	10000.000
ANAIOPAD Input Cap.	1.0000	1.0000	1.0000
ANAIOPAD Max Load	10000.000	10000.000	10000.000
ANAZI Input Cap.	0.0100	0.0100	0.0100
ANAZI Max Load	10000.000	10000.000	10000.000
ASRCN[0] Input Cap.	0.0100	0.0100	0.0100
ASRCN[0] Max Load	10000.000	10000.000	10000.000
ASRCN[1] Input Cap.	0.0100	0.0100	0.0100
ASRCN[1] Max Load	10000.000	10000.000	10000.000
ASRCN[2] Input Cap.	0.0100	0.0100	0.0100
ASRCN[2] Max Load	10000.000	10000.000	10000.000
ASRCN[3] Input Cap.	0.0100	0.0100	0.0100
ASRCN[3] Max Load	10000.000	10000.000	10000.000
ASRCN[4] Input Cap.	0.0100	0.0100	0.0100
ASRCN[4] Max Load	10000.000	10000.000	10000.000
ASRCN[5] Input Cap.	0.0100	0.0100	0.0100
ASRCN[5] Max Load	10000.000	10000.000	10000.000
ASRCN[6] Input Cap.	0.0100	0.0100	0.0100
ASRCN[6] Max Load	10000.000	10000.000	10000.000
ASRCP[0] Input Cap.	0.0100	0.0100	0.0100
ASRCP[0] Max Load	10000.000	10000.000	10000.000



ASRCP[1] Input Cap.	0.0100	0.0100	0.0100
ASRCP[1] Max Load	10000.000	10000.000	10000.000
ASRCP[2] Input Cap.	0.0100	0.0100	0.0100
ASRCP[2] Max Load	10000.000	10000.000	10000.000
ASRCP[3] Input Cap.	0.0100	0.0100	0.0100
ASRCP[3] Max Load	10000.000	10000.000	10000.000
ASRCP[4] Input Cap.	0.0100	0.0100	0.0100
ASRCP[4] Max Load	10000.000	10000.000	10000.000
ASRCP[5] Input Cap.	0.0100	0.0100	0.0100
ASRCP[5] Max Load	10000.000	10000.000	10000.000
ASRCP[6] Input Cap.	0.0100	0.0100	0.0100
ASRCP[6] Max Load	10000.000	10000.000	10000.000
REFIOA Input Cap.	0.0100	0.0100	0.0100
REFIOA Max Load	10000.000	10000.000	10000.000
REFIOB Input Cap.	0.0100	0.0100	0.0100
REFIOB Max Load	10000.000	10000.000	10000.000

Pin	Doromotor	Value		
PIII	in Parameter	best 1.10	typ 1.00	worst 0.90
ANAIOPAD (Input)	Min Transition (ns)	0.002	0.002	0.002
ANAIOPAD (Input)	Max Transition (ns)	0.675	0.675	0.675
ANAIOPAD (Input)	Swing (V)	0.0 - 1.95	0.0 - 1.8	0.0 - 1.65
ANAIOPAD (Input)	Delay thres. rising	0.975	0.9	0.825
	(V)			
ANAIOPAD (Input)	Delay thres. falling	0.975	0.9	0.825
	(V)			
ANAIOPAD (Input)	Slope thres. low (V)	-	-	-
ANAIOPAD (Input)	Slope thres. high (V)	-	-	-
ANAIOPAD (Output)	Min Transition (ns)	-	-	-
ANAIOPAD (Output)	Max Transition (ns)	-	-	-
ANAIOPAD (Output)	Swing (V)	0.0 - 1.95	0.0 - 1.8	0.0 - 1.65
ANAIOPAD (Output)	Delay thres. rising	0.975	0.9	0.825
	(V)			
ANAIOPAD (Output)	Delay thres. falling	0.975	0.9	0.825
	(V)			
ANAIOPAD (Output)	Slope thres. low (V)	0.585	0.54	0.495
ANAIOPAD (Output)	Slope thres. high (V)	1.365	1.26	1.155

Default Leakage Power (mW)	vdd	vdde
best 1.10 -40	3.844e-14	8.796e-08
typ 1.00 25	0.000e+00	4.901e-08
worst 0.90 125	0.000e+00	3.301e-07





Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY TWO AUTHORIZED ST REPRESENTATIVES, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2012 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com