

Competitive Programming Notebook

Programadores Roblox

Contents

1 Search and sort	2	7 Math	10
1.1 Monotonic Stack	2	7.1 Soma Pg Mod	10
1.2 Merge Sort	2	7.2 Fexp	10
2 Stress	2	7.3 Base Calc	10
2.1 Gen	2	7.4 Totient	11
3 Geometry	2	7.5 Equacao Diofantina	11
3.1 Lattice Points	2	7.6 Menor Fator Primo	11
3.2 Point Location	3	7.7 Exgcd	11
3.3 Convex Hull	3	7.8 Crivo	11
3.4 Point	3	7.9 Matrix	11
3.5 Inside Polygon	4	7.10 Combinatorics	12
4 DS	4	7.11 Divisores	12
4.1 Bit	4	7.12 Segment Sieve	12
4.2 Sparse Table	4	7.13 Discrete Log	12
4.3 Min Queue	4	7.14 Mod Inverse	12
4.4 Segtree Iterativa	5	7.15 Fft	13
4.5 Merge Sort Tree	5	8 Primitives	13
4.6 Seglazy Iterativa	5	9 Graph	13
4.7 Psum 2d	6	9.1 Min Cost Max Flow	13
4.8 Bit2d	6	9.2 Floyd Warshall	14
4.9 Segtree Lazy	6	9.3 Edmonds-karp	14
4.10 Seg Lazy Pa	7	9.4 Lca Jc	14
4.11 Trie Bits	7	9.5 Diametro	15
4.12 Segtree2d	7	9.6 Eulerian Path	15
4.13 Dsu	8	9.7 Lca	15
4.14 Ordered Set E Map	8	9.8 Topological Sort	16
4.15 Maximum Subarray Sum Range	8	9.9 Dijkstra	16
5 General	9	9.10 Acha Pontes	16
5.1 Mex	9	9.11 Khan	16
5.2 Bitwise	9	9.12 Bellman Ford	16
5.3 Debug	9	9.13 Dinitz	16
5.4 Count Permutations	9	9.14 Kruskal	17
5.5 Brute Choose	9	9.15 Kosaraju	17
5.6 Struct	9	10 DP	17
6 String	10	10.1 Bitmask	17
6.1 Trie	10	10.2 Kadane	18
6.2 Z Function	10	10.3 Knapsack	18
6.3 Kmp	10	10.4 Digit	18
6.4 Hashing	10	10.5 Edit Distance	18
		10.6 Lis Brunomonteiro	18
		10.7 Disjoint Blocks	18
		10.8 Lcs	18
		10.9 Lis	18
		10.10Lis Seg	19

1 Search and sort

1.1 Monotonic Stack

```

1 vector<int> find_esq(vector<int> &v, bool maior) {
2     int n = v.size();
3     vector<int> result(n);
4     stack<int> s;
5
6     for (int i = 0; i < n; i++) {
7         while (!s.empty() && (maior ? v[s.top()] <= v[i] : v[
8             s.top()] >= v[i])) {
9             s.pop();
10        }
11        if (s.empty()) {
12            result[i] = -1;
13        } else {
14            result[i] = v[s.top()];
15        }
16        s.push(i);
17    }
18    return result;
19 }
20
21 vector<int> find_dir(vector<int> &v, bool maior) {
22     int n = v.size();
23     vector<int> result(n);
24     stack<int> s;
25     for (int i = n - 1; i >= 0; i--) {
26         while (!s.empty() && (maior ? v[s.top()] <= v[i] : v[
27             s.top()] >= v[i])) {
28             s.pop();
29        }
30        if (s.empty()) {
31            result[i] = -1;
32        } else {
33            result[i] = v[s.top()];
34        }
35        s.push(i);
36    }
37    return result;
38 }

```

1.2 Merge Sort

```

1 int mergeAndCount(vector<int>& v, int l, int m, int r) {
2     int x = m - l + 1;
3     int y = r - m;
4     vector<int> left(x), right(y);
5     for (int i = 0; i < x; i++) left[i] = v[l + i];
6     for (int j = 0; j < y; j++) right[j] = v[m + 1 + j];
7     int i = 0, j = 0, k = l;
8     int swaps = 0;
9     while (i < x && j < y) {
10        if (left[i] <= right[j]) {
11            v[k++] = left[i++];
12        } else {
13            v[k++] = right[j++];
14            swaps += (x - i);
15        }
16    }
17    while (i < x) v[k++] = left[i++];
18    while (j < y) v[k++] = right[j++];
19    return swaps;
20 }
21
22 int mergeSort(vector<int>& v, int l, int r) {
23     int swaps = 0;
24     if (l < r) {
25         int m = l + (r - l) / 2;
26         swaps += mergeSort(v, l, m);
27         swaps += mergeSort(v, m + 1, r);
28         swaps += mergeAndCount(v, l, m, r);
29     }
30     return swaps;
31 }

```

2 Stress

2.1 Gen

```

1 // pre-compilar os headers:
2 // compilar template com g++ -H e procurar onde esta stdc++.h
3 // criar a pasta bits e incluir com "" ou inves de <
4 // compilar stress com: g++ -pipe -O3 -flto -march=native -
5 // mtune=native gen.cpp
6 // faz bastante diferena no runtime
7
8 #include <bits/stdc++.h>
9 #include <cstdlib>
10 #include <ctime>
11 using namespace std;
12
13 int randi(int L, int R) { return L + rand() % (R - L + 1); }
14 char randc(char L, char R) { return char(L + rand() % (R - L
15     + 1)); }
16
17 int main(int argc, char** argv) {
18     if (argc > 1) srand(atoi(argv[1]));
19     else srand(time(0));
20
21     int n = randi(1, 100);
22     cout << n << '\n';
23     for (int i = 0; i < n; i++) {
24         cout << randi(-10, 20) << ' ';
25     }
26     cout << '\n';
27 }
28
29 /*
30 script.sh
31
32 g++ -std=c++17 -O2 -o sol sol.cpp
33 g++ -std=c++17 -O2 -o brute brute.cpp
34 g++ -std=c++17 -O2 -o gen gen.cpp
35
36 for ((i = 1; ; i++)); do
37     ./gen $i > in.txt
38     ./sol < in.txt > out1.txt
39     ./brute < in.txt > out2.txt
40
41     if ! diff -q out1.txt out2.txt > /dev/null; then
42         echo "Mismatch found on test $i"
43         cat in.txt
44         echo "Your output:"
45         cat out1.txt
46         echo "Brute output:"
47         cat out2.txt
48         break
49     fi
50     echo "Test $i passed"
51 done
52
53 */

```

3 Geometry

3.1 Lattice Points

```

1 ll gcd(ll a, ll b) {
2     return b == 0 ? a : gcd(b, a % b);
3 }
4
5 ll area_triangulo(ll x1, ll y1, ll x2, ll y2, ll x3, ll y3) {
6     return abs(x1 * (y2 - y3) + x2 * (y3 - y1) + x3 * (y1 -
7         y2));
8 }
9
10 ll pontos_borda(ll x1, ll y1, ll x2, ll y2) {
11     return gcd(abs(x2 - x1), abs(y2 - y1));
12 }
13
14 int32_t main() {
15     ll x1, y1, x2, y2, x3, y3;
16     cin >> x1 >> y1;
17     cin >> x2 >> y2;
18     cin >> x3 >> y3;
19     ll area = area_triangulo(x1, y1, x2, y2, x3, y3);
20     ll tot_borda = pontos_borda(x1, y1, x2, y2) +
21         pontos_borda(x2, y2, x3, y3) + pontos_borda(x3, y3, x1,
22             y1);
23
24     ll ans = (area - tot_borda) / 2 + 1;
25     cout << ans << endl;
26
27     return 0;
28 }

```

3.2 Point Location

```

1
2 int32_t main(){
3     sws;
4
5     int t; cin >> t;
6
7     while(t--){
8
9         int x1, y1, x2, y2, x3, y3; cin >> x1 >> y1 >> x2 >>
            y2 >> x3 >> y3;
10
11         int deltax1 = (x1-x2), deltax1 = (y1-y2);
12
13         int compx = (x1-x3), compy = (y1-y3);
14
15         int ans = (deltax1*compy) - (compx*deltax1);
16
17         if(ans == 0){cout << "TOUCH\n"; continue;}
18         if(ans < 0){cout << "RIGHT\n"; continue;}
19         if(ans > 0){cout << "LEFT\n"; continue;}
20     }
21     return 0;
22 }

```

3.3 Convex Hull

```

1 #include <bits/stdc++.h>
2
3 using namespace std;
4 #define int long long
5 typedef int cod;
6
7 struct point
8 {
9     cod x,y;
10    point(cod x = 0, cod y = 0): x(x), y(y)
11    {}
12
13    double modulo()
14    {
15        return sqrt(x*x + y*y);
16    }
17
18    point operator+(point o)
19    {
20        return point(x+o.x, y+o.y);
21    }
22    point operator-(point o)
23    {
24        return point(x - o.x , y - o.y);
25    }
26    point operator*(cod t)
27    {
28        return point(x*t, y*t);
29    }
30    point operator/(cod t)
31    {
32        return point(x/t, y/t);
33    }
34
35    cod operator*(point o)
36    {
37        return x*o.x + y*o.y;
38    }
39    cod operator^(point o)
40    {
41        return x*o.y - y * o.x;
42    }
43    bool operator<(point o)
44    {
45        if( x != o.x) return x < o.x;
46        return y < o.y;
47    }
48
49 };
50
51 int ccw(point p1, point p2, point p3)
52 {
53     cod cross = (p2-p1) ^ (p3-p1);
54     if(cross == 0) return 0;
55     else if(cross < 0) return -1;
56     else return 1;
57 }

```

```

58
59 vector <point> convex_hull(vector<point> p)
60 {
61     sort(p.begin(), p.end());
62     vector<point> L,U;
63
64     //Lower
65     for(auto pp : p)
66     {
67         while(L.size() >= 2 and ccw(L[L.size()-2], L.back(),
68             , pp) == -1)
69         {
70             // ÃT -1 pq eu nÃo quero excluir os colineares
71             L.pop_back();
72         }
73         L.push_back(pp);
74     }
75     reverse(p.begin(), p.end());
76
77     //Upper
78     for(auto pp : p)
79     {
80         while(U.size() >= 2 and ccw(U[U.size()-2], U.back(),
81             pp) == -1)
82         {
83             U.pop_back();
84         }
85         U.push_back(pp);
86     }
87     L.pop_back();
88     L.insert(L.end(), U.begin(), U.end()-1);
89     return L;
90 }
91
92 cod area(vector<point> v)
93 {
94     int ans = 0;
95     int aux = (int)v.size();
96     for(int i = 2; i < aux; i++)
97     {
98         ans += ((v[i] - v[0])^(v[i-1] - v[0]))/2;
99     }
100    ans = abs(ans);
101    return ans;
102 }
103
104 int bound(point p1 , point p2)
105 {
106     return __gcd(abs(p1.x-p2.x), abs(p1.y-p2.y));
107 }
108 //teorema de pick [pontos = A - (bound+points)/2 + 1]
109
110 int32_t main()
111 {
112
113     int n;
114     cin >> n;
115
116     vector<point> v(n);
117     for(int i = 0; i < n; i++)
118     {
119         cin >> v[i].x >> v[i].y;
120     }
121
122     vector <point> ch = convex_hull(v);
123
124     cout << ch.size() << '\n';
125     for(auto p : ch) cout << p.x << " " << p.y << "\n";
126
127     return 0;
128 }

```

3.4 Point

```

1 template<class T>
2 struct Point {
3     typedef Point P;
4     T x, y;
5     explicit Point(T x=0, T y=0) : x(x), y(y) {}
6     bool operator<(P p) const { return tie(x,y) < tie(p.x,p.y)
7     }; }
8     bool operator==(P p) const { return tie(x,y)==tie(p.x,p.y)
9     }; }

```

```

8   P operator+(P p) const { return P(x+p.x, y+p.y); }
9   P operator-(P p) const { return P(x-p.x, y-p.y); }
10  P operator*(T d) const { return P(x*d, y*d); }
11  P operator/(T d) const { return P(x/d, y/d); }
12  T operator^(P p) const { return x*p.y - y*p.x; }
13  T dot(P p) const { return x*p.x + y*p.y; }
14  T cross(P p) const { return x*p.y - y*p.x; }
15  T cross(P a, P b) const { return (a-*this).cross(b-*this); }
16  T dist2() const { return x*x + y*y; }
17  double dist() const { return sqrt((double)dist2()); }
18
19  T orient(P a, P b, P c) {return (b-a)^(c-a);}
20
21  // angle to x-axis in interval [-pi, pi]
22  double angle() const { return atan2(y, x); }
23  P unit() const { return *this/dist(); } // makes dist()=1
24  P perp() const { return P(-y, x); } // rotates +90
    degrees
25  P normal() const { return perp().unit(); }
26  // returns point rotated 'a' radians ccw around the
    origin
27  P rotate(double a) const {
28      return P(x*cos(a)-y*sin(a),x*sin(a)+y*cos(a)); }
29      friend ostream& operator<<(ostream& os, P p) {
30          return os << "(" << p.x << ", " << p.y << ")"; }
31
32  // inside the disk of diameter [a, b]
33  bool inDisk(P a, P b, P p) {
34      return (a-p).dot(b-p) <= 0;
35  }
36
37  bool onSegment(P a, P b, P p) {
38      return orient(a,b,p) == 0 && inDisk(a,b,p);
39  }
40
41  bool properInter(P a, P b, P c, P d, P &ans) {
42      double oa = orient(c,d,a),
43             ob = orient(c,d,b),
44             oc = orient(a,b,c),
45             od = orient(a,b,d);
46      // Proper intersection exists iff opposite signs
47      if (oa*ob < 0 && oc*od < 0) {
48          P ans = (a*ob - b*oa) / (ob-oa);
49          return true;
50      }
51      return false;
52  }
53
54  set<P> inters(P a, P b, P c, P d) {
55      P out;
56      if (properInter(a,b,c,d,out)) return {out};
57      set<P> s;
58      if (onSegment(c,d,a)) s.insert(a);
59      if (onSegment(c,d,b)) s.insert(b);
60      if (onSegment(a,b,c)) s.insert(c);
61      if (onSegment(a,b,d)) s.insert(d);
62      return s;
63  }
64  };

```

3.5 Inside Polygon

```

1  // Convex O(logn)
2
3  bool insideT(point a, point b, point c, point e){
4      int x = ccw(a, b, e);
5      int y = ccw(b, c, e);
6      int z = ccw(c, a, e);
7      return !((x==1 or y==1 or z==1) and (x==-1 or y==-1 or z
    ==-1));
8  }
9
10 bool inside(vp &p, point e){ // ccw
11     int l=2, r=(int)p.size()-1;
12     while(l<r){
13         int mid = (l+r)/2;
14         if(ccw(p[0], p[mid], e) == 1)
15             l=mid+1;
16         else{
17             r=mid;
18         }
19     }
20     // bordo
21     // if(r==(int)p.size()-1 and ccw(p[0], p[r], e)==0)
    return false;

```

```

22 // if(r==2 and ccw(p[0], p[1], e)==0) return false;
23 // if(ccw(p[r], p[r-1], e)==0) return false;
24 return insideT(p[0], p[r-1], p[r], e);
25 }
26
27 // Any O(n)
28
29 int inside(vp &p, point pp){
30     // 1 - inside / 0 - boundary / -1 - outside
31     int n = p.size();
32     for(int i=0;i<n;i++){
33         int j = (i+1)%n;
34         if(line({p[i], p[j]}).inside_seg(pp))
35             return 0;
36     }
37     int inter = 0;
38     for(int i=0;i<n;i++){
39         int j = (i+1)%n;
40         if(p[i].x <= pp.x and pp.x < p[j].x and ccw(p[i], p[j],
    pp)==1)
41             inter++; // up
42         else if(p[j].x <= pp.x and pp.x < p[i].x and ccw(p[i],
    p[j], pp)==-1)
43             inter++; // down
44     }
45     if(inter%2==0) return -1; // outside
46     else return 1; // inside
47 }
48
49 }

```

4 DS

4.1 Bit

```

1 struct BIT {
2     int n;
3     vector<int> bit;
4     BIT(int n = 0): n(n), bit(n + 1, 0) {}
5     void add(int i, int delta) {
6         for(; i <= n; i += i & -i) bit[i] += delta;
7     }
8     int sum(int i) {
9         int r = 0;
10        for(; i > 0; i -= i & -i) r += bit[i];
11        return r;
12    }
13    int range_sum(int l, int r){
14        if (r < l) return 0;
15        return sum(r) - sum(l - 1);
16    }
17 };

```

4.2 Sparse Table

```

1 // 0-index, O(1)
2 struct SparseTable {
3     vector<vector<int>> st;
4     int max_log;
5     SparseTable(vector<int>& arr) {
6         int n = arr.size();
7         max_log = floor(log2(n)) + 1;
8         st.resize(n, vector<int>(max_log));
9         for (int i = 0; i < n; i++) {
10             st[i][0] = arr[i];
11         }
12         for (int j = 1; j < max_log; j++) {
13             for (int i = 0; i + (1 << j) <= n; i++) {
14                 st[i][j] = max(st[i][j - 1], st[i + (1 << (j
    - 1))][j - 1]);
15             }
16         }
17     }
18     int query(int L, int R) {
19         int tamanho = R - L + 1;
20         int k = floor(log2(tamanho));
21         return max(st[L][k], st[R - (1 << k) + 1][k]);
22     }
23 };

```

4.3 Min Queue

```

1 struct MinQueue {
2     deque<pair<int, int>> dq;
3     void push(int val, int idx) {
4         while (!dq.empty() && dq.back().first >= val) dq.
5             pop_back();
6         dq.emplace_back(val, idx);
7     }
8     void pop(int idx) {
9         if (!dq.empty() && dq.front().second == idx) {
10             dq.pop_front();
11         }
12     }
13     int get() {
14         return dq.front().first;
15     }
16     bool empty() {
17         return dq.empty();
18     }
19 };
20 /*
21 considerando janela de tamanho K
22 mq.push(v[i], i);
23 if (i >= k) {
24     mq.pop(i - k);
25 }
26 if (i >= k - 1) {
27     result.push_back(mq.get());
28 }
29 */

```

4.4 Segtree Iterativa

```

1 // Exemplo de uso:
2 // SegTree<int> st(vetor);
3 // range query e point update
4 template <typename T>
5 struct SegTree {
6     int n;
7     vector<T> tree;
8     T neutral_value = 0;
9     T combine(T a, T b) {
10         return a + b;
11     }
12
13     SegTree(const vector<T>& data) {
14         n = data.size();
15         tree.resize(2 * n, neutral_value);
16
17         for (int i = 0; i < n; i++)
18             tree[n + i] = data[i];
19
20         for (int i = n - 1; i > 0; --i)
21             tree[i] = combine(tree[i * 2], tree[i * 2 + 1]);
22     }
23
24     T query(int l, int r) {
25         T res_l = neutral_value, res_r = neutral_value;
26
27         for (l += n, r += n + 1; l < r; l >>= 1, r >>= 1) {
28             if (l & 1) res_l = combine(res_l, tree[l++]);
29             if (r & 1) res_r = combine(tree[--r], res_r);
30         }
31
32         return combine(res_l, res_r);
33     }
34
35     void update(int pos, T new_val) {
36         tree[pos += n] = new_val;
37         for (pos >>= 1; pos > 0; pos >>= 1)
38             tree[pos] = combine(tree[2 * pos], tree[2 * pos +
39

```

4.5 Merge Sort Tree

```

1 #define all(x) x.begin(), x.end()
2
3 struct MST {
4     int n;
5     vector<vector<int>> tree;
6     MST(vector<int> &a) {
7         n = a.size();
8         tree.resize(4 * n);
9         build(1, 0, n - 1, a);
10    }

```

```

11 void build(int x, int lx, int rx, vector<int> &a) {
12     if (lx == rx) {
13         tree[x] = { a[lx] };
14         return;
15     }
16     int mid = lx + (rx - lx) / 2;
17     build(2 * x, lx, mid, a);
18     build(2 * x + 1, mid + 1, rx, a);
19     auto &L = tree[2 * x], &R = tree[2 * x + 1];
20     tree[x].resize(L.size() + R.size());
21     merge(all(L), all(R), tree[x].begin());
22 }
23
24 int query(int x, int lx, int rx, int l, int r, int val) {
25     if (lx > r || rx < l) return 0;
26     if (lx >= l && rx <= r) {
27         auto &v = tree[x];
28         return lower_bound(all(v), val) - v.begin();
29     }
30     int mid = lx + (rx - lx) / 2;
31     return query(2 * x, lx, mid, l, r, val) + query(2 * x +
32         1, mid + 1, rx, l, r, val);
33 }
34
35 int query(int l, int r, int val) {
36     if (l > r) return 0;
37     return query(1, 0, n - 1, l, r, val);
38 }
39
40 /* mst.query(l, r, l) retorna quantos caras distintos no
41     range
42 map<int, int> last;
43 for (int i = 0; i < n; i++) {
44     if (last.count(a[i])) {
45         esq[i] = last[a[i]];
46     } else {
47         esq[i] = -1;
48     }
49     last[a[i]] = i;
50 }
51 MST mst(esq);
52 jogar vetor de ultima aparicao na seg
53 */

```

4.6 Seglazy Iterativa

```

1 template <typename T, typename L>
2 struct SegLazy {
3     int n, h;
4     vector<T> tree;
5     vector<L> lazy;
6     vector<bool> has_lazy;
7     vector<int> sz; // se len = pow2, remove e sz[p] = 1 << h
8         [p]
9
10    // --- Mudar aqui ---
11    const T T_neutral = LLONG_MAX;
12
13    inline T combine(T a, T b) {
14        return min(a, b);
15    }
16
17    inline T apply_lazy_to_node(T node, L delta, int len) {
18        return node + (T)delta;
19    }
20
21    inline L combine_lazy(L old_delta, L new_delta) {
22        return old_delta + new_delta;
23    }
24    // -----
25
26    SegLazy(const vector<T>& data) {
27        n = data.size();
28        h = 32 - __builtin_clz(n);
29        tree.assign(2 * n, T_neutral);
30        lazy.assign(n, L());
31        has_lazy.assign(n, false);
32        sz.assign(2 * n, 1);
33
34        for (int i = 0; i < n; i++) tree[n + i] = data[i];
35        for (int i = n - 1; i > 0; --i) {
36            tree[i] = combine(tree[i << 1], tree[i << 1 | 1]);
37
38            ;
39            sz[i] = sz[i << 1] + sz[i << 1 | 1];
40        }
41    }

```

```

40 inline void apply(int p, L v) {
41     tree[p] = apply_lazy_to_node(tree[p], v, sz[p]);
42     if (p < n) {
43         if (has_lazy[p]) lazy[p] = combine_lazy(lazy[p],
44 v);
45         else lazy[p] = v;
46         has_lazy[p] = true;
47     }
48 }
49 inline void build(int p) {
50     p += n;
51     while (p > 1) {
52         p >>= 1;
53         T res = combine(tree[p << 1], tree[p << 1 | 1]);
54         if (has_lazy[p]) tree[p] = apply_lazy_to_node(res,
55 lazy[p], sz[p]);
56         else tree[p] = res;
57     }
58 }
59 inline void push(int p) {
60     p += n;
61     for (int s = h; s > 0; --s) {
62         int i = p >> s;
63         if (has_lazy[i]) {
64             apply(i << 1, lazy[i]);
65             apply(i << 1 | 1, lazy[i]);
66             has_lazy[i] = false;
67         }
68     }
69 }
70 void update(int l, int r, L v) {
71     int l0 = l, r0 = r;
72     push(l); push(r);
73     for (l += n, r += n + 1; l < r; l >>= 1, r >>= 1) {
74         if (l & 1) apply(l++, v);
75         if (r & 1) apply(--r, v);
76     }
77     build(l0); build(r0);
78 }
79
80 T query(int l, int r) {
81     push(l); push(r);
82     T res_l = T_neutral, res_r = T_neutral;
83     for (l += n, r += n + 1; l < r; l >>= 1, r >>= 1) {
84         if (l & 1) res_l = combine(res_l, tree[l++]);
85         if (r & 1) res_r = combine(tree[--r], res_r);
86     }
87     return combine(res_l, res_r);
88 }
89
90 };

```

4.7 Psum 2d

```

1 vector<vector<int>> psum(h+1, vector<int>(w+1, 0));
2 for (int i=1; i<=h; i++){
3     for (int j=1; j<=w; j++){
4         cin >> psum[i][j];
5         psum[i][j] += psum[i-1][j]+psum[i][j-1]-psum[i-1][j
6         -1];
7     }
8 }
9 // retorna a psum2d do intervalo inclusivo [(a, b), (c, d)]
10 int retangulo(int a, int b, int c, int d){
11     c = min(c, h), d = min(d, w);
12     a = max(0LL, a-1), b = max(0LL, b-1);
13     return v[c][d]-v[a][d]-v[c][b]+v[a][b];

```

4.8 Bit2d

```

1 // 1-index
2 struct BIT2d {
3     int n, m;
4     vector<vector<int>> tree;
5     BIT2d(int n, int m) : n(n), m(m) {
6         tree.assign(n + 1, vector<int>(m + 1, 0));
7     }
8     void add(int y, int x, int delta) {
9         for (int i = y; i <= m; i += i & -i) {
10             for (int j = x; j <= m; j += j & -j) {
11                 tree[i][j] += delta;

```

```

12     }
13 }
14
15 int pref(int y, int x) {
16     int res = 0;
17     for (int i = y; i > 0; i -= i & -i) {
18         for (int j = x; j > 0; j -= j & -j) {
19             res += tree[i][j];
20         }
21     }
22     return res;
23 }
24 int query(int y1, int x1, int y2, int x2) {
25     return pref(y2, x2) - pref(y1 - 1, x2) - pref(y2, x1 - 1)
26     + pref(y1 - 1, x1 - 1);
27 };

```

4.9 Segtree Lazy

```

1 /*
2 Seg com double Lazy de soma e de set
3 tipo 1 - soma em range
4 tipo 2 - set em range
5 */
6 struct SegTree {
7     int n;
8     vector<int> v, tree;
9     vector<int> lazy_soma, lazy_set;
10     SegTree(vector<int> &a) : v(a), n(a.size()) {
11         tree.resize(4 * n);
12         lazy_soma.resize(4 * n, 0);
13         lazy_set.resize(4 * n, -1);
14         build(1, 0, n - 1);
15     };
16     void build(int x, int lx, int rx) {
17         if (lx == rx) {
18             tree[x] = v[lx];
19             return;
20         }
21         int mid = (lx + rx) / 2;
22         build(2 * x, lx, mid);
23         build(2 * x + 1, mid + 1, rx);
24         tree[x] = tree[2 * x] + tree[2 * x + 1];
25     }
26     void seta(int x, int lx, int rx, int val) {
27         tree[x] = val * (rx - lx + 1);
28         lazy_set[x] = val;
29         lazy_soma[x] = 0;
30     }
31     void soma(int x, int lx, int rx, int val) {
32         tree[x] += val * (rx - lx + 1);
33         if (lazy_set[x] != -1) {
34             lazy_set[x] += val;
35         } else {
36             lazy_soma[x] += val;
37         }
38     }
39     void push(int x, int lx, int rx) {
40         int mid = (lx + rx) / 2;
41         if (lazy_set[x] != -1) {
42             if (lx != rx) {
43                 seta(2 * x, lx, mid, lazy_set[x]);
44                 seta(2 * x + 1, mid + 1, rx, lazy_set[x]);
45             }
46             lazy_set[x] = -1;
47         }
48         if (lazy_soma[x] != 0) {
49             if (lx != rx) {
50                 soma(2 * x, lx, mid, lazy_soma[x]);
51                 soma(2 * x + 1, mid + 1, rx, lazy_soma[x]);
52             }
53             lazy_soma[x] = 0;
54         }
55     }
56     void update(int x, int lx, int rx, int l, int r, int val,
57 int type) {
58         push(x, lx, rx);
59         if (lx >= l && rx <= r) {
60             if (type == 1) soma(x, lx, rx, val);
61             else seta(x, lx, rx, val);
62             push(x, lx, rx);
63             return;
64         }
65         if (lx > r || rx < l) return;
66         int mid = (lx + rx) / 2;

```

```

66     update(2 * x, lx, mid, l, r, val, type);
67     update(2 * x + 1, mid + 1, rx, l, r, val, type);
68     tree[x] = tree[2 * x] + tree[2 * x + 1];
69 }
70 void update(int l, int r, int val, int type) {
71     update(1, 0, n - 1, l, r, val, type);
72 }
73 int query(int x, int lx, int rx, int l, int r) {
74     push(x, lx, rx);
75     if (lx >= l && rx <= r) return tree[x];
76     if (lx > r || rx < l) return 0;
77     int mid = (lx + rx) / 2;
78     return query(2 * x, lx, mid, l, r) + query(2 * x + 1, mid
79         + 1, rx, l, r);
80 }
81 int query(int l, int r) {
82     return query(1, 0, n - 1, l, r);
83 }

```

4.10 Seg Lazy Pa

```

1  /* Notas
2  PA eh da forma a0 (a) e razão (d)
3  na hora de propagar o lazy
4  aplica no no S = (a0 + (a0 + (n - 1) * d)) * n / 2 (
5  variante da soma total do no)
6  pros filhos, o da esquerda eh normal
7  lazy_a[esq] += lazy_a[x]
8  lazy_d[esq] += lazy_d[x]
9  pro da direita tem que mudar o a (que eh o elemento inicial
10  naquele no da direita)
11  lazy_a[dir] += a + len_esq * (d)
12  lazy_d[dir] += lazy_d[x]
13  */
14 int gauss(int n, int a, int d) {
15     // (a0 + an) * n / 2
16     if (n <= 0)
17         return 0;
18     return (a + (a + (n - 1) * d)) * n / 2;
19 }
20 struct SegTree {
21     int n;
22     vector<int> v, lazy_a, lazy_d, tree;
23     SegTree(vector<int> &a) : v(a), n(a.size()) {
24         tree.resize(4 * n);
25         lazy_a.resize(4 * n, 0);
26         lazy_d.resize(4 * n, 0);
27         build(1, 0, n - 1);
28     }
29     void build(int x, int lx, int rx) {
30         if (lx == rx) {
31             tree[x] = v[lx];
32             return;
33         }
34         int mid = (lx + rx) / 2;
35         build(2 * x, lx, mid);
36         build(2 * x + 1, mid + 1, rx);
37         tree[x] = tree[2 * x] + tree[2 * x + 1];
38     }
39     int query(int x, int lx, int rx, int l, int r) {
40         push(x, lx, rx);
41         if (lx >= l && rx <= r)
42             return tree[x];
43         if (lx > r || rx < l)
44             return 0;
45         int mid = (lx + rx) / 2;
46         return query(2 * x, lx, mid, l, r) + query(2 * x + 1, mid
47             + 1, rx, l, r);
48     }
49     int query(int l, int r) {
50         return query(1, 0, n - 1, l, r);
51     }
52     void push(int x, int lx, int rx) {
53         if (lazy_a[x] && lazy_d[x]) {
54             int tam = rx - lx + 1;
55             tree[x] += gauss(tam, lazy_a[x], lazy_d[x]);
56             if (lx != rx) {
57                 int mid = (lx + rx) / 2;
58                 int tam_esq = mid - lx + 1;
59                 lazy_a[2 * x] += lazy_a[x];
60                 lazy_d[2 * x] += lazy_d[x];
61                 lazy_a[2 * x + 1] += (lazy_a[x] + tam_esq * lazy_d[x]

```

```

62             lazy_d[2 * x + 1] += lazy_d[x];
63         }
64         lazy_a[x] = lazy_d[x] = 0;
65     }
66     void update(int x, int lx, int rx, int l, int r, int a, int
67         d) {
68         push(x, lx, rx);
69         if (lx >= l && rx <= r) {
70             lazy_a[x] += a + (lx - l) * d;
71             lazy_d[x] += d;
72             push(x, lx, rx);
73             return;
74         }
75         if (lx > r || rx < l)
76             return;
77         int mid = (lx + rx) / 2;
78         update(2 * x, lx, mid, l, r, a, d);
79         update(2 * x + 1, mid + 1, rx, l, r, a, d);
80         tree[x] = tree[2 * x] + tree[2 * x + 1];
81     }
82     void update(int l, int r, int a, int d) {
83         update(1, 0, n - 1, l, r, a, d);
84     }

```

4.11 Trie Bits

```

1  int trie[MAXN][2];
2  int cnt[MAXN][2];
3  int cur_node = 0;
4
5  void insere(int x) {
6      int node = 0;
7      for (int i = 29; ~i; i--) {
8          int bit = (1ll << i) & x ? 1 : 0;
9          if (trie[node][bit] == 0) trie[node][bit] = ++
10             cur_node;
11             cnt[node][bit]++;
12             node = trie[node][bit];
13     }
14
15     int query(int x) {
16         int r = 0;
17         int node = 0;
18         for (int i = 29; ~i; i--) {
19             int bit = (x >> i) & 1;
20             if (trie[node][bit ^ 1] != 0 && cnt[node][bit ^ 1] >
21                 0) {
22                 r |= (1ll << i);
23                 node = trie[node][bit ^ 1];
24             } else {
25                 node = trie[node][bit];
26             }
27         }
28         return r;

```

4.12 Segtree2d

```

1  // 0 index
2  struct SegTree2d {
3      int n;
4      vector<vector<int>> tree;
5      SegTree2d(int n) : n(n) {
6          tree.assign(4 * n, vector<int>(4 * n, 0));
7      }
8      void update_x(int no_y, int no_x, int lx, int rx, int x,
9          int val, bool folha_y) {
10         if (lx == rx) {
11             if (folha_y) tree[no_y][no_x] = val;
12             else tree[no_y][no_x] = tree[2 * no_y][no_x] + tree[2 *
13                 no_y + 1][no_x];
14             return;
15         }
16         int mid = (lx + rx) / 2;
17         if (x <= mid) update_x(no_y, 2 * no_x, lx, mid, x, val,
18             folha_y);
19         else update_x(no_y, 2 * no_x + 1, mid + 1, rx, x, val,
20             folha_y);
21         tree[no_y][no_x] = tree[no_y][2 * no_x] + tree[no_y][2 *
22             no_x + 1];

```

```

18 }
19 void update_y(int no_y, int ly, int ry, int y, int x, int
    val) {
20     if (ly == ry) {
21         update_x(no_y, 1, 0, n - 1, x, val, true);
22         return;
23     }
24     int mid = (ly + ry) / 2;
25     if (y <= mid) update_y(2 * no_y, ly, mid, y, x, val);
26     else update_y(2 * no_y + 1, mid + 1, ry, y, x, val);
27     update_x(no_y, 1, 0, n - 1, x, val, false);
28 }
29 int query_x(int no_y, int no_x, int lx, int rx, int x1, int
    x2) {
30     if (rx < x1 || lx > x2) return 0;
31     if (lx >= x1 && rx <= x2) return tree[no_y][no_x];
32     int mid = (lx + rx) / 2;
33     return query_x(no_y, 2 * no_x, lx, mid, x1, x2) + query_x(
        no_y, 2 * no_x + 1, mid + 1, rx, x1, x2);
34 }
35 int query_y(int no_y, int ly, int ry, int y1, int y2, int
    x1, int x2) {
36     if (ry < y1 || ly > y2) return 0;
37     if (ly >= y1 && ry <= y2) return query_x(no_y, 1, 0, n -
        1, x1, x2);
38     int mid = (ly + ry) / 2;
39     return query_y(2 * no_y, ly, mid, y1, y2, x1, x2) +
        query_y(2 * no_y + 1, mid + 1, ry, y1, y2, x1, x2);
40 }
41 void update(int y, int x, int val) {
42     update_y(1, 0, n - 1, y, x, val);
43 }
44 int query(int y1, int x1, int y2, int x2) {
45     return query_y(1, 0, n - 1, y1, y2, x1, x2);
46 }
47 };

```

4.13 Dsu

```

1 struct DSU {
2     vector<int> parent, size;
3     int C;
4     DSU(int n) : parent(n + 1), size(n + 1), C(n) {
5         for (int i = 1; i <= n; i++) {
6             parent[i] = i;
7             size[i] = 1;
8         }
9     }
10    int find(int a) {
11        if (parent[a] == a) return a;
12        return parent[a] = find(parent[a]);
13    }
14    int same(int a, int b) {
15        return find(a) == find(b);
16    }
17    int get_size(int a) {
18        return size[find(a)];
19    }
20    int count() {
21        return C;
22    }
23    void join(int a, int b) {
24        int pA = find(a);
25        int pB = find(b);
26        if (pA != pB) {
27            C--;
28            if (size[pA] > size[pB]) {
29                swap(pA, pB);
30            }
31            parent[pA] = pB;
32            size[pB] += size[pA];
33        }
34    }
35 };

```

4.14 Ordered Set E Map

```

1
2 #include<ext/pb_ds/assoc_container.hpp>
3 #include<ext/pb_ds/tree_policy.hpp>
4 using namespace __gnu_pbds;
5 using namespace std;
6

```

```

7 template<typename T> using ordered_multiset = tree<T,
    null_type, less_equal<T>, rb_tree_tag,
    tree_order_statistics_node_update>;
8 template <typename T> using o_set = tree<T, null_type, less<T
    >, rb_tree_tag, tree_order_statistics_node_update>;
9 template <typename T, typename R> using o_map = tree<T, R,
    less<T>, rb_tree_tag, tree_order_statistics_node_update
    >;
10
11 int main() {
12     int i, j, k, n, m;
13     o_set<int> st;
14     st.insert(1);
15     st.insert(2);
16     cout << *st.find_by_order(0) << endl; /// k-esimo elemento
17     cout << st.order_of_key(2) << endl; ///numero de elementos
        menores que k
18     o_map<int, int> mp;
19     mp.insert({1, 10});
20     mp.insert({2, 20});
21     cout << mp.find_by_order(0)->second << endl; /// k-esimo
        elemento
22     cout << mp.order_of_key(2) << endl; /// numero de elementos
        (chave) menores que k
23     return 0;
24 }

```

4.15 Maximum Subarray Sum Range

```

1 struct SegTree {
2     int n;
3     vector<array<int, 4>> tree;
4     vector<int> v;
5     SegTree(vector<int> &a) : v(a), n(a.size()) {
6         tree.resize(4 * n);
7         build(1, 0, n - 1);
8     }
9     void build(int x, int lx, int rx) {
10        if (lx == rx) {
11            tree[x] = { v[lx], v[lx], v[lx], v[lx] };
12            return;
13        }
14        int mid = lx + (rx - lx) / 2;
15        build(2 * x, lx, mid);
16        build(2 * x + 1, mid + 1, rx);
17        tree[x] = combine(tree[2 * x], tree[2 * x + 1]);
18    }
19    array<int, 4> query(int x, int lx, int rx, int l, int r) {
20        if (lx >= l && rx <= r)
21            return tree[x];
22        if (lx > r || rx < l)
23            return { 0, LINF, LINF, LINF };
24        int mid = lx + (rx - lx) / 2;
25        return combine(query(2 * x, lx, mid, l, r), query(2 * x +
            1, mid + 1, rx, l, r));
26    };
27    int query(int l, int r) {
28        return max(0ll, query(1, 0, n - 1, l, r)[3]);
29    }
30    void update(int x, int lx, int rx, int pos, int val) {
31        if (lx == rx) {
32            tree[x] = { val, val, val, val };
33            return;
34        }
35        int mid = lx + (rx - lx) / 2;
36        if (pos <= mid)
37            update(2 * x, lx, mid, pos, val);
38        else
39            update(2 * x + 1, mid + 1, rx, pos, val);
40        tree[x] = combine(tree[2 * x], tree[2 * x + 1]);
41    }
42    void update(int pos, int val) {
43        update(1, 0, n - 1, pos, val);
44    }
45    array<int, 4> combine(array<int, 4> x, array<int, 4> y) {
46        return {
47            x[0] + y[0],
48            max(x[1], x[0] + y[1]),
49            max(y[2], y[0] + x[2]),
50            max({x[3], y[3], x[2] + y[1]})
51        };
52    }

```


5 General

5.1 Mex

```

1 struct MEX {
2     map<int, int> f;
3     set<int> falta;
4     int tam;
5     MEX(int n) : tam(n) {
6         for (int i = 0; i <= n; i++) falta.insert(i);
7     }
8     void add(int x) {
9         f[x]++;
10        if (f[x] == 1 && x >= 0 && x <= tam) {
11            falta.erase(x);
12        }
13    }
14    void rem(int x) {
15        if (f.count(x) && f[x] > 0) {
16            f[x]--;
17            if (f[x] == 0 && x >= 0 && x <= tam) {
18                falta.insert(x);
19            }
20        }
21    }
22    int get() {
23        if (falta.empty()) return tam + 1;
24        return *falta.begin();
25    }
26 };

```

5.2 Bitwise

```

1 int check_kth_bit(int x, int k) {
2     return (x >> k) & 1;
3 }
4
5 void print_on_bits(int x) {
6     for (int k = 0; k < 32; k++) {
7         if (check_kth_bit(x, k)) {
8             cout << k << ' ';
9         }
10    }
11    cout << '\n';
12 }
13
14 int count_on_bits(int x) {
15     int ans = 0;
16     for (int k = 0; k < 32; k++) {
17         if (check_kth_bit(x, k)) {
18             ans++;
19         }
20    }
21    return ans;
22 }
23
24 bool is_even(int x) {
25     return ((x & 1) == 0);
26 }
27
28 int set_kth_bit(int x, int k) {
29     return x | (1 << k);
30 }
31
32 int unset_kth_bit(int x, int k) {
33     return x & ~(1 << k);
34 }
35
36 int toggle_kth_bit(int x, int k) {
37     return x ^ (1 << k);
38 }
39
40 bool check_power_of_2(int x) {
41     return count_on_bits(x) == 1;
42 }

```

5.3 Debug

```

1 template<typename T, typename U>
2 ostream& operator<<(ostream& os, const pair<T, U>& p) {
3     return os << "(" << p.first << ", " << p.second << ")";
4 }
5

```

```

6 template<typename T, typename = decltype(begin(declval<T>()))
7     , typename = enable_if_t<!is_same_v<T, string>>>
8     ostream& operator<<(ostream& os, const T& v) {
9         os << "{";
10        string sep;
11        for (const auto& x : v) os << sep << x, sep = ", ";
12        return os << "}";
13 }
14
15 #define db(x...) cout << "[" << #x << "]: ", [(auto... $){
16     ((cout << $ << "; ", ...); }(x), cout << '\n'

```

5.4 Count Permutations

```

1 // Returns the number of distinct permutations
2 // that are lexicographically less than the string t
3 // using the provided frequency (freq) of the characters
4 // 0(n*freq.size())
5 int countPermLess(vector<int> freq, const string &t) {
6     int n = t.size();
7     int ans = 0;
8
9     vector<int> fact(n + 1, 1), invfact(n + 1, 1);
10    for (int i = 1; i <= n; i++)
11        fact[i] = (fact[i - 1] * i) % MOD;
12    invfact[n] = fexp(fact[n], MOD - 2, MOD);
13    for (int i = n - 1; i >= 0; i--)
14        invfact[i] = (invfact[i + 1] * (i + 1)) % MOD;
15
16    // For each position in t, try placing a letter smaller
17    // than t[i] that is in freq
18    for (int i = 0; i < n; i++) {
19        for (char c = 'a'; c < t[i]; c++) {
20            if (freq[c - 'a'] > 0) {
21                freq[c - 'a']--;
22                int ways = fact[n - i - 1];
23                for (int f : freq)
24                    ways = (ways * invfact[f]) % MOD;
25                ans = (ans + ways) % MOD;
26                freq[c - 'a']++;
27            }
28            if (freq[t[i] - 'a'] == 0) break;
29            freq[t[i] - 'a']--;
30        }
31    }
32    return ans;
33 }

```

5.5 Brute Choose

```

1 vector<int> elements;
2 int N, K;
3 vector<int> comb;
4
5 void brute_choose(int i) {
6     if (comb.size() == K) {
7         for (int j = 0; j < comb.size(); j++) {
8             cout << comb[j] << ' ';
9         }
10        cout << '\n';
11        return;
12    }
13    if (i == N) return;
14    int r = N - i;
15    int preciso = K - comb.size();
16    if (r < preciso) return;
17    comb.push_back(elements[i]);
18    brute_choose(i + 1);
19    comb.pop_back();
20    brute_choose(i + 1);
21 }

```

5.6 Struct

```

1 struct Pessoa{
2     // Atributos
3     string nome;
4     int idade;
5
6     // Comparador
7     bool operator<(const Pessoa& other) const{
8         if(idade != other.idade) return idade > other.idade;
9         else return nome > other.nome;
10    }
11 }

```

6 String

6.1 Trie

```

1 // Trie por array
2 int trie[MAXN][26];
3 int tot_nos = 0;
4 vector<bool> acaba(MAXN, false);
5 vector<int> contador(MAXN, 0);
6
7 void insere(string s) {
8     int no = 0;
9     for(auto &c : s) {
10         if(trie[no][c - 'a'] == 0) {
11             trie[no][c - 'a'] = ++tot_nos;
12         }
13         no = trie[no][c - 'a'];
14         contador[no]++;
15     }
16     acaba[no] = true;
17 }
18
19 bool busca(string s) {
20     int no = 0;
21     for(auto &c : s) {
22         if(trie[no][c - 'a'] == 0) {
23             return false;
24         }
25         no = trie[no][c - 'a'];
26     }
27     return acaba[no];
28 }
29
30 int isPref(string s) {
31     int no = 0;
32     for(auto &c : s) {
33         if(trie[no][c - 'a'] == 0) {
34             return -1;
35         }
36         no = trie[no][c - 'a'];
37     }
38     return contador[no];
39 }

```

6.2 Z Function

```

1 vector<int> z_function(string s) {
2     int n = s.size();
3     vector<int> z(n);
4     int l = 0, r = 0;
5     for(int i = 1; i < n; i++) {
6         if(i < r) {
7             z[i] = min(r - i, z[i - l]);
8         }
9         while(i + z[i] < n && s[z[i]] == s[i + z[i]]) {
10             z[i]++;
11         }
12         if(i + z[i] > r) {
13             l = i;
14             r = i + z[i];
15         }
16     }
17     return z;
18 }

```

6.3 Kmp

```

1 vector<int> kmp(string &s) {
2     int m = s.size();
3     vector<int> lsp(m, 0);
4     for (int i = 1, j = 0; i < m; i++) {
5         while (j > 0 && s[j] != s[i]) j = lsp[j - 1];
6         if (s[i] == s[j]) j++;
7         lsp[i] = j;
8     }
9     return lsp;
10 }

```

6.4 Hashing

```

1 // String Hash template
2 // constructor(s) - 0(|s|)

```

```

3 // query(l, r) - returns the hash of the range [l,r] from
4 // left to right - 0(1)
5 // query_inv(l, r) from right to left - 0(1)
6 // patrocinado por tiagodfs
7 mt19937 rng(time(nullptr));
8
9 struct Hash {
10     const int X = rng();
11     const int MOD = 1e9+7;
12     int n; string s;
13     vector<int> h, hi, p;
14     Hash() {}
15     Hash(string s): s(s), n(s.size()), h(n), hi(n), p(n) {
16         for (int i=0;i<n;i++) p[i] = (i ? X*p[i-1]:1) % MOD;
17         for (int i=0;i<n;i++)
18             h[i] = (s[i] + (i ? h[i-1]:0) * X) % MOD;
19         for (int i=n-1;i>=0;i--)
20             hi[i] = (s[i] + (i+1<n ? hi[i+1]:0) * X) % MOD;
21     }
22     int query(int l, int r) {
23         int hash = (h[r] - (l ? h[l-1]*p[r-l+1]%MOD : 0));
24         return hash < 0 ? hash + MOD : hash;
25     }
26     int query_inv(int l, int r) {
27         int hash = (hi[l] - (r+1 < n ? hi[r+1]*p[r-l+1] % MOD
28             : 0));
29         return hash < 0 ? hash + MOD : hash;
30     }
31 };

```

7 Math

7.1 Soma Pg Mod

```

1 // 1 + r + r^2 + r^3 + ... r^n (mod m)
2 // 0(log(N)) funciona com qualquer m
3 // retorna {soma, r^n mod m}
4 array<int, 2> soma_pg(int r, int n, int m) {
5     if (n == 0) return {0, 1};
6
7     auto [mid, p] = soma_pg(r, n / 2, m);
8
9     int sum = (mid*p % m + mid) % m;
10    int np = p*p % m; // r^n
11
12    if (n&1) {
13        sum = (sum*r + 1) % m;
14        np = np*r % m;
15    }
16
17    return {sum, np};
18 }

```

7.2 Fexp

```

1 // a^e mod m
2 // 0(log n)
3
4 int fexp(int a, int e, int m) {
5     a %= m;
6     int ans = 1;
7     while (e > 0) {
8         if (e & 1) ans = ans*a % m;
9         a = a*a % m;
10        e /= 2;
11    }
12    return ans%m;
13 }

```

7.3 Base Calc

```

1 int char_to_val(char c) {
2     if (c >= '0' && c <= '9') return c - '0';
3     else return c - 'A' + 10;
4 }
5
6 char val_to_char(int val) {
7     if (val >= 0 && val <= 9) return val + '0';
8     else return val - 10 + 'A';
9 }
10

```

```

11 int to_base_10(string &num, int bfrom) {
12     int result = 0;
13     int pot = 1;
14     for (int i = num.size() - 1; i >= 0; i--) {
15         if (char_to_val(num[i]) >= bfrom) return -1;
16         result += char_to_val(num[i]) * pot;
17         pot *= bfrom;
18     }
19     return result;
20 }
21
22 string from_base_10(int n, int bto) {
23     if (n == 0) return "0";
24     string result = "";
25     while (n > 0) {
26         result += val_to_char(n % bto);
27         n /= bto;
28     }
29     reverse(result.begin(), result.end());
30     return result;
31 }
32
33 string convert_base(string &num, int bfrom, int bto) {
34     int n_base_10 = to_base_10(num, bfrom);
35     return from_base_10(n_base_10, bto);
36 }

```

7.4 Totient

```

1 // phi(n) = n * (1 - 1/p1) * (1 - 1/p2) * ...
2 int phi(int n) {
3     int result = n;
4     for (int i = 2; i * i <= n; i++) {
5         if (n % i == 0) {
6             while (n % i == 0)
7                 n /= i;
8             result -= result / i;
9         }
10    }
11    if (n > 1) // SE n sobrou, ele Ã um fator primo
12        result -= result / n;
13    return result;
14 }
15
16 // crivo phi
17 const int MAXN_PHI = 1000001;
18 int phiv[MAXN_PHI];
19 void phi_sieve() {
20     for (int i = 0; i < MAXN_PHI; i++) phiv[i] = i;
21     for (int i = 2; i < MAXN_PHI; i++) {
22         if (phiv[i] == i) {
23             for (int j = i; j < MAXN_PHI; j += i) phiv[j] -=
24                 phiv[j] / i;
25         }
26    }

```

7.5 Equacao Diofantina

```

1 int extended_gcd(int a, int b, int& x, int& y) {
2     if (a == 0) {
3         x = 0;
4         y = 1;
5         return b;
6     }
7     int x1, y1;
8     int gcd = extended_gcd(b % a, a, x1, y1);
9     x = y1 - (b / a) * x1;
10    y = x1;
11    return gcd;
12 }
13
14 bool solve(int a, int b, int c, int& x0, int& y0) {
15     int x, y;
16     int g = extended_gcd(abs(a), abs(b), x, y);
17     if (c % g != 0) {
18         return false;
19     }
20     x0 = x * (c / g);
21     y0 = y * (c / g);
22     if (a < 0) x0 = -x0;
23     if (b < 0) y0 = -y0;
24     return true;
25 }

```

7.6 Menor Fator Primo

```

1 const int MAXN = 2e6 + 2;
2 int spf[MAXN];
3 vector<int> primes;
4
5 void sieve() {
6     for (int i = 0; i < MAXN; i++) spf[i] = i;
7     for (int i = 2; i * i < MAXN; i++) {
8         if (spf[i] == i) {
9             for (int j = i * i; j < MAXN; j += i) {
10                 if (spf[j] == j) {
11                     spf[j] = i;
12                 }
13             }
14         }
15     }
16     for (int i = 2; i < MAXN; i++) {
17         if (spf[i] == i) {
18             primes.push_back(i);
19         }
20     }
21 }
22
23 map<int, int> factorize(int n) {
24     map<int, int> factors;
25     while (n > 1) {
26         factors[spf[n]]++;
27         n /= spf[n];
28     }
29     return factors;
30 }
31
32 int numero_de_divisores(int n) {
33     if (n == 1) return 1;
34     map<int, int> fatores = fatorar(n);
35     int nod = 1;
36     for (auto &[primo, expoente] : fatores) nod *= (expoente
37         + 1);
38     return nod;
39 }
40
41 // DEFINE INT LONG LONG
42 int soma_dos_divisores(int n) {
43     if (n == 1) return 1;
44     map<int, int> fatores = fatorar(n);
45     int sod = 1;
46     for (auto &[primo, expoente] : fatores) {
47         int termo_soma = 1;
48         int potencia_primo = 1;
49         for (int i = 0; i < expoente; i++) {
50             potencia_primo *= primo;
51             termo_soma += potencia_primo;
52         }
53         sod *= termo_soma;
54     }
55     return sod;
56 }

```

7.7 Exgcd

```

1 // 0 retorno da funcao eh {n, m, g}
2 // e significa que gcd(a, b) = g e
3 // n e m sao inteiros tais que an + bm = g
4 array<ll, 3> exgcd(int a, int b) {
5     if (b == 0) return {1, 0, a};
6     auto [m, n, g] = exgcd(b, a % b);
7     return {n, m - a / b * n, g};
8 }

```

7.8 Crivo

```

1 // O(n*log(log(n)))
2 bool composto[MAX]
3 for (int i = 1; i <= n; i++) {
4     if (composto[i]) continue;
5     for (int j = 2*i; j <= n; j += i)
6         composto[j] = 1;
7 }

```

7.9 Matrix

```

1 const int MOD = 1e9 + 7;
2
3 struct Matrix {
4     int N, M;
5     vector<vector<int>>> mat;
6     Matrix(int n, int m, bool I = false) : N(n), M(m) {
7         mat.assign(N, vector<int>(M, 0ll));
8         if (I) {
9             for (int i = 0; i < min(N, M); i++) {
10                 mat[i][i] = 1;
11             }
12         }
13     };
14     Matrix operator*(const Matrix &other) {
15         assert(M == other.N);
16         Matrix res(N, other.M);
17         for (int i = 0; i < N; i++) {
18             for (int k = 0; k < M; k++) {
19                 for (int j = 0; j < other.M; j++) {
20                     res.mat[i][j] = (res.mat[i][j] + mat[i][k]
21                                     * other.mat[k][j]) % MOD;
22                 }
23             }
24         }
25         return res;
26     }
27     Matrix exp(Matrix A, int B) {
28         assert(A.N == A.M);
29         Matrix res(A.N, A.M, true);
30         while (B) {
31             if (B & 1) res = res * A;
32             A = A * A;
33             B >>= 1;
34         }
35         return res;
36     };

```

7.10 Combinatorics

```

1 const int N = 200005;
2 const int MOD = 1e9 + 7;
3 // DEFINE INT LONG LONG PLMDS
4 int fat[N], fati[N];
5
6 // (a^b) % m em O(log b)
7 // coloque o fexp
8
9 int inv(int n) { return fexp(n, MOD - 2); }
10
11 void precalc() {
12     fat[0] = 1;
13     fati[0] = 1;
14     for (int i = 1; i < N; i++) fat[i] = (fat[i - 1] * i) %
15     MOD;
16     fati[N - 1] = inv(fat[N - 1]);
17     for (int i = N - 2; i >= 0; i--) fati[i] = (fati[i + 1] *
18     (i + 1)) % MOD;
19 }
20
21 int choose(int n, int k) {
22     if (k < 0 || k > n) return 0;
23     return (((fat[n] * fati[k]) % MOD) * fati[n - k]) % MOD;
24 }
25
26 // n! / (n-k)!
27 int perm(int n, int k) {
28     if (k < 0 || k > n) return 0;
29     return (fat[n] * fati[n - k]) % MOD;
30 }
31
32 // C_n = (1 / (n+1)) * C(2n, n)
33 int catalan(int n) {
34     if (n < 0 || 2 * n >= N) return 0;
35     int c2n_n = choose(2 * n, n);
36     return (c2n_n * inv(n + 1)) % MOD;

```

7.11 Divisores

```

1 // Retorna um vetor com os divisores de x
2 // eh preciso ter o crivo implementado
3 // 0(divisores)

```

```

4
5 vector<int> divs(int x){
6     vector<int> ans = {1};
7     vector<array<int, 2>> primos; // {primo, expoente}
8
9     while (x > 1) {
10         int p = crivo[x], cnt = 0;
11         while (x % p == 0) cnt++, x /= p;
12         primos.push_back({p, cnt});
13     }
14
15     for (int i=0; i<primos.size(); i++){
16         int cur = 1, len = ans.size();
17
18         for (int j=0; j<primos[i][1]; j++){
19             cur *= primos[i][0];
20             for (int k=0; k<len; k++){
21                 ans.push_back(cur*ans[k]);
22             }
23         }
24     }
25     return ans;
26 }

```

7.12 Segment Sieve

```

1 // Retorna quantos primos tem entre [l, r] (inclusivo)
2 // precisa de um vetor com os primos ate sqrt(r)
3 int seg_sieve(int l, int r){
4     if (l > r) return 0;
5     vector<bool> is_prime(r - l + 1, true);
6     if (l == 1) is_prime[0] = false;
7
8     for (int p : primos){
9         if (p * p > r) break;
10        int start = max(p * p, (l + p - 1) / p * p);
11        for (int j = start; j <= r; j += p){
12            if (j >= l) {
13                is_prime[j - l] = false;
14            }
15        }
16    }
17
18    return accumulate(all(is_prime), 0ll);
19 }

```

7.13 Discrete Log

```

1 // returns minimum x for which a^x = b (mod m), a and m are
2 // coprime.
3 // if the answer dont need to be greater than some value, the
4 // vector<int> can be removed
5 int discrete_log(int a, int b, int m) {
6     a %= m, b %= m;
7     int n = sqrt(m) + 1;
8
9     int an = 1;
10    for (int i = 0; i < n; ++i)
11        an = (an * 1ll * a) % m;
12
13    unordered_map<int, vector<int>> vals;
14    for (int q = 0, cur = b; q <= n; ++q) {
15        vals[cur].push_back(q);
16        cur = (cur * 1ll * a) % m;
17    }
18
19    int res = LLONG_MAX;
20
21    for (int p = 1, cur = 1; p <= n; ++p) {
22        cur = (cur * 1ll * an) % m;
23        if (vals.count(cur)) {
24            for (int q: vals[cur]){
25                int ans = n * p - q;
26                res = min(res, ans);
27            }
28        }
29    }
30    return res;
31 }

```

7.14 Mod Inverse

```

1 array<int, 2> extended_gcd(int a, int b) {

```

```

2     if (b == 0) return {1, 0};
3     auto [x, y] = extended_gcd(b, a % b);
4     return {y, x - (a / b) * y};
5 }
6
7 int mod_inverse(int a, int m) {
8     auto [x, y] = extended_gcd(a, m);
9     return (x % m + m) % m;
10 }

```

7.15 Fft

```

1 // multiplica dois polinomios em O(NlogN)
2
3 using cd = complex<double>;
4 const double PI = acos(-1);
5
6 void fft(vector<cd> &A, bool invert) {
7     int N = size(A);
8
9     for (int i = 1, j = 0; i < N; i++) {
10         int bit = N >> 1;
11         for (; j & bit; bit >>= 1)
12             j ^= bit;
13         j ^= bit;
14
15         if (i < j)
16             swap(A[i], A[j]);
17     }
18
19     for (int len = 2; len <= N; len <= 1) {
20         double ang = 2 * PI / len * (invert ? -1 : 1);
21         cd wlen(cos(ang), sin(ang));
22         for (int i = 0; i < N; i += len) {
23             cd w(1);
24             for (int j = 0; j < len/2; j++) {
25                 cd u = A[i+j], v = A[i+j+len/2] * w;
26                 A[i+j] = u + v;
27                 A[i+j+len/2] = u - v;
28                 w *= wlen;
29             }
30         }
31     }
32
33     if (invert) {
34         for (auto &x : A)
35             x /= N;
36     }
37 }
38
39 vector<int> multiply(vector<int> const& A, vector<int> const&
40 B) {
41     vector<cd> fa(begin(A), end(A)), fb(begin(B), end(B));
42     int N = 1;
43     while (N < size(A) + size(B))
44         N <= 1;
45     fa.resize(N);
46     fb.resize(N);
47
48     fft(fa, false);
49     fft(fb, false);
50     for (int i = 0; i < N; i++)
51         fa[i] *= fb[i];
52     fft(fa, true);
53
54     vector<int> result(N);
55     for (int i = 0; i < N; i++)
56         result[i] = round(fa[i].real());
57     return result;
58 }

```

8 Primitives

9 Graph

9.1 Min Cost Max Flow

```

1 // Encontra o menor custo para passar K de fluxo em um grafo
2 // com N vertices
3 // Funciona com multiplas arestas para o mesmo par de
4 // vertices

```

```

3 // Para encontrar o min cost max flow eh so fazer K =
4 // infinito
5 struct Edge {
6     int from, to, capacity, cost, id;
7 };
8
9 vector<vector<array<int, 2>>> adj;
10 vector<Edge> edges; // arestas pares sao as normais e suas
11 // reversas sao as impares
12
13 const int INF = LLONG_MAX;
14
15 void shortest_paths(int n, int v0, vector<int> &dist, vector<
16 int> &edge_to) {
17     dist.assign(n, INF);
18     dist[v0] = 0;
19     vector<bool> in_queue(n, false);
20     queue<int> q;
21     q.push(v0);
22     edge_to.assign(n, -1);
23
24     while (!q.empty()) {
25         int u = q.front();
26         q.pop();
27         in_queue[u] = false;
28         for (auto [v, id] : adj[u]) {
29             if (edges[id].capacity > 0 && dist[v] > dist[u] +
30 edges[id].cost) {
31                 dist[v] = dist[u] + edges[id].cost;
32                 edge_to[v] = id;
33                 if (!in_queue[v]) {
34                     in_queue[v] = true;
35                     q.push(v);
36                 }
37             }
38         }
39     }
40 }
41
42 void add_edge(int from, int to, int capacity, int cost) {
43     edges.push_back({from, to, capacity, cost, (int)edges.
44 size()});
45     edges.push_back({to, from, 0, -cost, (int)edges.size()});
46     // reversa
47 }
48
49 int min_cost_flow(int N, int K, int s, int t) {
50     adj.assign(N, vector<array<int, 2>>());
51
52     for (Edge e : edges) {
53         adj[e.from].push_back({e.to, e.id});
54     }
55
56     int flow = 0;
57     int cost = 0;
58     vector<int> dist, edge_to;
59     while (flow < K) {
60         shortest_paths(N, s, dist, edge_to);
61         if (dist[t] == INF)
62             break;
63
64         // find max flow on that path
65         int f = K - flow;
66         int cur = t;
67         while (cur != s) {
68             f = min(f, edges[edge_to[cur]].capacity);
69             cur = edges[edge_to[cur]].from;
70         }
71
72         // apply flow
73         flow += f;
74         cost += f * dist[t];
75         cur = t;
76         while (cur != s) {
77             int edge = edge_to[cur];
78             int rev_edge = edge^1;
79
80             edges[edge].capacity -= f;
81             edges[rev_edge].capacity += f;
82             cur = edges[edge].from;
83         }
84     }
85
86     if (flow < K)
87         return -1;
88 }

```

```

83     else
84         return cost;
85 }

```

9.2 Floyd Warshall

```

1 // SSP e acha ciclos.
2 // Bom com constraints menores.
3 // O(n^3)
4
5 int dist[501][501];
6
7 void floydWarshall() {
8     for(int k = 0; k < n; k++) {
9         for(int i = 0; i < n; i++) {
10            for(int j = 0; j < n; j++) {
11                dist[i][j] = min(dist[i][j], dist[i][k] +
12                                dist[k][j]);
13            }
14        }
15    }
16    void solve() {
17        int m, q;
18        cin >> n >> m >> q;
19        for(int i = 0; i < n; i++) {
20            for(int j = i; j < n; j++) {
21                if(i == j) {
22                    dist[i][j] = dist[j][i] = 0;
23                } else {
24                    dist[i][j] = dist[j][i] = linf;
25                }
26            }
27        }
28        for(int i = 0; i < m; i++) {
29            int u, v, w;
30            cin >> u >> v >> w; u--; v--;
31            dist[u][v] = min(dist[u][v], w);
32            dist[v][u] = min(dist[v][u], w);
33        }
34        floydWarshall();
35        while(q--) {
36            int u, v;
37            cin >> u >> v; u--; v--;
38            if(dist[u][v] == linf) cout << -1 << '\n';
39            else cout << dist[u][v] << '\n';
40        }
41    }

```

9.3 Edmonds-karp

```

1 // Edmonds-Karp com scalling O(E*lg(F))
2
3 int n, m;
4 const int MAXN = 510;
5 vector<vector<int>> capacity(MAXN, vector<int>(MAXN, 0));
6 vector<vector<int>> adj(MAXN);
7
8 int bfs(int s, int t, int scale, vector<int>& parent) {
9     fill(parent.begin(), parent.end(), -1);
10    parent[s] = -2;
11    queue<pair<int, int>> q;
12    q.push({s, LLONG_MAX});
13
14    while (!q.empty()) {
15        int cur = q.front().first;
16        int flow = q.front().second;
17        q.pop();
18
19        for (int next : adj[cur]) {
20            if (parent[next] == -1 && capacity[cur][next] >=
21                scale) {
22                parent[next] = cur;
23                int new_flow = min(flow, capacity[cur][next]);
24                q.push({next, new_flow});
25            }
26        }
27    }
28    return 0;
29
30    return 0;
31 }

```

```

32
33 int maxflow(int s, int t) {
34     int flow = 0;
35     vector<int> parent(MAXN);
36     int new_flow;
37     int scalling = 1ll << 62;
38
39     while (scalling > 0) {
40         while (new_flow = bfs(s, t, scalling, parent)){
41             if (new_flow == 0) continue;
42             flow += new_flow;
43             int cur = t;
44             while (cur != s) {
45                 int prev = parent[cur];
46                 capacity[prev][cur] -= new_flow;
47                 capacity[cur][prev] += new_flow;
48                 cur = prev;
49             }
50         }
51         scalling /= 2;
52     }
53
54     return flow;
55 }

```

9.4 Lca Jc

```

1 const int MAXN = 200005;
2 int N;
3 int LOG;
4
5 vector<vector<int>> adj;
6 vector<int> profundidade;
7 vector<vector<int>> cima; // cima[v][j] eh o 2^j-esimo
8                          // ancestral de v
9
10 void dfs(int v, int p, int d) {
11     profundidade[v] = d;
12     cima[v][0] = p; // o pai direto eh o 2^0-ésimo ancestral
13     for (int j = 1; j < LOG; j++) {
14         // se o ancestral 2^(j-1) existir, calculamos o 2^j
15         if (cima[v][j-1] != -1) {
16             cima[v][j] = cima[cima[v][j-1]][j-1];
17         } else {
18             cima[v][j] = -1; // nao tem ancestral superior
19         }
20     }
21     for (int nei : adj[v]) {
22         if (nei != p) {
23             dfs(nei, v, d + 1);
24         }
25     }
26 }
27
28 void build(int root) {
29     LOG = ceil(log2(N));
30     profundidade.assign(N + 1, 0);
31     cima.assign(N + 1, vector<int>(LOG, -1));
32     dfs(root, -1, 0);
33 }
34
35 int get_lca(int a, int b) {
36     if (profundidade[a] < profundidade[b]) {
37         swap(a, b);
38     }
39     // sobe 'a' ate a mesma profundidade de 'b'
40     for (int j = LOG - 1; j >= 0; j--) {
41         if (profundidade[a] - (1 << j) >= profundidade[b]) {
42             a = cima[a][j];
43         }
44     }
45     // se 'b' era um ancestral de 'a', entao 'a' agora e
46     // igual a 'b'
47     if (a == b) {
48         return a;
49     }
50     // sobe os dois juntos ate encontrar os filhos do LCA
51     for (int j = LOG - 1; j >= 0; j--) {
52         if (cima[a][j] != -1 && cima[a][j] != cima[b][j]) {
53             a = cima[a][j];
54             b = cima[b][j];
55         }
56     }
57     return cima[a][0];
58 }

```

9.5 Diametro

```

1  /*
2  0(N + M), retorna cara mais distante, len
3  do caminho em arestas e os caras do caminho em um vetor
4  Para pegar o diametro da arvore, chamar duas vezes
5  auto [a, DA, PA] = calc(1);
6  auto [b, len_diametro, caminho_diametro] = calc(a);
7  */
8  auto calc = [&](int S) -> tuple<int, int, vector<int>> {
9      queue<pair<int, int>> q;
10     q.push({S, 0});
11     vector<int> dp(n + 1, -1), pai(n + 1, 0);
12     dp[S] = 0;
13     pai[S] = -1;
14     int longe = S;
15     int dist = 0;
16     while (!q.empty()){
17         auto [u, d] = q.front();
18         q.pop();
19         if (d > dist){
20             dist = d;
21             longe = u;
22         }
23         for (int v : adj[u]){
24             if (dp[v] == -1){
25                 dp[v] = d + 1;
26                 pai[v] = u;
27                 q.push({v, d + 1});
28             }
29         }
30     }
31     int cur = longe;
32     vector<int> caminho;
33     while (cur != -1){
34         caminho.push_back(cur);
35         cur = pai[cur];
36     }
37     return { longe, dist, caminho };
38 };

```

9.6 Eulerian Path

```

1  /**
2  * versao que assume: #define int long long
3  *
4  * Retorna um caminho/ciclo euleriano em um grafo (se existir
5  * - g: lista de adjacencia (vector<vector<int>>)).
6  * - directed: true se o grafo for dirigido.
7  * - s: vertice inicial.
8  * - e: vertice final (opcional). Se informado, tenta caminho
9  *   de s ate e.
10 * - 0(Nlog(N))
11 * Retorna vetor com a sequencia de vertices, ou vazio se
12 *   impossivel.
13 */
14 vector<int> eulerian_path(const vector<vector<int>>& g, bool
15     directed, int s, int e = -1) {
16     int n = (int)g.size();
17     // copia das adjacencias em multiset para permitir
18     // remoção especifica
19     vector<multiset<int>> h(n);
20     vector<int> in_degree(n, 0);
21     vector<int> result;
22     stack<int> st;
23     // preencher h e indegrees
24     for (int u = 0; u < n; ++u) {
25         for (auto v : g[u]) {
26             ++in_degree[v];
27             h[u].emplace(v);
28         }
29     }
30     st.emplace(s);
31     if (e != -1) {
32         int out_s = (int)h[s].size();
33         int out_e = (int)h[e].size();
34         int diff_s = in_degree[s] - out_s;
35         int diff_e = in_degree[e] - out_e;
36         if (diff_s * diff_e != -1) return {}; // impossivel
37     }
38     for (int u = 0; u < n; ++u) {
39         if (e != -1 && (u == s || u == e)) continue;
40         int out_u = (int)h[u].size();

```

```

37         if (in_degree[u] != out_u || (!directed && (in_degree
38             [u] & 1))) {
39             return {};
40         }
41     }
42     while (!st.empty()) {
43         int u = st.top();
44         if (h[u].empty()) {
45             result.emplace_back(u);
46             st.pop();
47         } else {
48             int v = *h[u].begin();
49             auto it = h[u].find(v);
50             if (it != h[u].end()) h[u].erase(it);
51             --in_degree[v];
52             if (!directed) {
53                 auto it2 = h[v].find(u);
54                 if (it2 != h[v].end()) h[v].erase(it2);
55                 --in_degree[u];
56             }
57             st.emplace(v);
58         }
59     }
60     for (int u = 0; u < n; ++u) {
61         if (in_degree[u] != 0) return {};
62     }
63     reverse(result.begin(), result.end());
64     return result;

```

9.7 Lca

```

1  // LCA - CP algorithm
2  // preprocessing 0(NlogN)
3  // lca 0(logN)
4  // Uso: criar LCA com a quantidade de vertices (n) e lista de
5  //   adjacencias (adj)
6  //   chamar a funcao preprocess com a raiz da arvore
7  struct LCA {
8      int n, l, timer;
9      vector<vector<int>> adj;
10     vector<int> tin, tout;
11     vector<vector<int>> up;
12
13     LCA(int n, const vector<vector<int>>& adj) : n(n), adj(
14         adj) {}
15
16     void dfs(int v, int p) {
17         tin[v] = ++timer;
18         up[v][0] = p;
19         for (int i = 1; i <= l; ++i)
20             up[v][i] = up[up[v][i-1]][i-1];
21
22         for (int u : adj[v]) {
23             if (u != p)
24                 dfs(u, v);
25         }
26         tout[v] = ++timer;
27     }
28
29     bool is_ancestor(int u, int v) {
30         return tin[u] <= tin[v] && tout[u] >= tout[v];
31     }
32
33     int lca(int u, int v) {
34         if (is_ancestor(u, v))
35             return u;
36         if (is_ancestor(v, u))
37             return v;
38         for (int i = l; i >= 0; --i) {
39             if (!is_ancestor(up[u][i], v))
40                 u = up[u][i];
41         }
42         return up[u][0];
43     }
44
45     void preprocess(int root) {
46         tin.resize(n);
47         tout.resize(n);
48         timer = 0;
49         l = ceil(log2(n));
50         up.assign(n, vector<int>(l + 1));
51         dfs(root, root);
52     }

```

```
53 };
```

9.8 Topological Sort

```
1 vector<int> adj[MAXN];
2 vector<int> estado(MAXN); // 0: nao visitado 1: processamento
3 // 2: processado
4 vector<int> ordem;
5 bool temCiclo = false;
6
7 void dfs(int v) {
8     if(estado[v] == 1) {
9         temCiclo = true;
10        return;
11    }
12    if(estado[v] == 2) return;
13    estado[v] = 1;
14    for(auto &nei : adj[v]) {
15        if(estado[nei] != 2) dfs(nei);
16    }
17    estado[v] = 2;
18    ordem.push_back(v);
19    return;
20 }
```

9.9 Dijkstra

```
1 // SSP com pesos positivos.
2 // O((V + E) log V).
3
4 vector<int> dijkstra(int S) {
5     vector<bool> vis(MAXN, 0);
6     vector<ll> dist(MAXN, LLONG_MAX);
7     dist[S] = 0;
8     priority_queue<pii, vector<pii>, greater<pii>> pq;
9     pq.push({0, S});
10    while(pq.size()) {
11        ll v = pq.top().second;
12        pq.pop();
13        if(vis[v]) continue;
14        vis[v] = 1;
15        for(auto &[peso, vizinho] : adj[v]) {
16            if(dist[vizinho] > dist[v] + peso) {
17                dist[vizinho] = dist[v] + peso;
18                pq.push({dist[vizinho], vizinho});
19            }
20        }
21    }
22    return dist;
23 }
```

9.10 Acha Pontes

```
1 vector<int> d, low, pai; // d[v] Tempo de descoberta (
2 // discovery time)
3 vector<bool> vis;
4 vector<int> pontos_articulacao;
5 vector<pair<int, int>> pontes;
6 int tempo;
7
8 vector<vector<int>> adj;
9
10 void dfs(int u) {
11     vis[u] = true;
12     tempo++;
13     d[u] = low[u] = tempo;
14     int filhos_dfs = 0;
15     for (int v : adj[u]) {
16         if (v == pai[u]) continue;
17         if (vis[v]) { // back edge
18             low[u] = min(low[u], d[v]);
19         } else {
20             pai[v] = u;
21             filhos_dfs++;
22             dfs(v);
23             low[u] = min(low[u], low[v]);
24             if (pai[u] == -1 && filhos_dfs > 1) {
25                 pontos_articulacao.push_back(u);
26             }
27             if (pai[u] != -1 && low[v] >= d[u]) {
28                 pontos_articulacao.push_back(u);
29             }
30             if (low[v] > d[u]) {
```

```
30         pontes.push_back({min(u, v), max(u, v)});
31     }
32 }
33 }
34 }
```

9.11 Khan

```
1 // topo-sort DAG
2 // lexicograficamente menor.
3 // N: numero de vertices (1-indexado)
4 // adj: lista de adjacencia do grafo
5
6 const int MAXN = 5 * 1e5 + 2;
7 vector<int> adj[MAXN];
8 int N;
9
10 vector<int> kahn() {
11     vector<int> indegree(N + 1, 0);
12     for (int u = 1; u <= N; u++) {
13         for (int v : adj[u]) {
14             indegree[v]++;
15         }
16     }
17     priority_queue<int, vector<int>, greater<int>> pq;
18     for (int i = 1; i <= N; i++) {
19         if (indegree[i] == 0) {
20             pq.push(i);
21         }
22     }
23     vector<int> result;
24     while (!pq.empty()) {
25         int u = pq.top();
26         pq.pop();
27         result.push_back(u);
28         for (int v : adj[u]) {
29             indegree[v]--;
30             if (indegree[v] == 0) {
31                 pq.push(v);
32             }
33         }
34     }
35     if (result.size() != N) {
36         return {};
37     }
38     return result;
39 }
```

9.12 Bellman Ford

```
1 struct Edge {
2     int u, v, w;
3 };
4
5 // se x = -1, nao tem ciclo
6 // se x != -1, pegar pais de x pra formar o ciclo
7
8 int n, m;
9 vector<Edge> edges;
10 vector<int> dist(n);
11 vector<int> pai(n, -1);
12
13 for (int i = 0; i < n; i++) {
14     x = -1;
15     for (Edge &e : edges) {
16         if (dist[e.u] + e.w < dist[e.v]) {
17             dist[e.v] = max(-INF, dist[e.u] + e.w);
18             pai[e.v] = e.u;
19             x = e.v;
20         }
21     }
22 }
23
24 // achando caminho (se precisar)
25 for (int i = 0; i < n; i++) x = pai[x];
26
27 vector<int> ciclo;
28 for (int v = x; v = pai[v]) {
29     ciclo.push_back(v);
30     if (v == x && ciclo.size() > 1) break;
31 }
32 reverse(ciclo.begin(), ciclo.end());
```

9.13 Dinitz


```

1 // Complexidade:  $O(V^2E)$ 
2
3 struct FlowEdge {
4     int from, to;
5     long long cap, flow = 0;
6     FlowEdge(int from, int to, long long cap) : from(from),
7         to(to), cap(cap) {}
8 };
9
10 struct Dinic {
11     const long long flow_inf = 1e18;
12     vector<FlowEdge> edges;
13     vector<vector<int>> adj;
14     int qntV, qntE = 0;
15     int source, sink;
16     vector<int> level, ptr;
17     queue<int> q;
18
19     Dinic(int qntV, int source, int sink) : qntV(qntV),
20         source(source), sink(sink) {
21         adj.resize(qntV);
22         level.resize(qntV);
23         ptr.resize(qntV);
24     }
25
26     void add_edge(int from, int to, long long cap) {
27         edges.emplace_back(from, to, cap);
28         edges.emplace_back(to, from, 0);
29         adj[from].push_back(qntE);
30         adj[to].push_back(qntE + 1);
31         qntE += 2;
32     }
33
34     bool bfs() {
35         while (!q.empty()) {
36             int from = q.front();
37             q.pop();
38             for (int id : adj[from]) {
39                 if (edges[id].cap == edges[id].flow)
40                     continue;
41                 if (level[edges[id].to] != -1)
42                     continue;
43                 level[edges[id].to] = level[from] + 1;
44                 q.push(edges[id].to);
45             }
46         }
47         return level[sink] != -1;
48     }
49
50     long long dfs(int from, long long pushed) {
51         if (pushed == 0)
52             return 0;
53         if (from == sink)
54             return pushed;
55         for (int& cid = ptr[from]; cid < (int)adj[from].size
56             (); cid++) {
57             int id = adj[from][cid];
58             int to = edges[id].to;
59             if (level[from] + 1 != level[to])
60                 continue;
61             long long tr = dfs(to, min(pushed, edges[id].cap
62                 - edges[id].flow));
63             if (tr == 0)
64                 continue;
65             edges[id].flow += tr;
66             edges[id ^ 1].flow -= tr;
67             return tr;
68         }
69         return 0;
70     }
71
72     long long max_flow() {
73         long long f = 0;
74         while (true) {
75             fill(level.begin(), level.end(), -1);
76             level[source] = 0;
77             q.push(source);
78             if (!bfs())
79                 break;
80             fill(ptr.begin(), ptr.end(), 0);
81             while (long long pushed = dfs(source, flow_inf))
82                 f += pushed;
83         }
84     }
85
86     return f;
87 }

```

```

82     }
83 };

```

9.14 Kruskal

```

1 // Ordena as arestas por peso, insere se ja nao estiver no
2 // mesmo componente
3 //  $O(E \log E)$ 
4
5 struct Edge {
6     int u, v, w;
7     bool operator <(Edge const & other) {
8         return weight < other.weight;
9     }
10 }
11
12 vector<Edge> kruskal(int n, vector<Edge> edges) {
13     vector<Edge> mst;
14     DSU dsu = DSU(n + 1);
15     sort(edges.begin(), edges.end());
16     for (Edge e : edges) {
17         if (dsu.find(e.u) != dsu.find(e.v)) {
18             mst.push_back(e);
19             dsu.join(e.u, e.v);
20         }
21     }
22     return mst;
23 }

```

9.15 Kosaraju

```

1 bool vis[MAXN];
2 vector<int> order;
3 int component[MAXN];
4 int N, m;
5 vector<int> adj[MAXN], adj_rev[MAXN];
6
7 // dfs no grafo original para obter a ordem (pos-order)
8 void dfs1(int u) {
9     vis[u] = true;
10    for (int v : adj[u]) {
11        if (!vis[v]) {
12            dfs1(v);
13        }
14    }
15    order.push_back(u);
16 }
17
18 // dfs o grafo reverso para encontrar os SCCs
19 void dfs2(int u, int c) {
20     component[u] = c;
21     for (int v : adj_rev[u]) {
22         if (component[v] == -1) {
23             dfs2(v, c);
24         }
25     }
26 }
27
28 int kosaraju() {
29     order.clear();
30     fill(vis + 1, vis + N + 1, false);
31     for (int i = 1; i <= N; i++) {
32         if (!vis[i]) {
33             dfs1(i);
34         }
35     }
36     fill(component + 1, component + N + 1, -1);
37     int c = 0;
38     reverse(order.begin(), order.end());
39     for (int u : order) {
40         if (component[u] == -1) {
41             dfs2(u, c++);
42         }
43     }
44     return c;
45 }

```

10 DP

10.1 Bitmask

```

1 // dp de intervalos com bitmask

```

```

2 int prox(int idx) {
3     return lower_bound(S.begin(), S.end(), array<int, 4>{S[
4         idx][1], 011, 011, 011}) - S.begin();
5 }
6 int dp[1002][1000][1000][1000];
7
8 int rec(int i, int vis) {
9     if (i == (int)S.size()) {
10         if (__builtin_popcountll(vis) == N) return 0;
11         return LLONG_MIN;
12     }
13     if (dp[i][vis] != -1) return dp[i][vis];
14     int ans = rec(i + 1, vis);
15     ans = max(ans, rec(prox(i), vis | (1ll << S[i][3])) + S[i
16         ][2]);
17     return dp[i][vis] = ans;
18 }

```

10.2 Kadane

```

1 // O(n) - retorna maximum subarray sum
2 array<int, 3> kadane(vector<int> &a) {
3     int L = -1, R = -1, n = a.size();
4     int soma = 0, ans = -INF;
5     int fim = n - 1;
6     for (int i = n - 1; i >= 0; i--) {
7         if (a[i] > a[i] + soma) {
8             fim = i;
9             soma = a[i];
10        } else {
11            soma += a[i];
12        }
13        if (soma > ans) {
14            R = fim;
15            L = i;
16            ans = soma;
17        }
18    }
19    return { ans, L, R };
20 }

```

10.3 Knapsack

```

1 // dp[i][j] => i-esimo item com j-carga sobrando na mochila
2 // O(N * W)
3 vector<vector<int>> dp(N + 1, vector<int>(W + 1, 0));
4 for (int i = 1; i <= N; i++) dp[i][0] = 0;
5 for (int j = 0; j <= W; j++) dp[0][j] = 0;
6 for (int i = 1; i <= N; i++) {
7     for (int j = 0; j <= W; j++) {
8         dp[i][j] = dp[i - 1][j];
9         if (j >= items[i - 1].first) {
10            dp[i][j] = max(dp[i][j], dp[i - 1][j - items[i
11                - 1].first] + items[i - 1].second);
12        }
13    }
14 }
15 cout << dp[N][W] << '\n';

```

10.4 Digit

```

1 vector<int> digits;
2
3 int dp[20][10][2][2];
4
5 int rec(int i, int last, int flag, int started) {
6     if (i == (int)digits.size()) return 1;
7     if (dp[i][last][flag][started] != -1) return dp[i][last][
8         flag][started];
9     int lim;
10    if (flag) lim = 9;
11    else lim = digits[i];
12    int ans = 0;
13    for (int d = 0; d <= lim; d++) {
14        if (started && d == last) continue;
15        int new_flag = flag;
16        int new_started = started;
17        if (d > 0) new_started = 1;
18        if (!flag && d < lim) new_flag = 1;
19        ans += rec(i + 1, d, new_flag, new_started);
20    }
21    return dp[i][last][flag][started] = ans;
22 }

```

10.5 Edit Distance

```

1 vector<vector<int>> dp(n+1, vector<int>(m+1, LLONG_MIN));
2 for (int j = 0; j <= m; j++) dp[0][j] = j;
3 for (int i = 0; i <= n; i++) dp[i][0] = i;
4 for (int i = 1; i <= n; i++) {
5     for (int j = 1; j <= m; j++) {
6         if (a[i-1] == b[j-1]) {
7             dp[i][j] = dp[i-1][j-1];
8         } else {
9             dp[i][j] = min({dp[i-1][j] + 1, dp[i][j-1] +
10                 1, dp[i-1][j-1] + 1});
11         }
12     }
13 }
14 cout << dp[n][m];

```

10.6 Lis Brunomonteiro

```

1 // Calcula e retorna uma LIS O(n.log(n))
2 template<typename T> vector<T> lis(vector<T>& v) {
3     int n = v.size(), m = -1;
4     vector<T> d(n+1, INF);
5     vector<int> l(n);
6     d[0] = -INF;
7
8     for (int i = 0; i < n; i++) {
9         // Para non-decreasing use upper_bound()
10        int t = lower_bound(d.begin(), d.end(), v[i]) - d.
11            begin();
12        d[t] = v[i], l[i] = t, m = max(m, t);
13    }
14
15    int p = n;
16    vector<T> ret;
17    while (p-- > 0) {
18        if (l[p] == m) {
19            ret.push_back(v[p]);
20            m--;
21        }
22    }
23    reverse(ret.begin(), ret.end());
24    return ret;
25 }

```

10.7 Disjoint Blocks

```

1 // num max de subarrays disjuntos com soma x usando apenas
2 // prefixo i (ou seja, considerando prefixo a[1..i]).
3 int disjointSumX(vector<int> &a, int x) {
4     int n = a.size();
5     map<int, int> best; // best[pref] = melhor dp visto para
6     esse pref
7     best[0] = 0;
8     int pref = 0;
9     vector<int> dp(n + 1, 0); // dp[0] = 0
10    for (int i = 1; i <= n; i++) {
11        pref += a[i - 1];
12        dp[i] = dp[i - 1];
13        auto it = best.find(pref - x);
14        if (it != best.end()) {
15            dp[i] = max(dp[i], it->second + 1);
16        }
17        best[pref] = max(best[pref], dp[i]);
18    }
19    return dp[n];
20 }

```

10.8 Lcs

```

1 string s1, s2;
2 int dp[1001][1001];
3 int lcs(int i, int j) {
4     if (i < 0 || j < 0) return 0;
5     if (dp[i][j] != -1) return dp[i][j];
6     if (s1[i] == s2[j]) return dp[i][j] = 1 + lcs(i - 1, j -
7         1);
8     else return dp[i][j] = max(lcs(i - 1, j), lcs(i, j - 1));
9 }

```

10.9 Lis

```

1 int lis_nlogn(vector<int> &v) {
2     vector<int> lis;
3     lis.push_back(v[0]);
4     for (int i = 1; i < v.size(); i++) {
5         if (v[i] > lis.back()) {
6             // estende a lis
7             lis.push_back(v[i]);
8         } else {
9             // encontra o primeiro elemento em lis que >= v[i]
10            auto it = lower_bound(lis.begin(), lis.end(), v[i]);
11            *it = v[i];
12        }
13    }
14    return lis.size();
15 }
16
17 // lis na tree do problema da sub
18 const int MAXN_TREE = 100001;
19 vector<int> adj[MAXN_TREE];
20 int values[MAXN_TREE];
21 int ans = 0;
22
23 void dfs(int u, int p, vector<int> &tails) {
24     auto it = lower_bound(tails.begin(), tails.end(), values[u]);
25     int prev = -1;
26     bool coloquei = false;
27     if (it == tails.end()) {
28         tails.push_back(values[u]);
29         coloquei = true;
30     } else {
31         prev = *it;
32         *it = values[u];
33     }

```

```

34     ans = max(ans, (int)tails.size());
35     for (int v : adj[u]) {
36         if (v != p) {
37             dfs(v, u, tails);
38         }
39     }
40     if (coloquei) {
41         tails.pop_back();
42     } else {
43         *it = prev;
44     }
45 }

```

10.10 Lis Seg

```

1 // comprime coordenadas pra quando ai <= 1e9
2 vector<int> vals(a.begin(), a.end());
3 sort(vals.begin(), vals.end());
4 vals.erase(unique(vals.begin(), vals.end()), vals.end());
5 auto id = [&](int x) -> int {
6     return lower_bound(vals.begin(), vals.end(), x) - vals.begin();
7 };
8 for (int i = 0; i < n; i++) a[i] = id(a[i]);
9 // fim da parte de compr
10 SegTree seg(n);
11 // dp[i]: lis que termina em i
12 vector<int> dp(n, 1); // dp[i] = 1 base case
13 for (int i = 0; i < n; i++) {
14     if (a[i] > 0) dp[i] = seg.query(0, max(0ll, a[i] - 1)) + 1;
15     seg.update(a[i], dp[i]);
16 }
17 cout << *max_element(dp.begin(), dp.end()) << '\n';

```