

PFT SWING L FC-230V airless

The high-pressure pump with RotaAirless technology

Due to its various fields of application, e.g. spraying, filling, bonding and reinforcing, the powerful one ensures a high machine capacity utilization and is therefore an ideal supplement to the machine park.

upcoming

Q4/2023: New version available



THE SWING-EFFECT

PFT SWING AIRLESS

More quiet!

More robust!

More economical!

TECHNICAL DATA	
Part no.	00451336
Conveying capacity	up to 6.5 l/min, continuously adjustable
Conveying distance	up to 20 m
Working pressure	max. 135 bar
Rotor/Stator	306 airless
Motor	230 V, 1 Ph, 50 Hz, 3 kW, 0 – 280 rpm
Material outflow	DN12 female 1/2" external thread
Material hose	RONDO airless DN12 – 20 m
Spraying gun	In Line Texspray
Spraying cap	RAC X 545
Connection cable	BLA 2-16 A – 5 m
Filling height	720 mm
Hopper content	70 l
Dimensions: L/W/H	1,430 / 500 / 720 mm
Total weight	~ 105 kg



230 V



3.0 kW



1 Ph



6.5 l/min



max. 135 bar



PFT – ALWAYS AT YOUR SITE

ADVANTAGES AT A GLANCE



- 1** Material hopper one-piece, no back taper
Reduced material adhesion – quick and easy cleaning
- 2** Protective grid, low-lying
- 3** Quick pump replacement on construction site
- 4** Controls – clearly arranged and easily accessible
- 5** Tube bracket, integrated
- 6** Material filter
- 6** Constant electronic monitoring through pressure sensor
- 7** Puncture proof wheels
- Pump, valveless – RotaAirless technology:
Improved spray quality due to an additional kneading effect in the pump
- Pressure control via digital display
- Idling protection – extends the lifetime of the pump
- Conveying distance up to 20 metre – flexible hose with kink protection on machine outlet
- Various fields of application: spray plaster, grainy material up to 3 mm, colour*
- Low noise, compact and powerful
- Easy handling on construction site
- Robustly designed and suitable for construction site

* Please consider approval of colours.
Do not use with solvent-containing colours.

FIELDS OF APPLICATION

- Spray plaster
- Grainy material up to 3 mm*
- Colour**

*Not with Stator 306 airless
**Please consider approval of colours. Do not use with solvent-containing colours.



ACCESSORIES

- Bag squeezer
- Conversion kit – for air-assisted spraying of spray plaster
- Conversion kit – grainy material
- Conversion kit – colour
- CEE current manifold 400 V
RED 5-16 A | 3x BLA 2-16 A

PART NO.

00459811
00504344
00518542
00503759
00495147



The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net/360
www.youtube.com/knaufpften

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · D-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights and technical modifications reserved. The respective current version applies. Our warranty refers only to the perfect condition of our machines. Figures given in relation to consumption, quantity and design as well as performance data are based on experience and cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always valid. Illustrations may show customized versions, which are not included in the standard scope of delivery. Change, reprint and photomechanical as well as electronic reproduction, also of excerpts, is only permitted with the explicit approval of Knauf PFT GmbH & Co. KG.

PFT SWING airless FC-230V – EN/04.23/PFT