

Quantifying Vividness Reports Using Gaussian Process Regression

Oğul Can Yurdakul¹ (oyurdaku@uci.edu), Xueyi Huang², Angela Shen¹, Emil Olsson¹, Ali Ekhlasi¹, Michaela Klímová², Jorge Morales^{†2}, Megan A. K. Peters^{†1,3,4}

¹Department of Cognitive Sciences,
University of California Irvine, USA

²Department of Psychology,
Northeastern University, USA

³Department of Experimental Psychology,
University College London, UK

⁴Program in Brain, Mind, & Consciousness,
Canadian Institute for Advanced Research, Canada

[†]These authors contributed
equally as senior authors.


(1) How to characterise vividness?

Huang et al. (2025) used linear regression to reveal evidence of common structure in ‘vividness’ & large individual differences.

Current aims


- (1) Move beyond the parametric assumptions of linear models
- (2) Characterise individual differences in a principled manner

(2) Data and problem formulation



Vividness ratings (1 – 5 continuous scale)
Perceptual features (0 – 1 continuous scale): sharpness, opacity, saturation


What is the function $f(\cdot)$ that maps these features onto vividness?



(3) What are Gaussian processes?

Setup: N observations y_i of $f(\cdot)$ at input locations $\vec{x}_i$ such that $y_i = f(\vec{x}_i) + \varepsilon_i$

Core idea: Finite sets of evaluations of $f(\vec{x})$ are jointly Gaussian with the covariance structure determined by inputs $\vec{x}$ (Rasmussen and Williams 2005)



$$\text{Cov}[y_i, y_j] = k(\vec{x}_i, \vec{x}_j) + \sigma_\varepsilon^2 \delta_{ij}$$

$$= \sigma_f^2 \exp \left(-\frac{1}{2} \left(\frac{(\vec{x}_i^{\text{sha}} - \vec{x}_j^{\text{sha}})^2}{\ell_{\text{sharpness}}^2} + \frac{(\vec{x}_i^{\text{opa}} - \vec{x}_j^{\text{opa}})^2}{\ell_{\text{opacity}}^2} + \frac{(\vec{x}_i^{\text{sat}} - \vec{x}_j^{\text{sat}})^2}{\ell_{\text{saturation}}^2} \right) \right) + \sigma_\varepsilon^2 \delta_{ij}$$


where δ_{ij} is the impulse function that takes the value 1 only when $i = j$ and 0 otherwise.

Hyperparameters:

- **Kernel function:** Covariance between noiseless function evaluations
- **Noise standard deviation:** Uncertainty on measurements $\varepsilon_i \sim \mathcal{N}(0, \sigma_\varepsilon^2)$
- **Signal standard deviation:** Uncertainty on unobserved locations
- **Length scales:** Smoothness over variables

Model fits are obtained using MATLAB Statistics and Machine Learning Toolbox (2026).

(4) Gaussian processes reveal nonlinearities and clusters of individuals




Equal vividness manifolds

where different features correspond to the same vividness rating

Difference manifolds


where the difference Δ between two profiles is constant



Figures: Δ (Subject 11 - Supersubject) = 0

Non-planar manifolds imply that nonlinear relationships can be captured using Gaussian processes!

Hyperparameter-based clustering



Clustered using DBSCAN (Ester et al. 1996) and Satopaa et al. (2011) for knee detection.

Groups differ mostly in the way they are sensitive to the three perceptual features!

(5) Take-home messages

Vividness ratings...

- (1) can show nonlinear dependence on perceptual features, as seen through non-planar equal vividness manifolds over the feature space!
- (2) show individual differences in their dependence on these features, agreeing with Huang et al. (2025), ...yet there are trends in these differences!

Why use Gaussian processes?

- Non-parametric regression method not restricted by functional form
- Inherently generative model
- Model confidence/prediction intervals come naturally
- Not a black box model: hyperparameters are interpretable

Gaussian processes can help answer...

- How do individuals differ from the general population? From each other?
- How to choose input values to elicit a specific response for any multivariate nonlinear behavioral output, without parametric assumptions?
- ... and in a way that agrees with the whole population?

References

- Huang, Shen, Olsson, Garcia, Dijkstra, Peters[†], Morales[†] (2025). “What makes mental images vivid? Sharpness as the key visual dimension”. en. In: *Journal of vision*.
- Rasmussen, Williams (Nov. 2005). *Gaussian processes for machine learning*. en. Adaptive Computation and Machine Learning series. London, England: MIT Press.
- The MathWorks (2026). *Statistics and Machine Learning Toolbox version: 26.1 (R2026a)*. Natick, Massachusetts, United States.
- Ester, Kriegel, Sander, Xu (1996). “A Density-Based Algorithm for Discovering Clusters in Large Spatial Databases with Noise”. In: *Knowledge Discovery and Data Mining*.
- Satopaa, Albrecht, Irwin, Raghavan (2011). “Finding a ‘Kneedle’ in a Haystack: Detecting Knee Points in System Behavior”. In: *2011 31st International Conference on Distributed Computing Systems Workshops*.