



DEPARTMENT OF INFORMATICS

TECHNISCHE UNIVERSITÄT MÜNCHEN

Bachelor's Thesis in Informatics

Notification Timing for a Proactive Virtual Dietary Advisor

Oguz Gültepe





DEPARTMENT OF INFORMATICS

TECHNISCHE UNIVERSITÄT MÜNCHEN

Bachelor's Thesis in Informatics

Notification Timing for a Proactive Virtual Dietary Advisor

Timing von Benachrichtigungen für einen proaktiven virtuellen Ernährungsberater

Author:	Oguz Gültepe
Supervisor:	PD Dr. rer. nat. Georg Groh
Advisor:	Monika Wintergerst
Submission Date:	15.07.2019



I confirm that this bachelor's thesis in informatics is my own work and I have documented all sources and material used.

Munich, 15.07.2019

Oguz Gültepe

Acknowledgments

Abstract

Contents

Acknowledgments	iii
Abstract	iv
1 Introduction	1
1.1 Nutrition and Health	1
1.2 Health and Well Being Applications	1
1.3 Goal and Structure of the Thesis	1
2 Theoretical Background	2
2.1 Natural Language Processing	2
2.1.1 Regular Expressions	2
2.1.2 Information Extraction	7
2.1.3 Dialog Systems	8
2.2 Machine Learning	12
2.2.1 Basics of ML	12
2.2.2 Relevant Models	12
2.3 Nutrition	12
2.3.1 Dietary Assesment	12
2.3.2 Dietary Goals	12
3 Methodology	13
3.1 Chatbot	13
3.1.1 Design	13
3.1.2 Telegram Integration	13
3.1.3 Database	13
3.2 Machine Learning	13
3.2.1 Frameworks	13
3.2.2 Feature Templates	13
3.2.3 Models	13
3.2.4 Training and Testing	13
3.2.5 Implementation	13

Contents

4	Results	14
4.1	Section	14
5	Discussion	15
5.1	Section	15
6	Conclusion	16
6.1	Summary	16
6.2	Future Work	16
7	latex-guide	17
7.1	Section	17
7.1.1	Subsection	17
	List of Figures	19
	List of Tables	20
	Bibliography	21

1 Introduction

1.1 Nutrition and Health

1.2 Health and Well Being Applications

1.3 Goal and Structure of the Thesis

2 Theoretical Background

2.1 Natural Language Processing

Natural language processing (NLP) is a subfield of computer science which focuses on, as implied by the name, processing of human (natural) languages. NLP enables us to make use of copious knowledge that is expressed in natural language. [RN10]

In this section we will be taking a look at some NLP concepts that are relevant to us. Most of the knowledge provided here is based on [JMd]. We will start with regular expressions, powerful tools able to catch text patterns. Then we will be looking at information extraction from natural language. Finally, we will finish this chapter on dialog systems and chatbot.

2.1.1 Regular Expressions

A **regular expression** is formally defined as an algebraic notation that represents a specific set of strings. However, this representation is not explicit. Regular expressions denote textual patterns which are able to produce implicit sets. These patterns are useful for searching in text. A regular expression search function finds every instance of text in the corpus that belongs to the pattern's implicit set. These instances are said to be 'matched' by the pattern.

Regular expressions are supported in every computer language, word processor and text processing tool. However, there may be differences in how they treat certain expressions. As the knowledge provided here is based on [JMc], we will be treating expressions as they are shown there. Another thing to keep in mind is that this is not a comprehensive guide for regular expression. We will be looking at basics and some more complex operators we need for our specific problem.

Basic Regular Expression Patterns

Simplest regular expressions are sequences of characters. For example `snack` matches any string that contains the sequence 'snack'. Here are some examples that would be matched by this regular expression:

"I just had a small snack."

"His username was 123snacko."

As we see, this regular expression only searches for the sequence 'snack'. Whether the found sequence actually is a word or not is irrelevant.

The period . is treated as a special character: the wildcard. It matches any character, so for example `r.n` matches:

"I ran 5k today."

"You better run."

Another special character is the question mark: ?. Adding a question mark after an element makes the element optional. For example, `hours?` matches:

"The hour arm of the clock was missing."

"I have been waiting for you for hours."

Special characters can also be used as regular characters. We just need to put a backslash \ before the special character. For example, `Inc\.` matches:

"Monsters Inc. was a great movie."

Table 2.1: Regular Expression Basics

Regular Expression	Match	Example
<code>duck</code>	'duck'	<u>duck</u>
<code>r.ck</code>	'r' and 'ck' with any character in between	<u>rock</u> , <u>rack</u>
<code>minutes?</code>	'minute' or 'minutes'	<u>minute</u> , <u>minutes</u>
<code>\?</code>	'?'	How <u>?</u>

Square Brackets, Range and Negation

It is important to note that regular expressions are case sensitive, so `meal` matches the first example, but not the second:

"We had a tasty meal."

"Meal is ready."

This problem is solved by the use of square brackets: []. Square brackets signify a disjunction between the characters inside. So `[Mm]` means either 'M' or 'm' and `[Mm]ea1` matches both examples:

"We had a tasty meal."

"Meal is ready."

Square brackets can be used for regular expression that match any digit `[1234567890]` or any letter `[abcdefghijklmnopqrstuvwxyz]`. However, for such common disjunctions we can also use the dash - operator. Dash operator denotes a range: `[0-9]` matches any digit between '0' and '9'. `[a-z]` and `[A-Z]` match any lowercase letter and any

uppercase letter, respectively.

Another use of square brackets is negation. When a caret `^` is the first character inside a bracket, any character other than the ones inside the brackets is matched. `[^ab]` matches any character that is not 'a' or 'b'. `[^0-9]` matches any character that is not a digit.

It is important to note that when used outside of these contexts, both dash `-` and caret `^` have different meanings. Outside of the brackets, dash operator is treated as a character. When the caret occurs in the brackets after the first character, it is also treated as a character. For example, `0-9` matches the first sentence but not the second: "Please enter a value between 0-9."

"This course is worth 8 ECTS credits."

There are some shorthands for commonly used ranges or disjunctions. `\d` is equivalent to `[0-9]` and matches any digit. `\s` matches any whitespace.

Table 2.2: Use of Square Brackets

Regular Expression	Match	Example
<code>[Ss]nack</code>	'Snack' or 'snack'	<u>Snack</u> , <u>snack</u>
<code>[0-9]</code>	Any digit	<u>5</u> missed calls!
<code>[^abc]</code>	Any character that is not 'a', 'b' or 'c'	<u>ca</u> rb
<code>[3^2]</code>	'3', '^', or '2'	n <u>^</u> 1 equals n
<code>\d</code>	Any digit	<u>5</u> missed calls!
<code>\s</code>	Any whitespace	5 <u>_</u> missed <u>_</u> calls!

Disjunction and Anchors

Now, with the help of square brackets, we are capable of basic disjunction between characters. But what if we need a pattern that matches either 'meal' or 'snack'? `[mealssnack]` wouldn't work as square brackets denote character level disjunction. What we need here is the pipe symbol `|`, the disjunction operator. `snack|meal` matches both of the following examples:

"I need a snack."

"When was your last meal"

Next, we have the anchors: special characters that can specify locations in text. For example, the caret operator `^` when used outside of brackets specify the start of a line. The dollar sign `$` specifies the end of a line. So `^I|\?$` matches any sentence that either starts with I or ends with a question mark:

"I thought we were gonna eat together."

"Are you available for lunch ?

We have two more anchors that we can make use of: `\b` to match word boundaries and `\B` to match non-boundaries. For example, `\bsnack\b` matches the first sentence, but not the second:

"I just had a small snack."

"His username was 123snacko."

To use these anchors, it is important to understand what a word means. In terms of regular expressions, a word is defined as any sequence of digits, letters or underscores. So `\bap\b` would match `'A$ap'`. As `$` is neither a digit or a letter or underscore, it is treated as a word boundary.

Table 2.3: Disjunction and Anchors

Regular Expression	Match	Example
<code>eat ate</code>	<code>'eat'</code> or <code>'ate'</code>	I just <u>ate</u> .
<code>^\.</code>	Any character at the start of a line	<u>I</u> just ate.
<code>\.\$</code>	Any character at the end of a line	I just <u>ate</u> .
<code>\b59\b</code>	<code>'59'</code> between word boundaries	It costs \$ <u>59</u> .99.
<code>\B59\B</code>	<code>'59'</code> between non-boundaries	It costs \$2 <u>599</u> .

Kleene Operators, Grouping and Precedence

There are cases where we need to match repetitive patterns. For example, we might want to match any `'hey'` with an arbitrary amount of `'y's`. To do this, we can use the Kleene Star `*`. Kleene star means "0 or more occurrences of the preceding element". This means `y*` matches `''`, `'y'`, `'yy'` and any other number of `'y'` characters. So in order to match any `'hey'` with an arbitrary amount of `'y's`, we would use `heyy*`. This use, however, is so common that we have another operator for it: the Kleene Plus `+`. Kleene Plus means "1 or more occurrences of the preceding element". So `heyy*` and `hey+` are functionally equal.

But what if we need to match a phrase such as `'hahaha'`, which consists of an arbitrary number of `'ha's`? `ha+` wouldn't work, because the Kleene operator works on the preceding element. So how can we set `'ha'` as the preceding element?

This is where grouping comes into play. In regular expressions, grouping is done by wrapping a phrase in parentheses. From then on, the phrase inside the parentheses is treated as a singular entity by operators outside the parentheses. `(ha)+` matches any `'ha'`, `'haha'` and any number of repetitions of the phrase `'ha'`.

Grouping also comes in handy when using the disjunction operator. For example,

let's assume we need a regular expression that matches 'hour', 'minute', 'hours' and 'minutes'. We can't use `hour|minutes?`, because the disjunction is between `hour` and `minutes?`. This is because the `?` is evaluated first, then the sequences and only then the disjunction. Instead, we can use `(hours|minute)s?`. This expression works since the parentheses are evaluated before all the other operators.

The collection of rules determining which operator is evaluated first is called the operator precedence hierarchy. An operator x is said to have precedence over another operator y , if x is to be evaluated before y . Regular expression operator precedence hierarchy is as follows, from highest precedence to lowest precedence:

Table 2.4: Regular Expression Operator Precedence Hierarchy

Parantheses	()
Counters	* + ?
Sequences and anchors	seq ^I \. \$
Disjunction	

Table 2.5: Regular Expression Kleene Operators and Grouping

Regular Expression	Match	Example
<code>b*</code>	0 or more repetitions of 'b'	<u>aaabbb</u>
<code>a+</code>	1 or more repetitions of 'a'	<u>aaabbb</u>
<code>(ab)+</code>	1 or more repetitions of 'ab'	<u>aaabbb</u>

Capture Groups

Let's assume we have a list of names and we want to make sure all the names occur only once in the list. The following regular expression accomplishes that:

`\b([A-Z][a-z]*)\b.*\b1\b`

When we use parentheses for grouping, the text that matches the expression inside is stored in the memory. This stored text is referred to as a capture group. Capture groups are numbered from left to right and can be referenced by the use of a backslash, followed by the group number.

When we need to group expressions but do not want to store the matches in the memory, we can use non-capturing groups. Adding `?:` after the opening parenthesis makes a group non capturing.

2.1.2 Information Extraction

We have mentioned that massive amount of information is expressed in natural languages. The process of converting this information into a structured data format is called information extraction. In this subsection, we will be taking a look at information extraction techniques that are relevant to us.

We will start with extracting temporal expressions from text. We will continue with normalizing the extracted temporal expressions. Finally, we will end this subsection on template filling.

Knowledge provided in this subsection is based on [JMb].

Extracting and Normalizing Temporal Expressions

Temporal expressions are parts of text that refer to durations or points in time. Here, we will be focusing less on durations and more on points in time. Temporal expressions such as "17th of July" and "19.30" that directly refer to point in time are called absolute temporal expression. Expressions such as "last week" and "2 hours ago" that refer to points in time in relation to some other point are called relative temporal expressions.

In order to extract temporal information, we first need to find spans of text that contain temporal expressions. This task can be accomplished with the help of lexical triggers. Lexical triggers are textual phrases that imply the existence of a temporal expression. For example; yesterday, past, next or hour. It is possible to build automatons that search and find lexical triggers in text. Additional layers of automatons can be built over these in order to find the spans of temporal expressions based on the lexical triggers.

After extraction, temporal expressions need to be normalized. This process includes mapping the expressions to points in time, be it a calendar date, a time of the day or both. This is fairly simple for absolute time expressions, as they refer to points in time directly. Relative temporal expressions, however, refer to points in time in relation to the document's temporal anchor. A document's temporal anchor is the point in time in which the documents is set. This can for example be the date an article was published or the time a text message was sent. Based on the temporal anchor, relative temporal expressions can be mapped to points in time using temporal arithmetic.

Finally, the points in time, which the temporal expressions were mapped to, must be saved in a standardized way. The standards for saving temporal expressions can be seen in [19]

Template Filling

Many times we have to deal with texts describing common and stereotypical events. These events usually follow certain patterns or have certain participants with certain roles. Our knowledge of these common events may come in handy in information extraction. For example, when we hear the following:

"Would you like to join me for dinner at L'Osteria tomorrow at 8pm?"

Even if we have never heard of L'Osteria, we can assume that it is a restaurant. This is because inviting somebody for a dinner is a common event which usually includes an inviter, invitee, a restaurant and a time. In a simple way, such common events can be represented as templates with fixed slots to fill. A template for a dinner invitation would look something like Table 2.6

Table 2.6: Example Template For a Dinner Invitation

Key	Value
Inviter	You
Invitee	Me
Restaurant	L'Osteria
Time	Tomorrow 8pm

Such templates make it easy to infer details that are not explicitly mentioned, such as the fact that L'Osteria is a restaurant. The task of template filling refers to finding the events that fit particular templates and filling the associated templates with information extracted from the text.

2.1.3 Dialog Systems

In this subsection, we will be talking about dialog systems. Dialog systems are programs use natural language to communicate with the user. In this subsection, we will first go through the difference between task-oriented dialog agents and chatbots. Next we will be taking a look at modern task-oriented dialog systems: frame based dialog agents. Finally, we will end this subsection on control structures for such dialog agents. The knowledge provided in this subsection is based on [JMa].

Task-Oriented Dialog Agents vs Chatbots

The words chatbot and dialog agents are often used interchangeably by many people. However, in the context of NLP, this is a mistake. In NLP, chatbots refer to a distinct

class of dialog agents, the other class being task-oriented dialog agents. So what is the difference between the two classes? Let's start with task-oriented dialog agents.

Task-oriented dialog agents are dialog systems build to -as the name suggest- serve specific tasks. These tasks can include for example finding restaurants, booking hotels or sending messages. Popular digital assistants such as Alexa and Siri fall under this category. Chatbots, on the other hand, are dialog agents without specific goals, built to mimic human conversation.

Here we will be focusing on task based dialog agents rather than chatbots.

Frame Based Dialog Agents

What is a frame based dialog agent? In order to answer this question, we first need to understand some concepts.

Domains are specific areas of knowledge or activity such as computer science or fishing. Domains are modelled by abstract constructs called domain ontologies. A domain ontology defines concepts and relations that belong to a domain.

We build frames based on domain ontologies. A frame is a collection of slots that accept predefined types of values. The slots of a frame defines the information that the systems needs for the task. Dialog agents that are based on such frames are called frame based dialog agents.

Table 2.7 shows an example frame for a task-oriented dialog agent designed to make reservations at a restaurant:

Table 2.7: Example Frame for a Task-Oriented Dialog Agent

Slot	Type
Restaurant	String
Number of People	Integer
Reservation Date	Date
Reservation Time	Time

Control Structure for Frame Based Dialog

A task-oriented dialog agent needs to gather appropriate data to accomplish the task at hand. In order to achieve this, dialog systems implement control structures that guide the conversation. For a frame base dialog agent, the control structure is built around the frame. These control structures are usually finite-state automatas that are hand-designed for the task.

Let's consider the example frame shown at Table 2.7. First, for each slot, we come up with an associated question that elicits an answer to fill the slot. Table 2.8 shows these questions for our example frame.

Table 2.8: Questions for the Example Frame

Slot	Question
Restaurant	For which restaurant would you like to make a reservation?
Number of People	How many people will be present?
Reservation Date	For which day would you like to reserve?
Reservation Time	For what time would you like to reserve?


Based on these questions, we build a finites-state automata to guide the conversation. In this automata, questions are the states and user's answers are the transitions. Take a look at Figure 2.1 for an example finite-state automata that is built based on the questions at Table 2.8.

In our example, the conversation is controlled entirely by the automata. The user doesn't have much option other than answering the questions. This means that the user has no initiative; no control over the conversation. Systems where the user has no initiative such as the one shown at Figure 2.1 are called system-initiatives. The major advantage of system-initiative architecture is the fact that the system always knows what question is being answered. This alleviates the need to match answers with slots. It also allows for fine tuning the answer processing for the expected type of answer. However, such systems offer the user no flexibility. Consider the following input from the user:

"I would like reserve a table at L'Osteria for tomorrow"

This sentence already includes the information needed to fill two slots: Restaurant and Reservation Date. It is possible to augment a dialgo system with the ability to recognize such inputs, allowing for multiple slots to be filled at once. Such a system would pose the user questions for the empty slots, and simply skip the questions for the filled ones. These systems are called mixed-initiatives, as the user also holds some inititive to control the conversation.

Figure 2.1: Example Finite-State Automata as Control-Structure



2.2 Machine Learning

2.2.1 Basics of ML

2.2.2 Relevant Models

2.3 Nutrition

2.3.1 Dietary Assessment

2.3.2 Dietary Goals

3 Methodology

3.1 Chatbot

3.1.1 Design

Chatbot Architecture

Information Extraction

3.1.2 Telegram Integration

python-telegram-bot Library

Implementation

3.1.3 Database

SQLite3

Implementation

3.2 Machine Learning

3.2.1 Frameworks

3.2.2 Feature Templates

3.2.3 Models

3.2.4 Training and Testing

3.2.5 Implementation

4 Results

4.1 Section

5 Discussion

5.1 Section

Which models behave the best How long it takes for accurate observations.

6 Conclusion

6.1 Summary

6.2 Future Work

Initial ballpark times When to reach to the user? How often to reach the user? Intervention any time food choices are made Collab Filtering Context sensitive meal logging Real intervention behaviour AB tests between clustering and initial defaults

7 latex-guide

7.1 Section

Citation test [Lam94].

7.1.1 Subsection

See Table 7.1, Figure 7.1, Figure 7.2, Figure 7.3.

Table 7.1: An example for a simple table.

A	B	C	D
1	2	1	2
2	3	2	3



Figure 7.1: An example for a simple drawing.




Figure 7.2: An example for a simple plot.

```
SELECT * FROM tbl WHERE tbl.str = "str"
```

Figure 7.3: An example for a source code listing.

List of Figures

2.1	Example Finite-State Automata as Control-Structure	11
7.1	Example drawing	17
7.2	Example plot	18
7.3	Example listing	18

List of Tables

2.1	Regular Expression Basics	3
2.2	Regular Expression Square Brackets	4
2.3	Regular Expression Disjunction and Anchors	5
2.4	Regular Expression Operator Precedence Hierarchy	6
2.5	Regular Expression Kleene Operators and Grouping	6
2.6	Example Template For a Dinner Invitation	8
2.7	Example Frame for a Task-Oriented Dialog Agent	9
2.8	Questions for the Example Frame	10
7.1	Example table	17

Bibliography

- [19] *Date and time – Representations for information interchange – Part 1: Basic rules.* Standard. Geneva, CH: International Organization for Standardization, Feb. 2019.
- [JMa] D. Jurafsky and J. H. Martin. “Dialog Systems and Chatbots.” In: *Speech and Language Processing*. 3rd ed. Chap. 24. In preparation.
- [JMb] D. Jurafsky and J. H. Martin. “Information Extraction.” In: *Speech and Language Processing*. 3rd ed. Chap. 18. In preparation.
- [JMc] D. Jurafsky and J. H. Martin. “Regular Expressions, Text Normalization, and Edit Distance.” In: *Speech and Language Processing*. 3rd ed. Chap. 2. In preparation.
- [JMd] D. Jurafsky and J. H. Martin. *Speech and Language Processing*. 3rd ed. In preparation.
- [Lam94] L. Lamport. *LaTeX : A Documentation Preparation System User’s Guide and Reference Manual*. Addison-Wesley Professional, 1994.
- [RN10] S. J. Russell and P. Norvig. “Natural Language Processing.” In: *Artificial Intelligence: A Modern Approach*. 3rd ed. Pearson, 2010. Chap. 22.