Python For Data Science Cheat Sheet

Matplotlib

Learn Python Interactively at www.DataCamp.com



Matplotlib

Matplotlib is a Python 2D plotting library which produces publication-quality figures in a variety of hardcopy formats and interactive environments across matplotlib platforms.

Prepare The Data

Also see Lists & NumPy

```
>>> import numpy as np
>>> x = np.linspace(0, 10, 100)
>>> y = np.cos(x)
>>> z = np.sin(x)
```

```
2D Data or Images
>>> data = 2 * np.random.random((10, 10))
>>> data2 = 3 * np.random.random((10, 10))
>>> Y, X = np.mgrid(-3:3:100), -3:3:100)]
>>> U = -1 - X**2 + Y
>>> V = 1 + X - Y**2
>>> from matplotlib.cbook import get sample data
>>> img = np.load(get sample data('axes grid/bivariate normal.npy'))
```

Create Plot


```
>>> import matplotlib.pyplot as plt
```

```
>>> fig = plt.figure()
>>> fig2 = plt.figure(figsize=plt.figaspect(2.0))
```

All plotting is done with respect to an Axes. In most cases, a subplot will fit your needs. A subplot is an axes on a grid system.

```
>>> fig.add axes()
>>> axl = fig.add subplot(221) # row-col-num
>>> ax3 = fig.add subplot(212)
>>> fig3, axes = plt.subplots(nrows=2,ncols=2)
>>> fig4, axes2 = plt.subplots(ncols=3)
```

Plot Anatomy & Workflow



Workflow

The basic steps to creating plots with matplotlib are:

```
>>> import matplotlib.pyplot as plt
>>> x = [1,2,3,4]
>>> v = [10,20,25,30]
>>> fig = plt.figure() < Step 2
>>> ax = fig.add subplot(111) 55093
>>> ax.plot(x, y, color='lightblue', linewidth=3) Step 1 d
>>> ax.scatter([2,4,6],
                [5, 15, 25],
                color='darkgreen',
                marker='^')
>>> ax.set xlim(1, 6.5)
>>> plt.savefig('foo.png')
>>> plt.show()
```

Prepare data 2 Create plot 3 Plot 4 Customize plot 5 Save plot 6 Show plot

Customize Plot

Colors, Color Bars & Color Maps

```
>>> plt.plot(x, x, x, x**2, x, x**3)
>>> ax.plot(x, y, alpha = 0.4)
>>> ax.plot(x, y, c='k')
>>> fig.colorbar(im, orientation='horizontal')
>>> im = ax.imshow(img,
                   cmap='seismic')
```

```
>>> fig, ax = plt.subplots()
>>> ax.scatter(x,y,marker=".")
>>> ax.plot(x,y,marker="o")
```

```
>>> plt.plot(x,y,linewidth=4.0)
>>> plt.plot(x,y,ls='solid')
>>> plt.plot(x,y,ls='--')
>>> plt.plot(x,y,'--',x**2,y**2,'-.')
>>> plt.setp(lines,color='r',linewidth=4.0)
```

```
>>> ax.text(1,
            "Example Graph",
            style='italic')
>>> ax.annotate("Sine",
                  xy=(8, 0),
                  xycoords='data',
                  xytext=(10.5, 0),
textcoords='data',
                  arrowprops=dict(arrowstyle="->",
                                connectionstyle="arc3"),)
```

```
>>> plt.title(r'$sigma i=15$', fontsize=20)
```

```
Limits & Autoscaling
>>> ax.margins(x=0.0,y=0.1)
>>> ax.axis('equal')
>>> ax.set(xlim=[0,10.5], ylim=[-1.5,1.5])
>>> ax.set xlim(0,10.5)
```

>>> ax.set(title='An Example Axes', ylabel='Y-Axis' xlabel='X-Axis' >>> ax.legend(loc='best')

>>> ax.xaxis.set(ticks=range(1,5), ticklabels=[3,100,-12,"foo"]) >>> ax.tick params(axis='y', direction='inout', length=10)

Subplot Spacing

>>> fig3.subplots adjust(wspace=0.5, left=0.125. right=0.9, top=0.9, bottom=0.1) >>> fig.tight layout() Axis Spines

>>> axl.spines['top'].set visible(False)

Fit subplot(s) in to the figure area

Add padding to a plot

Set limits for x-axis

Manually set x-ticks

Set limits for x-and y-axis

Set the aspect ratio of the plot to 1

Set a title and x-and v-axis labels

Make y-ticks longer and go in and out

Adjust the spacing between subplots

No overlapping plot elements

Make the top axis line for a plot invisible >>> axl.spines['bottom'].set position(('outward',10)) Move the bottom axis line outward

Plottina Routines

```
>>> lines = ax.plot(x,y)
>>> ax.scatter(x,y)
>>> axes[0,0].bar([1,2,3],[3,4,5])
>>> axes[1,0].barh([0.5,1,2.5],[0,1,2])
>>> axes[1,1].axhline(0,45)
>>> axes[0,1].axvline(0.65)
>>> ax.fill(x,y,color='blue')
>>> ax.fill between (x, y, color='yellow')
```

Draw points with lines or markers connecting them Draw unconnected points, scaled or colored Plot vertical rectangles (constant width) Plot horiontal rectangles (constant height) Draw a horizontal line across axes Draw a vertical line across axes Draw filled polygons

Fill between y-values and o

>>> axes[0,1].arrow(0,0,0.5,0.5)	Add an arrow to the axes
>>> axes[1,1].quiver(y,z)	Plot a 2D field of arrows
>>> axes[0,1].streamplot(X,Y,U,V)	Plot 2D vector fields

222	axi.nist(y)
>>>	ax3.boxplot(y)
>>>	ax3.violinplot(z)

Plot a histogram Make a box and whisker plot Make a violin plot

```
interpolation='nearest',
          vmin=-2.
          vmax=2)
```

Colormapped or RGB arrays

>>> axes2[0].pcolor(data2) >>> axes2[0].pcolormesh(data) >>> CS = plt.contour(Y, X, U) >>> axes2[2].contourf(data1) >>> axes2[2]= ax.clabe1(CS)

Pseudocolor plot of 2D array Pseudocolor plot of 2D array Plot contours Plot filled contours

Label a contour plot

Save Plot

Save figures >>> plt.savefig('foo.png') Save transparent figures >>> plt.savefig('foo.png', transparent=True)

Show Plot >>> plt.show()

Close & Clear

>>> plt.cla() >>> plt.clf() >>> plt.close()

Clear an axis Clear the entire figure Close a window

DataCamp

