Discord Bot Automation Assistant

Discord Bot Automation Assistant Test Plan

Oguz Kaan Yildirim 307637

Table Of Contents

Table O	f Contents	2
INTRDC	OCUTION	3
Unit Tests for Use Cases		7
test_init.py		7
De	scription	7
1.	!project_help	8
2.	!receive_email <file name=""></file>	9
3.	!navigate_to_website	11
4.	!login	13
5.	!close_browser	15
6.	!get_price <website></website>	17
7.	!start_monitoring_price <website></website>	20
8.	!stop_monitoring_price <website></website>	22
9.	!check_availability <website></website>	24
10.	!start_monitoring_availability <website></website>	26
11.	!stop_monitoring_availability <website></website>	28
Conclusion		20

INTRDOCUTION

This document provides an overview of unit testing for a software project aimed at automating the monitoring of product prices and service availability. The goal of the testing is to ensure that all system components function correctly when tested in isolation. This modular approach facilitates the validation of core system functions, including command processing, browser automation, and data export, within a controlled test environment.

The system is composed of modules responsible for interacting with web browsers, processing user commands, retrieving product data from websites, and monitoring availability for services like reservations. These modules have undergone rigorous testing using Python's pytest framework. External systems like websites and Discord commands are simulated using mocks and patches, ensuring expected system behavior in both typical and edge-case scenarios.

This document includes:

- An outline of the testing strategy, scope, and objectives,
- A description of the tools and technologies used during testing,
- Solutions to challenges encountered when testing Discord commands,
- Details on the test setup, implementation, and how the testing framework integrates with the system architecture.

The purpose of the unit testing is to confirm that the system can accurately process user commands, interact with websites, retrieve data, log it, and generate reports. Isolating components during testing enhances confidence in the system's reliability and robustness.

To have a better look at the code/project especially to testing source codes; codes can be found in github. Test files are under UnitTesting Folder.

Unit Tests also has descriptions and executable steps explained in testing.

https://github.com/oguzky7/DiscordBotProject_CISC699/tree/develop/UnitTesting

Test Plan Overview

Scope

The scope of the unit tests covers all critical aspects of the system, ensuring each component performs its intended function independently. This modular testing approach covers:

- Command Processing and Core Features: Verifying that the system properly receives and processes user commands to monitor prices, check availability, and log data efficiently.
- **Browser Interactions:** Ensuring that the system can initiate, navigate, and close browser sessions while effectively interacting with web content.
- Data Logging and Export: Validating that price and availability data are logged and exported in structured formats such as Excel and HTML.
- **Error Handling:** Confirming that the system gracefully handles errors (e.g., invalid commands or network issues) and provides appropriate user feedback.

Objectives

The unit testing aims to:

- **Functional Verification:** Ensure that components like command processing, data retrieval, and logging function correctly in isolation.
- **Component Isolation:** By testing each module independently, failures in one area don't affect others, enabling easier identification of defects.
- Data Accuracy and Consistency: Ensure the system processes price and availability data correctly before logging and exporting it.
- **System Reliability:** Test the system's ability to handle various scenarios, including repeated commands, long-running processes, and invalid inputs.

Strategy

The strategy focuses on modular unit testing, ensuring each part of the system is validated without relying on external dependencies like live websites or browsers. Key elements include:

- Unit Testing: Each system module—command processing, web scraping, or data export—is tested independently.
- **Mocking and Simulation:** External systems are simulated using mocks, allowing tests to focus on internal logic without live interactions.
- Automated Execution: Tests are automated using pytest, ensuring consistency and enabling integration into CI/CD pipelines for automatic execution upon code changes.

Structure of the Tests

The tests are divided into suites targeting specific components:

- Control Layer: Verifies user commands are correctly processed.
- **Entity Layer:** Validates interactions with external systems (e.g., retrieving product prices or checking availability).
- Data Logging and Export: Ensures data is logged and exported without errors.

This structure allows the test framework to expand as the system evolves, enabling independent testing of new features without disrupting existing tests.

Expected Outcomes

This modular approach is expected to yield:

- · Accurate command processing with correct results,
- Error-free logging and export of data,
- Graceful handling of unexpected situations like invalid commands or network failures,
- Stable performance during long-running tasks, such as continuous monitoring of product prices.

Tools and Technologies

Pytest

The primary framework used for test execution is pytest, which supports both synchronous and asynchronous testing. This is critical since many system operations involve real-time monitoring and asynchronous tasks like web scraping. Integration with mocking tools allows thorough simulation of external dependencies, ensuring isolated and repeatable tests.

Unittest.mock

The unittest.mock library is key to isolating system components from external dependencies, such as web browsers and Discord commands. The system uses Mock and AsyncMock to simulate responses from these services, enabling tests to focus on internal logic.

 Mocking External Systems: Mocks simulate browser actions and Discord command inputs, allowing test isolation.

pytest-asyncio

As many system operations are asynchronous, pytest-asyncio manages async code in tests, ensuring that operations like price monitoring are tested properly.

Mocked Selenium

Selenium, a tool for browser automation, is mocked during unit testing to focus on internal logic without requiring real browser instances.

Purpose and Setup

Purpose of Unit Testing

The purpose of unit testing is to validate that each component of the system functions correctly in isolation, focusing on command processing, web interactions, and data export operations.

Challenges in Testing Discord Commands

Testing Discord commands posed a challenge due to the lack of native testing tools for discord.py. To address this, unit tests simulate command inputs and directly interact with the control layer methods, ensuring that the system logic is properly tested without relying on live Discord command handling. Setup of the Testing Environment

The environment is designed to ensure isolated component testing without live system dependencies:

- Mocking and Patching: The unittest.mock library simulates external systems like browsers and
 Discord commands, ensuring independent testing of each component.
- Asynchronous Testing: pytest-asyncio allows proper testing of asynchronous tasks like price monitoring.
- **Test Isolation:** Each test runs independently, ensuring faster execution and easier debugging. Implementation Details

The structure of the tests mirrors the system's modular architecture, with distinct test suites for each layer:

- Control Layer Tests: Validate command processing to ensure inputs are handled correctly.
- Entity Layer Tests: Confirm the core functionality of price retrieval, availability checking, and data export.
- Logging and Export Tests: Ensure data is correctly formatted and saved to Excel and HTML files.

By focusing on these areas, the unit tests confirm that the system's logic functions as intended, and any external dependencies are properly mocked for accurate results.

Unit Tests for Use Cases

Every use case has multiple unit tests in them for every step in main flow.

test init.py

Description

The test_init file serves two main purposes. First, it consolidates all necessary imports to avoid redundant import statements across multiple test files, improving maintainability and consistency. Second, it provides functionality to run all unit tests at once by executing test init.py.

```
import sys, os, pytest, logging, asyncio
sys.path.append(os.path.dirname(os.path.dirname(os.path.abspath(__file__))))
from unittest.mock import patch, AsyncMock, MagicMock, Mock

from control.AvailabilityControl import AvailabilityControl
from control.PriceControl import PriceControl
from control.BrowserControl import BrowserControl
from control.BotControl import BotControl

from entity.BrowserEntity import BrowserEntity
from entity.DataExportEntity import ExportUtils
from entity.PriceEntity import PriceEntity
from entity.AvailabilityEntity import AvailabilityEntity
from entity.EmailEntity import send_email_with_attachments

if __name__ == "__main__":
    pytest.main()
```

If specific tests need to be run individually, each test file has the if __name__ == "__main__": pytest.main([__file__]) block, allowing users to run that specific test file independently. This setup streamlines both the import process and test execution, making it easy to run tests collectively or individually based on the needs of the project.

```
#Test Code is here

# This condition ensures that the pytest runner handles the test run.
if __name__ == "__main__":
    pytest.main([__file__])
```

1. !project help

Description

This test ensures that the BotControl.receive_command() method processes the !project_help command correctly and returns the appropriate help message listing available commands.

Test Steps

The main flow for this use case is as follows, and we have unit tests for the following steps:

1. Control Layer Processing

This test will ensure that BotControl.receive_command() handles the !project_help command correctly and returns the expected help message.

- Command: "!project_help"
- Expected Output: "Here are the available commands:..."

```
@pytest.mark.asyncio
async def test_project_help_control():
    # Start logging the test case
    logging.info("Starting test: test_project_help_control")
    # Mocking the BotControl to simulate control layer behavior
    with patch('control.BotControl.BotControl.receive command', new callable=AsyncMock) as mock command:
        # Setup the mock to return the expected help message
        expected help message = "Here are the available commands:..."
        mock command.return value = expected help message
        control = BotControl()
        result = await control.receive_command("project_help")
        # Logging expected and actual outcomes
        logging.info(f"Expected outcome: '{expected_help_message}'")
        logging.info(f"Actual outcome: '{result}'")
        assert result == expected_help_message
        logging.info("Step 1 executed and Test passed: Control Layer Processing was successful")
```

Figure 1

2. !receive email <file name>

Description

This test ensures that the BotControl.receive_command() method processes the !receive_email command correctly by passing the file name to the email handler, sending the email, and generating the correct response.

Test Steps

The main flow for this use case is as follows, and we have unit tests for the following steps:

1. Control Layer Processing

This test ensures that BotControl.receive_command() handles the !receive_email command correctly, including proper parameter passing and validation.

2. Email Handling

This test focuses on the EmailEntity.send_email_with_attachments() function to ensure it processes the request to send the email with the attached file.

3. Response Generation

This test validates that the control layer correctly interprets the response from the email handling step and returns the appropriate result to the boundary layer.

```
UnitTesting/unitTest_receive_email.py::test_control_layer_processing
                                                                                               ----- live log call -
Starting test: test_control_layer_processing
Expected outcome: 'Email with file 'testfile.txt' sent successfully!'
Actual outcome: Email with file 'testfile.txt' sent successfully!
Step 1 executed and Test passed: Control Layer Processing was successful
UnitTesting/unitTest_receive_email.py::test_email_handling
                                                                             ----- live log call ---
Starting test: test_email_handling
Expected outcome: Contains 'Email with file 'testfile.txt' sent successfully!'
Actual outcome: Email with file 'testfile.txt' sent successfully!
Step 2 executed and Test passed: Email handling was successful
UnitTesting/unitTest_receive_email.py::test_response_generation
                                                                               ----- live log call ---
Starting test: test_response_generation
Expected outcome: 'Email with file 'testfile.txt' sent successfully!'
Actual outcome: Email with file 'testfile.txt' sent successfully!
Step 3 executed and Test passed: Response generation was successful
```

```
@pytest.mark.asyncio
async def test_control_layer_processing():
    # Mocking the email sending function to simulate email sending without actual I/O operations
    with patch('entity.EmailEntity.send email with attachments', new callable=AsyncMock) as mock email:
       mock email.return value = "Email with file 'testfile.txt' sent successfully!"
       bot_control = BotControl()
        result = await bot_control.receive_command("receive_email", "testfile.txt")
        # Assertion to check if the result is as expected
        assert result == "Email with file 'testfile.txt' sent successfully!"
        logging.info("Step 1 executed and Test passed: Control Layer Processing was successful")
def test email handling():
    # Mocking the SMTP class to simulate sending an email
    with patch('smtplib.SMTP') as mock_smtp:
       result = send_email_with_attachments("testfile.txt")
        assert "Email with file 'testfile.txt' sent successfully!" in result
        logging.info("Step 2 executed and Test passed: Email handling was successful")
# test_response_generation.py
@pytest.mark.asyncio
async def test_response_generation():
    # Mocking the BotControl.receive command to simulate control layer behavior
    with patch('control.BotControl.receive_command', new_callable=AsyncMock) as mock_receive:
       mock_receive.return_value = "Email with file 'testfile.txt' sent successfully!"
        # Creating an instance of BotControl
       bot_control = BotControl()
        # Calling the receive command method and passing the command and filename
       result = await bot_control.receive_command("receive_email", "testfile.txt")
        # Assertion to check if the result is as expected
        assert "Email with file 'testfile.txt' sent successfully!" in result
        logging.info("Step 3 executed and Test passed: Response generation was successful")
```

3. !navigate to website

Description

This test ensures that the BotControl.receive_command() method processes the !navigate_to_website command correctly by extracting the URL, navigating to the specified website, and returning the appropriate result.

Test Steps

The main flow for this use case is as follows, and we have unit tests for the following steps:

1. Control Layer Processing

This test ensures that BotControl.receive_command() handles the !navigate_to_website command correctly by extracting the URL and passing it to the browser control.

2. Browser Navigation

This test ensures that the BrowserEntity.navigate_to_website() function processes the navigation request to the specified URL correctly.

3. Response Generation

This test validates that the control layer correctly returns the appropriate result after the browser interaction is completed.

- Command: "!navigate_to_website"
- Test URL: "http://example.com"
- Expected Output: "Navigation successful"

```
UnitTesting/unitTest_navigate_to_website.py::test_command_processing_and_url_extraction
                                                                                                  ---- live log call -
Starting test: test_command_processing_and_url_extraction
Expected outcome: 'Navigating to URL
Actual outcome: Navigating to URL
Step 1 executed and Test passed: Command Processing and URL Extraction was successful
UnitTesting/unitTest_navigate_to_website.py::test_browser_navigation
                                                                                        ----- live log call ----
Starting test: test_browser_navigation
Expected outcome: 'Navigation successful'
Actual outcome: Navigation successful
Step 2 executed and Test passed: Browser Navigation was successful
UnitTesting/unitTest_navigate_to_website.py::test_response_generation
                                                                                        ----- live log call ----
Starting test: test_response_generation
Expected outcome: 'Navigation confirmed'
Actual outcome: Navigation confirmed
Step 3 executed and Test passed: Response Generation was successful
```

```
# Test for Command Processing and URL Extraction
@pytest.mark.asyncio
async def test command processing and url extraction():
    logging.info("Starting test: test_command_processing and url extraction")
    with patch('control.BrowserControl.BrowserControl.receive_command', new_callable=AsyncMock) as mock_receive:
        mock_receive.return_value = "Navigating to URL"
        browser_control = BrowserControl()
        result = await browser_control.receive_command("navigate_to_website", "http://example.com")
        assert result == "Navigating to URL"
        logging.info("Step 1 executed and Test passed: Command Processing and URL Extraction was successful")
@pytest.mark.asyncio
async def test_browser_navigation():
    logging.info("Starting test: test_browser_navigation")
   with patch('entity.BrowserEntity.BrowserEntity.navigate_to_website', new_callable=AsyncMock) as mock_navigate:
        mock_navigate.return_value = "Navigation successful"
        browser_entity = BrowserEntity()
        result = await browser_entity.navigate_to_website("http://example.com")
        assert result == "Navigation successful"
        logging.info("Step 2 executed and Test passed: Browser Navigation was successful")
# Test for Response Generation
@pytest.mark.asyncio
async def test response generation():
    logging.info("Starting test: test_response_generation")
    with patch('control.BrowserControl.BrowserControl.receive_command', new_callable=AsyncMock) as mock_receive:
        mock_receive.return_value = "Navigation confirmed"
        browser_control = BrowserControl()
        result = await browser_control.receive_command("confirm_navigation", "http://example.com")
        assert result == "Navigation confirmed"
        logging.info("Step 3 executed and Test passed: Response Generation was successful")
```

4. !login

Description

This test ensures that the BotControl.receive_command() method processes the !login command correctly by passing the website, username, and password to the browser and verifying the login process.

Test Steps

The main flow for this use case is as follows, and we will test the following steps:

1. Control Layer Processing

This test ensures that BotControl.receive_command() handles the !login command correctly, including proper parameter passing and validation.

2. Website Interaction

This test focuses on the BrowserEntity.login() function to ensure it processes the request to log in to the website using the provided credentials.

3. Response Generation

This test validates that the control layer correctly interprets the response from the website interaction step and returns the appropriate result to the boundary layer.

- Command: "!login"
- Test website: "http://example.com"
- Test username: "user"
- Test password: "pass"
- Expected Output: "Login successful"

```
UnitTesting/unitTest_login.py::test_control_layer_login

Starting test: Control Layer Processing for Login
Expected outcome: Control Object Result: Login successful!
Actual outcome: Control Object Result: Login successful!
Step 1 executed and Test passed: Control Layer Processing for Login was successful

PASSED
UnitTesting/unitTest_login.py::test_website_interaction

Starting test: Website Interaction for Login
Expected to attempt login on 'http://example.com'
Actual outcome: Login successful!
Step 2 executed and Test passed: Website Interaction for Login was successful

PASSED
UnitTesting/unitTest_login.py::test_response_generation

Starting test: Response Generation for Login
Expected outcome: 'Login successful!'
Actual outcome: Login successful!
Step 3 executed and Test passed: Response Generation for Login was successful

PASSED
```

```
@pytest.mark.asyncio
async def test control layer login():
   with patch('entity.BrowserEntity.BrowserEntity.login', new_callable=AsyncMock) as mock_login:
        mock login.return value = "Login successful!"
       browser control = BrowserControl()
        result = await browser control.receive command("login", "example.com", "user", "pass")
        assert result == "Control Object Result: Login successful!"
        logging.info("Step 1 executed and Test passed: Control Layer Processing for Login was successful")
@pytest.fixture
def browser_entity_setup():
   with patch('selenium.webdriver.Chrome') as mock_browser: # Mocking the Chrome browser
        entity = BrowserEntity()  # Creating an instance of BrowserEntity
       entity.driver = Mock() # Mocking the driver
       entity.driver.get = Mock() # Mocking the get method
       entity.driver.find_element = Mock() # Mocking the find_element method
       return entity
def test_website_interaction(browser_entity_setup):
   browser_entity = browser_entity_setup # Setting up the BrowserEntity
   browser_entity.login = Mock(return_value="Login successful!")  # Mocking the login method
   result = browser_entity.login("http://example.com", "user", "pass") # Calling the login method
   assert "Login successful!" in result # Assertion to check if the login was successful
    logging.info("Step 2 executed and Test passed: Website Interaction for Login was successful")
@pytest.mark.asyncio
async def test_response_generation():
   with patch('control.BrowserControl.BrowserControl.receive command', new callable=AsyncMock) as mock receive:
        mock_receive.return_value = "Login successful!"
        browser_control = BrowserControl()
        result = await browser_control.receive_command("login", "example.com", "user", "pass")
        assert "Login successful!" in result
        logging.info("Step 3 executed and Test passed: Response Generation for Login was successful")
```

5. !close browser

Description

This test ensures that the BotControl.receive_command() method processes the !close_browser command correctly by handling browser closure and returning the appropriate response.

Test Steps

The main flow for this use case is as follows, and we have unit tests for the following steps:

1. Control Layer Processing

This test ensures that BotControl.receive_command() handles the !close_browser command correctly.

2. Browser Closing

This test ensures that the BrowserEntity.close_browser() function successfully closes the browser.

3. Response Generation

This test validates that the control layer correctly interprets the browser closure and returns the appropriate result to the boundary layer.

- Command: "!close browser"
- · Expected Output: "Browser closed successfully"

```
@pytest.mark.asyncio
async def test_control_layer_processing():
    with patch('entity.BrowserEntity.BrowserEntity.close browser') as mock close:
        # Configure the mock to return different responses based on the browser state
       mock_close.side_effect = ["Browser closed successfully.", "No browser is currently open."]
       browser_control = BrowserControl()
        # First call simulates the browser being open and then closed
        result = await browser_control.receive_command("close_browser")
        assert result == "Control Object Result: Browser closed successfully."
        result = await browser control.receive command("close browser")
        assert result == "Control Object Result: No browser is currently open."
# Test for Browser Closing
def test_browser_closing():
   with patch('selenium.webdriver.Chrome', new_callable=MagicMock) as mock_chrome:
       mock_driver = mock_chrome.return_value # Mock the return value which acts as the driver
       mock_driver.quit = MagicMock() # Mock the quit method of the driver
        browser_entity = BrowserEntity()
        browser_entity.browser_open = True # Ensure the browser is considered open
        browser entity.driver = mock driver # Set the mock driver as the browser entity's driver
       result = browser_entity.close_browser()
       mock_driver.quit.assert_called_once()
        assert result == "Browser closed."
@pytest.mark.asyncio
async def test_response_generation():
   with patch('control.BrowserControl.BrowserControl.receive command', new callable=AsyncMock) as mock receive:
        mock_receive.return_value = "Browser closed successfully."
        browser control = BrowserControl()
        result = await browser_control.receive_command("close_browser")
        assert result == "Browser closed successfully."
```

6. !get price <website>

Description

This test ensures that the BotControl.receive_command() method processes the !get_price command correctly by extracting the website URL, retrieving the price, and logging the data to both Excel and HTML formats.

Test Steps

The main flow for this use case is as follows, and we have unit tests for the following steps:

1. Control Layer Processing

This test ensures that BotControl.receive_command() handles the !get_price command correctly, including URL parameter handling.

2. Price Retrieval

This test ensures that the PriceEntity.get_price_from_page() function retrieves the correct price from the webpage.

3. Data Logging to Excel

This test verifies that the retrieved price data is correctly logged to an Excel file.

4. Data Logging to HTML

This test ensures that the price data is correctly exported to an HTML file.

Test Data

• Command: "!get_price"

• Test website: "http://example.com/product"

• Expected Output: "100.00"

```
UnitTesting/unitTest get price.py::test control layer processing
Starting test: Control Layer Processing for get price command
Verifying that the receive command correctly processed the 'get price' command
Test passed: Control layer processing correctly handles 'get price'
UnitTesting/unitTest get price.py::test price retrieval
Starting test: Price Retrieval from webpage
Expected fetched price: '100.00'
Test passed: Price retrieval successful and correct
UnitTesting/unitTest get price.py::test response assembly and output
Starting test: Response Assembly and Output
Checking response contains price, Excel and HTML paths
Test passed: Correct response assembled and output
UnitTesting/unitTest get price.py::test data logging excel
Starting test: Data Logging to Excel
Verifying Excel file creation and data logging
Test passed: Data correctly logged to Excel
UnitTesting/unitTest_get_price.py::test_data_logging_html
Starting test: Data Export to HTML
Verifying HTML file creation and data export
Test passed: Data correctly exported to HTML
```

```
# Test 5: Response Assembly and Output

@pytest.mark.asyncio
async def test_response_assembly_and_output():
    logging.info("Starting test: Response Assembly and Output")

# Mock the 'get_price' method to simulate price retrieval
with patch('control.PriceControl.PriceControl.get_price', new_callable=AsyncMock) as mock_get_price:
    mock_get_price.return_value = ("100.00", "Data saved to Excel file at path.xlsx", "Data exported to HTML at path.html")

price_control = PriceControl()

# Call 'receive_command' with 'get_price' command
result = await price_control.receive_command("get_price", "https://example.com/product")

# Unpack the result
price, excel_path, html_path = result

logging.info("Checking response contains price, Excel, and HTML paths")
assert price == "100.00", f"Price did not match expected value, got {price}"
assert "path.xlsx" in excel_path, f"Excel path did not match, got {excel_path}"
assert "path.html" in html_path, f"HTML path did not match, got {html_path}"

logging.info("Test passed: Correct response assembled and output")
```

```
@pytest.mark.asyncio
async def test_control_layer_processing():
     logging.info("Starting test: Control Layer Processing for 'get_price' command")
     with patch('control.PriceControl.PriceControl.get_price', new_callable=AsyncMock) as mock_get_price:
          mock_get_price.return_value = ("100.00", "Data saved to Excel file at path.xlsx", "Data exported to HTML at path.html")
          price_control = PriceControl()
          # Simulate the command processing
          result = await price_control.receive_command("get_price", "https://example.com/product")
          logging.info("Verifying that the receive_command correctly processed the 'get_price' command")
          price, excel_path, html_path = result
          assert price == "100.00", f"Expected price '100.00', got {price}"
assert excel_path == "Data saved to Excel file at path.xlsx", f"Expected Excel path 'path.xlsx', got {excel_path}"
assert html_path == "Data exported to HTML at path.html", f"Expected HTML path 'path.html', got {html_path}"
          logging.info("Test passed: Control layer processing correctly handles 'get_price'")
@pytest.mark.asyncio
async def test_price_retrieval():
     logging.info("Starting test: Price Retrieval from webpage")
     with patch('entity.PriceEntity.PriceEntity.get_price_from_page', return_value="100.00") as mock_price:
          price_control = PriceControl()
          # Call the `get_price` method
result = await price_control.get_price("https://example.com/product")
          logging.info("Expected fetched price: '100.00'")
          assert "100.00" in result, f"Expected price '100.00', got {result}" logging.info("Test passed: Price retrieval successful and correct")
@pytest.mark.asyncio
async def test_data_logging_excel():
    logging.info("Starting test: Data Logging to Excel")
    # Mock the `get_price` method to avoid browser interaction
with patch('control.PriceControl.PriceControl.get_price', new_callable=AsyncMock) as mock_get_price:
         mock_get_price.return_value = ("100.00", "Data saved to Excel file at path.xlsx", "Data exported to HTML file at path.html")
        # Mock the log_to_excel method to simulate Excel data logging with patch('entity.DataExportEntity.ExportUtils.log_to_excel', return_value="Data saved to Excel file at path.xlsx") as mock_excel:
             price_control = PriceControl()
              _, excel_result, _ = await price_control.get_price("https://example.com/product")
             logging.info("Verifying Excel file creation and data logging")
assert "path.xlsx" in excel_result, f"Expected Excel path 'path.xlsx', got {excel_result}"
logging.info("Test passed: Data correctly logged to Excel")
# Test 4: Data Export to HTM
@pytest.mark.asyncio
async def test_data_logging_html():
     with patch('control.PriceControl.PriceControl.get_price', new_callable=AsyncMock) as mock_get_price:
         mock get price.return value = ("100.00", "Data saved to Excel file at path.xlsx", "Data exported to HTML file at path.html")
             price_control = PriceControl()
             _, _, html_result = await price_control.get_price("https://example.com/product")
              logging.info("Verifying HTML file creation and data export")
              assert "path.html' in html_result, f"expected HTML path 'path.html', got {html_result}" logging.info("Test passed: Data correctly exported to HTML")
```

7. !start monitoring price <website>

Description

This test ensures that the BotControl.receive_command() method processes the !start_monitoring_price command correctly by initiating price monitoring at regular intervals for the specified website.

Test Steps

The main flow for this use case is as follows, and we have unit tests for the following steps:

1. Control Layer Processing

This test ensures that BotControl.receive_command() handles the !start_monitoring_price command correctly, including proper URL parameter passing.

2. Price Monitoring Initiation

This test ensures that price monitoring is initiated and repeated at regular intervals by calling the get_price() function.

3. Stop Monitoring Logic

This test confirms that price monitoring can be stopped correctly and the final results are collected.

- Command: "!start monitoring price"
- Test website: "http://example.com/product"
- Expected Output: "Price monitoring started"

```
UnitTesting/unitTest_start_monitoring_price.py::test_control_layer_processing
Starting test: test control layer processing
Testing command processing for URL: https://example.com/product with frequency: 2
Patching receive command method...
Verifying if 'start monitoring price' was processed correctly...
Test passed: Control layer processed 'start monitoring price' correctly.
PASSED
UnitTesting/unitTest start monitoring price.py::test price monitoring initiation
Starting test: test price monitoring initiation
Initiating price monitoring for URL: https://example.com/product with frequency: 3
Patching get_price method...
Monitoring task started.
Simulated monitoring for 5 seconds, checking number of calls to get price.
Test passed: Price monitoring initiated and 'get price' called twice.
Stopping price monitoring...
Test passed: Monitoring stopped with 2 results.
UnitTesting/unitTest_start_monitoring_price.py::test_stop_monitoring_logic
Starting test: test stop monitoring logic
Initiating monitoring to test stopping logic for URL: https://example.com/product with frequency: 2
Patching get_price method...
Monitoring task started.
Simulated monitoring for 3 seconds, stopping monitoring now.
Test passed: Monitoring stopped with 1 result(s).
PASSED
```

8. !stop monitoring price <website>

Description

This test ensures that the BotControl.receive_command() method processes the !stop_monitoring_price command correctly by stopping the monitoring process and generating a final summary of the results.

Test Steps

The main flow for this use case is as follows, and we have unit tests for the following steps:

1. Control Layer Processing

This test ensures that BotControl.receive_command() handles the !stop_monitoring_price command correctly.

2. Stop Monitoring Logic

This test ensures that the monitoring process is stopped and results are collected.

3. Final Summary Generation

This test validates that a final summary of the price monitoring results is generated and returned.

- Command: "!stop monitoring price"
- Test website: "http://example.com/product"
- Expected Output: "Price monitoring stopped"

```
UnitTesting/unitTest stop monitoring price.py::test control layer processing
Starting test: test_control_layer_processing
Patching receive command method...
Verifying if 'stop monitoring price' was processed correctly...
Test passed: Control layer processed 'stop_monitoring_price' command correctly.
UnitTesting/unitTest_stop_monitoring_price.py::test_stop_monitoring_logic
Starting test: test_stop_monitoring_logic
Patching stop monitoring price method...
Checking if monitoring stopped and results were collected...
Monitoring was successfully stopped.
Results were collected successfully.
Test passed: Stop monitoring logic executed correctly.
UnitTesting/unitTest stop monitoring price.py::test final summary generation
Starting test: test final summary generation
Stopping price monitoring and generating final summary...
Verifying the final summary contains the collected results...
Test passed: Final summary generated correctly.
PASSED
```

9. !check availability <website>

Description

This test ensures that the BotControl.receive_command() method processes the !check_availability command correctly by checking the availability of the specified service on the website and logging the results.

Test Steps

The main flow for this use case is as follows, and we have unit tests for the following steps:

1. Control Layer Processing

This test ensures that BotControl.receive_command() handles the !check_availability command correctly.

2. Availability Checking

This test ensures that the AvailabilityEntity.check_availability() function checks the availability of the specified service.

3. Data Logging to Excel

This test verifies that the availability data is logged to an Excel file.

4. Data Logging to HTML

This test ensures that the availability data is exported to an HTML file.

- Command: "!check_availability"
- Test website: "http://example.com/reservation"
- Expected Output: "Availability confirmed"

UnitTesting/unitTest_check_availability.py::test_control_layer_command_reception

Starting test: Control Layer Command Reception for check_availability command
Verifying that the receive_command was called with correct parameters
Test passed: Control layer correctly processes 'check_availability'
PASSED
UnitTesting/unitTest_check_availability.py::test_availability_checking PASSED
UnitTesting/unitTest_check_availability.py::test_data_logging_excel

Starting test: Data Logging to Excel for check_availability command
Verifying Excel file creation and data logging
Test passed: Data correctly logged to Excel
PASSED
UnitTesting/unitTest_check_availability.py::test_data_logging_html

Starting test: Data Export to HTML for check_availability command
Verifying HTML file creation and data export
Test passed: Data correctly exported to HTML
PASSED

10. !start_monitoring_availability <website>

Description

This test ensures that the BotControl.receive_command() method processes the !start_monitoring_availability command correctly by initiating service availability monitoring at regular intervals for the specified website.

Test Steps

The main flow for this use case is as follows, and we have unit tests for the following steps:

1. Control Layer Processing

This test ensures that BotControl.receive_command() handles the !start_monitoring_availability command correctly.

2. Availability Monitoring Initiation

This test ensures that service availability monitoring is initiated and repeated at regular intervals.

3. Stop Monitoring Logic

This test confirms that availability monitoring can be stopped correctly and the final results are collected.

- Command: "!start monitoring availability"
- Test website: "http://example.com/reservation"
- Expected Output: "Availability monitoring started"

```
UnitTesting/unitTest start monitoring availability.py::test control layer processing
Starting test: test_control_layer_processing
Testing command processing for URL: https://example.com/availability with frequency: 1
Patching receive command method...
Verifying if 'start monitoring availability' was processed correctly...
Test passed: Control layer processed 'start_monitoring availability' correctly.
UnitTesting/unitTest start monitoring availability.py::test availability monitoring initiation
Starting test: test availability monitoring initiation
Initiating availability monitoring for URL: https://example.com/availability with frequency: 3
Patching check availability method...
Monitoring task started.
Simulated monitoring for 5 seconds, checking number of calls to check_availability.
Test passed: Availability monitoring initiated and 'check availability' called twice.
Stopping availability monitoring...
Test passed: Monitoring stopped with 2 results.
UnitTesting/unitTest start monitoring_availability.py::test_stop_monitoring_logic
Starting test: test stop monitoring logic
Initiating monitoring to test stopping logic for URL: https://example.com/availability with frequency: 1
Patching check_availability method...
Monitoring task started.
Simulated monitoring for 6 seconds, stopping monitoring now.
Test passed: Monitoring stopped with 1 result(s).
```

11. !stop monitoring availability < website>

Description

This test ensures that the BotControl.receive_command() method processes the

!stop monitoring availability command correctly by stopping the monitoring process and generating a

final summary of the results.

Test Steps

The main flow for this use case is as follows, and we have unit tests for the following steps:

1. Control Layer Processing

This test ensures that BotControl.receive_command() handles the !stop_monitoring_availability command correctly.

2. Stop Monitoring Logic

This test ensures that the monitoring process is stopped and results are collected.

3. Final Summary Generation

This test validates that a final summary of the availability monitoring results is generated and returned.

- Command: "!stop monitoring availability"
- Test website: "http://example.com/reservation"
- Expected Output: "Availability monitoring stopped"

```
UnitTesting/unitTest_stop_monitoring_availability.py::test_control_layer_processing

Starting test: Control Layer Processing for stop_monitoring_availability command
Test passed: Control layer processed stop_monitoring_availability command successfully.

PASSED
UnitTesting/unitTest_stop_monitoring_availability.py::test_monitoring_termination

Starting test: Monitoring Termination for stop_monitoring_availability
Stopping availability monitoring...
Test passed: Monitoring was terminated successfully.

PASSED
UnitTesting/unitTest_stop_monitoring_availability.py::test_final_summary_generation

Starting test: Final Results Summary for stop_monitoring_availability
Stopping availability monitoring and generating final summary...
Test passed: Final summary generated correctly.

PASSED
```

Conclusion

This project aimed to rigorously test various functionalities of the Discord bot, particularly focusing on control and entity layers across key use cases such as availability checking, price monitoring, and email handling. The test cases were structured to cover command reception, process execution, and result validation, ensuring that each component behaved as expected under both normal and boundary conditions.

Through the execution of the 34 unit tests, various issues were identified, such as ModuleNotFoundErrors and assertion failures, which were addressed promptly. This defect identification helped improve the robustness of the bot, highlighting the importance of unit testing in developing reliable software systems.

The structured approach, using pytest and mocking frameworks, allowed the testing process to be efficient and scalable. While limitations in testing the boundary layers, particularly in simulating real-world Discord interactions, were acknowledged, the tests effectively ensured that the core logic and functionalities performed correctly.

In conclusion, the thorough testing and defect resolution process not only enhanced the bot's performance but also provided valuable insights into software testing strategies, emphasizing the need for comprehensive test coverage in ensuring product quality.