

```
--- main.py ---
```

```
import discord
```

```
from discord.ext import commands
```

```
from entity.BrowserEntity import BrowserEntity
```

```
from boundary.HelpBoundary import HelpBoundary
```

```
from boundary.AccountBoundary import AccountBoundary
```

```
from boundary.StopBoundary import StopBoundary # Import StopBoundary
```

```
from boundary.LaunchBrowserBoundary import LaunchBrowserBoundary # Import
BrowserBoundary for browser launch
```

```
from boundary.CloseBrowserBoundary import CloseBrowserBoundary # Import
CloseBrowserBoundary for closing browser
```

```
from boundary.LoginBoundary import LoginBoundary
```

```
from boundary.NavigationBoundary import NavigationBoundary # Import NavigationBoundary for
navigating to a URL
```

```
from utils.Config import Config
```

```
# Set up the bot's intents
```

```
intents = discord.Intents.default()
```

```
intents.message_content = True # Enable reading message content
```

```
# Initialize the bot with the correct command prefix and intents
```

```
class MyBot(commands.Bot):
```

```
    async def setup_hook(self):
```

```
        browser_entity = BrowserEntity()
```

```
        await self.add_cog(HelpBoundary(self)) # Register HelpBoundary
```

```
        await self.add_cog(AccountBoundary(self)) # Register AccountBoundary
```

```
        await self.add_cog(StopBoundary(self)) # Register StopBoundary
```

```

await self.add_cog(LaunchBrowserBoundary(self, browser_entity))

await self.add_cog(NavigationBoundary(self, browser_entity))

        await self.add_cog(CloseBrowserBoundary(self, browser_entity))    # Register
CloseBrowserBoundary to close browser

await self.add_cog(LoginBoundary(self, browser_entity))


async def on_ready(self):

    # Greet the user when the bot is online

    print(f"Logged in as {self.user}")

        channel = discord.utils.get(self.get_all_channels(), name="general") # Adjust the channel
name

    if channel:

        await channel.send("Hi, I'm online! Type '!project_help' to see what I can do.")


async def on_command_error(self, ctx, error):

    """Handle unrecognized commands."""

    if isinstance(error, commands.CommandNotFound):

        await ctx.send("Command not recognized. Type !project_help to see the list of commands.")


# Run the bot

if __name__ == "__main__":

    bot = MyBot(command_prefix="!", intents=intents)

    print("Bot is starting...")

    bot.run(Config.DISCORD_TOKEN) # Run the bot with your token

```

--- Tests_URLs.txt ---

database password: postgres

Working Commands: Test commands

!project_help

!fetch_all_accounts

!add_account discordtestUser discordTestPass discordtestWebsite

!fetch_account_by_website discordtestWebsite

!delete_account 4

!stop_bot

!launch_browser

!close_browser

!navigate_to_website <https://www.google.com/>

!login bestbuy

!get_price

<https://www.bestbuy.com/site/microsoft-xbox-wireless-controller-for-xbox-series-x-xbox-series-s-xbox-one-windows-devices-sky-cipher-special-edition/6584960.p?skuId=6584960>

!monitor_price

<https://www.bestbuy.com/site/microsoft-xbox-wireless-controller-for-xbox-series-x-xbox-series-s-xbox-one-windows-devices-sky-cipher-special-edition/6584960.p?skuId=6584960>

!stop_monitoring

!check_availability <https://www.opentable.com/r/bar-spero-washington/>

!monitor_availability <https://www.opentable.com/r/bar-spero-washington/>

!monitor_availability <https://www.opentable.com/r/bar-spero-washington/> "October 2"

!stop_monitoring_availability

!stop_bot

Working on it:

!check_availability <https://www.opentable.com/r/bar-spero-washington/> "August 22" "8:00 PM"

URLs to Test:

<https://www.opentable.com/r/bar-spero-washington/>

https://www.ebay.com/itm/314411766963?_trkparms=amclsrc%3DITM%26aid%3D777008%26algo%3DPERSONAL.TOPIC%26ao%3D1%26asc%3D20240603121456%26meid%3Da07931f944bc4a5b95376fe64d0ab035%26pid%3D102177%26rk%3D1%26rkt%3D1%26itm%3D314411766963%26pmt%3D1%26noa%3D1%26pg%3D4375194%26algv%3DNoSignalMostWatched%26brand%3DSimpliSafe&_trksid=p4375194.c102177.m166540&_trkparms=parentrq%3A71497a9c1910a8cd54f819a0ffff582e%7Cpageci%3A59d1354a-5f2b-11ef-9c4d-f2c982e61003%7Ciid%3A1%7Cvlpname%3Avlp_homepage

<https://www.trendyol.com/puma/rebound-v6-low-p-736020132?boutiqueId=61&merchantId=184734&sav=true>

!get_price

<https://www.trendyol.com/puma/rebound-v6-low-p-736020132?boutiqueId=61&merchantId=184734&sav=true>

ok, now I want to add !stop_bot using BCE structure and dont forget professor feedbacks.

Please always check the pdf file I provided to you with all the codes in it for correct code. just put the working code in the correct files/places

--- AccountBoundary.py ---

```
from discord.ext import commands
```

```
from control.AccountControl import AccountControl
```

```
class AccountBoundary(commands.Cog):
```

```
def __init__(self, bot):
```

```
    self.bot = bot
```

```
    self.control = AccountControl()
```

```
@commands.command(name="fetch_all_accounts")
```

```
async def fetch_all_accounts(self, ctx):
```

```
    """Fetch all accounts from the database."""
```

```
    await ctx.send("Command recognized, taking action: Fetching all accounts.")
```

```
    accounts = self.control.fetch_all_accounts()
```

```
    if accounts:
```

```
        account_list = "\n".join([f"ID: {acc[0]}, Username: {acc[1]}, Password: {acc[2]}, Website: {acc[3]}" for acc in accounts])
```

```
        await ctx.send(f"Accounts:\n{account_list}")
```

```
    else:
```

```
        await ctx.send("No accounts found.")
```

```
@commands.command(name="fetch_account_by_website")
```

```
async def fetch_account_by_website(self, ctx, website: str):
```

```
    """Fetch an account by website."""
```

```
    await ctx.send(f"Command recognized, taking action: Fetching account for website {website}.")
```

```
    account = self.control.fetch_account_by_website(website)
```

```
    if account:
```

```
        await ctx.send(f"Account for {website}: Username: {account[0]}, Password: {account[1]}")
```

```
    else:
```

```
        await ctx.send(f"No account found for website {website}.")
```

```
@commands.command(name="add_account")
```

```

async def add_account(self, ctx, username: str, password: str, website: str):

    """Add a new account."""

    await ctx.send("Command recognized, taking action: Adding a new account.")

    result = self.control.add_account(username, password, website)

    if result:

        await ctx.send(f"Account for {website} added successfully.")

    else:

        await ctx.send(f"Failed to add account for {website}.")

```

```

@commands.command(name="delete_account")

async def delete_account(self, ctx, account_id: int):

    """Delete an account by ID."""

    await ctx.send(f"Command recognized, taking action: Deleting account with ID {account_id}.")

    result = self.control.delete_account(account_id)

    if result:

        await ctx.send(f"Account with ID {account_id} deleted successfully.")

    else:

        await ctx.send(f"Failed to delete account with ID {account_id}.")

```

--- CloseBrowserBoundary.py ---

```

from discord.ext import commands

from control.CloseBrowserControl import CloseBrowserControl

from entity.BrowserEntity import BrowserEntity

class CloseBrowserBoundary(commands.Cog):

```

```

def __init__(self, bot, browser_entity):

    self.bot = bot

    self.close_browser_control = CloseBrowserControl(browser_entity) # Pass the browser_entity
to the control

@commands.command(name='close_browser')

async def close_browser(self, ctx):

    await ctx.send("Command recognized, taking action to close the browser.")

    result = self.close_browser_control.close_browser()

    await ctx.send(result)

```

--- HelpBoundary.py ---

```

from discord.ext import commands

```

```

from control.HelpControl import HelpControl

```

```

class HelpBoundary(commands.Cog): # Cog to register with the bot

```

```

    def __init__(self, bot):

        self.bot = bot

        self.control = HelpControl() # Initialize control object

```

```

@commands.command(name="project_help")

```

```

async def project_help(self, ctx):

    """Send a message with all the available commands."""

    await ctx.send("Command recognized, taking action.") # Acknowledge the command

    help_message = self.control.get_help_message() # Get help message from control

    await ctx.send(help_message) # Send help message to Discord

```


--- LaunchBrowserBoundary.py ---

```
from discord.ext import commands
```

```
from control.LaunchBrowserControl import LaunchBrowserControl
```

```
class LaunchBrowserBoundary(commands.Cog):
```

```
    def __init__(self, bot, browser_entity):
```

```
        self.bot = bot
```

```
        self.launch_browser_control = LaunchBrowserControl(browser_entity) # Pass the
```

```
browser_entity to the control
```

```
    @commands.command(name='launch_browser')
```

```
    async def launch_browser(self, ctx):
```

```
        await ctx.send("Command recognized, taking action.")
```

```
        result = self.launch_browser_control.launch_browser()
```

```
        await ctx.send(result)
```

--- LoginBoundary.py ---

```
from discord.ext import commands
```

```
from control.LoginControl import LoginControl
```

```
class LoginBoundary(commands.Cog):
```

```
    def __init__(self, bot, browser_entity):
```

```
        self.bot = bot
```

```
        self.login_control = LoginControl(browser_entity) # Pass browser_entity to control
```

```
@commands.command(name='login')

async def login(self, ctx, site: str):

    await ctx.send("Command recognized, taking action.")

    result = await self.login_control.login(site)

    await ctx.send(result)
```

--- NavigationBoundary.py ---

```
import discord

from discord.ext import commands

from control.NavigationControl import NavigationControl
```

```
class NavigationBoundary(commands.Cog):

    def __init__(self, bot, browser_entity):

        self.bot = bot

        self.navigation_control = NavigationControl(browser_entity)
```

```
@commands.command(name='navigate_to_website')

async def navigate_to_website(self, ctx, site_name: str):

    await ctx.send("Command recognized, taking action.")

    result = self.navigation_control.navigate_to_website(site_name)

    await ctx.send(result)
```

--- StopBoundary.py ---

```
from discord.ext import commands
```

```
from control.StopControl import StopControl
```

```
class StopBoundary(commands.Cog):
```

```
    def __init__(self, bot):
```

```
        self.bot = bot
```

```
        self.control = StopControl()
```

```
    @commands.command(name="stop_bot")
```

```
    async def stop_bot(self, ctx):
```

```
        """Shut down the bot."""
```

```
        await ctx.send("Command recognized, taking action: Shutting down the bot.")
```

```
        await self.control.stop_bot(ctx, self.bot) # Call the control's method to stop the bot
```

```
--- __init__.py ---
```

```
#empty init file
```

```
--- AccountControl.py ---
```

```
from DataObjects.AccountDAO import AccountDAO
```

```
from DataObjects.AccountDTO import AccountDTO # Assuming the DTO file is in the dto folder
```

```
class AccountControl:
```

```
    def __init__(self):
```

```
        self.account_dao = AccountDAO()
```

```
    def add_account(self, username: str, password: str, website: str):
```

```
        """Add a new account to the database using DTO."""
```

```
self.account_dao.connect() # Establish database connection

account_dto = AccountDTO(username, password, website)

result = self.account_dao.add_account(account_dto)

self.account_dao.close() # Close the connection

return result
```

```
def delete_account(self, account_id: int):

    """Delete an account by ID."""

    self.account_dao.connect() # Establish database connection

    result = self.account_dao.delete_account(account_id)

    self.account_dao.reset_id_sequence()

    self.account_dao.close() # Close the connection

    return result
```

```
def fetch_all_accounts(self):

    """Fetch all accounts using the DAO."""

    self.account_dao.connect() # Establish database connection

    accounts = self.account_dao.fetch_all_accounts() # Fetch accounts from DAO

    self.account_dao.close() # Close the connection

    return accounts if accounts else None
```

```
def fetch_account_by_website(self, website: str):

    """Fetch an account by website."""

    self.account_dao.connect() # Establish database connection

    account = self.account_dao.fetch_account_by_website(website)
```

```
self.account_dao.close() # Close the connection

return account if account else None
```

--- CloseBrowserControl.py ---

```
class CloseBrowserControl:

    def __init__(self, browser_entity):

        self.browser_entity = browser_entity

    def close_browser(self):

        return self.browser_entity.close_browser()
```

--- HelpControl.py ---

```
class HelpControl:

    def get_help_message(self):

        """Returns a list of available bot commands."""

        return (

            "Here are the available commands:\n"

            "!project_help - Get help on available commands.\n"

            "!login 'website' - Log in to a website.\n"

            "!launch_browser - Launch the browser.\n"

            "!close_browser - Close the browser.\n"

            "!navigate_to_website - Navigate to a website.\n"

            "!get_price - Check the price of a product.\n"

            "!monitor_price - monitor a product price.\n"

            "!stop_monitoring - Stop monitoring a product.\n"
```

```
"!check_availability - Check the availability in a restaurant.\n"
```

```
"!monitor_availability - Monitor the availability in a restaurant.\n"
```

```
"!stop_monitoring_availability - Stop monitoring availability.\n"
```

```
"!stop_bot - Stop the bot.\n"
```

```
)
```

```
# "##!receive_notifications - Receive notifications for price changes.\n"
```

```
# "##!extract_data - Export data to Excel or HTML.\n"
```

```
--- LaunchBrowserControl.py ---
```

```
class LaunchBrowserControl:
```

```
    def __init__(self, browser_entity):
```

```
        self.browser_entity = browser_entity
```

```
    def launch_browser(self):
```

```
        return self.browser_entity.launch_browser()
```

```
--- LoginControl.py ---
```

```
from entity.BrowserEntity import BrowserEntity
```

```
from control.AccountControl import AccountControl
```

```
from selenium.webdriver.common.by import By
```

```
from selenium.webdriver.support.ui import WebDriverWait
```

```
from selenium.webdriver.support import expected_conditions as EC
```

```
from utils.css_selectors import Selectors
```

```
import asyncio
```

```
class LoginControl:
```

```
    def __init__(self, browser_entity):
```

```
        self.browser_entity = browser_entity # Manages browser state
```

```
        self.account_control = AccountControl() # Manages account data
```

```
    async def login(self, site: str):
```

```
        # Step 1: Fetch account credentials from the entity object
```

```
        account_info = self.account_control.fetch_account_by_website(site)
```

```
        if not account_info:
```

```
            return f"No account found for {site}"
```

```
        # account_info is a tuple (username, password), so access it by index
```

```
        username, password = account_info[0], account_info[1]
```

```
        print(f"Username: {username}, Password: {password}")
```

```
        # Step 3: Get the URL from the CSS selectors
```

```
        url = Selectors.get_selectors_for_url(site).get('url')
```

```
        print(url)
```

```
        if not url:
```

```
            return f"URL for {site} not found."
```

```
        # Step 4: Navigate to the URL and perform login (handled by the entity object)
```

```
        result = await self.browser_entity.perform_login(url, username, password)
```

```
        return result
```

--- NavigationControl.py ---

```
from entity.BrowserEntity import BrowserEntity
```

```
from utils.css_selectors import Selectors
```

```
class NavigationControl:
```

```
    def __init__(self, browser_entity):
```

```
        self.browser_entity = browser_entity
```

```
    def navigate_to_website(self, site: str):
```

```
        # Fetch URL in the control
```

```
        url = Selectors.get_selectors_for_url(site).get('url')
```

```
        if not url:
```

```
            return f"URL for {site} not found."
```

```
        return self.browser_entity.navigate_to_url(url)
```

--- StopControl.py ---

```
import discord
```

```
class StopControl:
```

```
    async def stop_bot(self, ctx, bot):
```

```
        """Stop the bot gracefully."""
```

```
        await ctx.send("The bot is shutting down...")
```

```
        await bot.close() # Close the bot
```



```
--- __init__.py ---
```

```
#empty init file
```

```
--- AccountDAO.py ---
```

```
import psycopg2
```

```
from utils.Config import Config
```

```
from DataObjects.AccountDTO import AccountDTO
```

```
class AccountDAO:
```

```
    def __init__(self):
```

```
        self.dbname = "postgres"
```

```
        self.user = "postgres"
```

```
        self.host = "localhost"
```

```
        self.port = "5432"
```

```
        self.password = Config.DATABASE_PASSWORD
```

```
    def connect(self):
```

```
        """Establish a database connection."""
```

```
        try:
```

```
            self.connection = psycopg2.connect(
```

```
                dbname=self.dbname,
```

```
                user=self.user,
```

```
                password=self.password,
```

```
                host=self.host,
```

```
                port=self.port
```

```
            )
```

```
self.cursor = self.connection.cursor()
```

```
print("Database Connection Established.")
```

```
except Exception as error:
```

```
    print(f"Error connecting to the database: {error}")
```

```
    self.connection = None
```

```
    self.cursor = None
```

```
def add_account(self, account_dto: AccountDTO):
```

```
    """Add a new account to the database using DTO."""
```

```
    try:
```

```
        query = "INSERT INTO accounts (username, password, website) VALUES (%s, %s, %s)"
```

```
        values = (account_dto.username, account_dto.password, account_dto.website)
```

```
        self.cursor.execute(query, values)
```

```
        self.connection.commit()
```

```
        print(f"Account {account_dto.username} added successfully.")
```

```
        return True
```

```
except Exception as error:
```

```
    print(f"Error inserting account: {error}")
```

```
    return False
```

```
def fetch_account_by_website(self, website):
```

```
    """Fetch account credentials for a specific website."""
```

```
    try:
```

```
        query = "SELECT username, password FROM accounts WHERE LOWER(website) =  
LOWER(%s)"
```

```
        self.cursor.execute(query, (website,))
```

```
    return self.cursor.fetchone()
```

```
except Exception as error:
```

```
    print(f"Error fetching account for website {website}: {error}")
```

```
    return None
```

```
def fetch_all_accounts(self):
```

```
    """Fetch all accounts from the database."""
```

```
    try:
```

```
        query = "SELECT id, username, password, website FROM accounts"
```

```
        self.cursor.execute(query)
```

```
        return self.cursor.fetchall()
```

```
except Exception as error:
```

```
    print(f"Error fetching accounts: {error}")
```

```
    return []
```

```
def delete_account(self, account_id):
```

```
    """Delete an account by its ID."""
```

```
    try:
```

```
        self.cursor.execute("DELETE FROM accounts WHERE id = %s", (account_id,))
```

```
        self.connection.commit()
```

```
        if self.cursor.rowcount > 0: # Check if any rows were affected
```

```
            print(f"Account with ID {account_id} deleted successfully.")
```

```
            return True
```

```
    else:
```

```
        print(f"No account found with ID {account_id}.")
```

```
        return False
```

except Exception as error:

print(f"Error deleting account: {error}")

return False

def reset_id_sequence(self):

"""Reset the ID sequence to the maximum ID."""

try:

reset_query = "SELECT setval('accounts_id_seq', (SELECT MAX(id) FROM accounts))"

self.cursor.execute(reset_query)

self.connection.commit()

print("ID sequence reset successfully.")

except Exception as error:

print(f"Error resetting ID sequence: {error}")

def close(self):

"""Close the database connection."""

if self.cursor:

self.cursor.close()

if self.connection:

self.connection.close()

print("Database connection closed.")

--- AccountDTO.py ---

dto/DataExportDTO.py

```
class AccountDTO:
```

```
    def __init__(self, username, password, website):
```

```
        self.username = username
```

```
        self.password = password
```

```
        self.website = website
```

```
--- DataExportDTO.py ---
```

```
class DataExportDTO:
```

```
    def __init__(self, command, url, result, entered_date=None, entered_time=None):
```

```
        self.command = command
```

```
        self.url = url
```

```
        self.result = result
```

```
        self.entered_date = entered_date
```

```
        self.entered_time = entered_time
```

```
    def validate(self):
```

```
        """Perform simple validation on the input data."""
```

```
        if not self.command or not self.url or not self.result:
```

```
            raise ValueError("Command, URL, and Result must all be provided.")
```

```
        return True # If validation passes
```

```
    def to_dict(self):
```

```
        """Convert the DTO to a dictionary for export utilities like Excel or HTML generation."""
```

```
        return {
```

```
            "Command": self.command,
```

```
            "URL": self.url,
```

```
"Result": self.result,  
"Entered Date": self.entered_date or "N/A",  
"Entered Time": self.entered_time or "N/A"  
}
```

--- BrowserEntity.py ---

```
import asyncio  
  
from selenium.webdriver.common.by import By  
from selenium.webdriver.support.ui import WebDriverWait  
from selenium.webdriver.support import expected_conditions as EC  
from selenium import webdriver  
from selenium.webdriver.chrome.service import Service  
from utils.css_selectors import Selectors
```

```
class BrowserEntity:  
    def __init__(self):  
        self.driver = None  
        self.browser_open = False  
  
    def set_browser_open(self, is_open: bool):  
        self.browser_open = is_open  
  
    def is_browser_open(self) -> bool:  
        return self.browser_open
```

```
def launch_browser(self):

    if not self.browser_open:

        options = webdriver.ChromeOptions()

        options.add_argument("--remote-debugging-port=9222")

        options.add_experimental_option("excludeSwitches", ["enable-automation"])

        options.add_experimental_option('useAutomationExtension', False)

        options.add_argument("--start-maximized")

        options.add_argument("--disable-notifications")

        options.add_argument("--disable-popup-blocking")

        options.add_argument("--disable-infobars")

        options.add_argument("--disable-extensions")

        options.add_argument("--disable-webgl")

        options.add_argument("--disable-webrtc")

        options.add_argument("--disable-rtc-smoothing")


        self.driver = webdriver.Chrome(service=Service(), options=options)

        self.browser_open = True

        return "Browser launched."

    else:

        return "Browser is already running."


def close_browser(self):

    if self.browser_open and self.driver:

        self.driver.quit()

        self.browser_open = False

        return "Browser closed."
```

else:

return "No browser is currently open."

def navigate_to_url(self, url):

Ensure the browser is launched before navigating

if not self.is_browser_open():

launch_message = self.launch_browser()

print(launch_message)

Navigate to the URL if browser is open

if self.driver:

self.driver.get(url)

return f"Navigated to {url}"

else:

return "Failed to open browser."

async def perform_login(self, url, username, password):

Navigate to the website

self.navigate_to_url(url)

await asyncio.sleep(3)

Enter the username

email_field = self.driver.find_element(By.CSS_SELECTOR,

Selectors.get_selectors_for_url(url)['email_field'])

email_field.send_keys(username)


```
await asyncio.sleep(3)
```

```
# Enter the password
```

```
password_field = self.driver.find_element(By.CSS_SELECTOR,
```

```
Selectors.get_selectors_for_url(url)['password_field'])
```

```
password_field.send_keys(password)
```

```
await asyncio.sleep(3)
```

```
# Click the login button
```

```
sign_in_button = self.driver.find_element(By.CSS_SELECTOR,
```

```
Selectors.get_selectors_for_url(url)['SignIn_button'])
```

```
sign_in_button.click()
```

```
await asyncio.sleep(5)
```

```
# Wait for the homepage to load
```

```
try:
```

```
WebDriverWait(self.driver,
```

```
30).until(EC.presence_of_element_located((By.CSS_SELECTOR,
```

```
Selectors.get_selectors_for_url(url)['homePage'])))
```

```
    return f"Logged in to {url} successfully with username: {username}"
```

```
except Exception as e:
```

```
    return f"Failed to log in: {str(e)}"
```

```
--- __init__.py ---
```

```
#empty init file
```

```
--- project_structure.py ---
```

```
import os
```

```
def list_files_and_folders(directory, output_file):
```

```
    with open(output_file, 'w') as f:
```

```
        for root, dirs, files in os.walk(directory):
```

```
            # Ignore .git and __pycache__ folders
```

```
            dirs[:] = [d for d in dirs if d not in ['.git', '__pycache__']]
```

```
            f.write(f"Directory: {root}\n")
```

```
            for dir_name in dirs:
```

```
                f.write(f"  Folder: {dir_name}\n")
```

```
            for file_name in files:
```

```
                f.write(f"      File: {file_name}\n")
```

```
# Update the directory path to your project folder
```

```
project_directory = "D:/HARRISBURG/Harrisburg Master's Fifth Term Late Summer/CISC  
699/DiscordBotProject_CISC699"
```

```
output_file = os.path.join(project_directory, "other/project_structure.txt")
```

```
# Call the function to list files and save output to .txt
```

```
list_files_and_folders(project_directory, output_file)
```

```
print(f"File structure saved to {output_file}")
```

```
--- project_text.py ---
```

```
import os
```

```
from fpdf import FPDF
```

```
# Directory where the project files are located
```

```
directory = r"D:\HARRISBURG\Harrisburg Master's Fifth Term Late Summer\CISC  
699\DiscordBotProject_CISC699"
```

```
output_pdf_path = os.path.join(directory, "other/project_text.pdf")
```

```
# Function to retrieve all text from files, ignoring .git and __pycache__ directories
```

```
def extract_project_text(directory):
```

```
    project_text = ""
```

```
    for root, dirs, files in os.walk(directory):
```

```
        # Ignore .git and __pycache__ directories
```

```
        dirs[:] = [d for d in dirs if d not in ['.git', '__pycache__']]
```

```
        for file in files:
```

```
            if file.endswith('.py') or file.endswith('.txt') or file.endswith('.md'): # Only considering relevant
```

```
file types
```

```
            file_path = os.path.join(root, file)
```

```
            try:
```

```
                with open(file_path, 'r', encoding='utf-8') as f:
```

```
                    project_text += f"--- {file} ---\n"
```

```
                    project_text += f.read() + "\n\n"
```

```
            except Exception as e:
```

```
                print(f"Could not read file {file_path}: {e}")
```

```
    return project_text
```

```
# Function to generate a PDF with the extracted text
```

```
def create_pdf(text, output_path):
```

```
    pdf = FPDF()
```

```
    pdf.set_auto_page_break(auto=True, margin=15)
```

```
    pdf.add_page()
```

```
    pdf.set_font("Arial", size=12)
```

```
    # Ensure proper encoding handling
```

```
    for line in text.split("\n"):
```

```
        # Convert the text to UTF-8 and handle unsupported characters
```

```
        try:
```

```
            pdf.multi_cell(0, 10, line.encode('latin1', 'replace').decode('latin1'))
```

```
        except UnicodeEncodeError:
```

```
            # Handle any other encoding issues
```

```
            pdf.multi_cell(0, 10, line.encode('ascii', 'replace').decode('ascii'))
```

```
    pdf.output(output_path)
```

```
# Extract project text and create the PDF
```

```
project_text = extract_project_text(directory)
```

```
if project_text:
```

```
    create_pdf(project_text, output_pdf_path)
```

```
    output_pdf_path
```

```
    print("PDF file created with all project's as text at: " + output_pdf_path)
```

```
else:
```

"No project text found."

--- test_addAccount.py ---

import sys, os

sys.path.append(os.path.dirname(os.path.dirname(os.path.abspath(__file__))))

from control.AccountControl import AccountControl

def test_add_account(username, password, website):

account_control = AccountControl()

Adding a new account

result = account_control.add_account(username, password, website)

if result:

print(f"Account for {website} added successfully.")

else:

print(f"Failed to add account for {website}.")

if __name__ == "__main__":

test_add_account("newUser", "newPassword123", "newWebsite") # Change values to test

--- test_deleteAccount.py ---

import sys, os

sys.path.append(os.path.dirname(os.path.dirname(os.path.abspath(__file__))))

```
from control.AccountControl import AccountControl
```

```
def test_delete_account(account_id):
```

```
    account_control = AccountControl()
```

```
    result = account_control.delete_account(account_id)
```

```
    if result:
```

```
        print(f"Account with ID {account_id} deleted successfully.")
```

```
    else:
```

```
        print(f"Failed to delete account with ID {account_id}.")
```

```
if __name__ == "__main__":
```

```
    test_delete_account(4) # You can change the account ID here for testing
```

```
--- test_excel_creation.py ---
```

```
import sys, os
```

```
from datetime import datetime
```

```
sys.path.append(os.path.dirname(os.path.dirname(os.path.abspath(__file__))))
```

```
from utils.exportUtils import ExportUtils
```

```
from DataObjects.DataExportDTO import DataExportDTO # Importing the DTO
```

```
def test_excel_creation():
```

```
    # Mock data that simulates the data received from a website
```

```
    mock_command = "MOCK_check_availability"
```

```
mock_url = "MOCKURL_https://www.opentable.com/r/bar-spero-washington/"
```

```
mock_result = "MOCK_No availability for the selected date."
```

```
mock_entered_date = datetime.now().strftime('%Y-%m-%d')
```

```
mock_entered_time = datetime.now().strftime('%H:%M:%S')
```

```
# Create DTO object
```

```
data_dto = DataExportDTO(  
    command=mock_command,  
    url=mock_url,  
    result=mock_result,  
    entered_date=mock_entered_date,  
    entered_time=mock_entered_time  
)
```

```
# Validate the DTO
```

```
try:
```

```
    data_dto.validate()
```

```
except ValueError as ve:
```

```
    print(f"Validation Error: {ve}")
```

```
    return
```

```
# Log data to Excel using the DTO
```

```
result_message = ExportUtils.log_to_excel(  
    command=data_dto.command,  
    url=data_dto.url,  
    result=data_dto.result,  
    entered_date=data_dto.entered_date,
```

```

        entered_time=data_dto.entered_time

    )

    # Output the result of the Excel file creation

    print(result_message)


if __name__ == "__main__":

    test_excel_creation()


--- test_fetchAccounts.py ---

import sys, os

sys.path.append(os.path.dirname(os.path.dirname(os.path.abspath(__file__))))

from control.AccountControl import AccountControl # Import the control layer directly


def test_fetch_accounts():

    account_control = AccountControl() # Use AccountControl instead of AccountBoundary

    # Fetching all accounts

    accounts = account_control.fetch_all_accounts()

    if accounts:

        for account in accounts:

            print(f"ID: {account[0]}, Username: {account[1]}, Password: {account[2]}, Website:
{account[3]}")

        else:

```



```

print("No accounts found.")

def test_fetch_account_by_website(website):

    account_control = AccountControl() # Use AccountControl instead of AccountBoundary

    # Fetch the account by website directly

    account = account_control.fetch_account_by_website(website)

    if account:

        username, password = account # Unpack the returned tuple

        print(f"Website: {website}, Username: {username}, Password: {password}")

    else:

        print(f"No account found for website: {website}")

if __name__ == "__main__":

    test_fetch_accounts() # Test fetching all accounts

    test_fetch_account_by_website("ebay") # Test fetching account for a specific website

--- test_html_creation.py ---

import sys, os

from datetime import datetime

sys.path.append(os.path.dirname(os.path.dirname(os.path.abspath(__file__))))

from DataObjects.DataExportDTO import DataExportDTO # Importing the DTO

from utils.exportUtils import ExportUtils

def test_html_creation():

```

```
# Mock data that simulates the data received from a website

mock_command = "MOCK_check_availability"

mock_url = "MOCK_https://www.opentable.com/r/bar-spero-washington/"

mock_result = "No availability for the selected date."


# Get the current date and time

mock_entered_date = datetime.now().strftime('%Y-%m-%d')

mock_entered_time = datetime.now().strftime('%H:%M:%S')


# Create DTO object

data_dto = DataExportDTO(

    command=mock_command,

    url=mock_url,

    result=mock_result,

    entered_date=mock_entered_date,

    entered_time=mock_entered_time

)


# Validate the DTO

try:

    data_dto.validate()

except ValueError as ve:

    print(f"Validation Error: {ve}")

    return


# Prepare the data for HTML export

mock_data = [data_dto.to_dict()]
```

```

# Export data to HTML using the DTO

result_message = ExportUtils.export_to_html(

    data=mock_data,

    command_name=data_dto.command

)


# Output the result of the HTML file creation

print(result_message)


if __name__ == "__main__":

    test_html_creation()


--- __init__.py ---

#empty init file


--- Config.py ---

class Config:

    DISCORD_TOKEN =

'MTI2OTM4MTE4OTA1NjMzNTk3Mw.Gihcfw.nrQ0x-JiL65P0LIQTO-rTyyXq0qC-2PSSBuXr8'

    CHANNEL_ID = 1269383349278081054

    DATABASE_PASSWORD = 'postgres'


--- css_selectors.py ---

class Selectors:

    SELECTORS = {

```

```
"trendyol": {  
  "price": ".featured-prices .prc-dsc" # Selector for Trendyol price  
},  
"ebay": {  
  "url": "https://signin.ebay.com/signin/",  
  "email_field": "#userid",  
  "continue_button": "[data-testid*='signin-continue-btn']",  
  "password_field": "#pass",  
  "login_button": "#sgnBt",  
  "price": ".x-price-primary span" # CSS selector for Ebay price  
},  
"bestbuy": {  
  "url": "https://www.bestbuy.com/signin/",  
  "email_field": "#fld-e",  
  "continue_button": ".cia-form__controls button",  
  "password_field": "#fld-p1",  
  "SignIn_button": ".cia-form__controls button",  
  "price": "[data-testid='customer-price'] span", # CSS selector for BestBuy price  
  "homePage": ".v-p-right-xxs.line-clamp"  
},  
"opentable": {  
  "url": "https://www.opentable.com/",  
  "date_field": "#restProfileSideBarDtpDayPicker-label",  
  "time_field": "#restProfileSideBarTimePickerDtpPicker",  
  "select_date": "#restProfileSideBarDtpDayPicker-wrapper", # button[aria-label*="{ }"]  
  "select_time": "h3[data-test='select-time-header']",  
  "no_availability": "div._8ye6OVzeOuU- span",
```

```
"find_table_button": ".find-table-button", # Example selector for the Find Table button
```

```
"availability_result": ".availability-result", # Example selector for availability results
```

```
"show_next_available_button": "button[data-test='multi-day-availability-button']", # Show  
next available button
```

```
"available_dates": "ul[data-test='time-slots'] > li", # Available dates and times
```

```
}
```

```
}
```

```
@staticmethod
```

```
def get_selectors_for_url(url):
```

```
    for keyword, selectors in Selectors.SELECTORS.items():
```

```
        if keyword in url.lower():
```

```
            return selectors
```

```
    return None # Return None if no matching selectors are found
```

```
--- exportUtils.py ---
```

```
import os
```

```
import pandas as pd
```

```
from datetime import datetime
```

```
class ExportUtils:
```

```
@staticmethod
```

```
def log_to_excel(command, url, result, entered_date=None, entered_time=None):
```

```
    # Determine the file path for the Excel file
```

```
    file_name = f"{command}.xlsx"
```

```
file_path = os.path.join("ExportedFiles", "excelFiles", file_name)

# Ensure directory exists
os.makedirs(os.path.dirname(file_path), exist_ok=True)

# Timestamp for current run
timestamp = datetime.now().strftime('%Y-%m-%d %H:%M:%S')

# If date/time not entered, use current timestamp
entered_date = entered_date or datetime.now().strftime('%Y-%m-%d')
entered_time = entered_time or datetime.now().strftime('%H:%M:%S')

# Check if the file exists and create the structure if it doesn't
if not os.path.exists(file_path):
    df = pd.DataFrame(columns=["Timestamp", "Command", "URL", "Result", "Entered Date",
"Entered Time"])
    df.to_excel(file_path, index=False)

# Load existing data from the Excel file
df = pd.read_excel(file_path)

# Append the new row
new_row = {
    "Timestamp": timestamp,
    "Command": command,
    "URL": url,
    "Result": result,
```

```

    "Entered Date": entered_date,

    "Entered Time": entered_time

}

# Add the new row to the existing data and save it back to Excel
df = pd.concat([df, pd.DataFrame([new_row])], ignore_index=True)
df.to_excel(file_path, index=False)

return f"Data saved to Excel file at {file_path}."

```

```
@staticmethod
```

```

def export_to_html(data, command_name):

    # Define file path for HTML

    file_name = f"{command_name}.html" # Only one HTML file per command, will be appended

    file_path = os.path.join("ExportedFiles", "htmlFiles", file_name)

    # Ensure the directory exists

    os.makedirs(os.path.dirname(file_path), exist_ok=True)

    # Check if the file already exists and append rows

    if os.path.exists(file_path):

        # Open the file and append rows

        with open(file_path, "r+", encoding="utf-8") as file:

            content = file.read()

            # Look for the closing </table> tag and append new rows before it

```

if "</table>" in content:

```
new_rows = ""
```

```
for row in data:
```

```
    # Ensure all necessary keys are in the row dictionary
```

```
    new_rows += f"<tr><td>{row.get('Timestamp', 'N/A')}</td><td>{row.get('Command', 'N/A')}</td><td>{row.get('URL', 'N/A')}</td><td>{row.get('Result', 'N/A')}</td><td>{row.get('Entered Date', 'N/A')}</td><td>{row.get('Entered Time', 'N/A')}</td></tr>\n"
```

```
    # Insert new rows before </table>
```

```
content = content.replace("</table>", new_rows + "</table>")
```

```
file.seek(0) # Move pointer to the start
```

```
file.write(content)
```

```
file.truncate() # Truncate any remaining content
```

```
file.flush() # Flush the buffer to ensure it's written
```

else:

```
    # If the file doesn't exist, create a new one with table headers
```

```
    with open(file_path, "w", encoding="utf-8") as file:
```

```
        html_content = "<html><head><title>Command Data</title></head><body>"
```

```
        html_content += f"<h1>Results for {command_name}</h1><table border='1'>"
```

```
                                html_content +=
```

```
"<tr><th>Timestamp</th><th>Command</th><th>URL</th><th>Result</th><th>Entered Date</th><th>Entered Time</th></tr>"
```

```
    for row in data:
```

```
        # Ensure all necessary keys are in the row dictionary
```

```
        html_content += f"<tr><td>{row.get('Timestamp', 'N/A')}</td><td>{row.get('Command', 'N/A')}</td><td>{row.get('URL', 'N/A')}</td><td>{row.get('Result', 'N/A')}</td><td>{row.get('Entered Date', 'N/A')}</td><td>{row.get('Entered Time', 'N/A')}</td></tr>\n"
```



```
html_content += "</table></body></html>"
```

```
file.write(html_content)
```

```
file.flush() # Ensure content is written to disk
```

```
print(f"Created new HTML file at {file_path}.")
```

```
return f"HTML file saved and updated at {file_path}."
```