

--- Config.py ---

class Config:

DISCORD_TOKEN =

'MTI2OTM4MTE4OTA1NjMzNTk3Mw.Gihcfw.nrQ0x-JiL65P0LIQTO-rTyyXq0qC-2PSSBuXr8'

CHANNEL_ID = 1269383349278081054

DATABASE_PASSWORD = 'postgres'

--- css_selectors.py ---

class Selectors:

SELECTORS = {

"google": {

"url": "https://www.google.com/"

},

"ebay": {

"url": "https://signin.ebay.com/signin/",

"email_field": "#userid",

"continue_button": "[data-testid*='signin-continue-btn']",

"password_field": "#pass",

"login_button": "#sgnBt",

"price": ".x-price-primary span" # CSS selector for Ebay price

},

"bestbuy": {

"priceUrl":

"https://www.bestbuy.com/site/microsoft-xbox-wireless-controller-for-xbox-series-x-xbox-series-s-xbox-one-windows-devices-sky-cipher-special-edition/6584960.p?skuId=6584960",

"url": "https://www.bestbuy.com/signin/",

"email_field": "#fld-e",

```

        "#continue_button": ".cia-form__controls button",

        "password_field": "#fld-p1",

        "SignIn_button": ".cia-form__controls button",

        "price": "[data-testid='customer-price'] span", # CSS selector for BestBuy price

        "homePage": ".v-p-right-xxs.line-clamp"

    },

    "opentable": {

        "url": "https://www.opentable.com/",

        "unavailableUrl": "https://www.opentable.com/r/bar-spero-washington/",

        "availableUrl": "https://www.opentable.com/r/the-rux-nashville",

        "date_field": "#restProfileSideBarDtpDayPicker-label",

        "time_field": "#restProfileSideBarTimePickerDtpPicker",

        "select_date": "#restProfileSideBarDtpDayPicker-wrapper", # button[aria-label*="{ }"]

        "select_time": "h3[data-test='select-time-header']",

        "no_availability": "div._8ye6OVzeOuU- span",

        "find_table_button": ".find-table-button", # Example selector for the Find Table button

        "availability_result": ".availability-result", # Example selector for availability results

        "show_next_available_button": "button[data-test='multi-day-availability-button']", # Show
next available button

        "available_dates": "ul[data-test='time-slots'] > li", # Available dates and times

    }

}

@staticmethod
def get_selectors_for_url(url):

    for keyword, selectors in Selectors.SELECTORS.items():

```

```
    if keyword in url.lower():  
        return selectors  
  
    return None # Return None if no matching selectors are found
```

--- exportUtils.py ---

```
import os
```

```
import pandas as pd
```

```
from datetime import datetime
```

```
class ExportUtils:
```

```
    @staticmethod
```

```
    def log_to_excel(command, url, result, entered_date=None, entered_time=None):
```

```
        # Determine the file path for the Excel file
```

```
        file_name = f"{command}.xlsx"
```

```
        file_path = os.path.join("ExportedFiles", "excelFiles", file_name)
```

```
        # Ensure directory exists
```

```
        os.makedirs(os.path.dirname(file_path), exist_ok=True)
```

```
        # Timestamp for current run
```

```
        timestamp = datetime.now().strftime('%Y-%m-%d %H:%M:%S')
```

```
        # If date/time not entered, use current timestamp
```

```
        entered_date = entered_date or datetime.now().strftime('%Y-%m-%d')
```

```
        entered_time = entered_time or datetime.now().strftime('%H:%M:%S')
```

```

# Check if the file exists and create the structure if it doesn't

if not os.path.exists(file_path):

    df = pd.DataFrame(columns=["Timestamp", "Command", "URL", "Result", "Entered Date",
"Entered Time"])

    df.to_excel(file_path, index=False)


# Load existing data from the Excel file

df = pd.read_excel(file_path)


# Append the new row

new_row = {

    "Timestamp": timestamp,

    "Command": command,

    "URL": url,

    "Result": result,

    "Entered Date": entered_date,

    "Entered Time": entered_time

}


# Add the new row to the existing data and save it back to Excel

df = pd.concat([df, pd.DataFrame([new_row])], ignore_index=True)

df.to_excel(file_path, index=False)


return f"Data saved to Excel file at {file_path}."


@staticmethod

def export_to_html(command, url, result, entered_date=None, entered_time=None):

```

```
"""Export data to HTML format with the same structure as Excel."""
```

```
# Define file path for HTML
```

```
file_name = f"{command}.html"
```

```
file_path = os.path.join("ExportedFiles", "htmlFiles", file_name)
```

```
# Ensure directory exists
```

```
os.makedirs(os.path.dirname(file_path), exist_ok=True)
```

```
# Timestamp for current run
```

```
timestamp = datetime.now().strftime('%Y-%m-%d %H:%M:%S')
```

```
# If date/time not entered, use current timestamp
```

```
entered_date = entered_date or datetime.now().strftime('%Y-%m-%d')
```

```
entered_time = entered_time or datetime.now().strftime('%H:%M:%S')
```

```
# Data row to insert
```

```
new_row = {
```

```
    "Timestamp": timestamp,
```

```
    "Command": command,
```

```
    "URL": url,
```

```
    "Result": result,
```

```
    "Entered Date": entered_date,
```

```
    "Entered Time": entered_time
```

```
}
```

```
# Check if the HTML file exists and append rows
```

```

if os.path.exists(file_path):

    # Open the file and append rows

    with open(file_path, "r+", encoding="utf-8") as file:

        content = file.read()

        # Look for the closing </table> tag and append new rows before it

        if "</table>" in content:

                                                    new_row_html    =

f"<tr><td>{new_row['Timestamp']}</td><td>{new_row['Command']}</td><td>{new_row['URL']}</td><

td>{new_row['Result']}</td><td>{new_row['Entered          Date']}</td><td>{new_row['Entered

Time']}</td></tr>\n"

        content = content.replace("</table>", new_row_html + "</table>")

        file.seek(0) # Move pointer to the start

        file.write(content)

        file.truncate() # Truncate any remaining content

        file.flush() # Flush the buffer to ensure it's written

else:

    # If the file doesn't exist, create a new one with table headers

    with open(file_path, "w", encoding="utf-8") as file:

        html_content = "<html><head><title>Command Data</title></head><body>"

        html_content += f"<h1>Results for {command}</h1><table border='1'>"

                                                    html_content    +=

f"<tr><th>Timestamp</th><th>Command</th><th>URL</th><th>Result</th><th>Entered

Date</th><th>Entered Time</th></tr>"

                                                    html_content    +=

f"<tr><td>{new_row['Timestamp']}</td><td>{new_row['Command']}</td><td>{new_row['URL']}</td><

td>{new_row['Result']}</td><td>{new_row['Entered          Date']}</td><td>{new_row['Entered

Time']}</td></tr>\n"

```

```
html_content += "</table></body></html>"
```

```
file.write(html_content)
```

```
file.flush() # Ensure content is written to disk
```

```
return f"HTML file saved and updated at {file_path}."
```

```
--- MyBot.py ---
```

```
import discord
```

```
from discord.ext import commands
```

```
from boundary.BrowserBoundary import BrowserBoundary
```

```
from boundary.NavigationBoundary import NavigationBoundary
```

```
from boundary.HelpBoundary import HelpBoundary
```

```
from boundary.StopBoundary import StopBoundary
```

```
from boundary.LoginBoundary import LoginBoundary
```

```
from boundary.AccountBoundary import AccountBoundary
```

```
from boundary.AvailabilityBoundary import AvailabilityBoundary
```

```
from boundary.PriceBoundary import PriceBoundary
```

```
class MyBot(commands.Bot):
```

```
    async def setup_hook(self):
```

```
        await self.add_cog(BrowserBoundary())
```

```
        await self.add_cog(NavigationBoundary())
```

```
        await self.add_cog(HelpBoundary())
```

```
await self.add_cog(StopBoundary())

await self.add_cog(LoginBoundary())

await self.add_cog(AccountBoundary())

await self.add_cog(AvailabilityBoundary())

await self.add_cog(PriceBoundary())
```

```
async def on_ready(self):

    print(f"Logged in as {self.user}")

    channel = discord.utils.get(self.get_all_channels(), name="general") # Adjust the channel
name if needed

    if channel:

        await channel.send("Hi, I'm online! Type '!project_help' to see what I can do.")

async def on_command_error(self, ctx, error):

    if isinstance(error, commands.CommandNotFound):

        await ctx.send("Command not recognized. Type !project_help to see the list of commands.")
```