```
--- AccountControl.py ---

from DataObjects.AccountDAO import AccountDAO


class AccountControl:
    def __init__(self):
        self.account_dao = AccountDAO()  # DAO for database operations

    def receive_command(self, command_data, *args):
        """Handle all account-related commands and process business logic."""
        print("Data received from boundary:", command_data)

        if command_data == "fetch_all_accounts":
            return self.fetch_all_accounts()

        elif command_data == "fetch_account_by_website":
            website = args[0] if args else None
            return self.fetch_account_by_website(website)

        elif command_data == "add_account":
            username, password, website = args if args else (None, None, None)
            return self.add_account(username, password, website)

        elif command_data == "delete_account":
            account_id = args[0] if args else None
            return self.delete_account(account_id)

        else:
```

```
            result = "Invalid command."
            print(result)
            return result

    def add_account(self, username: str, password: str, website: str):
        """Add a new account to the database."""
        self.account_dao.connect()
        result = self.account_dao.add_account(username, password, website)
        self.account_dao.close()

            result_message = f"Account for {website} added successfully." if result else f"Failed to add account for {website}."
        print(result_message)
        return result_message

    def delete_account(self, account_id: int):
        """Delete an account by ID."""
        self.account_dao.connect()
        try:
            result = self.account_dao.delete_account(account_id)
        except Exception as e:
            print(f"Error deleting account: {e}")
            return "Error deleting account."
        self.account_dao.reset_id_sequence()
        self.account_dao.close()

        result_message = f"Account with ID {account_id} deleted successfully." if result else f"Failed to
```

```
delete account with ID {account_id}."
        print(result_message)
        return result_message

    def fetch_all_accounts(self):
        """Fetch all accounts using the DAO."""
        self.account_dao.connect()
        try:
            accounts = self.account_dao.fetch_all_accounts()
        except Exception as e:
            return "Error fetching accounts."
        self.account_dao.close()

        if accounts:
                account_list = "\n".join([f"ID: {acc[0]}, Username: {acc[1]}, Password: {acc[2]}, Website:
{acc[3]}" for acc in accounts])
            result_message = f"Accounts:\n{account_list}"
        else:
            result_message = "No accounts found."

        print(result_message)
        return result_message

    def fetch_account_by_website(self, website: str):
        """Fetch an account by website."""
        try:
            self.account_dao.connect()
```

```
            account = self.account_dao.fetch_account_by_website(website)
            self.account_dao.close()

            # Logic to format the result within the control layer
            if account:
                return account
            else:
                return f"No account found for {website}."

        except Exception as e:
            return f"Error: {str(e)}"
```

```
--- AvailabilityControl.py ---
import asyncio
from entity.AvailabilityEntity import AvailabilityEntity
from datetime import datetime
from utils.css_selectors import Selectors

class AvailabilityControl:
    def __init__(self):
        self.availability_entity = AvailabilityEntity()  # Initialize the entity
        self.is_monitoring = False  # Monitor state
        self.results = []  # List to store monitoring results

    async def receive_command(self, command_data, *args):
        """Handle all commands related to availability."""
```

```
    print("Data received from boundary:", command_data)

    if command_data == "check_availability":
        url = args[0]
        date_str = args[1] if len(args) > 1 else None
        return await self.check_availability(url, date_str)

    elif command_data == "start_monitoring_availability":
        url = args[0]
        date_str = args[1] if len(args) > 1 else None
        frequency = args[2] if len(args) > 2 else 15
        return await self.start_monitoring_availability(url, date_str, frequency)

    elif command_data == "stop_monitoring_availability":
        return self.stop_monitoring_availability()

    else:
        print("Invalid command.")
        return "Invalid command."


async def check_availability(self, url: str, date_str=None):
    """Handle availability check and export results."""
    print("Checking availability...")
    # Call the entity to check availability
    try:
        if not url:
```

```
        selectors = Selectors.get_selectors_for_url("opentable")
        url = selectors.get('availableUrl')
        if not url:
            return "No URL provided, and default URL for openTable could not be found."
        print("URL not provided, default URL for openTable is: " + url)

    availability_info = await self.availability_entity.check_availability(url, date_str)

# Prepare the result
    result = f"Checked availability: {availability_info}"
except Exception as e:
    result = f"Failed to check availability: {str(e)}"
print(result)

# Create a DTO (Data Transfer Object) for export
data_dto = {
    "command": "check_availability",
    "url": url,
    "result": result,
    "entered_date": datetime.now().strftime('%Y-%m-%d'),
    "entered_time": datetime.now().strftime('%H:%M:%S')
}

# Export data to Excel/HTML via the entity
self.availability_entity.export_data(data_dto)
return result
```

```
async def start_monitoring_availability(self, url: str, date_str=None, frequency=15):
    """Start monitoring availability at a specified frequency."""
    print("Monitoring availability")
    if self.is_monitoring:
        result = "Already monitoring availability."
        print(result)
        return result

    self.is_monitoring = True  # Set monitoring to active
    try:
        while self.is_monitoring:
            # Call entity to check availability
            result = await self.check_availability(url, date_str)
            self.results.append(result) # Store the result in the list
            await asyncio.sleep(frequency)  # Wait for the specified frequency before checking again

    except Exception as e:
        error_message = f"Failed to monitor availability: {str(e)}"
        print(error_message)
        return error_message

    return self.results


def stop_monitoring_availability(self):
    """Stop monitoring availability."""
```

```
        print("Stopping availability monitoring...")
        result = None
        try:
            if not self.is_monitoring:
                # If no monitoring session is active
                result = "There was no active availability monitoring session. Nothing to stop."
            else:
                # Stop monitoring and collect results
                self.is_monitoring = False
                result = "Results for availability monitoring:\n"
                result += "\n".join(self.results)
                result = result + "\n" + "\nAvailability monitoring stopped successfully!"
                print(result)
        except Exception as e:
            # Handle any error that occurs
            result = f"Error stopping availability monitoring: {str(e)}"

        return result
```

--- BrowserControl.py ---

```
from entity.BrowserEntity import BrowserEntity

class BrowserControl:

    def __init__(self):
```

```
        # Initialize the entity object inside the control layer
        self.browser_entity = BrowserEntity()

    def receive_command(self, command_data):
        # Validate the command
        print("Data Received from boundary object: ", command_data)
        if command_data == "launch_browser":
            # Call the entity to perform the actual operation
            try:
                result = self.browser_entity.launch_browser()
                return result
            except Exception as e:
                return str(e)  # Return the error message

        elif command_data == "close_browser":
            # Call the entity to perform the close operation
            try:
                result = self.browser_entity.close_browser()
                return result
            except Exception as e:
                return str(e)  # Return the error message

        else:
            return "Invalid command."
```

--- HelpControl.py ---

```
class HelpControl:
    def receive_command(self, command_data):
        """Handles the command and returns the appropriate message."""
        print("Data received from boundary:", command_data)

        if command_data == "project_help":
            help_message = (
                "Here are the available commands:\n"
                "!project_help - Get help on available commands.\n"
                "!fetch_all_accounts - Fetch all stored accounts.\n"
                "!add_account 'username' 'password' 'website' - Add a new account to the database.\n"
                "!fetch_account_by_website 'website' - Fetch account details by website.\n"
                "!delete_account 'account_id' - Delete an account by its ID.\n"
                "!launch_browser - Launch the browser.\n"
                "!close_browser - Close the browser.\n"
                "!navigate_to_website 'url' - Navigate to a specified website.\n"
                "!login 'website' - Log in to a website (e.g., !login bestbuy).\n"
                "!get_price 'url' - Check the price of a product on a specified website.\n"
                  "!start_monitoring_price 'url' 'frequency' - Start monitoring a product's price at a specific interval (frequency in minutes).\n"
                "!stop_monitoring_price - Stop monitoring the product's price.\n"
                "!check_availability 'url' - Check availability for a restaurant or service.\n"
                "!start_monitoring_availability 'url' 'frequency' - Monitor availability at a specific interval.\n"
                "!stop_monitoring_availability - Stop monitoring availability.\n"
                "!stop_bot - Stop the bot.\n"
            )
```

```
            return help_message
        else:
            return "Invalid command."
```

--- LoginControl.py ---

```
from control.AccountControl import AccountControl
from entity.BrowserEntity import BrowserEntity
from utils.css_selectors import Selectors

class LoginControl:
    def __init__(self):
        self.browser_entity = BrowserEntity()
        self.account_control = AccountControl()  # Manages account data

    async def receive_command(self, command_data, site=None):
        """Handle login command and perform business logic."""
        print("Data received from boundary:", command_data)

        if command_data == "login" and site:
            try:
                # Fetch account credentials from the entity
                account_info = self.account_control.fetch_account_by_website(site)
                if not account_info:
                    return f"No account found for {site}"

                username, password = account_info[0], account_info[1]
```

```
            print(f"Username: {username}, Password: {password}")

            # Get the URL from the CSS selectors
            url = Selectors.get_selectors_for_url(site).get('url')
            print(url)
            if not url:
                return f"URL for {site} not found."

            result = await self.browser_entity.login(url, username, password)
        except Exception as e:
            result = str(e)
        return result
    else:
        return "Invalid command or site."


--- NavigationControl.py ---
from entity.BrowserEntity import BrowserEntity
from utils.css_selectors import Selectors

class NavigationControl:

    def __init__(self):
        # Initialize the entity object inside the control layer
        self.browser_entity = BrowserEntity()

    def receive_command(self, command_data, url=None):
```

```
        # Validate the command
        print("Data Received from boundary object: ", command_data)
        if command_data == "navigate_to_website":
            if not url:
                selectors = Selectors.get_selectors_for_url("google")
                url = selectors.get('url')
                if not url:
                    return "No URL provided, and default URL for google could not be found."
                print("URL not provided, default URL for Google is: " + url)
            try:
                result = self.browser_entity.navigate_to_website(url) # Call the entity to perform the actual
operation
            except Exception as e:
                result = str(e)
            return result
        else:
            return "Invalid command."



--- PriceControl.py ---
import asyncio
from datetime import datetime
from entity.PriceEntity import PriceEntity
from utils.css_selectors import Selectors

class PriceControl:
    def __init__(self):
```

```
    self.price_entity = PriceEntity()  # Initialize PriceEntity for fetching and export
    self.is_monitoring = False  # Monitoring flag
    self.results = []  # Store monitoring results


async def receive_command(self, command_data, *args):
    """Handle all price-related commands and process business logic."""
    print("Data received from boundary:", command_data)

    if command_data == "get_price":
        url = args[0] if args else None
        return await self.get_price(url)

    elif command_data == "start_monitoring_price":
        url = args[0] if args else None
        frequency = args[1] if len(args) > 1 else 20
        return await self.start_monitoring_price(url, frequency)

    elif command_data == "stop_monitoring_price":
        return self.stop_monitoring_price()

    else:
        return "Invalid command."


async def get_price(self, url: str):
    """Handle fetching the price from the entity."""
```

```
print("getting price...")
try:
    if not url:
        selectors = Selectors.get_selectors_for_url("bestbuy")
        url = selectors.get('priceUrl')
        if not url:
            return "No URL provided, and default URL for BestBuy could not be found."
        print("URL not provided, default URL for BestBuy is: " + url)

    # Fetch the price from the entity

    result = self.price_entity.get_price_from_page(url)
    print(f"Price found: {result}")
    data_dto = {
                "command": "monitor_price",
                "url": url,
                "result": result,
                "entered_date": datetime.now().strftime('%Y-%m-%d'),
                "entered_time": datetime.now().strftime('%H:%M:%S')
            }

            # Pass the DTO to PriceEntity to handle export
    self.price_entity.export_data(data_dto)

except Exception as e:
    return f"Failed to fetch price: {str(e)}"
```

```
        return result



    async def start_monitoring_price(self, url: str, frequency=20):
        """Start monitoring the price at a given interval."""
        print("Starting price monitoring...")
        try:
            if self.is_monitoring:
                return "Already monitoring prices."

            self.is_monitoring = True
            previous_price = None

            while self.is_monitoring:
                current_price = await self.get_price(url)
                # Determine price changes and prepare the result
                result = ""
                if current_price:
                    if previous_price is None:
                        result = f"Starting price monitoring. Current price: {current_price}"
                    elif current_price > previous_price:
                        result = f"Price went up! Current price: {current_price} (Previous: {previous_price})"
                    elif current_price < previous_price:
                                    result = f"Price went down! Current price: {current_price} (Previous:
{previous_price})"
                    else:
                        result = f"Price remains the same: {current_price}"
```

```
                previous_price = current_price
            else:
                result = "Failed to retrieve the price."

            # Add the result to the results list
            self.results.append(result)
            await asyncio.sleep(frequency)

    except Exception as e:
        self.results.append(f"Failed to monitor price: {str(e)}")


def stop_monitoring_price(self):
    """Stop the price monitoring loop."""
    print("Stopping price monitoring...")
    result = None
    try:
        if not self.is_monitoring:
            # If no monitoring session is active
            result = "There was no active price monitoring session. Nothing to stop."
        else:
            # Stop monitoring and collect results
            self.is_monitoring = False
            result = "Results for price monitoring:\n"
            result += "\n".join(self.results)
            result = result + "\n" +"\nPrice monitoring stopped successfully!"
            print(result)
```

```
        except Exception as e:
            # Handle any error that occurs
            result = f"Error stopping price monitoring: {str(e)}"

        return result
```

--- StopControl.py ---

```
import discord

class StopControl:
    async def receive_command(self, command_data, ctx):
        """Handle the stop bot command."""
        print("Data received from boundary:", command_data)

        if command_data == "stop_bot":
            # Get the bot from the context (ctx) dynamically
            bot = ctx.bot  # This extracts the bot instance from the context
            await ctx.send("The bot is shutting down...")
            print("Bot is shutting down...")
            await bot.close()  # Close the bot
            result = "Bot has been shut down."
            print(result)
            return result
        else:
```

```
        result = "Invalid command."
        return result
```

--- __init__.py ---

```
#empty init file
```