SEI - Developer Guide

Date: November 4, 2026

Adobe

Table of Contents

SEI - Developer Guide 3
- Quick Reference 3
- Architecture Overview 3
- Local Development Setup 6
- Design System 7
- Scripts & Integrations 10
- Blocks Reference 15
- Templates 18
- Pages and Content Inventory 18
- Common Development Tasks 19
- Environments 20
- Git Workflow 21
- Known Issues and Caveats 21
- Troubleshooting 22
- Resources 22
- Support Contacts 23

SEI - Developer Guide

This guide is for developers taking over the SEI demo site on AEM Edge Delivery Services. It explains how the code is organized, which parts are custom, how the visitor-profile layer works, and how to make changes safely.

The site was built in October and November 2026. It started as a Figma-driven design system and block library. Later work added a personalized "visitor journey" demo layer (personas, journeys, lifecycle stages, a scripted assistant and a scheduler) and five alternative home-page designs from the stardust design pipeline.

Quick Reference

Resource	URL / Value
Code repository	GitHub `oharris69/sei` (from Config Service: `code.owner` = oharris69, `code.repo` = sei)
Content source	Document Authoring (DA): `https://content.da.live/oharris69/sei`
Config Service org / site	`oharris69` / `sei`
Setup type	Standard single site (only `sei` uses this code repository; not repoless)
Preview	https://main--sei--oharris69.aem.page/
Live	https://main--sei--oharris69.aem.live/
Feature branch preview	`https://{branch}--sei--oharris69.aem.page/{path}`
Local dev (previewed content)	http://localhost:3000/ (default `aem up` port)
Local dev (local content folder)	`http://localhost:3001/content/{page}` (this project's convention)
Lint	`npm run lint` (CI), or `npx eslint blocks scripts` and `npx stylelint "blocks/**/*.css" "styles/*.css"`

Status at handover (November 4, 2026): ESLint and Stylelint pass with no errors. Preview and live both return 200 for every journey page. Unknown paths return the branded `404.html`.

Architecture Overview

Tech Stack

- Vanilla JavaScript (ES modules, ES2020+). No framework and no build step: files are served as they are in the repository.
- CSS3 with custom properties. All block CSS is scoped to the block class.
- Content is authored in Document Authoring (DA) and delivered as semantic HTML that blocks then decorate.
- `package.json` has only `devDependencies` (ESLint with the airbnb-base config, and Stylelint with stylelint-config-standard). There are no runtime npm dependencies.
- One vendored third-party library: Lenis v1.3.19 (MIT), used for smooth scrolling. It is shipped as `blocks/uc-cinematic/lenis.min.js` and `lenis.min.css`. No CDNs are used anywhere.
- Fonts are self-hosted in `/fonts`. CircularXX is the licensed brand face. Archivo and Source Serif 4 are used only by the rebrand variant.

Project Structure

```
├── 404.html              # Branded "not part of the demo yet" page
├── head.html             # CSP + aem.js / scripts.js / styles.css
├── blocks/               # 65 blocks (63 custom; columns + widget = boilerplate)
│   ├── header/           # nav + experience.js (persona / journey bar)
│   ├── footer/  fragment/  modal/
│   ├── assistant/        # chat panel + answers.js (canned answers)
│   ├── scheduler/  adaptive/  readiness/  entry-mock/  video/
│   ├── <Figma library>   # hero, cards, tabs, stats, fund-*, strategy-*
│   ├── sd-*              # stardust refresh       /index-stardust
│   ├── ua-*              # uplift variant A       /index-uplift-a (+ B, C)
│   ├── ub-*              # uplift variant B       /index-uplift-b
│   ├── uc-cinematic/     # uplift C motion layer  /index-uplift-c
│   └── rb-*              # rebrand                /index-rebrand
├── scripts/
│   ├── aem.js            # Core library (vendored - DO NOT MODIFY)
│   ├── scripts.js        # Page decoration, E-L-D phases, global features
│   ├── profile.js        # Visitor profile, personas, journeys, stages, data layer
│   ├── why.js            # "Why am I seeing this?" panel
│   ├── presenter.js      # Demo presenter menu (?presenter / Alt+Shift+P)
│   ├── consent-check.js  # Boilerplate consent stub (declines by default)
│   └── consented.js      # Empty placeholder for consented martech
├── styles/
│   ├── styles.css        # Critical CSS + design tokens
│   ├── fonts.css         # CircularXX @font-face (lazy)
│   ├── lazy-styles.css   # Empty placeholder
│   ├── why.css           # Loaded on demand by why.js
│   └── presenter.css     # Loaded on demand by presenter.js
├── fonts/                # CircularXX, Archivo, Source Serif 4, DM Sans
├── icons/                # 24x24 SVG icons (:icon-name: / .icon-<name>)
├── stardust/             # Design pipeline artifacts (not served)
├── reference/            # Figma block notes, page renders (not served)
└── content -> (symlink)  # Local .plain.html mirror of DA (outside git)
```

There is no `templates/` folder, no `models/` folder (this is not a Universal Editor project), no `scripts/utils.js` and no `scripts/delayed.js`. The delayed phase is implemented inline in `scripts.js`.

Three-Phase Loading (E-L-D)

Edge Delivery Services uses a strict Eager-Lazy-Delayed loading strategy to achieve a Lighthouse score of 100. Every file and script must be placed in the correct phase.

Phase	Purpose	What loads in this project	Performance impact
Eager	Render above-the-fold content as fast as possible (LCP)	`styles/styles.css`, `scripts/scripts.js`, the special-link click handler, `decorateMain`, the first section and its blocks. `fonts.css` also loads here, but only on desktop (900px or wider) or when a session flag says fonts were already loaded.	Blocks LCP, so keep it minimal
Lazy	Load the rest of the page after first paint	`profile.recordView()`, header (nav plus experience bar), remaining sections, footer, the SEI Assistant launcher, the auto-opening modal scheduler, `lazy-styles.css`, `fonts.css`	Runs after Eager completes
Delayed	Non-essential work	`consent-check.js`, the presenter menu (only when switched on) and the Alt+Shift+P listener	Never blocks rendering

Rules for developers:

- **Never add third-party scripts to the eager or lazy phases.** Add them in `loadDelayed()` in `scripts.js`. Martech that needs consent goes in `scripts/consented.js`.
- **Never load fonts eagerly on mobile.** The `loadFonts()` logic already handles this.
- Blocks in the first section load eagerly; all others load lazily, based on their position in the DOM. Pages whose first block is heavy (for example `readiness`, `entry-mock` or `uc-cinematic`) pay that cost before LCP.
- The header and footer are loaded in the lazy phase by `loadHeader()` / `loadFooter()` from `aem.js`. The header first awaits `recordView()`, so the journey bar renders with the current page already counted.

Key Files & How They Connect

File	Role	Connects to
`scripts/aem.js`	Core library (vendored, **DO NOT MODIFY**). The project uses `buildBlock`, `createOptimizedPicture`, `decorateBlocks`, `decorateIcons`, `decorateSections`, `decorateTemplateAndTheme`, `getMetadata`, `loadCSS`, `loadScript`, `loadHeader`, `loadFooter`, `loadSection(s)`, `sampleRUM` (404 page), `toClassName` and `waitForFirstImage`.	Imported by `scripts.js`, `why.js`, `presenter.js` and blocks
`scripts/scripts.js`	Entry point. Runs the E-L-D phases. Contains the Trusted Types policy, auto-blocks, button and eyebrow decoration, special-link handling, the assistant launcher and the presenter loader.	Imports `aem.js`; dynamically imports `profile.js`, `modal.js`, `fragment.js` and `presenter.js`
`scripts/profile.js`	The visitor model: personas, journeys, lifecycle stages, campaigns, booking, `.ics` files, and `window.adobeDataLayer` events.	Imported by header/experience, modal, assistant, scheduler, adaptive, readiness, entry-mock, video, specialist, ua-role-panel, why, presenter and 404
`scripts/why.js`	The "Why am I seeing this?" dialog and the `whyButton()` factory.	Used by the header experience bar, `adaptive` and `ua-role-panel`
`scripts/presenter.js`	Presenter menu for live demos.	Loaded from `loadDelayed()`
`blocks/fragment/fragment.js`	`loadFragment(path)`: fetches `{path}.plain.html`, decorates it and loads its sections. It also handles local `/content` preview paths. **The only cross-block import allowed.**	Used by header, footer, modal and `buildAutoBlocks`
`blocks/modal/modal.js`	Not authored as a block. Opens `/modals/*` fragments in `<dialog>`, routes `/contact` to the right scheduler, and checks PDF links.	Imported by `scripts.js`

File	Role	Connects to
`styles/styles.css`	Tokens, typography, buttons, section styles, chips, the launcher and the Why trigger.	Every block

Execution flow: page load → `scripts.js` → `loadEager()` (special-link handler, `decorateMain`, first section) → `loadLazy()` (`recordView`, header, sections, footer, launcher, auto modal, `lazy-styles.css`, `fonts.css`) → `loadDelayed()` (consent stub, presenter).

Local Development Setup

Prerequisites

- Node.js 20 or later. CI runs Node 24; there is no `.nvmrc`.
- AEM CLI: run it with `npx -y @adobe/aem-cli` (or `npm install -g @adobe/aem-cli`).
- Access to the GitHub repository `oharris69/sei`. To edit content you also need DA access to `oharris69/sei`.

Setup Steps

```
git clone https://github.com/oharris69/sei.git
cd sei
npm install            # dev tooling only (ESLint, Stylelint)
npx -y @adobe/aem-cli up
```

Local Server (previewed content)

- URL: http://localhost:3000
- Serves your local code against **previewed** content from DA (`.aem.page`).
- Reloads automatically when files change.
- If another project already uses port 3000, add `--port 3001`.

Local Server (local content folder)

This project also keeps a local mirror of the content as `.plain.html` files. In this workspace `content/` is a symlink to a folder outside the git repository. To develop against that mirror:

```
npx -y @adobe/aem-cli up --html-folder content --prefer-plain-html --port 3001
# pages: http://localhost:3001/content/index
#        http://localhost:3001/content/bd-breakaway, /content/modals/assistant ...
```

The code is written to work under the `/content` prefix:

- `profile.currentPath()` strips `/content`, and `profile.pageHref()` adds it back for internal links built by code (journey steps, presenter, assistant links).
- `fragment.loadFragment()` prefixes fragment fetches with `/content`, and resolves `./images/...` against `/content/` from any page depth.
- `isSpecialLink()` and `getModalPath()` accept both `/modals/x` and `/content/modals/x`.
- Metadata and section-metadata tables are **not** converted locally. The local pages put section styles directly as classes on the section `<div>`, which matches what the backend emits. Page metadata such as `modal` and `assistant` only exists on the DA pages.

Inspecting backend markup

Always check the markup the backend actually delivers before changing a block:

```
curl -s https://main--sei--oharris69.aem.page/etfs.plain.html | head -80
curl -s http://localhost:3000/etfs.plain.html          # via aem up
```

`buildAutoBlocks` rewrites content before blocks run: `/fragments/` links are inlined and `/widgets/` links become `widget` blocks. Authors also omit and add cells, so decorate defensively.

Linting

```
npm run lint           # eslint . && stylelint (what CI runs on every push)
npm run lint:fix
```

CI (`.github/workflows/main.yaml`) runs `npm ci` and `npm run lint` on every push. `*.min.js` is ignored by ESLint, which keeps Lenis out of the lint run.

Design System

All tokens are CSS custom properties on `:root` in `styles/styles.css`. Use them in new block CSS instead of hard-coded values.

Colors

```
--color-ink: #131517;        --color-ink-soft: #101828;   --color-slate: #364153;
--color-gray-600: #4a5565;   --color-gray-500: #6a7282;   --color-gray-400: #99a1af;
--color-gray-300: #d9d9d9;   --color-gray-200: #e5e7eb;   --color-gray-100: #f3f4f6;
--color-gray-50: #f9fafb;    --color-white: #fff;
--color-red: #d82b2a;        --color-red-dark: #b82322;   /* primary CTA */
--color-cyan: #00c0f3;       --color-cyan-bright: #00c4f8;
--color-green: #a6ce39;      --color-orange: #f6a01a;

/* gradients */
--gradient-brand:
  linear-gradient(225deg, var(--color-green) 0%, var(--color-cyan) 100%);
--gradient-brand-horizontal:
  linear-gradient(90deg, var(--color-cyan) 0%, var(--color-green) 100%);
--gradient-newsletter: linear-gradient(225deg, #00c5fa 25%, #086c8a 100%);

/* semantic */
--background-color: var(--color-white);  --light-color: var(--color-gray-50);
--dark-color: var(--color-ink);          --text-color: var(--color-ink);
--link-color: var(--color-ink);          --link-hover-color: var(--color-red);
--border-color: var(--color-gray-200);
```

Typography

```
--body-font-family: circularxx, circularxx-fallback, sans-serif;
--heading-font-family: circularxx, circularxx-heading-fallback, sans-serif;
--heading-font-weight: 1000;          /* resolves to the CircularXX ExtraBlack cut */
```

Token	Mobile	Desktop (900px or wider)
`--heading-font-size-xxl` (h1)	44px	64px
`--heading-font-size-xl`	34px	48px
`--heading-font-size-l` (h2)	30px	36px
`--heading-font-size-m` (h3)	24px	32px
`--heading-font-size-s` (h4)	20px	24px
`--heading-font-size-xs` (h5)	18px	20px
`--body-font-size-xl / l / m / s / xs`	22 / 18 / 16 / 14 / 12px	same

Layout and Spacing

Token	Mobile	Desktop
`--content-max-width`	1280px	1280px
`--content-padding`	20px	24px
`--section-spacing`	48px	64px
`--nav-height`	64px	80px
`--experience-height` (persona bar)	48px	48px
`--radius-card` / `--radius-input`	15px	15px

The `<header>` reserves `calc(var(--nav-height) + var(--experience-height))` to avoid CLS while the nav and experience bar load. If you change the experience bar height, update this token.

Breakpoints

Name	Query	Usage
Mobile	default	Mobile-first base styles
Small tablet	`(width >= 600px)` / `(width < 600px)`	Card grids, the sd-case-studies rail, bar-chart compact mode
Tablet (stardust blocks)	`(width > 640px)`	ua-, *ub-* and rb-* layouts
Desktop	`(width >= 900px)` (most common; > 900px in some stardust blocks)	Token step-up, nav switches from hamburger to desktop (`header.js` matches `min-width: 900px`)
Large	`(width >= 1200px)` / `(width > 1180px)`	A few wide layouts

Name	Query	Usage
Motion	`(prefers-reduced-motion: reduce)`	Used in 23 places; every new animation must honor it

Fonts

Family (CSS name)	Files	Weights / ranges	Used by
`circularxx` (CircularXX, licensed from Lineto)	`fonts/CircularXXSub-*.woff2` (Latin plus the site's punctuation, about 47 KB per weight) and `fonts/CircularXXWeb-*.woff2` (Latin Extended, arrows, maths; loaded only for those characters through `unicode-range`)	Regular maps to 100–450, Medium to 451–750, Black to 751–925, ExtraBlack to 926–1000. Italic: Italic 100–450, MediumItalic 451–1000.	Body and headings site-wide
`circularxx-fallback`, `circularxx-heading-fallback`	`local('Arial')` with `size-adjust` and ascent/descent overrides	—	Metric-matched fallbacks, so text doesn't jump when the brand font arrives
`Archivo` (variable, 100–900, width 62–125%) and `Source Serif 4` (variable, normal and italic)	`fonts/archivo-latin-variable.woff2`, `fonts/source-serif-4-latin*.woff2`	Variable	Only the rebrand page. They are declared in `blocks/rb-hero/rb-hero.css`, not in `fonts.css`
DM Sans	`fonts/dmsans-latin*.woff2`	—	**Unused.** It was the stand-in before CircularXX; safe to delete

Licensing: CircularXX is a licensed commercial font. Anyone who forks or reuses this repository for another site must confirm the Lineto license covers that use. The `.woff` files are not referenced by `fonts.css`; only the `.woff2` files are used.

Global Content Conventions (decorated in scripts.js and styles.css)

- **Buttons:** `decorateButtons()` turns a paragraph that holds only a link into a button, based on its formatting.
  - `<strong><a>` = red `primary`.
  - `<em><a>` = ink `secondary`.
  - `<strong><em><a>` = outlined `accent`.
  - An unformatted lone link in default content becomes an `arrow-link` (text link with a cyan arrow).
  - Icons inside primary or secondary buttons are inverted to white.
- **Eyebrows:** `decorateEyebrows()` adds `.eyebrow` to a short (60 characters or fewer) ALL-CAPS paragraph directly before an h1–h3.

- **Heading highlights:** `<em>` inside an h1–h3 is green and `<strong>` is cyan.
- **Chips:** inline `<code>` renders as a bordered tag chip.
- **Icons:** `:name:` in authoring becomes `<span class="icon icon-name">`, loaded from `/icons/name.svg`.

Section Styles

These are applied with section metadata `Style` in DA, or as a class on the section `<div>` locally.

Class	Effect
`light` / `highlight`	Gray-50 band with section padding
`dark`	Ink band, white text, links inherit the text color
`gradient`	Brand green-to-cyan band, white text
`green`	Solid brand-green band (results headers: white h1/h2, ink paragraph)
`display`	Larger h2, 20–22px lead paragraph, centered image
`heading-link`	h2 on the left and a lone link on the right in one row
`narrow`	880px content width
`centered`	Centered default content
`flush` / `flush-bottom`	Remove the section margin, or only the bottom margin
`footnotes`	Small gray legal and source notes

Stardust blocks set their own tokens on `main > .section.<block>-container` (`--sd-*`, `--ua-*`, `--ub-*`, `--rb-*`). Those values apply only inside that block's section; nothing global changes.

Scripts & Integrations

scripts.js customizations

Function	What it does	Notes
Trusted Types policy	Creates a `default` policy that strips `srcdoc` iframes and `<script>` tags from HTML written through `createContextualFragment` and `document.write`.	`head.html` sets `require-trusted-types-for 'script'`
`buildAutoBlocks`	Inlines `/fragments/` links and turns `/widgets/` links into `widget` blocks.	Boilerplate behavior
`decorateButtons` / `decorateEyebrows`	The global conventions described above.	Run inside `decorateMain`, so fragments and modals get them too
`handleSpecialLinks`	A document-level click listener registered in the **eager** phase. Same-origin links to `/modals/*`, `/contact` and any `*.pdf` are handed to `modal.followLink()`.	Catches clicks made before the page has finished loading. Clicks with Cmd, Ctrl or Shift, and `download` links, are left alone.
`buildAssistantLauncher`	Adds the fixed red "SEI Assistant — Ask a question" link (`.assistant-launcher`).	See below

Function	What it does	Notes
Auto modal	In the lazy phase, page metadata `modal` (a path) and `modal-delay` (seconds, default 8) call `scheduleModal()`.	Shows once per browser session (`sessionStorage` key `sei-modal-shown:<path>`)
`loadDelayed`	Imports `consent-check.js` and handles the presenter (`?presenter`, `localStorage` key `sei-presenter`, Alt+Shift+P).	No analytics tags are loaded

Assistant launcher:

- Page metadata `assistant` picks the chat. A value of `off` removes the launcher; a `/modals/...` path forces that chat.
- Otherwise the chat follows the visitor's persona through `assistantFor()`:
  - advisor → `/modals/assistant-advisor`
  - RIA → `/modals/assistant-etf`
  - everyone else → `/modals/assistant`
- The link `href` updates whenever the profile changes.
- A `requestAnimationFrame`-throttled overlap check, run on scroll, resize and `ResizeObserver`, adds `.compact` (icon only) when the full bar would cover a link, button, input or heading. The full label comes back on hover or focus.

Page metadata in use on DA:

- `/enterprise-ria`: `assistant=/modals/assistant-etf`, `modal=/modals/etf-needs`, `modal-delay=8`.
- `/etfs`: `assistant=/modals/assistant-etf`, `modal=/modals/portfolio-evaluator`, `modal-delay=12`.

Visitor profile (scripts/profile.js)

Everything is demo data stored **in the browser only**, under the `localStorage` key `sei-profile`. Nothing is sent to a server.

The profile object has these fields: `persona`, `personaSource`, `steps`, `booking`, `contact`, `views`, `campaign`, `firstCampaign` and `answers`.

Personas (`PERSONAS`):

id	Label	Journey	Specialist (scheduler modal)	Assistant
`advisor`	Financial advisor	`breakaway`	Eric Dunn (`/modals/schedule-eric-dunn`)	`/modals/assistant-advisor`
`ria`	Enterprise RIA	`etf`	Clayton Johnson (`/modals/schedule-clayton-johnson`)	`/modals/assistant-etf`
`asset-manager`	Asset manager	`administration`	Clayton Johnson	`/modals/assistant`

Journeys (`JOURNEYS`):

- **breakaway:** Explore `/bd-breakaway` → Pathfinder `/pathfinder` → Meet SEI `/pathfinder-specialist` (completes on booking) → Partner match `/partner-match`.
- **etf:** Explore `/enterprise-ria` → SEI ETFs `/etfs` → Evaluate `/portfolio-evaluator` → Results `/portfolio-evaluator-results`.
- **administration:** Explore `/asset-managers` → Client stories `/` (`infer: false`) → Talk to SEI (no page; completes on booking).

Lifecycle stages:

- `STAGES` runs Discover → Engage → Try → Buy → Expand.
- `PAGE_STAGES` maps each page path to a stage. The visitor's `lifecycleStage()` is the furthest stage among the pages they've viewed, and is at least "Buy" once a call is booked.

Persona sources (`personaSource`):

- `selected`: the "I'm a…" menu.
- `campaign`: from a UTM link.
- `inferred`: from the journey a viewed page belongs to, or from a booking.
- `assistant`: "I'm an RIA" typed in the chat.
- `readiness`: from the readiness check.
- `presenter`: set in the presenter menu.
- `not-in-demo`: picked on the 404 page.

A persona the visitor selected is never overwritten by a campaign.

Campaigns:

- `readCampaign()` reads `utm_source`, `utm_medium`, `utm_campaign` and `utm_content` from the landing URL.
- `utm_campaign` values map to personas: `bd-breakaway` → advisor, `enterprise-ria` → ria, `ims` → asset-manager.
- The `/start/*` entry mocks link out with these parameters.

Main API:

Area	Functions
Reading the profile	`getProfile()`, `onProfileChange(cb)` (the `sei:profile` window event)
Recording activity	`recordView()`, `setPersona(id, source)`, `saveAnswers(key, value)`
Booking	`book(booking, contact)` (also fires `sei:booked`), `calendarHref(booking)` (`.ics` data URL in US Eastern time, DST-aware)
Journey and stage	`journeyStatus()`, `lifecycleStage()`, `pageStage()`, `specialistFor()`, `assistantFor()`
Presenter and reset	`simulateStage(stageId)`, `resetProfile()` (also clears the `sei-modal-shown:*` session keys)
Paths	`currentPath()`, `pageHref()`

Adobe Client Data Layer:

`track(event, data)` pushes `{ event, page: {path, stage}, visitor: {persona, personaSource, journey, stage, lifecycleStage, booked, campaign}, ...data }` onto `window.adobeDataLayer`. No Web SDK or Launch property is connected yet, so these events are collected but not sent anywhere. To wire up Adobe Analytics or CJA, load the tag in `loadDelayed()` (or in `consented.js` behind consent) and map these events.

Area	Events
Page and campaign	`page-view`, `campaign-landing`, `page-not-in-demo`
Persona and journey	`persona-selected`, `persona-cleared`, `journey-step-click`, `adaptive-shown`, `why-opened`
Chat and modals	`modal-opened`, `chat-opened`, `chat-message`, `chat-booking-started`
Booking	`talk-to-advisor-click`, `booking-confirmed`, `calendar-download`

Area	Events
Readiness check	`readiness-started`, `readiness-completed`
Media and entry mocks	`video-play`, `ad-click`, `ai-referral-click`
Demo tools	`presenter-stage`, `profile-reset`

Other window/DOM events:

Event	Fired by	Purpose
`sei:profile`	`profile.js` on save	Re-render listeners
`sei:booked`	`book()`	`specialist` block shows the booked state
`modal:open`	`openModal()` on the dialog	—
`modal:close`	Content inside a dialog (bubbling)	Closes the dialog; used by the scheduler's Back and Done buttons
`fund-finder:change` / `fund-table:ready`	`fund-finder` / `fund-table` blocks	Client-side filtering
`consent.update`	`consent-check.js`	Consent state

Header experience bar (blocks/header/experience.js)

- `header.js` loads the `/nav` fragment (or the page's `nav` metadata) and applies the standard brand / sections / tools structure. Nav dropdowns are `<button aria-expanded>` elements. The hamburger is used below 900px.
- `header.js` then appends `buildExperience()`, a bar under the nav that is never authored. It contains:
  - **"I'm a…" persona menu:** setting a persona keeps the visitor on the page. "Start over" clears the profile and reloads.
  - **Journey strip:** steps marked `done`, `current` or `here`. A step with no page opens the specialist's scheduler. On small screens a "2/4 · Pathfinder" summary replaces the strip.
  - **"Why?" button.**
  - **Action:** "Talk to an advisor" (the specialist's modal), or the booked-call pill with an "Add to calendar" `.ics` link.
- Everything re-renders on `onProfileChange`.
- Page-scoped overrides:
  - `body.ub-hero-roles` (uplift B) hides the persona picker until a role is chosen.
  - `body.rb-page` (rebrand) restyles the whole header and footer through `blocks/rb-hero/rb-chrome.css`.
  - `body.entry-mock-page` hides the header, footer and launcher.

"Why am I seeing this?" (scripts/why.js)

`openWhy(from)` lazy-loads `styles/why.css` and opens a modal `<dialog>` with four sections:

- **Your role,** with a plain-language reason based on `personaSource`.
- **Where you are:** the lifecycle stage list plus journey progress.
- **What you've done:** pages viewed, campaign source, readiness answers, booking and shared email.
- **How this works,** with a "Clear my profile" reset.

`whyButton(from, label)` returns a trigger button for the header (`Why?`), `adaptive` and `ua-role-panel`. The production note in the panel says these signals would come from Adobe Experience Platform and CJA. That copy is still flagged as a placeholder in `stardust/journal.md`.

Presenter menu (scripts/presenter.js)

This is a demo-only floating "Demo" panel. You can turn it on in three ways:

- add `?presenter` to any URL (remembered in `localStorage` `sei-presenter`)
- press Alt+Shift+P
- remove it with "Hide this menu"

The panel offers:

- **Demo journeys:** Home; Broker dealer (starts at `/start/linkedin`); RIA Enterprise (starts at `/start/ai-search`); IMS (`/asset-managers`).
- **Role chips:** set the persona, with `personaSource` = `presenter`.
- **Lifecycle stage chips:** `simulateStage()`.
- **"Book a call now":** the next weekday at 11:00 AM, with sample contact details.
- **"Reset demo"** and **"Hide this menu".**

Modals (blocks/modal/modal.js)

Modals are **not authored as a block.** Any link to `/modals/<name>` opens the fragment at that path in a `<dialog class="modal modal-<name>">`.

- **Docked chat:** names starting with `assistant` get `modal-docked`. They open non-modally (`dialog.show()`) as a bottom-right chat panel, and Escape is handled by hand.
- **Centered modals:** all other modals use `showModal()` and lock page scroll (`body.modal-open`).
- **Caching:** dialogs are cached per path and reused.
- **Persona chat fallback:** a persona chat that isn't published (for example `/modals/assistant-etf` missing) falls back to `/modals/assistant`.
- **`/contact` links** open `specialistFor().modal`, the visitor's own specialist scheduler. That is what the nav "Contact Us" button does.
- **PDF links** are checked with `fetch(..., {method: 'HEAD'})`. A missing PDF navigates to `<path without .pdf>?missing=pdf`, which lands on the branded 404 instead of a bare CDN error.
- **Closing from inside:** content inside a dialog can close it by dispatching a bubbling `modal:close` event.

Published modal fragments:

- `/modals/assistant`, `/modals/assistant-advisor`, `/modals/assistant-etf`
- `/modals/schedule-eric-dunn`, `/modals/schedule-clayton-johnson`
- `/modals/etf-needs`, `/modals/portfolio-evaluator`

Branded 404 (404.html)

`404.html` is a self-contained page. It loads `scripts.js` (header, footer and modals keep working) and `profile.js`.

- It describes the missing item in plain words, for example "The BD to RIA transition roadmap article", "The SEIV fact sheet" or "The … PDF" (from `?missing=pdf`).
- It records `page-not-in-demo` plus a RUM `404` sample.
- It offers either the visitor's next journey step and their specialist, or a "Pick up a journey" persona chooser (`personaSource` = `not-in-demo`).
- It carries `noindex, nofollow`.
- Its CSP is shorter than `head.html`'s: it has no `require-trusted-types-for` and no `frame-src`.

Consent and martech

`consent-check.js` and `consented.js` are unchanged boilerplate.

- Consent is **declined** by default.
- `?consent=accept` loads `consented.js`, which is empty.

- A real CMP (for example OneTrust) and analytics are not integrated. This is the place to add them.

Blocks Reference

Every block follows the standard contract: `blocks/<name>/<name>.js` exports `default function decorate(block)`, and `<name>.css` loads alongside it. Content is `<div class="name variant">`, then rows, then cells. All blocks below were created or customized for this project. `columns` and `widget` are untouched boilerplate and are not listed. `reference/BLOCK-LIBRARY.md` has fuller authoring notes for the Figma blocks; parts of it are now out of date (see Known Issues).

Platform and interactive blocks

Block	Purpose	Content model / variants	Key features and gotchas
`header`	Nav plus experience bar	`/nav` fragment: brand / sections / tools	Adds the experience bar (see above). The nav uses `.arrow-link` cleanup and aria-labels on icon links.
`footer`	Site footer	`/footer` fragment in 3 sections: links, brand, legal	Each heading plus its list becomes a `.footer-column`. The brand section's first `ul` becomes `.footer-nav` and the second becomes `.footer-social`.
`fragment`	Include a fragment	Link or path	Exports `loadFragment()`. Local `/content` prefix and `./images/` handling.
`assistant`	SEI Assistant chat panel (inside the docked modal)	Optional `[h2 title]` row, then message rows. A links-only row becomes quick-action buttons; an italic-only row sets the input placeholder; a picture plus link becomes a video thumbnail.	Scripted: `answers.js` matches keywords (prepare, breakaway, cost, custody, Pathfinder, ETFs, …) to canned answers. Quick replies depend on persona and page. "I'm an RIA" sets the persona. In-chat booking offers 2 slots (10:00 AM and 2:00 PM on upcoming weekdays) and calls `book()`. There is no model or API behind it.
`scheduler`	4-step booking wizard: Advisor → Date & Time → Your Details → Confirm	Rows: `[h2 title]`, then key/value rows `Advisor`, `Times` (a list; `<s>`struck or ~prefixed = unavailable), `Timezone` (default EST), `Days` (default 10 weekdays from tomorrow)	Calls `book()`, then shows the done panel with an `.ics` link. The Back button on step 1 and "Done" dispatch `modal:close`. The advisor name falls back to "…with Name," in the title. Nothing is sent to a server.
`adaptive`	Content that changes with persona and lifecycle stage	One row per version: first cell `default`, `advisor`, `ria` or `asset-manager` (optionally plus stages, e.g. `advisor buy expand`); second cell = content	Match order: persona plus current stage, then persona, then `default`. Re-renders on profile change. Adds a Why button and fires `adaptive-shown`. Used on `/`.
`readiness`	One-question-at-a-time readiness check ending in a tailored result	Row 1: intro. `Question` rows: question text + list (answers score 0, 1, 2… in order). `Result N` rows: content shown when score ≥ N (the highest match wins). Optional `Persona` row: persona id	Calls `saveAnswers('readiness')` and `setPersona(..., 'readiness')`. Adds `has-readiness` to its section and sits over the hero art. Used on `/bd-breakaway`.
`entry-mock`	Simulated third-party start page (LinkedIn-style feed with an SEI ad, or an AI-assistant answer)	Rows keyed by the first cell. `social`: Profile, Ad, Post, Promoted. `ai-answer`: Assistant, Question, Answer.	Adds `body.entry-mock-page`, which hides the SEI header, footer and launcher, and shows a "(simulated)" label. Links carry `utm_*` parameters. Fires `ad-click` / `ai-referral-click`. Used on `/start/linkedin` and `/start/ai-search`.

Block	Purpose	Content model / variants	Key features and gotchas
`video`	Poster that turns into a player on click	A picture (poster), a link (video) and optional caption text	Supported links: a Brightcove player URL (`players.brightcove.net/<account>/<player>_default/index.html?videoId=…`), an AEM Assets Dynamic Media delivery URL (`delivery-pX-eY.adobeaemcloud.com/adobe/assets/urn:aaid:aem:…`, rewritten to `/play?autoplay=1`), or an `.mp4` (native `<video>`). Any other link shows the poster only (`no-source`). Fires `video-play`. The iframe relies on CSP `frame-src https:`.
`specialist`	Matched-specialist card	`[photo, name, role, location]` `[label + reasons list][CTA]`, optional `[availability][Book link]`. Variant `muted`.	Switches to the booked state on `sei:booked` or a stored booking (matched by advisor name). Moved into the `program` panel on `/pathfinder-specialist`.

Figma design-system blocks

Block	Purpose	Variants	Key features and gotchas
`hero`	Full-bleed image hero	`short`, `home`	The image is set to eager loading with high fetch priority. `home` splits the h1 at ` ` into white bands (rewrites the heading with innerHTML).
`cards`	Card grid	`promo`, `leadership`, `promo expand`	Per-card `inverse` cell. `expand` is a desktop accordion: the first tap only activates the tile. A leadership card with exactly one link becomes clickable as a whole.
`callout`	Gradient band with copy and a clipboard stat	—	Only the first two cells are used.
`tabs`	ARIA tabs with text or logo labels	`case-study`	Roving tabindex with arrow keys (no Home/End). The tab with a bold label opens first.
`stats`	Figures over a map	per-row `featured`	Only one featured stat. The background picture is not optimized.
`spotlight`	Video thumbnail plus quote	—	The play control links out; it has no inline player.
`teaser`	Dark split promo band	—	Content is always placed before media.
`promo`	Tall image card for pop-ups	—	The image is eager-loaded even inside a modal.
`personalize`	"Choose your path" options card	`stacked` (added automatically)	Visual selection only; it does not change the profile.
`newsletter`	Sign-up band (on 11 pages)	—	**Mock submit:** it validates the email and shows a thank-you message, but never posts.
`benefits`	Two benefit columns	`benefits-split` (automatic)	A picture paragraph before an h3 becomes that item's icon.
`checklist`	Consultation checklist	—	Sets `--checklist-cols`.
`feature-video`	Video thumbnail plus a feature list	—	The play control only links out.
`podcast`	Podcast player card	`is-playing` state	Plays an `.mp3` link through `<audio>`. Share uses the Web Share API or the clipboard. It throws if the cover cell has no `img`.

Block	Purpose	Variants	Key features and gotchas
`program`	Pathfinder step navigation plus panel	`video`	Active step: the bold one, else the one linking to the current path. Pulls a following `.specialist-wrapper` into the panel. The video controls are decorative.
`match-header`	Partner-match header	—	Icon badge and chip paragraphs.
`bar-chart`	Grouped SVG bar chart	—	Has a screen-reader data table. Redraws on resize and when fonts load. Colors are hard-coded.
`fund-compare`	Radar chart plus fund list	—	Needs 3 or more axes. Fixed size and colors.
`fund-finder` + `fund-table`	Search and filters plus a sortable table (`/etfs`)	—	Linked by `fund-finder:change` and `fund-table:ready`. Filter keys are slugs of the dropdown names and must match the italic (hidden) header columns of the table. Only one finder per page.
`fund-cards`	Performance-leader cards	—	Relies on the global `button-wrapper` class.
`result-cards`	Matched-strategy results	`tone-*` (automatic)	Tag tones come from hard-coded keyword regexes.
`strategy-cards`	Searchable, filterable strategy cards with a risk meter	—	The risk cell must match `^\d+(/\d+)?$`.
`strategy-finder`	Criteria tile picker	`tone-*`, `stacked`	Selections become query parameters on the results CTA.
`top-choice`	"SEI top choice" panel	—	Static content; no profile logic.

Stardust home-page variant blocks

These blocks implement five alternative home pages produced by the stardust pipeline. Each family is self-contained and scoped by prefix. The variants were built on a **frozen foundation**: shared scripts, styles, header, footer and existing blocks were not changed. They also reuse the site's button and eyebrow decoration.

Family	Page	Blocks	Notes
`sd-*` brand-faithful refresh	`/index-stardust`	`sd-hero`, `sd-promos` (LCP image eager), `sd-statement`, `sd-case-studies` (ARIA tabs with Home/End), `sd-reach`, `sd-perspectives`, `sd-newsletter`	`sd-hero` keeps only the h1 and the first paragraph.
`ua-*` uplift A	`/index-uplift-a` (also used by B and C)	`ua-hero`, `ua-promos`, `ua-role-panel` (a restyled `adaptive` that uses profile.js and why.js; all versions stay in the DOM, hidden), `ua-statement`, `ua-case-tabs`, `ua-stats`, `ua-leaders`, `ua-newsletter`	`uc-cinematic` depends on `ua-*` class names such as `.ua-hero-bar` and `.ua-stat-value > p`. Don't rename them.
`ub-*` uplift B	`/index-uplift-b`	`ub-hero` (role "doors"; adds `body.ub-hero-roles`), `ub-proof-wall`, `ub-promo-rail`	Reuses `ua-statement`, `ua-stats`, `ua-leaders` and `ua-newsletter`.
`uc-cinematic` uplift C	`/index-uplift-c`	One motion-layer block placed after `ua-hero`	See below.

Family	Page	Blocks	Notes
rb-* rebrand	/index-rebrand	rb-hero, rb-directory, rb-listings, rb-positioning, rb-spec-sheet, rb-ledger, rb-leaders, rb-newsletter	rb-hero must be on the page: it declares the Archivo and Source Serif 4 @font-face rules, adds body.rb-page and loads rb-chrome.css.

All the stardust newsletter blocks (sd-, ua-, rb-newsletter) submit nothing; like newsletter, they validate on the client only.

uc-cinematic motion layer:

- **Loading:** it loads the vendored Lenis (loadScript / loadCSS) after the window load event, with lerp 0.1, syncTouch: false (touch scrolling stays native) and anchors: false.
- **Where Lenis is off:** it is prevented on the header, dialogs, .assistant, textarea, select and [data-lenis-prevent]. It stops while body.modal-open is set or a modal dialog is open.
- **Animations:** wipes on hero bars, h2 bars, stat rules and numerals, cards and the case-study panel. They are driven by IntersectionObserver and MutationObserver and gated on html.uc-motion.
- **Reduced motion:** when prefers-reduced-motion: reduce is set at load, html.uc-motion is never added and Lenis never loads. If the setting turns on mid-visit, stopMotion() reveals everything and destroys Lenis.
- **Print:** beforeprint reveals everything.
- **Scope:** all rules are scoped to main:has(.uc-cinematic.block), and only one layer runs per page.
- **Test hook:** window.__lenis is exposed for the pipeline's motion checks.

Rebrand chrome: every rule in blocks/rb-hero/rb-chrome.css is prefixed with body.rb-page. It overrides --body-font-family, --heading-font-family, --link-color, --nav-height and --experience-height, and restyles the nav, experience bar, footer and launcher for that page only. Archivo Fallback is referenced in the CSS but never declared, so the fallback is plain Arial without metric matching.

Templates

This project uses no templates. There is no templates/ folder and no page sets template metadata. Page-level variation comes from blocks that add body classes: rb-page, ub-hero-roles and entry-mock-page.

Pages and Content Inventory

Path	Purpose / key blocks
/	Home: hero home, cards promo expand, adaptive, tabs case-study, stats, cards leadership, newsletter
/index-stardust, /index-uplift-a, /index-uplift-b, /index-uplift-c, /index-rebrand	Alternative home-page designs (stardust)
/bd-breakaway, /pathfinder, /pathfinder-specialist, /partner-match	Financial advisor "breakaway" journey (readiness, program, specialist, match-header, checklist)
/enterprise-ria, /etfs, /portfolio-	Enterprise RIA / ETF journey (fund-finder, fund-table, strategy-finder, bar-chart, fund-compare, result-cards)

Path	Purpose / key blocks
`evaluator`, `/portfolio-evaluator-results`	
`/asset-managers`	Asset-manager (IMS) journey entry
`/insights/videos/summit-wealth-partnering-with-purpose`	Video page (`video` block)
`/start/linkedin`, `/start/ai-search`	Simulated entry pages (`entry-mock`)
`/modals/*`	7 modal fragments (assistants, schedulers, pop-ups)
`/nav`, `/footer`	Header and footer fragments

Links to pages that are not part of the demo (for example `/solutions/*`, `/about/*`) intentionally land on the branded 404.

Common Development Tasks

Add a New Block

1. Check `curl https://main--sei--oharris69.aem.page/<page>.plain.html` to see the real markup authors produce.
2. Create `blocks/{name}/{name}.js` with `export default function decorate(block)` and a JSDoc header describing the rows and cells, as the existing blocks do.
3. Create `blocks/{name}/{name}.css`. Write it mobile first, with desktop at `@media (width >= 900px)`. Scope every rule to `.{name}`; `-wrapper` and `-container` are section classes. Use the tokens from `styles.css`. Add a `prefers-reduced-motion` fallback for any transition.
4. Decorate defensively: classify cells by content, tolerate missing or extra cells, and use `createOptimizedPicture` for images.
5. Import shared code only from `/scripts/` (for example `profile.js` or `why.js`). `fragment/fragment.js` is the only cross-block import.
6. Run `npm run lint`. Test locally, then push a feature branch and include `https://{branch}--sei--oharris69.aem.page/{path}` in the PR. A PR without that link is rejected.

Add a persona, journey step or lifecycle mapping

1. Edit `PERSONAS`, `JOURNEYS`, `PAGE_STAGES` or `CAMPAIGNS` in `scripts/profile.js`.
2. For a new specialist, publish a `/modals/schedule-<name>` fragment with a `scheduler` block. For a new chat, publish `/modals/assistant-<persona>`; it falls back to `/modals/assistant` until it exists.
3. Add quick replies in `blocks/assistant/answers.js` (`SUGGESTIONS`, `PAGE_SUGGESTIONS`, `TOPICS`).
4. If `adaptive` content should react to the new persona, author an `adaptive` row keyed by the new persona id.
5. Existing visitors keep their old profile. Use “Start over” or the presenter’s “Reset demo” to test from a clean state.

Add a pop-up

1. Author a page under `/modals/<name>` in DA and preview and publish it.

2. Link to `/modals/<name>` from any page, or set page metadata `modal` = `/modals/<name>` plus `modal-delay` = seconds to open it automatically once per session.
3. Size or position it with `.modal-<name>` rules in `blocks/modal/modal.css`. Names starting with `assistant` dock as a chat panel.

Modify Global Styles

1. Edit `styles/styles.css`, keeping critical CSS lean. Remember that the stardust pages and the rebrand chrome (`rb-chrome.css`) rely on the global classes and tokens.
2. Test the main journey pages **and** the five home variants.
3. Watch for CLS: the header height reservation, the font fallbacks and image sizes.

Add Analytics/Marketing Tools

1. Load tags (Adobe Web SDK / Launch, a CMP) from `loadDelayed()` in `scripts.js`, or from `scripts/consented.js` once a real consent check replaces the stub in `consent-check.js`.
2. Never add them to the eager or lazy phases.
3. Map the existing `window.adobeDataLayer` events (see the table above). The data layer array is created on the first `track()` call.
4. Check in the Network tab that the tags load late.

Debug a Block

1. Check the browser console for errors.
2. Compare the backend `.plain.html` with the decorated DOM. Remember that `decorateButtons` and `decorateEyebrows` have already run before your block.
3. Check that variant classes are applied, and that the block isn't hidden by a page-scoped body class.
4. For personalization bugs, inspect `localStorage['sei-profile']`, open the "Why?" panel, and use `?presenter` to set the role and stage quickly.
5. For data layer events, run `window.adobeDataLayer` in the console.

Environments

Environment	URL pattern	Purpose
Local	http://localhost:3000 (or `:3001/content/<page>` with the local folder)	Development
Feature branch	`https://{branch}--sei--oharris69.aem.page/{path}`	PR testing
Preview	https://main–sei–oharris69.aem.page/	Staging, with previewed DA content
Live	https://main–sei–oharris69.aem.live/	Production / demo

Merging to `main` ships code immediately. Content previews and publishes separately from DA. Configuration lives in the Config Service at `admin.hlx.page/config/oharris69/sites/sei.json`; `fstab.yaml`, `helix-query.yaml` and `paths.json` are retired and must not be reintroduced.

Git Workflow

Branch Naming

- Features: `feature/description`. Fixes: `fix/description`.
- Keep names short and lowercase: the branch name becomes part of a hostname (URL length limits).

PR Requirements

1. Include the feature-branch preview URL (`https://{branch}--sei--oharris69.aem.page/{path}`) in the PR description, using the before/after template in `.github/pull_request_template.md`.
2. Pass linting (CI runs `npm run lint`).
3. Test on the branch preview: journeys, modals, and the home variants if you touched shared code.
4. No console errors.

Files that must not be served

Every committed file is publicly served unless it is excluded in `.hlxignore`. That file currently excludes:

- dotfiles and `*.md`
- `package*.json` and `LICENSE`
- `reference/*`, `migration-work/*`, `stardust/` and `exports/`
- `DESIGN.json` and `DESIGN-*.json`
- `.claude-plugin/`

When adding tooling or working files, add them to `.hlxignore` (and `.gitignore` if they shouldn't be committed). At handover, the `.claude-plugin/` lines in `.gitignore` and `.hlxignore` are uncommitted local edits, and `.agents/`, `.migration/` and `reference/` are untracked.

Known Issues and Caveats

- **Demo-only behavior:** the assistant, scheduler, newsletter forms and readiness check run entirely in the browser. No data is sent anywhere, and there is no CRM, calendar or LLM integration. The `.ics` file is generated client-side.
- **No analytics connected:** data layer events are pushed but not consumed. The consent stub always declines unless `?consent=accept` is set.
- **`reference/BLOCK-LIBRARY.md` is partly out of date.** It still describes DM Sans as the stand-in font and heading weight 900. The code now uses CircularXX with `--heading-font-weight: 1000`, and the heading sizes it lists are the desktop values only.
- **Stardust conversion logs** (`stardust/*conversion-log*.md`) record:
  - The content width is 1232px against the prototypes' 1280px, so some text wraps one extra line.
  - The hero line splitting collapses while editing in-context.
  - "→" falls outside the CircularXX Sub subset, so it is served from the Web file (or a fallback font on the rebrand page).
  - Lenis boots after `load`, and back/forward scroll restoration was not tested.
  - Which home variant goes forward is an **open decision** (`stardust/journal.md`).
  - Two items in these logs are stale. The footer overflow at 900–1024px was addressed in commit `d3175b6`. The missing modal image under local preview is handled by `fragment.js`'s `./images/` rewriting.
- **Hard-coded demo data:** personas, specialists, journeys and stage mappings (`profile.js`), canned answers (`answers.js`), chart colors, tag-tone regexes and booking slots.

- **Unused assets:** the DM Sans font files and the `.woff` (non-woff2) CircularXX files are not referenced. Two identical copies of `terrazzo-tile.svg` (86 KB) exist, in `rb-hero` and `rb-positioning`.
- **`scripts/aem.js` is vendored.** Never edit it; upgrade it only by replacing it from the boilerplate.

Troubleshooting

Block not loading?

1. Check that the block folder name matches the class name, and that the JS exports `default function decorate`.
2. Check the Network tab for 404s on `/blocks/<name>/<name>.js` or `.css`.
3. Check whether a page-scoped body class (`entry-mock-page`, `rb-page`, `ub-hero-roles`) is hiding it.

Styles not applying?

1. Check CSS specificity. The rebrand chrome uses `body.rb-page …` selectors, and stardust tokens are section-scoped.
2. Check that the file is loading (Network tab), and run Stylelint.

Modal or chat doesn't open?

1. Check that the `/modals/<name>` page is previewed and published (`curl https://main--sei--oharris69.aem.page/modals/<name>.plain.html`).
2. The link must be same-origin. Cmd/Ctrl/Shift-clicks and `download` links are deliberately ignored.
3. An auto-opening modal shows only once per session. Clear `sessionStorage`, or use "Reset demo".

Personalization looks wrong?

1. Open the "Why?" panel, or inspect `localStorage['sei-profile']`.
2. A persona the visitor picked in the menu wins over campaigns. Reset the profile to test UTM links again.
3. On the local folder server, check that paths include `/content`; code-built links rely on `pageHref()`.

Content not updating?

1. Clear the browser cache.
2. Check that the page was previewed (and published, for live) in DA.
3. Wait 1–2 minutes for the CDN cache.

Fonts look wrong?

1. `fonts.css` loads lazily on mobile, so the metric-matched Arial fallback shows first. This is expected.
2. On the rebrand page, check that `rb-hero` is on the page; it declares Archivo and Source Serif 4.

Resources

Resource	URL
Edge Delivery Services Documentation	https://www.aem.live/docs/
Developer Tutorial	https://www.aem.live/developer/tutorial
Block Collection	https://www.aem.live/developer/block-collection

Resource	URL
E-L-D Loading (Keeping it 100)	https://www.aem.live/developer/keeping-it-100
Best Practices	https://www.aem.live/docs/dev-collab-and-good-practices
Config Service / Admin API	https://www.aem.live/docs/admin.html
Document Authoring	https://da.live/
Project notes	`AGENTS.md`, `reference/BLOCK-LIBRARY.md`, `stardust/journal.md`, `stardust/*conversion-log*.md`

Support Contacts

Role	Contact
Repository owner / original developer	Owen (GitHub `oharris69`)
Site administrators	See the Config Service `access.admin` roles for site `sei`
Project-specific contacts	*To be added by the receiving team*