

Analysis For Exercise 3.2: Posterior Probabilities With LDA And QDA

Created: 09/17/2023 by Tom Lever (TSL2b@Virginia.edu)

Updated: 09/17/2023 by Tom Lever (TSL2b@Virginia.edu)

I completed this exercise myself.

2. Differences Between LDA And QDA

LDA1 and QDA1: Describe distinct source files

This is code for Linear Discriminant Analysis

This is code for Quadratic Discriminant Analysis

LDA {34,35} and QDA {34,35}: Define distinct classes

class LDA:

"""Creates a class for Linear Discriminant Analysis

class QDA:

"""Creates a class for Quadratic Discriminant Analysis

LDA {71,72} and QDA {71,72}: Initialize a mean covariance matrix versus initialize a dictionary for class-specific covariance matrices

compute the mean covariance matrix

self.cov = np.zeros([self.num_cols, self.num_cols])

compute the covariance matrix of each class

self.covs = dict()

LDA {74,75} and QDA74: Calculate mean covariance matrix versus calculate class-specific covariance matrix

self.cov = self.cov + self.num_obs[name] * np.cov(np.transpose(self.data[self.data_labels == name, :]))

self.cov = self.cov / self.num_rows

self.covs[name] = np.cov(np.transpose(self.data[self.data_labels == name, :]))

LDA92 and QDA91: Construct multivariate Gaussian Probability Density Function with mean covariance matrix versus class-specific covariance matrix

likelihoods[idx] = multivariate_gaussian_pdf(x, self.means[name], self.cov)

likelihoods[idx] = multivariate_gaussian_pdf(x, self.means[name], self.covs[name])

LDA94: Remove of blank line

LDA {99,100} and QDA {97,98}: Change described model

print('LDA Predicted Class: ' + self.class_names[indices_sorted[0]])

print('LDA Class Likelihoods:')

print('QDA Predicted Class: ' + self.class_names[indices_sorted[0]])

```
print('QDA Class Likelihoods:')
```

LDA112 and QDA110: Changed model name and constructor

```
model_lda = LDA('iris_data.csv')
```

```
model_qda = QDA('iris_data.csv')
```

LDA115 and QDA 113: Changed use of model

```
model_lda.compute_likelihoods(Iris_setosa_observation)
```

```
model_qda.compute_likelihoods(Iris_setosa_observation)
```

LDA{122,123} and QDA{120,121}: Changed use of model

```
model_lda.compute_probabilities(Iris_setosa_observation, uninformative_priors)
```

```
print(model_lda)
```

```
model_qda.compute_probabilities(Iris_setosa_observation, uninformative_priors)
```

```
print(model_qda)
```

3. In both Exercise3.2_Linear_Discriminant_Analysis.py and

Exercise3.2_Quadratic_Discriminant_Analysis.py,

```
def compute_probabilities(self, x, priors):
    likelihoods = self.compute_likelihoods(x)
    number_of_classes = len(priors)
    array_of_prior_probabilities = np.zeros(number_of_classes)
    index = 0
    for class_name in self.class_names:
        array_of_prior_probabilities[index] = priors[class_name]
        index += 1
    joint_probabilities = np.multiply(likelihoods,
array_of_prior_probabilities)
    total_and_marginal_probability = np.sum(joint_probabilities)
    posterior_probabilities = joint_probabilities /
total_and_marginal_probability
    indices_that_sort_posterior_probabilities =
np.argsort(posterior_probabilities[::-1])
    print('LDA Predicted Class:' +
self.class_names[indices_that_sort_posterior_probabilities[0]])
    print('LDA Class Posterior Probabilities:')
    for index in range(0, len(indices_that_sort_posterior_probabilities)):
        print(self.class_names[indices_that_sort_posterior_probabilities[inde
x]] + ': ' +
str(posterior_probabilities[indices_that_sort_posterior_probabilities[index]]))
    return posterior_probabilities
```

4. Predicted Classes And Posterior Probabilities For Carl's Observations, LDA And QDA, And Uninformative Priors

Predicted Classes And Posterior Probabilities For Carl's Observations, LDA, And Uninformative Priors

Carl's First Observation:

LDA Predicted Class:Iris-versicolor

LDA Class Posterior Probabilities:

Iris-versicolor: 0.9999970568617268

Iris-virginica: 2.94313827322853e-06

Iris-setosa: 1.0221808316494076e-17

Carl's Second Observation:

LDA Predicted Class:Iris-versicolor

LDA Class Posterior Probabilities:

Iris-versicolor: 0.5602348418832768

Iris-virginica: 0.43976515811672334

Iris-setosa: 2.4269307963452403e-28

Predicted Classes And Posterior Probabilities For Carl's Observations, QDA, And Uninformative Priors

Carl's First Observation:

QDA Predicted Class:Iris-versicolor

QDA Class Posterior Probabilities:

Iris-versicolor: 0.9999701265523081

Iris-virginica: 2.9873447691956454e-05

Iris-setosa: 2.71126344764457e-52

Carl's Second Observation:

QDA Predicted Class:Iris-virginica

QDA Class Posterior Probabilities:

Iris-virginica: 0.5648248061588751

Iris-versicolor: 0.4351751938411249

Iris-setosa: 2.7265939261013007e-103

5. Predicted Classes And Posterior Probabilities For Carl's Observations, LDA And QDA, And Informative Priors

Predicted Classes And Posterior Probabilities For Carl's Observations, LDA, And Informative Priors

Carl's First Observation:

LDA Predicted Class:Iris-versicolor

LDA Class Posterior Probabilities:
Iris-versicolor: 0.9999896990918361
Iris-virginica: 1.0300908163807187e-05
Iris-setosa: 5.110866553279631e-18

Carl's Second Observation:
LDA Predicted Class:Iris-virginica
LDA Class Posterior Probabilities:
Iris-virginica: 0.7331468987640914
Iris-versicolor: 0.2668531012359085
Iris-setosa: 5.780022600099131e-29

Predicted Classes And Posterior Probabilities For Carl's Observations, QDA, And Informative Priors

Carl's First Observation:
QDA Predicted Class:Iris-versicolor
QDA Class Posterior Probabilities:
Iris-versicolor: 0.9998954507411951
Iris-virginica: 0.00010454925880481221
Iris-setosa: 1.355530487899472e-52

Carl's Second Observation:
QDA Predicted Class:Iris-virginica
QDA Class Posterior Probabilities:
Iris-virginica: 0.8195837457481516
Iris-versicolor: 0.18041625425184843
Iris-setosa: 5.651997976619851e-104