

The GraphQL API has been updated

In Strapi 5, the GraphQL API has been updated. It handles the new, flattened response format (see [related breaking change](#)), and can also now accept [Relay-style](#) queries.

This page is part of the [breaking changes database](#) and provides information about the breaking change and additional instructions to migrate from Strapi v4 to Strapi 5.

🔧 Is this breaking change affecting plugins? **Yes**

🤖 Is this breaking change automatically handled by a codemod? **No**

List of changes

Topic	Description of the changes
File upload support	- Removed <code>upload</code> <code>multipleUpload</code> mutations - Removed <code>updateFileInfo</code> mutation in favor of using the <code>updateUploadFile</code> mutation - Removed <code>removeFile</code> mutation in favor of using the <code>deleteUploadFile</code> mutation - Removed <code>folder</code> queries & mutations - Removed <code>createUploadFile</code> mutation
Internationalization support	Removed the <code>createXXLocalization</code> mutations in favor of being able to update any locale from the main <code>updateXXX</code> mutation
Draft & Publish support	Removed <code>publicationState</code> in favor of <code>status</code> to align with the new Draft & Publish behavior
Schema changes	Simplified the basic queries with no <code>meta</code> / <code>pagination</code>

Topic	Description of the changes
	Introduced <code>Connection</code> to add pagination

For an extensive description of the new Strapi 5 GraphQL API, please refer to the [GraphQL API](#) reference documentation.

Migration

To gradually convert to the new GraphQL API format, follow these steps:

1. Enable v4 compatibility mode with the `v4CompatibilityMode` flag in the configuration of the GraphQL plugin (see [plugins configuration](#)):

```
{
  restaurants {
    data {
      id
      attributes {
        title
        image {
          data {
            id
            attributes {
              url
            }
          }
        }
      }
    }
  }
  images {
    data {
      id
      attributes {
        url
      }
    }
  }
  xToOneRelation {
    data {
      id
      attributes {

      }
    }
  }
}
```

```

    }
    xToManyRelation {
      data {
        id
        attributes {
          field
        }
      }
    }
  }
}
meta {
  pagination {
    page
    pageSize
  }
}
}
}

```

2. Use `documentId` instead of `id` for contentType queries & mutations:

```

{
  restaurants {
    data {
      documentId
      attributes {
        title
        image {
          data {
            documentId
            attributes {
              url
            }
          }
        }
      }
    }
    images {
      data {
        documentId
        attributes {
          url
        }
      }
    }
  }
  xToOneRelation {

```

```

      data {
        documentId
        attributes {

        }
      }
    }
    xToManyRelation {
      data {
        documentId
        attributes {
          field
        }
      }
    }
  }
}
meta {
  pagination {
    page
    pageSize
  }
}
}
}

```

```

{
  mutation {
    updateRestaurant(
      documentId: "some-doc-id",
      data: { title: "My great restaurant" }
    ) {
      data {
        documentId
        attributes {
          title
          image {
            data {
              documentId
              attributes {
                url
              }
            }
          }
        }
      }
    }
  }
}

```

```
}  
}  
}  
}
```

3. Move to `_connection` without changing response format (only applies to queries):

```
{  
  # collection fields can be renamed to _connection to get a v4 compat response  
  restaurants_connection {  
    data {  
      id  
      attributes {  
        title  
        image {  
          data {  
            id  
            attributes {  
              url  
            }  
          }  
        }  
      }  
      # collection fields can be renamed to _connection to get a v4 compat  
      response  
      images_connection {  
        data {  
          id  
          attributes {  
            url  
          }  
        }  
      }  
      xToOneRelation {  
        data {  
          id  
          attributes {  
            field  
          }  
        }  
      }  
      # collection fields can be renamed to _connection to get a v4 compat  
      response  
      xToManyRelation_connection {  
        data {  
          id
```

```

        attributes {
            field
        }
    }
}
}
meta {
    pagination {
        page
        pageSize
    }
}
}
}

```

4. Remove attributes (applies to queries & mutation responses):

```

{
  # collection fields can be renamed to _connection to get a v4 compat response
  restaurants_connection {
    data {
      id
      title
      image {
        data {
          id
          url
        }
      }
    }
  }
  # collection fields can be renamed to _connection to get a v4 compat response
  images_connection {
    data {
      id
      url
    }
  }
  xToOneRelation {
    data {
      id
      field
    }
  }
  # collection fields can be renamed to _connection to get a v4 compat response
  xToManyRelation_connection {

```

```

      data {
        id
        field
      }
    }
  }
  meta {
    pagination {
      page
      pageSize
    }
  }
}
}

```

5. Use new naming or the simpler queries:

```

{
  # Rename data to nodes & meta.pagination to pageInfo
  restaurants_connection {
    nodes {
      id
      title
      # can remove data in single Images
      image {
        id
        url
      }
      # collection fields can be renamed to _connection to get a v4 compat response
      images_connection {
        nodes {
          id
          url
        }
      }
    }
    # can remove data in xToOne
    xToOneRelation {
      id
      field
    }
    # collection fields can be renamed to _connection to get a v4 compat response
    xToManyRelation_connection {
      nodes {
        id
        field
      }
    }
  }
}

```

```

    }
  }
}
pageInfo {
  page
  pageSize
}
}
}

```

```

{
  # remove _connection & data if you don't need pagination att all
  restaurants {
    id
    title
    image {
      id
      url
    }
    # remove _connection & data
    images {
      id
      url
    }
    xToOneRelation {
      id
      field
    }
    # remove _connection & data
    xToManyRelation {
      id
      field
    }
  }
}
}

```

Tags: [breaking changes](#) [content API](#) [GraphQL](#) [upgrade to Strapi 5](#)

[✎ Contribute to this page on GitHub](#)