

Technical Report

List of Technical Abbreviations and Acronyms

Acronym	Full Expanded Form (Definition)
GIS	Geographic Information System
API	Application Programming Interface
REST	Representational State Transfer
RLS	Row-Level Security (PostgreSQL Access Policy)
JWT	JSON Web Token (Authentication Token)
JSON / JSONB	JavaScript Object Notation / Binary JavaScript Object Notation
SQL	Structured Query Language
ACID	Atomicity, Consistency, Isolation, Durability (Database Transaction Properties)
DOM	Document Object Model (Browser Document Tree)
FCP	First Contentful Paint (Web Performance Metric)
FOUC	Flash of Unstyled Content
WCAG	Web Content Accessibility Guidelines
OSM	OpenStreetMap (Open-Source Geographic Data)
SVG	Scalable Vector Graphics
CDN	Content Delivery Network
UUID	Universally Unique Identifier
PK / FK	Primary Key / Foreign Key (Relational Database Constraints)
KNUST	Kwame Nkrumah University of Science and Technology

1. Introduction and Background

At Kwame Nkrumah University of Science and Technology (KNUST), campus life is driven by an active student body and numerous associations organizing hundreds of extracurricular, academic, professional, and social events each semester. These range from academic conferences, symposiums, and software hackathons to society dinners, sports tournaments, night markets, and religious fellowships.

Despite the high volume of events, publicity and registration mechanisms across the university remain heavily fragmented. Organizers rely on physical paper flyers pasted over public notice boards, unindexed broadcast messages on WhatsApp group chats, and short-lived social media stories. This lack of a structured digital channel leads to high information decay, poor attendance estimation, venue confusion among freshmen and non-resident students, and severe logistical bottlenecks during door check-ins.

2. Problem Statement and Objectives

The primary challenge addressed by this project is the absence of a reliable, centralized, and spatially aware event coordination platform for the university. Specific issues include:

- **Information Scattering:** Students frequently miss relevant developmental programs due to uncoordinated publicity channels.

- **Geospatial Ambiguity:** Navigating diverse venue locations across campus—such as the Great Hall, Paa Joe Stadium, College of Science Auditorium, and Prempeh II Library—is challenging without an integrated Geographic Information System (GIS).
- **Capacity and Roster Bottlenecks:** Student societies lack real-time registration caps and verified attendee rosters, causing hall overcrowding or unexpected empty seats.

The primary objective of EVENTWEB is to design and implement an institutional-grade platform that unifies event discovery, provides spatial navigation on an interactive campus map, automates ticket reservation with unique verification codes, and provides verified societies with an administrative management dashboard.

3. System Architecture and Frontend Layer Stack

EVENTWEB is engineered following a decoupled, three-tier cloud software architecture consisting of an ultra-high-performance client presentation layer, a managed relational database layer, and a serverless notification engine.

3.1 Detailed Presentation Layer Architecture (Frontend Stack)

The frontend is architected as an ultra-fast, zero-overhead client layer prioritizing sub-second First Contentful Paint (FCP) and high visual fidelity without the heavy execution overhead of bloated single-page application frameworks. The presentation layer comprises five coordinated engineering subsystems:

1. Declarative Component State Engine (`DCLogic`):

Rather than relying on heavy Document Object Model (DOM) virtual abstraction layers, the frontend utilizes an efficient reactive component architecture. The core component state maintains centralized reactive properties (`cat`, `query`, `sort`, `venue`, `openId`, `hero`, `autoplay`, `dragX`, `dragging`). Component lifecycles (`componentDidMount`, `componentDidUpdate`, `componentWillUnmount`) manage background timers, custom DOM event bindings, and bi-directional synchronization with the Geographic Information System (GIS) map.

2. Modernist CSS Design System & Custom Property Tokens:

All visual styling is centralized inside a formal Cascading Style Sheets (CSS) token layer (`eventweb.css`). The system enforces three core visual rules:

- *Zero-Radius Philosophy* (`--ew-radius: 0px`): Strict modernist/Swiss design principles where cards, buttons, tags, chips, and modal sheets feature razor-sharp geometric edges.
- *1px Precision Hairline Boundaries* (`--ew-rule: 1px`): Replaced thick neo-brutalist borders with clean 1px hairlines (`--ew-rule-color`) allowing cards, sticky headers, and input controls to blend seamlessly.
- *Curated Color Ramps & WCAG AA Contrast*: Brand blue (`#1a3ee8`) clears a 7.25:1 contrast ratio on light grounds adhering to Web Content Accessibility Guidelines (WCAG) Level AA; dark mode automatically adjusts background tokens (`--ew-bg: #090a0f`) and surface borders (`--ew-rule-color: #29324a`) with zero Flash of Unstyled Content (FOUC).

3. 3D Perspective Hero Deck & Gesture Physics Engine:

The hero section renders an interactive 3D poster deck where card offsets, rotation angles, scale factors, and opacity layers are computed deterministically:

- Card index 0: `scale: 1.0, opacity: 1.0, z-index: 30, rotation: 0°`
- Card index 1: `scale: 0.86, opacity: 0.5, z-index: 20, rotation: +3°`
- Card index 2: `scale: 0.74, opacity: 0.24, z-index: 10, rotation: +5.5°`

The gesture physics engine hooks into Pointer Events (`pointerdown`, `pointermove`, `pointerup`), tracking touch/mouse drag displacement (`dragX`) with a 70px release threshold that snaps to adjacent cards or springs back fluidly.

4. Smart 5-Second Inactivity Autoplay State Machine:

When left idle, the poster stack advances automatically every 5000ms. An interaction state listener monitors user navigation: clicking next/previous buttons, selecting carousel indicators, dragging a poster, or selecting a category clears the active interval and immediately restarts a fresh 5-second countdown. Opening an event registration sheet pauses autoplay to ensure uninterrupted reading.

5. Client-Side GIS Map Web Component (``):

Encapsulated Leaflet.js cartography embedded directly into the DOM tree. Implements stacking context isolation (`isolation: isolate; z-index: 1`) to prevent Leaflet internal tile panes from overlapping the sticky top navigation header during vertical scrolling.

4. Technical Stack Justification

Component	Technology	Technical Justification
Frontend UI	HTML5 & Vanilla JavaScript	Eliminates heavy framework bundle overhead; provides sub-second First Contentful Paint (FCP).
Design System	Modernist CSS (1px rules)	Zero border-radius, clean hairline rules, and full Web Content Accessibility Guidelines (WCAG) compliance.
Spatial GIS	Leaflet.js + OSM Cartography	Lightweight client-side Geographic Information System map rendering with accurate KNUST campus venue coordinates.
Relational Database	Supabase (PostgreSQL 15)	ACID transaction guarantees, atomic capacity triggers, and native Row-Level Security (RLS).
Authentication	Supabase Auth (JWT)	Role-based separation via JSON Web Tokens between public student attendees and verified society organizers.
Object Storage	Supabase Storage (`event-posters`)	Content Delivery Network (CDN) backed image storage with secure authenticated write permissions.
Email Dispatch	Resend API + Edge Functions	Serverless Application Programming Interface (API) execution ensuring high deliverability without exposing private keys.

5. Relational Database Design and Data Integrity

The relational database schema is normalized across three core tables to guarantee referential integrity and eliminate data redundancy:

- **Organizers Table (`organizers`):** Stores society and faculty organizer profiles linked directly to Supabase Auth (`auth.users.id`). Fields include Universally Unique Identifier (`id` as Primary Key), `org\_name`, `org\_type` (Society, Faculty, Club, Committee), `email`, and `is\_verified`.
- **Events Table (`events`):** Stores comprehensive event metadata including title, category ENUM (Academic, Social, Sports, Religious, Business), venue name, date, time, total capacity, registered count, poster image URL, and Binary JSON (`options` as JSONB) attendance tiers.
- **Registrations Table (`registrations`):** Records individual student ticket reservations. Each row contains a Foreign Key (FK) reference to `events.id`, an optional reference to `user\_id`, a unique door check-in reference code (`EW-XXXX-XX`), the selected tier name, and reminder opt-in status.

5.1 Atomic Concurrency Trigger for Capacity Management

A critical vulnerability in event registration web applications is the race condition, where simultaneous attendee requests can lead to overbooking beyond hall limits. To prevent this, EVENTWEB implements an atomic Structured Query Language (SQL) trigger function executing at the database level:

```
CREATE OR REPLACE FUNCTION public.handle_new_registration()
RETURNS trigger AS $$
BEGIN
  UPDATE public.events SET reg_count = reg_count + 1 WHERE id = new.event_id;
  RETURN new;
END;
$$ LANGUAGE plpgsql SECURITY DEFINER;

CREATE TRIGGER on_registration_created
AFTER INSERT ON public.registrations
FOR EACH ROW EXECUTE PROCEDURE public.handle_new_registration();
```

5.2 Security and Row-Level Security (RLS)

Row-Level Security (RLS) is strictly enabled on all database tables. Public anonymous users have `SELECT` access only to published events and `INSERT` permissions to register. Organizers are restricted via `auth.uid() = organizer\_id` so that they can only modify or view attendance logs for events they have published.

6. Geospatial Mapping and Campus Venue Coordinates

To assist students in locating event venues across KNUST, EVENTWEB integrates a dedicated Leaflet Geographic Information System (GIS) module mapped to calibrated campus coordinates:

- **Great Hall:** 6.67475° N, -1.57220° W (Main Ceremonial Hall and Matriculation/Congregation Auditorium)
- **Paa Joe Stadium:** 6.67780° N, -1.56950° W (University Sports Grounds, Marathon Starts, Outdoor Fairs)
- **College of Science Auditorium:** 6.67350° N, -1.56650° W (Academic Conferences, STEM Competitions)
- **Prempeh II Library:** 6.67510° N, -1.57180° W (Central Academic Resource and Seminar Rooms)
- **KNUST Interdenominational Church:** 6.68508° N, -1.57270° W (Religious Fellowships and Services)
- **Central Campus / Brunei Complex:** 6.67644° N, -1.57343° W (Night Markets, Fusion Festivals)

The mapping layer uses Scalable Vector Graphics (SVG) drafting pins with category-coded color indicators. Selecting an event in the list smoothly pans the map viewport to that venue, while tapping a map marker instantly filters the event roster.

7. Transactional Pass and Reminder Pipeline (Resend)

When a student registers, Supabase triggers a serverless Edge Function running on the Deno runtime. This function calls the Resend REST Application Programming Interface (API) to dispatch an immediate confirmation pass containing the event title, flyer thumbnail, society name, date, venue, and unique entry verification code (`EW-XXXX-XX`). API keys are securely stored in server environment variables and never exposed to client browsers.

8. Conclusion

EVENTWEB demonstrates how modern web engineering, geospatial cartography, and cloud database architectures can solve a tangible logistical challenge in tertiary education. By replacing fragmented publicity channels with a unified, aesthetically refined platform, EVENTWEB provides students and student societies with a dependable, scalable, and high-performance event coordination infrastructure.