

The Command Event Module API

Get Event Occurrences

Operation: get_event_occurrences

One or more search parameters may be entered.

Parameter	Type	Description
event_status	Number	0 - Inactive/Cancelled, 1 – Active, 3 – all (default 1)
event_tentative	Number	0 - No, 1 – Yes, 3- all (default 3)
esiid	Number	Event Supplemental Type 0 - All 1 - Golf Tournament 2 – Meeting From event supplemental information table. Default 0
Evtid	Number	Event Type – from event_type table 0 for all. Default 0.
Seid	Number	Season ID or 0 for all, default 0.
Sort	Text	a – Alpha, d – date. Default d.
start_date	Date	Earliest date of tournament (optional)
end_date	Date	Latest date of tournament (optional)

Returns

Variable	Value	Description
Success	True/False	
Message	String	Message for failure of operation
Event information	See below	

Needed in return

event_start_date

Get POY Years

Operation: get_poy_years

Gets a list of all the years that there are poy points.

Parameter	Type	Description
poygid	Number	POY Group ID
order	A – Ascending, D – Descending	Order of years. Descending is default.

Returns

Variable	Value	Description
Success	True/False	
Message	String	Message for failure of operation
See below		

```
<result>
<success>true</success>
<message/>
<years>
<year>2017</year>
<year>2016</year>
</years>
</result>
```

Get POY Group Name

Operation: get_group_name

Gets a list of all the years that there are poy points.

Parameter	Type	Description
poygid	Number	POY Group ID

Returns

Variable	Value	Description
Success	True/False	
Message	String	Message for failure of operation
See below		

```
<result>
<success>true</success>
<message/>
<poy_group_name>MGA</ poy_group_name >
</result>
```

Get the POY standings

get_poy_standings

Parameter	Type	Description
poygid	Number	POY Group ID
year	Year of standings	

Returns

Variable	Value	Description
Success	True/False	
Message	String	Message for failure of operation
See below		

```
<result>
<success>true</success>
<message/>
<players>
<player>
<cid>99999</cid>
<first_name>Joe</first_name>
<middle_name>A< /middle_name>
<last_name>Smith< /last_name>
<suffix_name>Jr< /suffix_name>
<club_name>Bonnie Brier</club_name>
<pro>1</pro>
<pro_year>1987</pro_year>
<total_points>150</total_points>
</player>
</players>
</result>
```

Operation: get_poy_contact_points

Get the POY points for a contact.

Parameter	Type	Description
poygid	Number	POY Group ID
year	Year of standings	
cid	Contact id	

Returns

Variable	Value	Description
Success	True/False	
Message	String	Message for failure of operation
See below		

```
<result>
<success>true</success>
<message/>
<cid>99999</cid>
<first_name>Joe</first_name>
<middle_name>A< /middle_name>
<last_name>Smith< /last_name>
<suffix_name>Jr< /suffix_name>
<pro>1</pro>
<pro_year>1987</pro_year>
<points>
<point>
<poy_points >150</poy_points>
<event_occurrence_name>95 Senior Am</event_occurrence_name>
<poy_finish>1</poy_finish>
<poy_tied>0</poy_tied>
</point>
</points>
</result>
```

Operation: get_poy_contact_points_by_year

Get the POY points for a contact.

Parameter	Type	Description
poygid	Number	POY Group ID
cid	Contact id	

Returns

Variable	Value	Description
Success	True/False	
Message	String	Message for failure of operation
See below		

```
<result>
<success>true</success>
<message/>
<cid>99999</cid>
<first_name>Joe</first_name>
<middle_name>A< /middle _name>
<last_name>Smith< /last _name>
<suffix_name>Jr< /suffix _name>
<pro>1</pro>
<pro_year>1987</pro_year>
<points>
<point>
<year >2017</year >
<total_points >150</ total_points>
</point>
</points>
</result>
```